## .graphqlrc X

```
overwrite: true
     schema: schema.graphql
     documents: ./src/**/*.tsx
     extensions
       codegen
         generates:
           src/:
             config:
               dedupeOperationSuffix: true
               documentMode: graphQLTag
               nonOptionalTypename: true
               omitOperationSuffix: true
               preResolveTypes: true?
               withHooks: true
             plugins:

    typescript-operations

               - typescript-react-apollo
17
             preset: near-operation-file
             presetConfig:
               baseTypesPath: __generated__/types.ts
               extension: .ts
               folder: __generated__
           src/__generated__/types.ts:
             config:
               namingConvention: keep
             plugins:
               - typescript
```

## CountryList.ts X

```
* const { data, loading, error } = useCountryListQuery({
96 * variables: {
98 | * });
     export function useCountryListQuery(
       baseOptions?: Apollo.QueryHookOptions<</pre>
101
         CountryListQuery,
102
         CountryListQueryVariables
103
104
       >,
     ) {
105
        const options = { ...defaultOptions, ...baseOptions };
106
        return Apollo.useQuery<CountryListQuery, CountryListQueryVariables>(
107
         CountryListDocument,
108
109
         options,
110
       );
111
       baseOptions?: Apollo.LazyQueryHookOptions<</pre>
         CountryListQuery,
          CountryListQueryVariables
        return Apollo.useLazyQuery<CountryListQuery, CountryListQueryVariables>(
```