```
.graphqlrc    X

1    overwrite: true
2    schema: schema.graphql
3    documents: ./src/**/*.tsx
4    extensions:
5      codegen:
6        generates:
7          src/:
8            plugins:
9              - typescript-operations
10           preset: near-operation-file
11           presetConfig:
12             baseTypesPath: __generated__/types.ts
13             extension: .ts
14             folder: __generated__
15         src/__generated__/types.ts:
16           config:
17             namingConvention: keep
18           plugins:
19             - typescript
```

```json
{
    "name": "graphql-example-app",
    "version": "0.1.0",
    ▷ Debug
    "scripts": {
      "start": "react-scripts start",
      "lint": "eslint ./src/**/*.{ts,tsx}",
      "build": "react-scripts build",
      "test": "react-scripts test",
      "eject": "react-scripts eject",
      "type-check": "tsc --noEmit",
      "graphql:generate": "graphql codegen"
    },
    "lint-staged": {
      "src/**/*.{js,jsx,ts,tsx,json,css,scss,md}": [
        "prettier --write"
      ]
    },
    "dependencies": {
      "@apollo/client": "^3.3.11",
      "@chakra-ui/react": "^1.3.4",
      "@emotion/react": "^11.1.5",
      "@emotion/styled": "^11.1.5",
      "framer-motion": "^3.10.0",
      "react": "^17.0.1",
      "react-dom": "^17.0.1",
      "react-icons": "^4.2.0",
      "react-router-dom": "^5.2.0",
      "web-vitals": "^1.0.1"
```