`CountryList.tsx`

```
CountryList
  __generated__
    CountryList.ts                                              U
  CountryList.tsx
```

```
→  graphql-example-app git:(main) ✗ yarn run graphql:generate
yarn run v1.22.10
$ graphql codegen
  ✔ Parse configuration
  ✔ Generate outputs
✨  Done in 2.34s.
```

Terminal

```
→  graphql-example-app git:(main) ✗ yarn run graphql:generate
yarn run v1.22.10
$ graphql codegen
   ✔ Parse configuration
   ✔ Generate outputs
✨  Done in 2.34s.
```

📁 CountryList   ●
  📁 __generated__   ●
    TS CountryList.ts   U
  ⚛ CountryList.tsx

CountryList.ts   X

```typescript
import * as Types from '../../../__generated__/types';

export type CountryListVariables = Types.Exact<{ [key: string]: never }>;

export type CountryList = {
  __typename: 'Query';
  countries?: Types.Maybe<
    Array<
      Types.Maybe<{
        __typename: 'Country';
        _id?: Types.Maybe<string>;
        name: string;
        subregion?: Types.Maybe<{
          __typename: 'Subregion';
          _id?: Types.Maybe<string>;
          name: string;
        }>;
      }>
    >
  >;
};
```