




SHEN ZHEN PTC VISION TECH CO., LTD

01 客户检测需求 - 缺陷成像形态

Note: Defect descriptions are all based on imaging pictures of samples received.

序号	缺陷名称	缺陷形态	缺陷描述	备注
1	切割不良 Bari		Such defects exist on the edge of the product, the defect protrudes relative to the edge of the product, and The contrast of the background is obvious, the transition pixels are less, and the overall grey scale of the defective part is uniform.	
2	凹凸波纹 Bumpy Wave		Such defects are distributed on the surface of the product, and there are slight depressions on the opposite surface of the defects. The shape of the depression is long, the contrast is low, the edge of the defect is not obvious, and the defect part. The overall grey level is uniform.	
3	凹凸不平 Bumpy		Such defects are distributed on the surface of the product, and there are slight depressions on the opposite surface of the defects. The shape of the depression is circular, the contrast is low, the edge of the defect is not obvious, and it faces the light source. The part is relatively bright, and the part facing away from the light source is relatively dark	
4	崩边 Chipping		Such defects exist at the edge of the product, and the defect exists in part relative to the complete product. Defect, the background color is exposed at the defect, the edge contrast of the defect is high, and the transition pixel less, the overall grey level of the defective part is uniform;	


01 客户检测需求 - 缺陷成像形态

注：缺陷描述全部基于所收到的样品的成像图片，如有出入，请补充缺陷样品。

序号	缺陷名称	缺陷形态	缺陷描述	备注
5	凹坑 Dent		Such defects are distributed on the surface of the product, and there are slight depressions on the opposite surface of the defects. The shape of the depression is circular, the contrast is low, the edge of the defect is not obvious, and it faces the light source. The part is relatively bright, and the part facing away from the light source is relatively dark, and the whole is not uneven similar defects of the same class;	
6	脏污 Dirty		Such defects are dirt attached to the surface, depending on the degree of dirt, the overall gray scale and contrast fluctuate slightly, and when it is slight, part of the bottom plate color will be exposed, lacking. The overall defect is relatively clear, there are more transition pixels for minor defects, and the internal grayscale of defects relatively uniform;	
7	边缘翘起 Edge Warp		Such defects are distributed in the area close to the edge of the product, and the defects are caused by uneven surface constructed in round blocks or long strips, with weaker features on the raised part of the short side presentation, the long-side curve is temporarily invisible under the current imaging conditions, and the edge of the defect is not obvious, low overall contrast;	Received a total of 6 edge lift defects, sample, only 2 pieces of short side warping can be slight defects are seen, and the remaining 4 pieces are the image features are very faint and cannot be seen.
8	锈点 Iron		Such defects are distributed on the surface of the product, appearing in the form of reddish-yellow dots as a whole, with excessive, there are many pixels, depending on the degree of defect, the contrast fluctuates greatly, and the slight difficult to tell.	


01 客户检测需求 - 缺陷成像形态

注：缺陷描述全部基于所收到的样品的成像图片，如有出入，请补充缺陷样品。

序号	缺陷名称	缺陷形态	缺陷描述	备注
9	压印 Katasuke		Such defects are distributed on the surface of the product, and the surface of the product is depressed at the defect, and the concave shape, it is dot-shaped or strip-shaped, the part facing the light source is brighter overall, and the part facing the light source in the north, some parts are darker overall;	
10	线痕 Line		Such defects are distributed on the surface of the product, and the overall defect is slightly smaller than the surface of the product, elevated, elongated, very slight features, low defect contrast, poor edges obvious;	
11	针孔 Pin Hole		Such defects are distributed on the surface of the product, and the defect area is sunken compared to the surface, and the defect, the overall characteristics are acceptable, reaching the inspection standard, and the part facing the light source is brighter overall, the part of the north-facing light source is darker overall;	
12	粗糙 Rough		Such defects are distributed on the surface of the product, and the defect area is relatively large, which is caused by the low-contrast, the dotted areas are connected into a larger area, the entropy value of the defect area is low, and the gray level is different. Uniform, low contrast;	

01 客户检测需求 - 缺陷成像形态

注：缺陷描述全部基于所收到的样品的成像图片，如有出入，请补充缺陷样品。

序号	缺陷名称	缺陷形态	缺陷描述	备注
13	划伤 Scratches		This kind of defect is distributed on the surface of the product, and the defect is caused by scratching the surface of the product by a hard object. Caused by the defect, the inner part of the material will be exposed at the defect, and the whole is strip-shaped, and the surface of the defect white, clear edges, high contrast, less excessive pixels;	
14	粘胶 Stickly		This type of defect is the glue attached to the surface of the product, the glue is in the form of dots or short strips of curls, the part facing the light source is white, and the part facing away from the light source is gray-black, with clear edges. Higher contrast, fewer transition pixels;	
15	白裂纹 White Crack		Such defects are distributed on the surface of the product, and the defects are caused by external force extrusion and collision structural damage defect, the surface of the defect is damaged, exposing the internal material, and the edge is relatively sharp, high contrast, the internal gray histogram distribution is bimodal, facing the light source, part of it is white, and the part against the light source is gray-black.	A total of 3 samples with white crack defects were received. Due to improper express delivery, 2 of the samples were broken along the defect, and only 1 complete sample was received for this type of defect.