

Flagship <

U6 Long-Range

U6-LR

160,00 €
193,60 € VAT incl.
[No restock date yet](#)



Ceiling-mounted WiFi 6 AP with 8 spatial streams and extended signal range.

Note. WiFi 6 for 5 GHz. WiFi 4 for 2.4 GHz.

Login for Notifications

Powerful Accessories

PoE+ Adapter (30W)

15,73 € VAT incl.

Arm Mount

31,46 € VAT incl.

[Installation Guide](#)

Overview

Dimensions	ø220 x 48 mm (ø8.7 x 1.9")
WiFi Standard	WiFi 6
Spatial Streams	8
Coverage Area	185 m² (2,000 ft²)
Max. Client Count	350+
Uplink	GbE
Mounting	Ceiling, Wall (Pro Mount Included)
Weatherproofing	IP54
Power Method	PoE+ ⓘ

Performance	
MIMO	
5 GHz	4 x 4 (DL/UL MU-MIMO)
2.4 GHz	4 x 4 (SU-MIMO)
Max. Data Rate	
5 GHz	2.4 Gbps (BW160)
2.4 GHz	600 Mbps (BW40)
Antenna Gain	
5 GHz	5.5 dBi
2.4 GHz	4 dBi
Max. TX Power	
5 GHz	26 dBm
2.4 GHz	26 dBm
Max. BSSIDs	8 per Radio
Supported Data Rates	
802.11ax (WiFi 6)	7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80) 7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2, HE 160)
802.11ac (WiFi 5)	6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80) 6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2, VHT 160)
802.11n	6.5 Mbps to 600 Mbps (MCS0 - MCS31, HT 20/40)

Features	
Wireless Meshing	✓
Band Steering	✓
802.11v BSS Transition Management	✓
802.11r Fast Roaming	✓
802.11k Radio Resource Management (RRM)	✓
Advanced Radio Management	✓
Passpoint (Hotspot 2.0)	✓
Captive Hotspot Portal	
Custom Branding Landing Page	✓
Voucher Authentication	✓
Payment-Based Authentication	✓
External Portal Server Support	✓
Password Authentication	✓
Guest Network Isolation	✓
Private Pre-Shared Key (PPSK)	✓
WiFi Speed Limiting	✓
Client Device Isolation	✓
WiFi Schedules	✓
RADIUS over TLS (RadSec)	✓
Dynamic RADIUS-assigned VLAN	✓
Hardware	
Max. Power Consumption	18.5W
Supported Voltage Range	44–57V DC
Networking Interface	(1) GbE RJ45 port
Weight	Device: 800 g (1.8 lb) With mount: 930 g (2.1 lb)
Management	Ethernet Bluetooth
Enclosure Material	Polycarbonate
Mount Material	Stainless steel (SUS304)
LEDs	
System	White/Blue

Channel Bandwidth	HT 20/40, VHT 20/40/80/160, HE 20/40/80/160 (MHz)
Operating Frequency	US/CA: 2400 - 2472 MHz U-NII-1: 5150 - 5250 MHz U-NII-2A: 5250 - 5350 MHz U-NII-2C: 5470 - 5725 MHz U-NII-3: 5725 - 5850 MHz Worldwide: 2400 - 2483.5 MHz 5150 - 5850 MHz
Ambient Operating Temperature	-30 to 60° C (-22 to 140° F)
Ambient Operating Humidity	5 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, SRRC, Anatel: 10457-21-08356
Software	
Application Requirements	
UniFi Network	Version 6.0.45 and later

Stay in Touch

Email

Subscribe

