

#include<stdio.h>

```
int main()
{
    int arr[100];
    int n, i;

    printf("Enter the number of elements: ");
    scanf("%d", &n);

    printf("Enter the elements:\n");

    for(i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }

    printf("The elements are:\n");

    for(i = 0; i < n; i++)
    {
        printf("%d ", arr[i]);
    }

    return 0;
}
```

```
int main()
{
    int arr[100];
    int n, i, sum = 0;

    printf("Enter the number of elements: ");
    scanf("%d", &n);

    printf("Enter the elements:\n");

    for(i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }

    for(i = 0; i < n; i++)
    {
        sum = sum + arr[i];
    }

    printf("Sum = %d\n", sum);

    return 0;
}
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^_ Go To Line

M-U Undo
M-E Redo

M-A
M-6

System load: 0.0

Usage of /: 0.2% of 1006.85GB

Memory usage: 7%

Swap usage: 0%

Processes:

78

Users logged in:

0

IPv4 address for eth0: 172.19.160.16

* Canonical Workshop gives developers fast, composable, reproducible, and secure developer environments that are perfect for agentic workflows.

<https://ubuntu.com/workshop>

This message is shown once a day. To disable it please create the /home/krati_gupta/.hushlogin file.

```
krati_gupta@DESKTOP-6N3A075:~$ nano array1.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array1.c -o array1
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array1
```

Enter the number of elements: 5

Enter the elements:

10

20

30

40

50

The elements are:

```
10 20 30 40 50 krati_gupta@DESKTOP-6N3A075:~$ nano array2.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array2.c -o array2
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array2
```

Enter the number of elements: 4

Enter the elements:

20

10

30

50

Sum = 110

```
krati_gupta@DESKTOP-6N3A075:~$
```

GNU nano 7.2

#include <stdio.h>

array3.c *

int main()

{

int arr[100];

int n, i;

int max, min;

printf("Enter the number of elements: ");

scanf("%d", &n);

printf("Enter the elements:\n");

for(i = 0; i < n; i++)

{

scanf("%d", &arr[i]);

}

max = arr[0];

min = arr[0];

for(i = 1; i < n; i++)

{

if(arr[i] > max)

{

max = arr[i];

}

if(arr[i] < min)

{

min = arr[i];

}

}

^G Help
^X Exit^O Write Out
^R Read File^W Where Is
^_ Replace^K Cut
^U Paste^T Execute
^J Justify^C Location
^_ Go To LineM-U Undo
M-E RedoM-A Set Mark
M-6 Copy

```
printf("Enter the number of elements: ");  
scanf("%d", &n);
```

```
printf("Enter the elements:\n");
```

```
for(i = 0; i < n; i++)  
{  
    scanf("%d", &arr[i]);  
}
```

```
max = arr[0];  
min = arr[0];
```

```
for(i = 1; i < n; i++)  
{  
    if(arr[i] > max)  
    {  
        max = arr[i];  
    }  
  
    if(arr[i] < min)  
    {  
        min = arr[i];  
    }  
}
```

```
printf("Maximum = %d\n", max);  
printf("Minimum = %d\n", min);
```

```
return 0;
```

```
^G Help  
^X Exit
```

```
^O Write Out  
^R Read File
```

```
^W Where Is  
^_ Replace
```

```
^K Cut  
^U Paste
```

```
^T Execute  
^J Justify
```

```
^C Location  
^_ Go To Line
```

```
M-U Undo  
M-E Redo
```

```
M-A  
M-6
```

This message is shown once a day. To disable it please create the
/home/krati_gupta/.hushlogin file.

```
krati_gupta@DESKTOP-6N3A075:~$ nano array1.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array1.c -o array1
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array1
```

Enter the number of elements: 5

Enter the elements:

10

20

30

40

50

The elements are:

```
10 20 30 40 50 krati_gupta@DESKTOP-6N3A075:~$ nano array2.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array2.c -o array2
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array2
```

Enter the number of elements: 4

Enter the elements:

20

10

30

50

Sum = 110

```
krati_gupta@DESKTOP-6N3A075:~$ nano array3.c
```

```
krati_gupta@DESKTOP-6N3A075:~$
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array3.c -o array3
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array3
```

Enter the number of elements: 5

Enter the elements:

12

5

90

23

7

Maximum = 90

Minimum = 5

```
krati_gupta@DESKTOP-6N3A075:~$
```



Thunderstorm w...
In effect



Search



ENG
IN

acer

```
int main()
{
    int arr[100];
    int n, i;
    int even = 0, odd = 0;

    printf("Enter the number of elements: ");
    scanf("%d", &n);

    printf("Enter the elements:\n");

    for(i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }

    for(i = 0; i < n; i++)
    {
        if(arr[i] % 2 == 0)
        {
            even++;
        }
        else
        {
            odd++;
        }
    }

    printf("Even numbers = %d\n", even);
    printf("Odd numbers = %d\n", odd);

    return 0;
}
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^/ Go To Line

M-U Undo
M-E Redo

M-A Set Mark
M-6 Copy

The elements are:

10 20 30 40 50 krati_gupta@DESKTOP-6N3A075:~\$ nano array2.c

krati_gupta@DESKTOP-6N3A075:~\$ gcc array2.c -o array2

krati_gupta@DESKTOP-6N3A075:~\$./array2

Enter the number of elements: 4

Enter the elements:

20

10

30

50

Sum = 110

krati_gupta@DESKTOP-6N3A075:~\$ nano array3.c

krati_gupta@DESKTOP-6N3A075:~\$

krati_gupta@DESKTOP-6N3A075:~\$ gcc array3.c -o array3

krati_gupta@DESKTOP-6N3A075:~\$./array3

Enter the number of elements: 5

Enter the elements:

12

5

90

23

7

Maximum = 90

Minimum = 5

krati_gupta@DESKTOP-6N3A075:~\$ nano array4.c

krati_gupta@DESKTOP-6N3A075:~\$ gcc array4.c -o array4

krati_gupta@DESKTOP-6N3A075:~\$./array4

Enter the number of elements: 5

Enter the elements:

10

90

80

30

10

Even numbers = 5

Odd numbers = 0

krati_gupta@DESKTOP-6N3A075:~\$

GNU nano 7.2

#include <stdio.h>

array5.c *

int main()

{

int arr[100];

int n, i;

int positive = 0, negative = 0, zero = 0;

printf("Enter the number of elements: ");
scanf("%d", &n);

printf("Enter the elements:\n");

for(i = 0; i < n; i++)

{

scanf("%d", &arr[i]);

}

for(i = 0; i < n; i++)

{

if(arr[i] > 0)

{

positive++;

}

else if(arr[i] < 0)

{

negative++;

}

else

{

zero++;

}

}

^G Help
^X Exit^O Write Out
^R Read File^W Where Is
^_ Replace^K Cut
^U Paste^T Execute
^J Justify^C Location
^_ Go To LineM-U Undo
M-E RedoM-A Set Mark
M-G Copy

```
printf("Enter the number of elements: ");  
scanf("%d", &n);
```

```
printf("Enter the elements:\n");
```

```
for(i = 0; i < n; i++)  
{  
    scanf("%d", &arr[i]);  
}
```

```
for(i = 0; i < n; i++)  
{  
    if(arr[i] > 0)  
    {  
        positive++;  
    }  
    else if(arr[i] < 0)  
    {  
        negative++;  
    }  
    else  
    {  
        zero++;  
    }  
}
```

```
printf("Positive numbers = %d\n", positive);  
printf("Negative numbers = %d\n", negative);  
printf("Zeroes = %d\n", zero);
```

```
return 0;
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^_ Go To Line

M-U Undo
M-E Redo

M-A Set Mark
M-6 Copy

#include <stdio.h>

array6.c *

int main()

{

int arr[100];

int n, i, key;

int found = 0;

printf("Enter the number of elements: ");
scanf("%d", &n);

printf("Enter the elements:\n");

for(i = 0; i < n; i++)

{

scanf("%d", &arr[i]);

}

printf("Enter the element to search: ");
scanf("%d", &key);

for(i = 0; i < n; i++)

{

if(arr[i] == key)

{

printf("Element found at index %d\n", i);

found = 1;

break;

}

}

if(found == 0)

{

^G Help
^X Exit^O Write Out
^R Read File^W Where Is
^_ Replace^K Cut
^U Paste^T Execute
^J Justify^C Location
^_ Go To LineM-U Undo
M-E RedoM-A Set Mark
M-6 Copy

```
int found = 0;

printf("Enter the number of elements: ");
scanf("%d", &n);

printf("Enter the elements:\n");

for(i = 0; i < n; i++)
{
    scanf("%d", &arr[i]);
}

printf("Enter the element to search: ");
scanf("%d", &key);

for(i = 0; i < n; i++)
{
    if(arr[i] == key)
    {
        printf("Element found at index %d\n", i);
        found = 1;
        break;
    }
}

if(found == 0)
{
    printf("Element not found\n");
}

return 0;
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

Enter the elements:

10

7

8

5

4

9

Even numbers = 3

Odd numbers = 3

krati_gupta@DESKTOP-6N3A075:~\$ nano array5.c

krati_gupta@DESKTOP-6N3A075:~\$

krati_gupta@DESKTOP-6N3A075:~\$ gcc array5.c -o array5

krati_gupta@DESKTOP-6N3A075:~\$./array5

Enter the number of elements: 6

Enter the elements:

10

-5

0

8

-2

0

Positive numbers = 2

Negative numbers = 2

Zeros = 2

krati_gupta@DESKTOP-6N3A075:~\$ nano array6.c

krati_gupta@DESKTOP-6N3A075:~\$ gcc array6.c -o array6

krati_gupta@DESKTOP-6N3A075:~\$./array6

Enter the number of elements: 5

Enter the elements:

10

12

18

20

90

Enter the element to search: 20

Element found at index 3

krati_gupta@DESKTOP-6N3A075:~\$

#include <stdio.h>

array7.c *

int main()

{

int arr[100];

int n, i, temp;

printf("Enter the number of elements: ");
scanf("%d", &n);

printf("Enter the elements:\n");

for(i = 0; i < n; i++)

{

scanf("%d", &arr[i]);

}

for(i = 0; i < n / 2; i++)

{

temp = arr[i];

arr[i] = arr[n - 1 - i];

arr[n - 1 - i] = temp;

}

printf("Reversed array:\n");

for(i = 0; i < n; i++)

{

printf("%d ", arr[i]);

}

return 0;

^G Help
^X Exit^O Write Out
^R Read File^W Where Is
^_ Replace^K Cut
^U Paste^T Execute
^J Justify^C Location
^_ Go To LineM-U Undo
M-E RedoM-
M-

krati_gupta@DESKTOP-6N3A075

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array5.c -o array5
krati_gupta@DESKTOP-6N3A075:~$ ./array5
```

Enter the number of elements: 6

Enter the elements:

10

-5

0

8

-2

0

Positive numbers = 2

Negative numbers = 2

Zeroes = 2

```
krati_gupta@DESKTOP-6N3A075:~$ nano array6.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array6.c -o array6
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array6
```

Enter the number of elements: 5

Enter the elements:

10

12

18

20

90

Enter the element to search: 20

Element found at index 3

```
krati_gupta@DESKTOP-6N3A075:~$ nano array7.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array7.c -o array7
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array7
```

Enter the number of elements: 5

Enter the elements:

10

60

90

80

60

Reversed array:

60 80 90 60 10 krati_gupta@DESKTOP-6N3A075:~\$

#include <stdio.h>

array8.c *

int main()

{

int a[100], b[100], c[200];

int n1, n2, i;

printf("Enter number of elements in first array: ");
scanf("%d", &n1);

printf("Enter elements of first array:\n");

for(i = 0; i < n1; i++)

{

scanf("%d", &a[i]);

}

printf("Enter number of elements in second array: ");
scanf("%d", &n2);

printf("Enter elements of second array:\n");

for(i = 0; i < n2; i++)

{

scanf("%d", &b[i]);

}

for(i = 0; i < n1; i++)

{

c[i] = a[i];

}

for(i = 0; i < n2; i++)

^G Help
^X Exit^O Write Out
^R Read File^W Where Is
^_ Replace^K Cut
^U Paste^T Execute
^J Justify^C Location
^_ Go To LineM-U Undo
M-E Redo

```
    scanf("%d", &a[i]);
}

printf("Enter number of elements in second array: ");
scanf("%d", &n2);

printf("Enter elements of second array:\n");

for(i = 0; i < n2; i++)
{
    scanf("%d", &b[i]);
}

for(i = 0; i < n1; i++)
{
    c[i] = a[i];
}

for(i = 0; i < n2; i++)
{
    c[n1 + i] = b[i];
}

printf("Merged array:\n");

for(i = 0; i < n1 + n2; i++)
{
    printf("%d ", c[i]);
}

return 0;
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano array6.c
krati_gupta@DESKTOP-6N3A075:~$ gcc array6.c -o array6
krati_gupta@DESKTOP-6N3A075:~$ ./array6
Enter the number of elements: 5
Enter the elements:
10
12
18
20
90
Enter the element to search: 20
Element found at index 3
krati_gupta@DESKTOP-6N3A075:~$ nano array7.c
krati_gupta@DESKTOP-6N3A075:~$ gcc array7.c -o array7
krati_gupta@DESKTOP-6N3A075:~$ ./array7
Enter the number of elements: 5
Enter the elements:
10
60
90
80
60
Reversed array:
60 80 90 60 10
krati_gupta@DESKTOP-6N3A075:~$ nano array8.c
krati_gupta@DESKTOP-6N3A075:~$ gcc array8.c -o array8
krati_gupta@DESKTOP-6N3A075:~$ ./array8
Enter number of elements in first array: 3
Enter elements of first array:
10
20
30
Enter number of elements in second array: 2
Enter elements of second array:
20
30
Merged array:
10 20 30 20 30
krati_gupta@DESKTOP-6N3A075:~$
```

```
    if(num < 0)
    {
        num = -num;
    }

    while(num > 0)
    {
        digit = num % 10;
        count[digit]++;
        num = num / 10;
    }while(num > 0)
    {
        digit = num % 10;
        count[digit]++;
        num = num / 10;
    }
}

for(i = 0; i < 10; i++)
{
    if(count[i] > maxCount)
    {
        maxCount = count[i];
        maxDigit = i;
    }
}

printf("Digit occurring most times = %d\n", maxDigit);
printf("It occurs %d times\n", maxCount);

return 0;
```

GNU nano 7.2
#include <stdio.h>

array10.c *

```
int main()
{
    int arr[100];
    int n, i, key;
    int low, high, mid;
    int found = 0;

    printf("Enter the number of elements: ");
    scanf("%d", &n);

    printf("Enter elements in sorted order:\n");

    for(i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }

    printf("Enter the element to search: ");
    scanf("%d", &key);

    low = 0;
    high = n - 1;

    while(low <= high)
    {
        mid = (low + high) / 2;

        if(arr[mid] == key)
        {
            printf("Element found at index %d\n", mid);
            found = 1;
        }
    }
}
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^_ Go To Line

M-U Undo
M-E Redo

M-A Set Mark
M-G Copy



GNU nano 7.2

array10.c *

```
scanf("%d", &key);
```

```
low = 0;
```

```
high = n - 1;
```

```
while(low <= high)
```

```
{
```

```
    mid = (low + high) / 2;
```

```
    if(arr[mid] == key)
```

```
    {
```

```
        printf("Element found at index %d\n", mid);
```

```
        found = 1;
```

```
        break;
```

```
    }
```

```
    else if(arr[mid] < key)
```

```
    {
```

```
        low = mid + 1;
```

```
    }
```

```
    else
```

```
    {
```

```
        high = mid - 1;
```

```
    }
```

```
}
```

```
if(found == 0)
```

```
{
```

```
    printf("Element not found\n");
```

```
}
```

```
return 0;
```



^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^_ Go To Line

M-U Undo
M-E Redo

M-A Set M
M-6 Copy



Search

1 22°C
Partly sunny

acer

krati_gupta@DESKTOP-6N3A075

Enter number of elements in second array: 2
Enter elements of second array:

20

30

Merged array:

10 20 30 20 30

krati_gupta@DESKTOP-6N3A075:~\$ nano array9.c

krati_gupta@DESKTOP-6N3A075:~\$ gcc array9.c -o array9

krati_gupta@DESKTOP-6N3A075:~\$./array9

Enter an integer: 11223311

Digit occurring most times = 1

It occurs 4 times

krati_gupta@DESKTOP-6N3A075:~\$ nano array10.c

krati_gupta@DESKTOP-6N3A075:~\$

krati_gupta@DESKTOP-6N3A075:~\$ gcc array10.c -o array10

krati_gupta@DESKTOP-6N3A075:~\$./array10

Enter the number of elements: 6

Enter elements in sorted order:

10

20

30

40

50

60

Enter the element to search: 56

Element not found

krati_gupta@DESKTOP-6N3A075:~\$ gcc array10.c -o array10

krati_gupta@DESKTOP-6N3A075:~\$./array10

Enter the number of elements: 5

Enter elements in sorted order:

10

20

30

40

50

Enter the element to search: 40


Element found at index 3

krati_gupta@DESKTOP-6N3A075:~\$

22°C
Partly sunny



Search



ENG
IN

acer

```
#include <stdio.h>

int main()
{
    int num, digit;
    int count[10] = {0};
    int i, maxCount = 0, maxDigit = 0;

    printf("Enter an integer: ");
    scanf("%d", &num);

    if(num == 0)
    {
        count[0] = 1;
    }
    else
    {
        if(num < 0)
        {
            num = -num;
        }

        while(num > 0)
        {
            digit = num % 10;
            count[digit]++;
            num = num / 10;
        }
        while(num > 0)
        {
            digit = num % 10;
            count[digit]++;
            num = num / 10;
        }
    }
}
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^_ Go To Line

M-U Undo
M-E Redo

krati_gupta@DESKTOP-6N3A...

GNU nano 7.2

#include <stdio.h>

int main()

{

int arr[100];

int n, i, element, position;

printf("Enter the number of elements: ");
scanf("%d", &n);

printf("Enter elements in sorted order:\n");

for(i = 0; i < n; i++)
{
scanf("%d", &arr[i]);
}

printf("Enter the element to insert: ");
scanf("%d", &element);

position = 0;

while(position < n && arr[position] < element)
{
position++;
}

for(i = n; i > position; i--)
{
arr[i] = arr[i - 1];
}

arr[position] = element;

array11.c *

Close

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^_ Go To Line

M-U Undo
M-E Redo

M-A Set Mark
M-6 Copy



21°C
Partly sunny



Search



13:02
15-09-2026

acer

krati_gupta@DESKTOP-6N3Av

GNU nano 7.2

array11.c *

```
for(i = 0; i < n; i++)
{
    scanf("%d", &arr[i]);
}

printf("Enter the element to insert: ");
scanf("%d", &element);

position = 0;

while(position < n && arr[position] < element)
{
    position++;
}

for(i = n; i > position; i--)
{
    arr[i] = arr[i - 1];
}

arr[position] = element;
n++;

printf("Array after insertion:\n");

for(i = 0; i < n; i++)
{
    printf("%d ", arr[i]);
}

return 0;
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^/ Go To Line

M-U Undo
M-E Redo

M-A
M-6

GNU nano 7.2

array12.c *

```
#include <stdio.h>

int main()
{
    int arr[100];
    int n, i, element, position;

    printf("Enter the number of elements: ");
    scanf("%d", &n);

    printf("Enter the elements:\n");

    for(i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }

    printf("Enter the element to insert: ");
    scanf("%d", &element);

    printf("Enter the position (0 to %d): ", n);
    scanf("%d", &position);

    if(position < 0 || position > n)
    {
        printf("Invalid position\n");
    }
    else
    {
        for(i = n; i > position; i--)
        {
            arr[i] = arr[i - 1];
        }
    }
}
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^/ Go To Line

M-U Undo
M-E Redo

M-A Set Mark
M-6 Copy

```
}

printf("Enter the element to insert: ");
scanf("%d", &element);

printf("Enter the position (0 to %d): ", n);
scanf("%d", &position);

if(position < 0 || position > n)
{
    printf("Invalid position\n");
}
else
{
    for(i = n; i > position; i--)
    {
        arr[i] = arr[i - 1];
    }

    arr[position] = element;
    n++;

    printf("Array after insertion:\n");

    for(i = 0; i < n; i++)
    {
        printf("%d ", arr[i]);
    }
}

return 0;
```

krati_gupta@DESKTOP-6N3A075

Enter the element to search: 56

Element not found

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array10.c -o array10
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array10
```

Enter the number of elements: 5

Enter elements in sorted order:

10

20

30

40

50

Enter the element to search: 40

Element found at index 3

```
krati_gupta@DESKTOP-6N3A075:~$ nano array11.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array 11.c -o array11
```

cc1: fatal error: 11.c: No such file or directory
compilation terminated.

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array11.c -o array11
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array11
```

Enter the number of elements: 2

Enter elements in sorted order:

10

20

Enter the element to insert: 10

Array after insertion:

```
10 10 20 krati_gupta@DESKTOP-6N3A075:~$ nano array12.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array12.c -o array12
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array12
```

Enter the number of elements: 3

Enter the elements:

10

20

30

Enter the element to insert: 10

Enter the position (0 to 3): 2

Array after insertion:

```
10 20 10 30 krati_gupta@DESKTOP-6N3A075:~$
```

30

40

50

Enter the element to search: 40

Element found at index 3

krati_gupta@DESKTOP-6N3A075:~\$ nano array11.c

krati_gupta@DESKTOP-6N3A075:~\$ gcc array 11.c -o array11

cc1: fatal error: 11.c: No such file or directory
compilation terminated.

krati_gupta@DESKTOP-6N3A075:~\$ gcc array11.c -o array11

krati_gupta@DESKTOP-6N3A075:~\$./array11

Enter the number of elements: 2

Enter elements in sorted order:

10

20

Enter the element to insert: 10

Array after insertion:

10 10 20 krati_gupta@DESKTOP-6N3A075:~\$ nano array12.c

krati_gupta@DESKTOP-6N3A075:~\$ gcc array12.c -o array12

krati_gupta@DESKTOP-6N3A075:~\$./array12

Enter the number of elements: 3

Enter the elements:

10

20

30

Enter the element to insert: 10

Enter the position (0 to 3): 2

Array after insertion:

10 20 10 30 krati_gupta@DESKTOP-6N3A075:~\$ nano array13.c

krati_gupta@DESKTOP-6N3A075:~\$ gcc array13.c -o array13

array13.c: In function 'main':

array13.c:27:18: error: expected ';' before '}' token

27 |

break

}

krati_gupta@DESKTOP-6N3A075:~\$ nano array13.c

krati_gupta@DESKTOP-6N3A075:~\$ nano array

```
krati_gupta@DESKTOP-6N3A075:~$ nano array13.c
krati_gupta@DESKTOP-6N3A075:~$ gcc array13.c -o array13
array13.c: In function 'main':
```

```
array13.c:27:18: error: expected ';' before '}' token
   27 |         break
      |                ^
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano array13.c
krati_gupta@DESKTOP-6N3A075:~$ gcc array13.c -o array13
array13.c: In function 'main':
```

```
array13.c:26:18: error: expected ';' before '}' token
   26 |         break
      |                ^
```

```
   27 |     }
      |     ~
array13.c:51:1: error: expected declaration or statement at end of input
   51 | }
      | ^
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano array13.c
krati_gupta@DESKTOP-6N3A075:~$ gcc array13.c -o array13
array13.c: In function 'main':
array13.c:51:1: error: expected declaration or statement at end of input
   51 | }
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano array13.c
krati_gupta@DESKTOP-6N3A075:~$ gcc array13.c -o array13
krati_gupta@DESKTOP-6N3A075:~$ ./array13
```

Enter the number of elements: 2

Enter the elements:

10

20

Enter the element to delete: 10

Array after deletion:

20 krati_gupta@DESKTOP-6N3A075:~\$

```
array13.c: In function 'main':  
array13.c:26:18: error: expected ';' before '}' token
```

```
26 |         break
```

```
27 |     }
```

```
array13.c:51:1: error: expected declaration or statement at end of input
```

```
51 | }
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano array13.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array13.c -o array13
```

```
array13.c: In function 'main':
```

```
array13.c:51:1: error: expected declaration or statement at end of input
```

```
51 | }
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano array13.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array13.c -o array13
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array13
```

```
Enter the number of elements: 2
```

```
Enter the elements:
```

```
10
```

```
20
```

```
Enter the element to delete: 10
```

```
Array after deletion:
```

```
20 krati_gupta@DESKTOP-6N3A075:~$ nano array13.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano array14.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc array14.c -o array14
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./array14
```

```
Enter the number of elements: 3
```

```
Enter the elements:
```

```
10
```

```
20
```

```
80
```

```
Largest = 80
```

```
Second largest = 20
```

```
krati_gupta@DESKTOP-6N3A075:~$
```

GNU nano 7.2

array13.c

```
#include <stdio.h>
int main()
{
    int arr[100];
    int n, i, element;
    int position = -1;

    printf("Enter the number of elements: ");
    scanf("%d", &n);

    printf("Enter the elements:\n");

    for(i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }

    printf("Enter the element to delete: ");
    scanf("%d", &element);

    for(i = 0; i < n; i++)
    {
        if(arr[i] == element)
        {
            position = i;
            break;
        }
    }

    if(position == -1)
    {
        printf("Element not found\n");
    }
    else
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^ Replace

^K Cut
^U Paste

[Read 51 lines]
^T Execute
^J Justify

^C Location
^/ Go To Line

M-U Undo
M-E Redo

M-A Set
M-6 Copy

ENG
IN



Thunderstorm w...
In effect



Search

acer

```
for(i = 0; i < n; i++)
{
    if(arr[i] == element)
    {
        position = i;
        break;}
}

if(position == -1)
{
    printf("Element not found\n");
}
else
{
    for(i = position; i < n - 1; i++)
    {
        arr[i] = arr[i + 1];
    }

    n--;

    printf("Array after deletion:\n");

    for(i = 0; i < n; i++)
    {
        printf("%d ", arr[i]);
    }

    return 0;
}
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^/ Go To Line

M-U Undo
M-E Redo

M-A Set Mark
M-6 Copy

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int arr[100];
```

```
    int n, i;
```

```
    int largest, secondLargest;
```

```
    int foundSecond = 0;
```

```
    printf("Enter the number of elements: ");
```

```
    scanf("%d", &n);
```

```
    if(n < 2)
```

```
    {
```

```
        printf("At least two elements are required.\n");
```

```
        return 0;
```

```
    }
```

```
    printf("Enter the elements:\n");
```

```
    for(i = 0; i < n; i++)
```

```
    {
```

```
        scanf("%d", &arr[i]);
```

```
    }
```

```
    largest = arr[0];
```

```
    for(i = 1; i < n; i++)
```

```
    {
```

```
        if(arr[i] > largest)
```

```
        {
```

```
            largest = arr[i];
```

```
        }
```

[Read 59 lines]

^C Location
^/ Go To Line

M-U Undo
M-E Redo

M-A
M-6

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify



Search

```
for(i = 1; i < n; i++)
{
    if(arr[i] > largest)
    {
        largest = arr[i];
    }
}

for(i = 0; i < n; i++)
{
    if(arr[i] < largest)
    {
        if(foundSecond == 0 || arr[i] > secondLargest)
        {
            secondLargest = arr[i];
            foundSecond = 1;
        }
    }
}

if(foundSecond == 0)
{
    printf("There is no second largest distinct element.\n");
}
else
{
    printf("Largest = %d\n", largest);
    printf("Second largest = %d\n", secondLargest);
}

return 0;
```

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^/ Go To Line

M-U Undo
M-E Redo

M-A
M-6