

```
#include <stdio.h>
```

```
int main() {
```

```
    float percentage;
```

```
    printf("Enter percentage (0-100): ");
```

```
    scanf("%f", &percentage);
```

```
    if (percentage >= 90 && percentage <= 100)
```

```
        printf("Grade A\n");
```

```
    else if (percentage >= 80 && percentage < 90)
```

```
        printf("Grade B\n");
```

```
    else if (percentage >= 70 && percentage < 80)
```

```
        printf("Grade C\n");
```

```
    else if (percentage >= 60 && percentage < 70)
```

```
        printf("Grade D\n");
```

```
    else if (percentage >= 0 && percentage < 60)
```

```
        printf("Grade F\n");
```

```
    else
```

```
        printf("Invalid percentage!\n");
```

```
    return 0;
```

```
}
```

```
#include <stdio.h>
#include <math.h>

int main() {
    float a, b, c, discriminant, root1, root2, realPart, imagPart;
    printf("Enter coefficients a, b and c: ");
    scanf("%f %f %f", &a, &b, &c);

    discriminant = b * b - 4 * a * c;

    if (discriminant > 0) {
        root1 = (-b + sqrt(discriminant)) / (2 * a);
        root2 = (-b - sqrt(discriminant)) / (2 * a);
        printf("Roots are real and different: %.2f and %.2f\n", root1, root2);
    } else if (discriminant == 0) {
        root1 = root2 = -b / (2 * a);
        printf("Roots are real and same: %.2f and %.2f\n", root1, root2);
    } else {
        realPart = -b / (2 * a);
        imagPart = sqrt(-discriminant) / (2 * a);
        printf("Roots are complex and different: %.2f + %.2fi and %.2f - %.2fi\n", realPart, imagPart, realPart, imagPart);
    }
    return 0;
}
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc quadratic.c -o quadratic -lm
krati_gupta@DESKTOP-6N3A075:~$ ./quadratic
Enter coefficients a, b and c: 5 6 8
Roots are complex and different: -0.60 + 1.11i and -0.60 - 1.11i
krati_gupta@DESKTOP-6N3A075:~$ gcc quadratic.c -o quadratic -lm
krati_gupta@DESKTOP-6N3A075:~$ ./quadratic
Enter coefficients a, b and c: 15 12 13
Roots are complex and different: -0.40 + 0.84i and -0.40 - 0.84i
krati_gupta@DESKTOP-6N3A075:~$ gcc quadratic.c -o quadratic -lm
krati_gupta@DESKTOP-6N3A075:~$ ./quadratic
Enter coefficients a, b and c: 2 5 3
Roots are real and different: -1.00 and -1.50
krati_gupta@DESKTOP-6N3A075:~$ graades.c
graades.c: command not found
krati_gupta@DESKTOP-6N3A075:~$ nano grades.c
krati_gupta@DESKTOP-6N3A075:~$ nano grades.c
krati_gupta@DESKTOP-6N3A075:~$ gcc grade.c -o grade
cc1: fatal error: grade.c: No such file or directory
compilation terminated.
krati_gupta@DESKTOP-6N3A075:~$ gcc grades.c -o grades
krati_gupta@DESKTOP-6N3A075:~$ ./grades
Enter percentage (0-100): 65
Grade D
krati_gupta@DESKTOP-6N3A075:~$ nano largest .c
krati_gupta@DESKTOP-6N3A075:~$ nano largest.c
krati_gupta@DESKTOP-6N3A075:~$ gcc largest.c -o largest
krati_gupta@DESKTOP-6N3A075:~$ ./largset
-bash: ./largset: No such file or directory
krati_gupta@DESKTOP-6N3A075:~$ gcc largest.c
krati_gupta@DESKTOP-6N3A075:~$ gcc largest.c -o largest
krati_gupta@DESKTOP-6N3A075:~$ ./largest
Enter three numbers: 2 4 5
The largest number is 5.00
krati_gupta@DESKTOP-6N3A075:~$
```

GNU nano 7.2

```
#include<stdio.h>
```

```
int main(){
```

```
float num1,num2,num3;
```

```
printf("Enter three numbers: ");
```

```
scanf("%f %f %f", &num1,&num2,&num3);
```

```
if (num1 >= num2 && num1 >= num3) {
```

```
    printf("The largest number is %.2f\n",num1);
```

```
} else if (num2>= num1 && num2 >= num3){
```

```
    printf("The largest number is %.2f\n",num2);
```

```
}else{
```

```
printf("The largest number is %.2f\n", num3);
```

```
}
```

```
return 0;
```

```
}
```