

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int a, b, c;
```

```
    printf("Enter three sides: ");
```

```
    scanf("%d %d %d", &a, &b, &c);
```

```
    if (a == b && b == c)
```

```
    {
```

```
        printf("Equilateral triangle");
```

```
    }
```

```
    else if (a == b || b == c || a == c)
```

```
    {
```

```
        printf("Isosceles triangle");
```

```
    }
```

```
    else
```

```
    {
```

```
        printf("Scalene triangle");
```

```
    }
```

```
    return 0;
```

```
}
```

```
prati_gupta@DESKTOP-6N3A075:~$ ./operator
```

```
Enter operator (+, -, *, /, %):
```

```
Enter two numbers: 45 56
```

```
Result: 101.00
```

```
prati_gupta@DESKTOP-6N3A075:~$
```

```
printf("Enter two numbers: ");
scanf("%lf %lf", &num1, &num2);

switch (op) {
    case '+':
        printf("Result: %.2lf\n", num1 + num2);
        break;
    case '-':
        printf("Result: %.2lf\n", num1 - num2);
        break;
    case '*':
        printf("Result: %.2lf\n", num1 * num2);
        break;
    case '/':
        if (num2 != 0)
            printf("Result: %.2lf\n", num1 / num2);
        else
            printf("Error: Division by zero\n");
        break;
    case '%':
        if ((int)num2 != 0)
            printf("Result: %d\n", (int)num1 % (int)num2);
        else
            printf("Error: Division by zero\n");
        break;
    default:
        printf("Invalid operator entered.\n");
}

return 0;
```

GNU nano 7.2

membership.c

```
#include <stdio.h>

int main() {
    int days;
    printf("Enter number of late days: ");
    scanf("%d", &days);

    if (days <= 0) {
        printf("No fine.\n");
    } else if (days <= 5) {
        printf("Total fine: ₹%d\n", days * 2);
    } else if (days <= 10) {
        printf("Total fine: ₹%d\n", (5 * 2) + (days - 5) * 4);
    } else if (days <= 30) {
        printf("Total fine: ₹%d\n", (5 * 2) + (5 * 4) + (days - 10) * 6);
    } else {
        printf("Membership Cancelled.\n");
    }

    return 0;
}
```

[Wrote 21 lines]

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify

^C Location
^/ Go To Line

M-U Undo
M-E Redo

M-A Set Mark
M-6 Copy

```
include <stdio.h>
```

```
int main() {  
    int days;  
    printf("Enter number of late days: ");  
    scanf("%d", &days);  
  
    if (days <= 0) {  
        printf("No fine.\n");  
    } else if (days <= 5) {  
        printf("Total fine: ₹%d\n", days * 2);  
    } else if (days <= 10) {  
        printf("Total fine: ₹%d\n", (5 * 2) + (days - 5) * 4);  
    } else if (days <= 30) {  
        printf("Total fine: ₹%d\n", (5 * 2) + (5 * 4) + (days - 10) * 6);  
    } else {  
        printf("Membership Cancelled.\n");  
    }  
  
    return 0;  
}
```



G Help
X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

^T Execute
^J Justify



```
krati_gupta@DESKTOP-6N3A075:~$ nano profit.c
krati_gupta@DESKTOP-6N3A075:~$ gcc profit.c -o profit
krati_gupta@DESKTOP-6N3A075:~$ ./profit
Enter Cost Price (CP): 100
Enter Selling Price (SP): 180
Profit = 80.00
Profit Percentage = 80.00%
krati_gupta@DESKTOP-6N3A075:~$
```

```
#include <stdio.h>
```

```
int main() {
```

```
    float cp, sp, profit, loss, profit_percentage, loss_percentage;
```

```
    // Step 1: User se Cost Price aur Selling Price input lo
```

```
    printf("Enter Cost Price (CP): ");
```

```
    scanf("%f", &cp);
```

```
    printf("Enter Selling Price (SP): ");
```

```
    scanf("%f", &sp);
```

```
    // Step 2: Check karo ki profit hai ya loss
```

```
    if (sp > cp) {
```

```
        profit = sp - cp;
```

```
        profit_percentage = (profit / cp) * 100;
```

```
        printf("Profit = %.2f\n", profit);
```

```
        printf("Profit Percentage = %.2f%%\n", profit_percentage);
```

```
    }
```

```
    else if (cp > sp) {
```

```
        loss = cp - sp;
```

```
        loss_percentage = (loss / cp) * 100;
```

```
        printf("Loss = %.2f\n", loss);
```

```
        printf("Loss Percentage = %.2f%%\n", loss_percentage);
```

```
    }
```

```
    else {
```

```
        printf("No Profit, No Loss.\n");
```

```
    }
```

```
    return 0;
```

```
}
```

```
#include <stdio.h>
```

```
int main() {  
    float units, bill = 0;  
    printf("Enter units consumed: ");  
    scanf("%f", &units);  
  
    if (units <= 0) {  
        bill = 0;  
    } else if (units <= 100) {  
        bill = units * 5;  
    } else if (units <= 200) {  
        bill = (100 * 5) + (units - 100) * 7;  
    } else if (units <= 300) {  
        bill = (100 * 5) + (100 * 7) + (units - 200) * 10;  
    } else {  
        bill = (100 * 5) + (100 * 7) + (100 * 10) + (units - 300) * 12;  
    }  
  
    printf("Total Electricity Bill: ₹%.2f\n", bill);  
  
    return 0;  
}
```

```
#include <stdio.h>
```

```
int main() {
```

```
    char op;
```

```
    double num1, num2;
```

```
    printf("Enter operator (+, -, *, /, %%): ");
```

```
    scanf(" %c", &op);
```

```
    printf("Enter two numbers: ");
```

```
    scanf("%lf %lf", &num1, &num2);
```

```
    switch (op) {
```

```
        case '+':
```

```
            printf("Result: %.2lf\n", num1 + num2);
```

```
            break;
```

```
        case '-':
```

```
            printf("Result: %.2lf\n", num1 - num2);
```

```
            break;
```

```
        case '*':
```

```
            printf("Result: %.2lf\n", num1 * num2);
```

```
            break;
```

```
        case '/':
```

```
            if (num2 != 0)
```

```
                printf("Result: %.2lf\n", num1 / num2);
```

```
            else
```

```
                printf("Error: Division by zero\n");
```

```
            break;
```

```
        case '%':
```

```
            if ((int)num2 != 0)
```

```
                printf("Result: %d\n", (int)num1 % (int)num2);
```

```
            else
```

```
                printf("Error: Division by zero\n");
```

```
bills.c:1:9: error: expected '=', ',', ';', 'asm' or '__attribute__' before '<' token
```

```
1 | include <stdio.h>
  |         ^
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano bills.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc bills.c -o bills
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./bills
```

```
Enter units consumed: 15
```

```
Total Electricity Bill: ₹75.00
```

```
krati_gupta@DESKTOP-6N3A075:~$
```

Command 'nnao' not found, did you mean:

command 'nano' from snap nano (9.2)

command 'nano' from deb nano (7.2-2ubuntu0.2)

See 'snap info <snapname>' for additional versions.

```
krati_gupta@DESKTOP-6N3A075:~$ nano membership.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc membership.c -o membership
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./membership
```

Enter number of late days: 3

Total fine: ₹6

```
krati_gupta@DESKTOP-6N3A075:~$ nano bills.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc bills.c -o bills
```

```
bills.c:1:9: error: expected '=', ',', ';', 'asm' or '__attribute__' before '<' token
```

```
1 | include <stdio.h>
```

```
|
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano bills.c
```

```
krati_gupta@DESKTOP-6N3A075:~$ gcc bills.c -o bills
```

```
krati_gupta@DESKTOP-6N3A075:~$ ./bills
```

```
#include <stdio.h>
```

```
int main() {  
    float units, bill = 0;  
    printf("Enter units consumed: ");  
    scanf("%f", &units);  
  
    if (units <= 0) {  
        bill = 0;  
    } else if (units <= 100) {  
        bill = units * 5;  
    } else if (units <= 200) {  
        bill = (100 * 5) + (units - 100) * 7;  
    } else if (units <= 300) {  
        bill = (100 * 5) + (100 * 7) + (units - 200) * 10;  
    } else {  
        bill = (100 * 5) + (100 * 7) + (100 * 10) + (units - 300) * 12;  
    }  
  
    printf("Total Electricity Bill: ₹%.2f\n", bill);  
  
    return 0;  
}
```

```
krati_gupta@DESKTOP-6N3A075:~$ nano profit.c
krati_gupta@DESKTOP-6N3A075:~$ gcc profit.c -o profit
krati_gupta@DESKTOP-6N3A075:~$ ./profit
Enter Cost Price (CP): 100
Enter Selling Price (SP): 180
Profit = 80.00
Profit Percentage = 80.00%
krati_gupta@DESKTOP-6N3A075:~$ nano membership.c
krati_gupta@DESKTOP-6N3A075:~$ gcc membership.c -o profit
membership.c:1:10: fatal error: stdio.stdio.h: No such file or directory
   1 | #include <stdio.stdio.h>
     |               ^~~~~~
compilation terminated.
krati_gupta@DESKTOP-6N3A075:~$ nano membership.c
krati_gupta@DESKTOP-6N3A075:~$ gcc membership.c -o profit
krati_gupta@DESKTOP-6N3A075:~$ ./membership
-bash: ./membership: No such file or directory
krati_gupta@DESKTOP-6N3A075:~$ gcc membership.c -o membership
krati_gupta@DESKTOP-6N3A075:~$ ./ membership
-bash: ./: Is a directory
krati_gupta@DESKTOP-6N3A075:~$ nnao membership.c
Command 'nnao' not found, did you mean:
  command 'nano' from snap nano (9.2)
  command 'nano' from deb nano (7.2-2ubuntu0.2)
See 'snap info <snapname>' for additional versions.
krati_gupta@DESKTOP-6N3A075:~$ nano membership.c
krati_gupta@DESKTOP-6N3A075:~$ gcc membership.c -o membership
krati_gupta@DESKTOP-6N3A075:~$ ./membership
Enter number of late days: 3
Total fine: ₹6
krati_gupta@DESKTOP-6N3A075:~$
```