

TP 5 React Native :

Installer React Navigation et dépendances

```
npm install @react-navigation/drawer
npm install react-native-gesture-handler
react-native-reanimated
```

Mise en place du AuthContext

Créer un contexte global pour gérer si l'utilisateur est connecté ou pas.

/context/AuthContext.js

```
import { createContext, useState } from "react";

export const AuthContext = createContext();

export default function AuthProvider({ children }) {
  const [user, setUser] = useState(null);

  const login = (name) => {
    setUser({ username: name });
  };

  const logout = () => setUser(null);

  return (
    <AuthContext.Provider value={{ user, login, logout }}>
      {children}
    </AuthContext.Provider>
  );
}
```

Navigation conditionnelle

App.js

```
import { NavigationContainer } from "@react-navigation/native";
import AuthProvider, { AuthContext } from "../context/AuthContext";
import AppDrawer from "../navigation/AppDrawer";
import LoginScreen from "../screens/LoginScreen";
import { useContext } from "react";

function RootNavigator() {
  const { user } = useContext(AuthContext);

  return user ? <AppDrawer /> : <LoginScreen />;
}

export default function App() {
  return (
    <AuthProvider>
      <NavigationContainer>
        <RootNavigator />
      </NavigationContainer>
    </AuthProvider>
  );
}
```

Login Screen

/screens/LoginScreen.js

```
import { useState, useContext } from "react";
import { View, Text, TextInput, Button, StyleSheet } from "react-native";
import { AuthContext } from "../../context/AuthContext";

export default function LoginScreen() {
  const [name, setName] = useState("");
  const { login } = useContext(AuthContext);

  return (
    <View style={styles.container}>
      <Text style={styles.title}>Connexion</Text>

      <TextInput
        style={styles.input}
        placeholder="Votre nom"
      />
    </View>
  );
}
```

```

        value={name}
        onChangeText={setName}
      />

      <Button title="Se connecter" onPress={() => login(name)} />
    </View>
  );
}

const styles = StyleSheet.create({
  container: {
    flex: 1,
    justifyContent: "center",
    padding: 20,
  },
  title: { fontSize: 28, marginBottom: 20, textAlign: "center" },
  input: {
    borderWidth: 1,
    borderColor: "#ccc",
    marginBottom: 20,
    padding: 10,
    borderRadius: 6,
  },
});

```

Drawer Navigator

/navigation/AppDrawer.js

```

import { createDrawerNavigator } from "@react-navigation/drawer";
import AppStack from "../AppStack";
import ProfileScreen from "../screens/ProfileScreen";

const Drawer = createDrawerNavigator();

export default function AppDrawer() {
  return (
    <Drawer.Navigator>
      <Drawer.Screen name="Tâches" component={AppStack} />
      <Drawer.Screen name="Profil" component={ProfileScreen} />
    </Drawer.Navigator>
  );
}

```

/navigation/AppStack.js

```
import { createNativeStackNavigator } from "@react-navigation/native-stack";
import TodoListScreen from "../screens/TodoListScreen";
import TodoDetailsScreen from "../screens/TodoDetailsScreen";

const Stack = createNativeStackNavigator();

export default function AppStack() {
  return (
    <Stack.Navigator>
      <Stack.Screen name="Liste" component={TodoListScreen} />
      <Stack.Screen name="Détails" component={TodoDetailsScreen} />
    </Stack.Navigator>
  );
}
```

TodoList - /screens/TodoListScreen.js

```
import { useState, useEffect } from "react";
import { View, Text, Button, FlatList, TouchableOpacity } from "react-native";

export default function TodoListScreen({ navigation }) {
  const [todos, setTodos] = useState([]);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    console.log("Chargement des tâches...");

    setTimeout(() => {
      setTodos([
        { id: 1, title: "Faire les courses" },
        { id: 2, title: "Sortir le chien" },
        { id: 3, title: "Coder une app RN" },
      ]);
      setLoading(false);
    }, 1000);
  }, []); // [] => exécute une seule fois au montage

  if (loading) {
    return (
      <View style={{ flex: 1, justifyContent: "center", alignItems: "center" }}>
        <Text style={{ fontSize: 20 }}>Chargement...</Text>
      </View>
    );
  }

  return (
```

```

<View style={{ flex: 1, padding: 20 }}>
  <Text style={{ fontSize: 24, marginBottom: 10 }}>Mes tâches</Text>

  <FlatList
    data={todos}
    keyExtractor={(i) => i.id.toString()}
    renderItem={({ item }) => (
      <TouchableOpacity
        onPress={() =>
          // TODO : naviguer vers "Détails" avec id + title
        }
      >
        <Text style={{ padding: 10, fontSize: 18 }}>{item.title}</Text>
      </TouchableOpacity>
    )}
  />
</View>
);
}

```

Écran Détails avec paramètres

/screens/ToDoDetailsScreen.js

```

import { View, Text } from "react-native";

export default function ToDoDetailsScreen({ route }) {
  const { id, title } = route.params;

  return (
    <View style={{ flex: 1, justifyContent: "center", alignItems: "center" }}>
      <Text style={{ fontSize: 30 }}>{title}</Text>
      <Text style={{ fontSize: 20, marginTop: 10 }}>ID : {id}</Text>
    </View>
  );
}

```

Profil + Déconnexion :

/screens/[ProfileScreen.js](#)

```
import { useContext } from "react";

import { View, Text, Button } from "react-native";

import { AuthContext } from "../context/AuthContext";

export default function ProfileScreen() {

  const { user, logout } = useContext(AuthContext);

  return (

    <View style={{ flex: 1, justifyContent: "center", alignItems: "center" }}>

      <Text style={{ fontSize: 24 }}>Utilisateur : {user.username}</Text>

      <Button title="Se déconnecter" onPress={logout} />

    </View>

  );
}
```

Exercice supplémentaire : Composant AppBar

Créer un composant AppBar dans le dossier /components.

- Le composant doit recevoir un titre via les props.
- Il doit afficher ce titre dans une barre placée en haut de l'écran.

Ajouter un bouton "Logout" à droite dans l'AppBar.

- Ce bouton doit appeler la fonction `logout()` provenant du `AuthContext`.

Intégrer le composant AppBar dans `TodoListScreen`

- Le titre affiché doit être : "Mes tâches".
- Vérifiez que l'AppBar apparaît bien au-dessus de la liste des tâches.