BRAND IDENTITY SYSTEM

Nexit Construction

Structural N



IDENTITY DIRECTION

Civil work, building and construction

Reliability and Excellence

The mark

A clear signature for the company name, service and core message.

NEXIT
CONSTRUCTION LTD.
RELIABILITY AND EXCELLENCE

FULL LOCKUP

Use the complete logo where the company name and service need to read together.

Design idea

Beam-like strokes build a strong N. Red angles add a sense of direction, and the grounded base gives the full lockup a stable finish.

Key elements

- Structural beam geometry
- A red direction cue
- A stable baseline



EMBLEM

Color palette

A small, repeatable set of colors for clear recognition across print and screens.

PRIMARY

#252525

Use for the main brand field and strongest text.

ACCENT

#D84135

Use for key details, dividers and highlights.

SUPPORT

#EFEFEB

Use for secondary emphasis and warm surfaces.

LIGHT FIELD

#FFFFFF

Use behind the logo for maximum clarity.

Recommended balance



Primary 55% Accent 25% Support 20%

Red and black follow the supplied brief. Warm white is a supporting background for print.

Type and clear space

Keep the logo readable by giving it a consistent hierarchy and breathing room.

TYPE STYLE

Use a bold geometric sans for the company name and a neutral sans for project details. Keep the service line lighter than the wordmark.

DISPLAY

Nexit Construction

SUPPORTING LINE

CIVIL WORK, BUILDING AND CONSTRUCTION

Reliability and Excellence

CLEAR SPACE



Keep at least one emblem-width of clear space around the lockup.

MINIMUM SIZE

Full lockup: 28 mm wide / Emblem: 12 mm high

Recommended starting values; check legibility on the final material.

Applications

Suggested placements show how the identity can move from formal to compact use.



SITE BOARD

Use the full lockup when the company name must read at a distance.



VEHICLE PANEL

Keep the service line and slogan secondary to the company name.



HARD HAT / PROFILE

Use the emblem alone when space is limited.

USE GUIDANCE

Use the full lockup on site boards and fleet panels. Keep the emblem alone for small hard-hat marks and profile images.