Project: Worked examples
Title: ISO 286 limits and fits
Status: DRAFT Author: TempestOS (2026-10-23) Checker: — (—) Issued: —

1. Scope and method

Hole and shaft limits for a nominal size and tolerance classes, the resulting fit (clearance, transition or interference) and its extreme values, from the ISO 286-1 formulae.
i = 0.45·D^(1/3) + 0.001·D (µm) at the geometric mean D of the size step; ITn = multiplier × i; fundamental deviations by letter from the published formulae; hole deviations by the general rule (EI = −es for A–H; ES = −ei + Δ for K–ZC). Limits = nominal + deviations; fit extremes from the limits.
Ref: ISO 286-1:2010 §4, §5 — Bases of tolerances, deviations and fits — tolerance grades and fundamental deviations
Ref: ISO 286-2:2010 — Tables of standard tolerance classes and limit deviations (not reproduced)

2. Inputs

SYMBOL	DESCRIPTION	VALUE	UNIT	SOURCE	VALID RANGE
D	Nominal size	25	mm	drawing: DRG-SHAFT-12 rev A	1 … 500 mm
hole_letter	Hole fundamental deviation letter	H		spec: DRG-SHAFT-12 note 3: H7/g6	any
hole_grade	Hole IT grade	7		spec: DRG-SHAFT-12 note 3	5 … 11
shaft_letter	Shaft fundamental deviation letter	g		spec: DRG-SHAFT-12 note 3	any
shaft_grade	Shaft IT grade	6		spec: DRG-SHAFT-12 note 3	4 … 11

3. Assumptions

A1. IT values and fundamental deviations are the unrounded results of the ISO 286-1 formulae at the geometric mean of the size step. (The tabulated values apply the standard's own rounding and may differ by about 1 µm; enter overrides from a released reference record where the tabulated value governs.)
A2. Hole deviations follow the general rule from the shaft deviations, with Δ = ITn − IT(n−1) where the standard applies it. (Table-specific departures in the standard are not reproduced; use the overrides where they govern.)

4. Working

```
[6] D_step = size step (lower, upper]                    ISO 286-1 §4
= (18, 30] mm
= 23.238 mm
```
Geometric mean of the size step

```
[7] i = 0.45·D^(1/3) + 0.001·D                           ISO 286-1 §5
= D = 23.238 mm
= 1.3074 µm
```
Standard tolerance unit

```
[8] IT_hole = IT7                                        ISO 286-1 §5
= 16 × i
= 20.918 µm
```
Hole tolerance

[9] IT_shaft = IT6 ISO 286-1 §5
= 10 × i
= 13.074 µm
Shaft tolerance
[10] es = fundamental deviation 'g' ISO 286-1 §5
= -2.5·D^0.34
= -7.2853 µm
Shaft upper deviation
[11] ei = es - IT_shaft ISO 286-1 §5
= -7.2853 - 13.074
= -20.359 µm
Shaft lower deviation
[12] ES = EI + IT_hole ISO 286-1 §5
= 0 + 20.918
= 20.918 µm
Hole upper deviation
[13] EI = fundamental deviation 'H' ISO 286-1 §5
= -es of the same letter
= 0 µm
Hole lower deviation
[14] D_hole_max = D + ES
= 25 mm + 20.918 µm
= 25.021 mm
Hole maximum
[15] D_hole_min = D + EI
= 25 mm + 0 µm
= 25 mm
Hole minimum
[16] d_shaft_max = D + es
= 25 mm + -7.2853 µm
= 24.993 mm
Shaft maximum
[17] d_shaft_min = D + ei
= 25 mm + -20.359 µm
= 24.98 mm
Shaft minimum
[18] c_max = ES - ei
= 20.918 µm - (-20.359 µm)
= 41.277 µm
Maximum clearance (negative: minimum interference)
[19] c_min = EI - es
= 0 µm - (-7.2853 µm)
= 7.2853 µm
Minimum clearance (negative: maximum interference)
[20] i_max = es - EI
= (-7.2853 µm) - 0 µm
= -7.2853 µm
Maximum interference
[21] i_min = ei - ES
= (-20.359 µm) - 20.918 µm
= -41.277 µm
Minimum interference (negative: maximum clearance)

```
[22] fit = fit class
= H7/g6
= "clearance"
```
Fit kind: clearance, transition or interference
```
[23] c_mean = (c_max + c_min) / 2
= (41.277 µm + 7.2853 µm) / 2
= 24.281 µm
```
Mean clearance

5. Results

SYMBOL	VALUE	DESCRIPTION
IT_hole	20.918 µm	Hole tolerance
IT_shaft	13.074 µm	Shaft tolerance
ES	20.918 µm	Hole upper deviation
EI	0 µm	Hole lower deviation
es	-7.2853 µm	Shaft upper deviation
ei	-20.359 µm	Shaft lower deviation
D_hole_max	25.021 mm	Hole maximum
D_hole_min	25 mm	Hole minimum
d_shaft_max	24.993 mm	Shaft maximum
d_shaft_min	24.98 mm	Shaft minimum
fit	"clearance"	Fit kind
c_max	41.277 µm	Maximum clearance
c_min	7.2853 µm	Minimum clearance
i_max	-7.2853 µm	Maximum interference
i_min	-41.277 µm	Minimum interference
c_mean	24.281 µm	Mean clearance

6. Checks (governing first)

RESULT	CHECK	DEMAND	CAPACITY	UTILISATION	REF
PASS	Fit classified	H7/g6	clearance	0	

7. Applicability

No warnings.

8. Verification

Template mech.iso286-fit@1.0.0 Content hash 546cca00925adbf3 Engine calc-engine/1.0.0
Known-answer cases passed 2/2 Test run 2026-10-23 12:00 UTC TempestOS 0.26.0