

Double-click on a text section to edit it.

If a small red "X" appears near the bottom-right corner of the text box it means there is text unable to be displayed because it does not fit in

Application Options:



Ghostshield Sila-Tek 3500 is a water based sodium densifier used as a primer to strengthen and harden concrete.

Substrates: Concrete

Coverage: One (1) concentrated gallon covers up to 1,000 square feet per coat; two (2) coats are required. Coverage varies based on porosity and texture of the substrate.

Surface Preparation: Surface should be clean, dry and free from previous sealers and contaminants. Protect surface from rain for 24 hours before and after application.

Tools: Use a low-pressure pump sprayer, 3/8" nap roller or brush.

Reconstitution Ratio: 1:3 (prior to use). If priming concrete mix one (1) gallon concentrate with four (4) gallons of water; if polishing concrete, mix one (1) gallon concentrate with three (3) gallons of water.

Warranty: KreteTek warrants that its manufactured products shall be free from material defects and will conform to formulation standards and contain all components in their proper proportion. Should any of the products be proven defective, the liability to KreteTek shall be limited to replacement of the material proven to be defective and shall in no case be liable otherwise or for incidental or consequential damages. KreteTek makes no warranties as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied. User shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. For complete instructions contact us at 855-KRETETEK (855-573-8383) or visit our website at ghostshield.com.

Application: Mix well prior to use. Apply uniformly. Use enough material to keep the surface wet for about a minute before substrate penetration. Broom out puddles thoroughly. Apply the second coat 30 minutes after the first.

Application Temperature Limits: Surface and air temperature must be between 40° - 90°F during application and for 8 hours following.

Drying Time: Dry-to-touch in two (2) hours. Allow 24 hours for pedestrian and heavy traffic.

Shelf Life: One (1) year in tightly sealed, unopened container. Keep from freezing and store in a cool, dry place.

Caution: Always test a small area of each surface to confirm suitability, coverage rate, and desired results before beginning overall application. Use appropriate protective equipment such as gloves and protective eyewear during mixing and application. Do not ingest. Avoid contact with eyes. In the case of contact, rinse immediately with plenty of water and seek medical attention.

Refer to the Material Safety Data Sheet (MSDS) prior to use, available at: <http://msds.ghostshield.com/silatek3500>



LOW VOC CONTENT



100-YEAR WARRANTY



PRODUCT & PACKAGING MADE IN U.S.A.

