

## RSS – AL 2

# Kevlar Tubular Webbing Descender

- ▶ Simple operation – Just squeeze lever to go!
- ▶ Closed System – Keep Debris and clothing out – prevents Jamming
- ▶ Passes/Exceeds NFPA Manner of Function (3478 lbs; 3034 lbs NFPA min.)
- ▶ 6# Horizontal Pull, 12# Vertical Pull
- ▶ Flat/Compact – Packs Well in SCBA FFRED, Pocket Pack or Egress Bag
- ▶ No Handles Protrude to Get Caught on Sill
- ▶ Utilizes 3/8” Kevlar Tubular Webbing, Exceeds 5000# tensile strength and is fire rated to withstand 860 degrees temperature rating



**RIT Safety Solutions, LLC**  
[www.RITSafetySolutions.com](http://www.RITSafetySolutions.com)  
800-254-2990



# NEW: RSS – AL 3

## Kevlar Rope Descender

- Simple operation – Just squeeze lever to go!
- Closed System – Keep Debris and clothing out - prevents Jamming
- Passes/Exceeds NFPA Manner of Function (3478 lbs; 3034 lbs NFPA min.)
- Standard with 6" Kevlar Lanyard w/ tri link for pre rigged attach point
- Flat/Compact – Packs Well in SCBA FFRED, Pocket Pack or Egress Bag
- No Handles Protrude to Get Caught on Sill
- Utilizes 7.5mm 100% Kevlar Rope – Exceeds 5000# tensile strength and is fire rated to withstand 860 degrees temperature rating



**RIT Safety Solutions, LLC**  
**[www.RITSafetySolutions.com](http://www.RITSafetySolutions.com)**  
**800-254-2990**

