



RIT SAFETY SOLUTIONS, LLC

CLASS II KEVLAR HARNESS

Working hard to keep workers safe.

CLASS II KEVLAR HARNESSES

All Harnesses can be made for external or internal use, please specify when ordering

- Class II Kevlar Harness w/ D Ring
- Class II Kevlar Harness w/ Steel Ladder Hook & D Ring
- Class II Kevlar Harness w/ CMC Hook & D Ring

AVAILABLE CUSTOMIZATION OPTIONS

- Center, left, OR right closures
- Internal OR external
- Attachments:
 - Ladder Hook
 - Positioning Hook
- Adjustable waist and leg straps for comfort
- Extra-large size available – up to 68" waist
- "A-Frame" prevents user from inverting during egress
- Can add padding (additional cost)

COMPONENTS & DATA

- Nylon Webbing 1 3/4"
 - 10,000# Tensile Strength
- Kevlar Webbing 1 3/4"
 - 10,000# Tensile Strength
 - Fire Rated at 860°F
 -
- Standards for Safety:
 - NFPA 1983 – Life Safety Rope and Equipment for Emergency Services, 2012 Edition

Without Padding →



← With Padding

This life safety harness meets the requirements of NFPA 1983 standard on life safety rope and equipment for emergency services, 2012 and the optional flame resistance requirements of NFPA 1983 Class II

Emergency services Class II Life Safety Harness in accordance with NFPA 1983-2012

For a complete list of certifications, or for further questions, please visit our website www.ritsafety.com