

# POCKET PACK ESCAPE SYSTEM

## NFPA 1983 LIFE SAFETY ROPE & EQUIPMENT FOR EMERGENCY SERVICES, 2012 EDITION

WEIGHT: 2lbs 13.6z (Webbing) 50 ft





WEIGHT: 3lbs 8z (Rope) 50 ft







1900 Enterprise Parkway, Suite H

Twinsburg, Ohio 44087

[www.ritsafetyolutions.com](http://www.ritsafetyolutions.com)

Component	Description
<p>RSS HOOK</p>  A red, curved metal hook with a black webbing strap attached to one end.	<p>RSS ANCHOR HOOK</p> <ul style="list-style-type: none"> <li>- CERTIFIED TO THE NFPA 1983 STANDARD ON LIFE SAFETY, 2012 EDITION <ul style="list-style-type: none"> <li>• Length – 7"</li> <li>• Width – 4.5"</li> <li>• Opening – 3"</li> <li>• Weight – 6.5 oz</li> </ul> </li> <li>- MBS of 23.7 kN</li> <li>- Red/Orange Fluorescent Cover (FR) over 1" Kevlar Pull Tab with 1 3/4" Folded Kevlar Webbing</li> </ul>
<p>Webbing</p>  A long, yellow webbing strap with black webbing at both ends.	<p>RSS- Tubular Webbing 7/16</p> <ul style="list-style-type: none"> <li>- Material and Construction 100% KEVLAR</li> <li>- Heat Rating for Fire Rated Webbing per NFPA</li> <li>- Burn "hang time" 300# weight <ul style="list-style-type: none"> <li>• Turn off at 8 minutes @ 400 Degrees C</li> </ul> </li> <li>- Weight 1.36 lbs per 50 ft</li> <li>- MBS 5,000 lbs</li> </ul>
<p>RSS-AL-2 WEBBING DESCENDER</p>  A metal descender device with a red hook and a yellow webbing strap.	<p>RSS-AL2 WEBBING DESCENDER</p> <ul style="list-style-type: none"> <li>- Material 6061 ALUMINUM</li> <li>- MBS 14.9 Kn, 3349 lbs</li> <li>- Horizontal Travel Force(in lbs) <ul style="list-style-type: none"> <li>• 6 POUNDS Dry AL-2</li> <li>• 12-16 POUNDS Wet AL-2</li> </ul> </li> </ul>
<p>RSS-AL-R ROPE DESCENDER</p>  A metal descender device with a red hook and a yellow rope.	<p>RSS-AL-R ROPE DESCENDER</p> <ul style="list-style-type: none"> <li>- Material 6061 ALUMINUM</li> <li>- MBS 14.9 Kn, 3349 lbs</li> <li>- Horizontal Travel Force(in lbs) <ul style="list-style-type: none"> <li>• 12 POUNDS Dry AL-R</li> <li>• 14-18 POUNDS Wet AL-R</li> </ul> </li> </ul>

<p>Carabiner – Option instead of Tri Link</p> 	<p>SMC LIGHT ALLOY</p> <ul style="list-style-type: none"> <li>- NFPA / ANSI CERTIFIED CARABINER WITH 3500 POUND GATE STRENGTH, G RATED TO 10,000 POUNDS</li> <li>- ¼ TURN AUTO LOCKING</li> <li>- Captive Pin YES</li> <li>- MBS G RATED 10,000 POUNDS</li> </ul>
<p>Pocket Bag</p> 	<p>Pocket Bag</p> <ul style="list-style-type: none"> <li>- Size 10"x10"x0.5"</li> <li>(Can adjust size for customization)</li> <li>- 1,000 Denier Cordura. Designed to hold complete egress components. The rope/webbing, hook and descender have designated compartments in the bag to keep the system organized and prevent tangling.</li> </ul>
<p>Single Belt</p> 	<p>Kevlar Single Belt - Certified</p> <ul style="list-style-type: none"> <li>- 1 ¾" 100 % KEVLAR WEBBING, 10,000+ POUNDS TENSILE STRENGTH</li> <li>- Fire Rated up to 860 Degrees F</li> <li>- Size adjustability STANDARD SIZE TO 54" X-LARGE TO 68"</li> <li>- Certified NFPA 1983-2012</li> </ul>
<p>Class II Harness</p> 	<p>Harness Class II (Kevlar or Nylon)</p> <ul style="list-style-type: none"> <li>- 1 ¾" 100 % KEVLAR WEBBING, 10,000+ POUNDS TENSILE STRENGTH</li> <li>- 2 Attachment Points</li> <li>- Fire Rated up to 860 Degrees F</li> <li>- Size adjustability STANDARD SIZE TO 54" X-LARGE TO 68 INCHES</li> <li>- Center, Right or Left Closure</li> <li>- "A Frame" prevents user from flipping over</li> <li>- Certified NFPA 1983-2012</li> </ul>

1900 Enterprise Parkway, Suite H

Twinsburg, Ohio 44087

800-254-2990

[www.ritsafetyolutions.com](http://www.ritsafetyolutions.com)