

# Algorithms and data structures 2: D&C

Boris Kirikov

24.9.2015

# Outline


- 0. Revision
- 1. Sums
- 2. Recurrent relations
- 3. Inversions
- 4. Karatsuba
- 5. Megainversions

# Estimating sums: Abel transform

**Th:**  $a_n, b_n, B_n = b_0 + \dots + b_n$

$$\sum_{n=0}^N a_n b_n = a_n B_n - \sum_{n=0}^{N-1} B_n (a_{n+1} - a_n)$$

## Estimating sums 2: integrals



## Estimating sums 3: Stolz–Cesàro theorem

**Th:**  $a_n, b_n$  – int seq.,  $b_n$  – strictly monotone,  $\neg \exists b_0: b_n \rightarrow b_0$ .

$$\lim \frac{a_{n+1} - a_n}{b_{n+1} - b_n} = l$$

$$\Rightarrow \lim \frac{a_n}{b_n} = l$$

# Generating functions

**Def:**  $a_0, a_1, \dots, a_n.$

$$\mathcal{A}(t) = \sum_{n=0}^{\infty} a_n t^n$$

# Generating functions

**Def:**  $a_0, a_1, \dots, a_n.$

$$\mathcal{A}(t) = \sum_{n=0}^{\infty} a_n t^n$$

**Sug:**

$$\sum x^n = \frac{1}{1-x}$$

# Master theorem

**Th:**  $a > 0, b > 1, d \geq 0$

$$T(n) = aT\left(\frac{n}{b}\right) + O(n^d)$$

$$T(n) = \begin{cases} O(n^d), & d > \log_b a \\ O(n^d \log n), & d = \log_b a \\ O(n^{\log_b a}), & d < \log_b a \end{cases}$$



## Back to algos: inversions

**Def:** An inversion in array is pair of indexes  $i, j$ :  $i < j$  and  $A_i > A_j$ .

**Task:** Given an array, find number of inversions in it.

## Back to algos: multiplication

How much operations it take to multiply two polynomials:

- ▶ of  $\deg = 2$ ?

## Back to algos: multiplication

How much operations it take to multiply two polynomials:

- ▶ of  $\deg = 2$ ?

$$(ax + b)(cx + d) = acx^2 + (ad + bc)x + bd$$

This is 4 multiplications, but. . .

## Back to algos: multiplication

How much operations it take to multiply two polynomials:

- ▶ of  $\deg = 2$ ?

$$(ax + b)(cx + d) = acx^2 + (ad + bc)x + bd$$

This is 4 multiplications, but. . .

$$(ad + bc) = (a + b)(c + d) - ac - bd$$

So we only need these three.

## Back to algos: multiplication

How much operations it take to multiply two polynomials:

- ▶ of  $\deg = 2$ ?

$$(ax + b)(cx + d) = acx^2 + (ad + bc)x + bd$$

This is 4 multiplications, but. . .

$$(ad + bc) = (a + b)(c + d) - ac - bd$$

So we only need these three.

- ▶ any degree?

## Back to algos: multiplication

How much operations it take to multiply two polynomials:

- ▶ of  $\deg = 2$ ?

$$(ax + b)(cx + d) = acx^2 + (ad + bc)x + bd$$

This is 4 multiplications, but. . .

$$(ad + bc) = (a + b)(c + d) - ac - bd$$

So we only need these three.

- ▶ any degree?

Yes, divide!

## Harder task: megainversions

**Def:** megainversion in array:  $i < j < k, A_i > A_j > A_k$ .

**Task:** the same.

## Harder task: megainversions

**Def:** megainversion in array:  $i < j < k, A_i > A_j > A_k$ .

**Task:** the same.

**Def:** one side inversion



EOF