

ByteBoost Workshop: Project Description

Shape-Constrained Boosted Symbolic Regression for Interpretable Neural Scaling Laws: A Cross-Testbed Investigation

1 Field of science

Computer Science: Machine Learning and Artificial Intelligence, specifically the foundations of large language models (neural scaling laws) and interpretable machine learning via symbolic regression. Secondary field: High-Performance Computing and computer architecture (cross-platform performance characterization).

2 Abstract / summary

Training a modern AI language model can cost millions of dollars, so researchers use scaling laws to predict performance from model size and training data before committing resources. These equations guide major hardware and budget decisions, but their mathematical form is usually chosen manually and then fitted to measured results.

Our project uses symbolic regression to discover the scaling-law equation directly from data. Symbolic regression searches many candidate formulas and returns an interpretable equation rather than a black-box model. Unconstrained searches, however, often produce formulas that fit existing measurements but extrapolate unrealistically, predicting negative error or worse performance with more data.

We therefore require every candidate formula to satisfy admissibility axioms: larger models and additional data cannot increase error; improvements must diminish with scale; error must remain positive; and performance must approach an irreducible floor. We mathematically certify these properties across the full domain of interest, not only at measured points ([Sections 4.2, 4.4 and 4.5](#)).

The formula is built incrementally from a standard scaling law, adding one correction at a time while preserving all guarantees ([Sections 4.3 and 4.4](#)). We also prove that the corrections improve fit without changing the irreducible error floor or the asymptotic rate of improvement. One search method rejects inadmissible corrections; another penalizes violations and drives them toward zero while bounding any remaining shortfall ([Section 4.6](#)).

The project has two computational bottlenecks. Model training will use Cerebras CS-3 systems on PSC’s Neocortex platform and will be compared with completed NVIDIA GPU runs ([Sections 3.1 and 3.2](#)). Formula discovery is a large CPU-bound search dominated by interval-arithmetic certification. Because it is highly parallel and relies mainly on scalar or imperfectly vectorized Python and JAX code, Stony Brook’s high-core-count AMA27 AmpereOne cluster is well suited to the workload ([Sections 3.1 and 4.4](#)).

Deliverables will include a certified scaling-law formula fitted to our training data, an open-source discovery library, and a concise methods report ([Section 5.2](#)). An initial set of trained models is already public ([Section 3.5](#)).

3 Key requirements

3.1 Testbed hardware (requested)

- **Neocortex (PSC):** Cerebras CS-3 wafer-scale systems for the model-pretraining grid in [Sections 3.4 and 3.5](#) (<https://www.psc.edu/resources/neocortex/>). Each CS-3 is built around a Wafer Scale Engine 3 (WSE-3) with on-chip SRAM and extreme memory bandwidth, so a model in our N range can stay on a single wafer without multi-GPU model parallelism. We use Neocortex only for pretraining; loss curves are compared to our existing NVIDIA GPU runs ([Section 3.2](#)).
- **AMA27 (Stony Brook Supercomputing Center / ACCESS):** Arm-based AmpereOne A192-32M cluster for the CPU-bound symbolic-regression search of [Section 4.3](#) and the certification inner loop of [Section 4.4](#). Per the ACCESS resource description, phase 1 deploys 312 single-socket compute nodes, each with a 192-core AmpereOne A192-32M CPU and 384 GB DDR5, linked by 200 Gbps NDR InfiniBand, with a 5 PB GPFS filesystem (<https://support.access-ci.org/affinity-groups/ama27>). AMA27 is the Stony Brook Arm testbed featured in ByteBoost 2.0 (in place of the retired Ookami A64FX system). We do *not* rely on A64FX-style 512-bit SVE or HBM: the GP/IA workload is population-parallel and largely scalar, so the useful AMA27 properties are Arm ISA diversity versus our AMD EPYC (x86) baselines, high core counts per node, and dense node count for concurrent candidate evaluation.

3.2 Baseline hardware (already available to us)

GPU baselines (pretraining comparisons): 200 NVIDIA GH200 superchips on DeltaAI at NCSA, plus a local four-GH200 cluster. **CPU baselines (search/certification comparisons):** three 256-core AMD EPYC (x86) machines, against which we will profile the AMA27 AmpereOne port.

3.3 Software and tools

PyTorch 2.x with FlashAttention for pretraining; `uv` for environment management and `Weights & Biases` for experiment logging [1]; `gplearn` for the hard-constrained symbolic-regression path of [Sections 4.3 and 4.4](#) with custom admissibility predicates [2]; Deep Symbolic Optimization (DSO) with a transformer-based controller for the soft-constrained path of [Section 4.6](#); JAX with custom JVP rules and a Python interval-arithmetic backend for the automatic-differentiation-plus-interval-arithmetic proof step of [Section 4.4](#).

3.4 Models

Decoder-only transformer language models in the LLaMA architecture [3], spanning roughly 10M–1.4B parameters, across several tokens-per-parameter ratios ($M = D/N$), following the Step Law protocol [4] and the overtraining regime of Gadre et al. [5], with μP / $\mu\text{Transfer}$ [6] to decouple optimization from scale.

3.5 Datasets

Wikipedia [7], RedPajama [8], and FineWeb-Edu [9] pretraining corpora; an already-public `colinear_scaling_models` collection on Hugging Face [10] (trained checkpoints and loss curves from an initial DeltaAI grid).

4 Method summary (technical)

4.1 Setup

Let N be the parameter count, D the training-token count, and $\mathcal{H} = \{h_1, \dots, h_m\}$ a finite set of remaining hyperparameters. For each coordinate $h \in \{N, D\} \cup \mathcal{H}$, let H_h be its finite set of admissible values and $\phi_h: H_h \rightarrow \mathbb{R}_{>0}$ a strictly monotone preprocessing map; write $\phi_i := \phi_{h_i}$ for brevity. The configuration space is the product $\mathbb{H} := \prod_{h \in \{N, D\} \cup \mathcal{H}} H_h$, with typical element $\mathbf{h} \in \mathbb{H}$ (so N, D, h_i denote the corresponding coordinates of $\mathbf{h}$). Let $L: \mathbb{H} \rightarrow \mathbb{R}$ be validation loss; we seek $\hat{L} \approx L$. We are given a labeled dataset $\mathcal{D} = \{(\mathbf{h}_\ell, L(\mathbf{h}_\ell))\}_{\ell=1}^n \subset \mathbb{H} \times \mathbb{R}$. For each scale variable $x \in \{N, D\}$ set $x_{\min} := \min H_x > 0$ and $x_{\max} := \max H_x$, treat x as continuous on $[x_{\min}, \infty)$, and take all derivatives with the other coordinates held fixed.

4.2 Admissibility axioms

$\hat{L}$ is *admissible* ($\hat{L} \in \mathcal{S}$) if it satisfies (A1)–(A6) below. Where an axiom mentions a scale variable x , it is imposed for each $x \in \{N, D\}$ with the other coordinates held fixed.

- (A1) **Monotone decrease.** $\frac{\partial \hat{L}}{\partial x} \leq 0$ for all $x \geq x_{\min}$.
- (A2) **Diminishing returns.** $\frac{\partial^2 \hat{L}}{\partial x^2} \geq 0$ for all $x \geq x_{\min}$.
- (A3) **Irreducible loss.** There is a positive *joint floor* L_∞ and, along each axis, a *marginal floor* L_x^∞ :
 - (i) *Joint floor.* There exists $L_\infty > 0$ such that $\hat{L}(\mathbf{h}) > L_\infty$ for every $\mathbf{h} \in \mathbb{H}$.
 - (ii) *Marginal floor.* For each $x \in \{N, D\}$ and every fixed choice of the other coordinates, the single-axis limit

$$L_x^\infty := \lim_{t \rightarrow \infty} \hat{L}(\mathbf{h})|_{x=t} \quad (1)$$

exists and is finite, and satisfies $L_x^\infty \geq L_\infty$.

Equality $L_x^\infty = L_\infty$ holds only in the joint limit (all scale variables $\rightarrow \infty$ together); along a single axis the marginal floor is in general strictly larger.

- (A4) **Asymptotic power-law decay.** Relative to the marginal floor (1),

$$\lim_{t \rightarrow \infty} \frac{\log(\hat{L}(\mathbf{h})|_{x=t} - L_x^\infty)}{\log t} = c_x \quad \text{for some } c_x < 0. \quad (2)$$

- (A5) **Positivity.** $\hat{L}(\mathbf{h}) > 0$ for all $\mathbf{h} \in \mathbb{H}$.
- (A6) **Graceful saturation.** $\hat{L}$ is continuous and differentiable (C^1) in x on $[x_{\min}, \infty)$, with $\hat{L}(x_{\min}, \cdot)$ finite and $> L_\infty$.

These encode physical priors on loss surfaces that unconstrained symbolic regression routinely violates. In particular, (A4) must use L_x^∞ rather than L_∞ : along a single axis the excess over the joint floor need not vanish, so a power-law rate would not be identifiable against L_∞ .

4.3 Boosted construction

The ensemble is built stagewise, $\hat{L}^{(j)} = \hat{L}^{(j-1)} + \hat{L}_j$, under an *admissibility invariant*: $\hat{L}^{(j)} \in \mathcal{S}$ for every $j = 0, \dots, K$ (Section 4.2). Throughout, $\hat{L}_j$ (subscript) is the stage- j correction and $\hat{L}^{(j)}$ (superscript) is the cumulative ensemble through stage j , so in particular $\hat{L}^{(0)} = \hat{L}_0$. Stage 0 is a generalized Chinchilla law, fit in closed form and admissible by construction with joint floor $L_\infty = E$ and stage-0

asymptotic exponents $c_N^{(0)} = -\alpha$, $c_D^{(0)} = -\beta$ (the rates c_x in (A4) of Section 4.2 along N and D):

$$\hat{L}^{(0)} = \hat{L}_0 = \frac{A}{N^\alpha} + \frac{B}{D^\beta} + \sum_{i=1}^m \frac{C_i}{\phi_i(h_i)^{\gamma_i}} + E, \quad A, B, C_i, E, \alpha, \beta, \gamma_i > 0. \quad (3)$$

Each later stage $j \geq 1$ fits Huber pseudo-residuals of the current ensemble, with clipping threshold

$$\delta_j := \text{median}_{\ell=1, \dots, n} |L(\mathbf{h}_\ell) - \hat{L}^{(j-1)}(\mathbf{h}_\ell)| \quad (4)$$

so that outlier runs cannot dominate:

$$\tilde{r}_j^{(\ell)} := \begin{cases} L(\mathbf{h}_\ell) - \hat{L}^{(j-1)}(\mathbf{h}_\ell) & \text{if } |L(\mathbf{h}_\ell) - \hat{L}^{(j-1)}(\mathbf{h}_\ell)| \leq \delta_j, \\ \delta_j \cdot \text{sign}(L(\mathbf{h}_\ell) - \hat{L}^{(j-1)}(\mathbf{h}_\ell)) & \text{otherwise.} \end{cases} \quad (5)$$

Corrections are sought by genetic-programming search over expression trees with operators $\{+, \times, \div\} \cup \{\text{pow}_p : p \in \mathcal{P}\}$ for a finite set $\mathcal{P} \subset \mathbb{R} \setminus \{0\}$ (where $\text{pow}_p(z) = |z|^p$ for $z > 0$) and bounded depth.

4.4 Stagewise admissibility

Checking that the full ensemble $\hat{L}^{(j)}$ obeys (A1)–(A6) of Section 4.2 is a continuum statement over $\mathbb{H}$. Admissibility of the update is nonetheless equivalent to local conditions on the *increment*: given $\hat{L}^{(j-1)} \in \mathcal{S}$ with joint floor L_∞ , $\hat{L}^{(j)} = \hat{L}^{(j-1)} + \hat{L}_j$ is admissible *if and only if* $\hat{L}_j$ satisfies, for each $x \in \{N, D\}$,

$$\begin{aligned} \text{(i)} \quad & \frac{\partial \hat{L}_j}{\partial x} \leq -\frac{\partial \hat{L}^{(j-1)}}{\partial x} \quad \text{for all } x \geq x_{\min}, \\ \text{(ii)} \quad & \frac{\partial^2 \hat{L}_j}{\partial x^2} \geq -\frac{\partial^2 \hat{L}^{(j-1)}}{\partial x^2} \quad \text{for all } x \geq x_{\min}, \\ \text{(iii)} \quad & \hat{L}_j(\mathbf{h}) > -\hat{L}^{(j-1)}(\mathbf{h}) \quad \text{for all } \mathbf{h} \in \mathbb{H}, \\ \text{(iv)} \quad & \hat{L}^{(j-1)}(\mathbf{h}) + \hat{L}_j(\mathbf{h}) > L_\infty \quad \text{for all } \mathbf{h} \in \mathbb{H}, \\ \text{(v)} \quad & \hat{L}_j(\mathbf{h})|_{x=t} = O(t^{c_{x,j}}) \text{ as } t \rightarrow \infty \text{ for some } c_{x,j} < c_x^{(0)}, \\ \text{(vi)} \quad & \hat{L}_j \in C^\infty \text{ on } [x_{\min}, x_{\max}] \text{ with } |\hat{L}_j(x_{\min}, \cdot)| < \infty. \end{aligned} \quad (6)$$

Conditions (i)–(iv) and (vi) are still quantified over continua ((i)–(ii) on the half-line $x \geq x_{\min}$; (iii)–(iv) on $\mathbb{H}$), and (v) is an asymptotic statement: none of these can be decided by sampling finitely many points of $\mathbb{H}$. They become machine-checkable because every GP proposal g is a concrete finite expression tree built from $\{+, \times, \div\} \cup \{\text{pow}_p : p \in \mathcal{P}\}$. Write $F := \hat{L}^{(j-1)} + g$. Two complementary certificates decide whether g preserves (6): interval checks establish (i)–(iv) and (vi) on the compact box $\mathcal{I}_x$ covering the observed grid, while the structural check decides (v) exactly (and thereby controls the $x \rightarrow \infty$ tail that the box does not cover).

(a) *Sound interval-arithmetic checks* (conditions (i)–(iv), (vi) on $\mathcal{I}_x$). Over the compact box $\mathcal{I}_x := [x_{\min}, x_{\max}]$ (other coordinates ranging over their finite H_h), forward-mode automatic differentiation composed with interval arithmetic [11, 12] evaluates g bottom-up on interval operands and returns guaranteed enclosures $\underline{f} \leq f \leq \bar{f}$ on $\mathcal{I}_x$ for $f \in \{F, \partial F/\partial x, \partial^2 F/\partial x^2\}$, in time linear in the tree size. A candidate is accepted when, for each $x \in \{N, D\}$,

$$\overline{\partial F/\partial x} \leq 0, \quad \underline{\partial^2 F/\partial x^2} \geq 0, \quad \underline{F} > L_\infty, \quad \bar{F} < \infty. \quad (7)$$

Because the enclosures are sound, (7) is a *sufficient* certificate that the corresponding continuum conditions hold *everywhere* on $\mathcal{I}_x$, not merely at sampled points: $\overline{\partial F/\partial x} \leq 0$ forces $\partial F/\partial x \leq 0$ on $\mathcal{I}_x$

(hence (i) on the box), and likewise for (ii); $\underline{F} > L_\infty > 0$ forces both (iii) and (iv) on the configurations covered by the product of boxes; $\overline{F} < \infty$ forces the finiteness half of (vi) (smoothness of g on $\mathcal{I}_x$ follows from the operator set). The test is conservative: a failure of (7) does *not* prove that g fails (6) (interval over-approximation can reject a truly admissible update), but every accepted g is guaranteed to preserve admissibility on $\mathcal{I}_x$. That one-sided decidability is exactly what a hard filter needs, and evaluating (7) on each GP candidate is the inner-loop hot spot, the direct target of the AMA27 performance work.

(b) *Exact structural checks* (condition (v), and prerequisites for it). Define the asymptotic exponent $\text{ord}(g, x)$ recursively on the tree: constants and leaves other than x contribute 0; $\text{pow}_p(x)$ contributes p ; products add exponents; quotients subtract; sums take the maximum. Then (v) holds with $c_{x,j} = \text{ord}(g, x)$ precisely when $\text{ord}(g, x) < c_x^{(0)}$ for each $x \in \{N, D\}$. We additionally require that each scale variable $x \in \{N, D\}$ appears as a leaf of g (otherwise the exponent in x is undefined or vacuously 0). Both tests are exact, finite walks over a finite tree, with no floating-point search over $\mathbb{H}$.

Algorithm 1 enforces (6) via certificates (a)–(b) at every stage.

Algorithm 1 Shape-constrained boosted symbolic regression

Require: Dataset $\mathcal{D} = \{(\mathbf{h}_\ell, L(\mathbf{h}_\ell))\}_{\ell=1}^n$, stages K

Ensure: Admissible ensemble $\hat{L}^{(K)} \in \mathcal{S}$

- 1: Fit $\hat{L}_0$ via (3) on $\mathcal{D}$; set $\hat{L}^{(0)} \leftarrow \hat{L}_0$
 - 2: **for** $j = 1, \dots, K$ **do**
 - 3: Compute δ_j via (4)
 - 4: Compute $\tilde{r}_j^{(\ell)}$ for all $\ell = 1, \dots, n$ via (5)
 - 5: Find $\hat{L}_j \in \arg \min_g \frac{1}{n} \sum_{\ell=1}^n (\tilde{r}_j^{(\ell)} - g(\mathbf{h}_\ell))^2$ subject to certificates (a)–(b) for (6)
 - 6: $\hat{L}^{(j)} \leftarrow \hat{L}^{(j-1)} + \hat{L}_j$
 - 7: **end for**
 - 8: **return** $\hat{L}^{(K)}$
-

4.5 Guarantee

If $\hat{L}_0 \in \mathcal{S}$ and every $\hat{L}_j$ is accepted by certificates (a)–(b) of Section 4.4, then for all j : $\hat{L}^{(j)} \in \mathcal{S}$; writing $L_\infty^{(j)}$ for the joint floor of $\hat{L}^{(j)}$, one has $L_\infty^{(j)} = E$; and the asymptotic exponents are preserved,

$$\lim_{t \rightarrow \infty} \frac{\log(\hat{L}^{(j)}(\mathbf{h})|_{x=t} - L_x^\infty)}{\log t} = c_x^{(0)}, \quad (8)$$

where L_x^∞ is the marginal floor of $\hat{L}^{(j)}$ along x (equal to that of $\hat{L}_0$). Boosting therefore improves fit *without* corrupting the interpretable constants researchers actually quote.

4.6 Soft-constrained variant

A second path replaces the hard admissibility filter of Algorithm 1 and Section 4.4 with per-axiom violation scores on the same candidate ensemble $F := \hat{L}^{(j-1)} + g$. Using the interval enclosures of

Section 4.4(a) and the structural quantities of (b), define

$$\begin{aligned}
v_{\text{mono}}(g) &= \max_{x \in \{N, D\}} \max\left(0, \overline{\partial F / \partial x}\right), & (\text{monotonicity gap}), \\
v_{\text{conv}}(g) &= \max_{x \in \{N, D\}} \max\left(0, -\overline{\partial^2 F / \partial x^2}\right), & (\text{convexity gap}), \\
v_{\text{irred}}(g) &= \max(0, L_\infty - \underline{F}), & (\text{floor gap}), \\
v_{\text{decay}}(g) &= \max_{x \in \{N, D\}} \max(0, \text{ord}(g, x) - c_x^{(0)} + \varepsilon_{\text{decay}}), & (\text{power-law gap}), \\
v_{\text{leaf}}(g) &= |\{x \in \{N, D\} : x \notin \text{leaves}(g)\}|, & (\text{missing scale leaves}).
\end{aligned} \tag{9}$$

Here $\varepsilon_{\text{decay}} > 0$ is a fixed margin so that $v_{\text{decay}}(g) = 0$ forces the strict inequality $\text{ord}(g, x) \leq c_x^{(0)} - \varepsilon_{\text{decay}} < c_x^{(0)}$ required by (6)(v); $\text{leaves}(g)$ is the set of variable leaves of the expression tree g . Every score is nonnegative, and $v_{\text{mono}} = v_{\text{conv}} = v_{\text{irred}} = v_{\text{leaf}} = 0$ iff the corresponding hard certificate passes (for v_{decay} , zero is sufficient but slightly stronger than (v) because of the margin). Writing a for an axiom index ranging over $\{\text{mono}, \text{conv}, \text{irred}, \text{decay}, \text{leaf}\}$ and $\lambda_a > 0$ for its penalty weight, the aggregate violation is $V(g) = \sum_a v_a(g)$. Stage j then minimizes the penalized fitness

$$F_j(g) = \underbrace{\frac{1}{n} \sum_{\ell=1}^n (\tilde{r}_j^{(\ell)} - g(\mathbf{h}_\ell))^2}_{\text{data fit}} + \underbrace{\sum_a \lambda_a v_a(g)^2}_{\text{axiom penalty}}, \tag{10}$$

where F_j is a scalar fitness (distinct from the ensemble map F above), the first term is mean squared error of g against the Huber pseudo-residuals (5), and the second term penalizes axiom gaps (squared so the penalty gradient vanishes at zero violation). Candidates that already satisfy (6) therefore incur no penalty pressure. This path carries its own guarantee: $V = 0$ at every stage recovers the hard result exactly; the interval-based scores v_{mono} , v_{conv} , v_{irred} upper-bound the corresponding true pointwise violations (while v_{decay} and v_{leaf} are exact), yielding a *measured* admissibility gap rather than silent failure; and for a sufficiently small decay margin every correction that passes the hard admissibility certificates has zero penalty, so the soft search provably contains the hard one of Section 4.4. Comparing the two paths (certified-but-restricted versus free-but-scored) is one of the empirical questions the project settles.

5 Additional information

5.1 Collaborators welcome

The project splits into two fairly independent tracks, so a teammate could own either one. The *modeling* track ports and benchmarks transformer pretraining on Neocortex’s Cerebras CS-3 systems (Section 3.1) and profiles it against our NVIDIA GPU runs (Section 3.2; useful background: PyTorch, or curiosity about the Cerebras software stack). The *search* track ports the genetic-programming symbolic-regression loop of Section 4.3 to AMA27 (Section 3.1) and profiles the certification inner loop of Section 4.4 on AmpereOne against our AMD EPYC (x86) CPU baselines (useful background: C/C++ or Python performance work, or an interest in Arm/HPC profiling); a self-contained slice of it is benchmarking the hard-constrained path (Section 4.4) against the soft-constrained one (Section 4.6). No prior scaling-law expertise is needed for either; the main thing is an appetite for making code run fast on unusual hardware.

5.2 Deliverables

- (1) An admissible boosted scaling law ([Sections 4.2 and 4.5](#)) fit on the collected training grid ([Section 3.5](#));
- (2) a public release of the shape-constrained symbolic-regression library with the interval-arithmetic-certified admissibility checking of [Section 4.4](#); and (3) a short paper on the method of [Section 4](#).

6 References

- [1] Lukas Biewald. Experiment tracking with weights & biases. <https://wandb.ai/>, 2020. Software available from wandb.com.
- [2] Trevor Stephens. gplearn: Genetic programming in Python. <https://gplearn.readthedocs.io/>, 2015. Software library.
- [3] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurélien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. LLaMA: Open and efficient foundation language models, 2023. URL <https://arxiv.org/abs/2302.13971>.
- [4] Houyi Li, Wenzhen Zheng, Qiufeng Wang, Hanshan Zhang, Zili Wang, Shijie Xuyang, et al. Predictable scale: Part i, step law: Optimal hyperparameter scaling law in large language model pretraining, 2025. URL <https://arxiv.org/abs/2503.04715>.
- [5] Samir Yitzhak Gadre, Georgios Smyrnis, Vaishaal Shankar, Suchin Gururangan, Mitchell Wortsman, Rulin Shao, Jean Mercat, et al. Language models scale reliably with over-training and on downstream tasks, 2024. URL <https://arxiv.org/abs/2403.08540>.
- [6] Greg Yang, Edward J. Hu, Igor Babuschkin, Szymon Sidor, Xiaodong Liu, David Farhi, Nick Ryder, Jakub Pachocki, Weizhu Chen, and Jianfeng Gao. Tensor programs v: Tuning large neural networks via zero-shot hyperparameter transfer. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. URL <https://arxiv.org/abs/2203.03466>. arXiv:2203.03466.
- [7] Wikimedia Foundation. Wikimedia downloads. <https://dumps.wikimedia.org>, 2023. Wikipedia dumps; also available as <https://huggingface.co/datasets/wikimedia/wikipedia>.
- [8] Together Computer. RedPajama: An open dataset for training large language models. <https://huggingface.co/datasets/togethercomputer/RedPajama-Data-1T>, 2023. Hugging Face dataset.
- [9] Guilherme Penedo et al. FineWeb-Edu: Educational subset of FineWeb. <https://huggingface.co/datasets/HuggingFaceFW/fineweb-edu>, 2024. Hugging Face dataset.
- [10] Leibniz Lab. colinear_scaling_models: Scaling-grid checkpoints and loss curves. https://huggingface.co/datasets/leibnitz-lab/colinear_scaling_models, 2025. Hugging Face dataset.
- [11] Ramon E. Moore, R. Baker Kearfott, and Michael J. Cloud. *Introduction to Interval Analysis*. Society for Industrial and Applied Mathematics (SIAM), 2009. doi: 10.1137/1.9780898717716. URL <https://doi.org/10.1137/1.9780898717716>.
- [12] G. Kronberger, F. O. de França, B. Burlacu, C. Haider, and M. Kommenda. Shape-constrained symbolic regression: Improving extrapolation with prior knowledge. *Evolutionary Computation*, 30(1):75–98, 2022. doi: 10.1162/evco_a_00294. URL https://doi.org/10.1162/evco_a_00294.

7 Notation

Symbol	Meaning
N, D	Parameter count and training-token count (scale variables).
M	Tokens-per-parameter ratio $M = D/N$ (Section 3.4).
$\mathcal{H} = \{h_1, \dots, h_m\}$	Remaining hyperparameters; $m = \mathcal{H} $.
i	Hyperparameter index, $i = 1, \dots, m$ (distinct from data-point index ℓ).
H_h	Finite set of admissible values for coordinate $h \in \{N, D\} \cup \mathcal{H}$.
ϕ_h, ϕ_i	Strictly monotone preprocessing $\phi_h: H_h \rightarrow \mathbb{R}_{>0}$; $\phi_i := \phi_{h_i}$.
$\mathbb{H}$	Configuration space $\prod_h H_h$.
$\mathbf{h}$	Typical element of $\mathbb{H}$ (coordinates N, D, h_i).
$L, \hat{L}$	True validation loss and its approximation.
$\mathcal{D}, n, \ell$	Labeled dataset $\{(\mathbf{h}_\ell, L(\mathbf{h}_\ell))\}_{\ell=1}^n$; $n = \mathcal{D} $; data-point index ℓ .
x	Generic scale variable, $x \in \{N, D\}$.
t	Dummy limit variable along a scale axis (e.g. $\hat{L}(\mathbf{h}) _{x=t}$).
$x_{\min}, x_{\max}$	$\min H_x$ and $\max H_x$.
$\mathcal{S}$	Set of admissible scaling laws (Section 4.2).
$L_\infty, L_\infty^{(j)}$	Joint irreducible-loss floor; joint floor of $\hat{L}^{(j)}$ ($L_\infty^{(j)} = E$ under the hard path).
L_x^∞	Marginal floor along axis x (1).
$c_x, c_x^{(0)}$	Asymptotic power-law exponent along x (A4); stage-0 value $c_N^{(0)} = -\alpha$, $c_D^{(0)} = -\beta$.
j, K	Boosting stage index; number of correction stages after stage 0 (Algorithm 1).
$\hat{L}_j, \hat{L}^{(j)}$	Stage- j correction (subscript) and cumulative ensemble through stage j (superscript); $\hat{L}^{(0)} = \hat{L}_0$.
$A, B, C_i, E, \alpha, \beta, \gamma_i$	Positive coefficients/exponents of the stage-0 Chinchilla law (3); joint floor $L_\infty = E$.
δ_j	Huber clipping threshold at stage j (4).
$\tilde{r}_j^{(\ell)}$	Huber pseudo-residual for data point ℓ at stage j (5).
$\mathcal{P}, p$	Finite set of admissible powers $\mathcal{P} \subset \mathbb{R} \setminus \{0\}$; generic element p .
pow_p	Power primitive $\text{pow}_p(z) = z ^p$ for $z > 0$.
g, F	Candidate expression tree; ensemble-plus-candidate $F = \hat{L}^{(j-1)} + g$.
$c_{x,j}, \text{ord}(g, x)$	Asymptotic exponent of correction/candidate g along x ; $c_{x,j} = \text{ord}(g, x)$ in (6)(v).
$\mathcal{I}_x$	Compact certification box $[x_{\min}, x_{\max}]$ (Section 4.4).
$\underline{f}, \bar{f}$	Interval-arithmetic lower/upper enclosures of f on $\mathcal{I}_x$ (global over that box for fixed x ; soft scores take $\max_{x \in \{N, D\}}$ of the per-axis gaps).
$a, v_a(g), V(g)$	Soft-path axiom index $a \in \{\text{mono}, \text{conv}, \text{irred}, \text{decay}, \text{leaf}\}$; per-axiom violation score; aggregate $V = \sum_a v_a$ (9).
$\varepsilon_{\text{decay}}$	Positive margin in v_{decay} so zero score implies strict power-law decay (9).
$\text{leaves}(g)$	Set of variable leaves of expression tree g .
λ_a	Positive penalty weight for axiom a .
$F_j(g)$	Soft-path penalized fitness at stage j (10) (distinct from F).