

MEK3220 - Formulae sheet

Krister Stræte Karlsen

November 10, 2015

THE DISPLACEMENT GRADIENT

$$\nabla \mathbf{u} = \begin{pmatrix} \frac{\partial u_x}{\partial x} & \frac{\partial u_x}{\partial y} & \frac{\partial u_x}{\partial z} \\ \frac{\partial u_y}{\partial x} & \frac{\partial u_y}{\partial y} & \frac{\partial u_y}{\partial z} \\ \frac{\partial u_z}{\partial x} & \frac{\partial u_z}{\partial y} & \frac{\partial u_z}{\partial z} \end{pmatrix}$$

Comment: If $\nabla \mathbf{u} = (\nabla \mathbf{u})^T$ we have that $\nabla \mathbf{u} = \epsilon$, the *strain tensor*.

STRAIN TENSOR

$$\epsilon = \frac{1}{2}((\nabla \mathbf{u})^T + \nabla \mathbf{u})$$

CAUCHY'S EQUILIBRIUM EQUATION

$$\mathbf{f}_v + \nabla \cdot \sigma^T = 0$$

HOOKE'S LAW

$$\{\sigma\} = \lambda(\nabla \cdot \mathbf{u})I + \mu\epsilon$$

or

$$\begin{aligned} \sigma_{xx} &= (2\mu + \lambda)\epsilon_{xx} + \lambda(\epsilon_{yy} + \epsilon_{zz}), & \sigma_{yz} &= \sigma_{zy} = 2\mu\epsilon_{yz} \\ \sigma_{yy} &= (2\mu + \lambda)\epsilon_{yy} + \lambda(\epsilon_{xx} + \epsilon_{zz}), & \sigma_{xz} &= \sigma_{zx} = 2\mu\epsilon_{xz} \\ \sigma_{zz} &= (2\mu + \lambda)\epsilon_{zz} + \lambda(\epsilon_{yy} + \epsilon_{xx}), & \sigma_{xy} &= \sigma_{yx} = 2\mu\epsilon_{xy} \end{aligned}$$

INVERTED HOOKE'S LAW

NAVIER'S EQUATION FOR ELASTIC MEDIA IN MOTION


$$\frac{\partial^2 \mathbf{u}}{\partial t^2} = \mu \nabla^2 \mathbf{u} + (\lambda + \mu) \nabla \nabla \cdot \mathbf{u} + \mathbf{f}_v$$

Comment: For mechanical equilibrium set LHS. equal to zero.

LAMÈ COEFFICIENTS

BEAM EQUATIONS

Euler-Bernoulli and some additional important relations



$$\frac{d^2 w(x)}{dx^2} = -\frac{M_y(x)}{EI}, \quad \frac{dM_y(x)}{dx} = F_z, \quad \frac{dF_z}{dx} = -F_{ext}^{(z)}$$

EQUATION OF CONTINUITY

$$\frac{\partial \rho}{\partial t} + \nabla \cdot \rho \mathbf{v} = 0$$

NAVIER-STOKES

$$\frac{d\mathbf{v}}{dt} + (\mathbf{v} \cdot \nabla) \mathbf{v} = \mathbf{g} - \frac{1}{\rho} \nabla p + \nu \nabla^2 \mathbf{v}, \quad \nabla \cdot \mathbf{v} = 0$$

ISOTROPIC VISCOUS STRESS

$$\sigma = \text{pressure} + \text{shear stress} = (-p)I + \mu((\nabla \mathbf{v})^T + \nabla \mathbf{v})$$

ENERGY EQUATIONS

Kinetic energy(per volume) for fluid:

$$E_k = \frac{1}{2}\rho\mathbf{v}^2 = \frac{1}{2}\rho(u^2 + v^2 + w^2)$$

Work done by wall(at $y = h$ with length: L) from shear stress(σ_{xy}) on fluid:

$$W = U(h)L\sigma_{xy}(h)$$

[add figure]