

Guided Exercise: The Kubernetes and OpenShift Command-line Interfaces

Access an OpenShift cluster by using the command-line to get information about cluster services and nodes.

Outcomes

- Use the OpenShift web console to locate the installation file for the `oc` OpenShift command-line interface.
- Get and use a token from the web console to access the cluster from the command line.
- Identify key differences between the `kubectl` and `oc` command-line tools.
- Identify the main components of OpenShift and Kubernetes.

As the student user on the workstation machine, use the `lab` command to prepare your system for this exercise.

This command ensures that all resources are available for this exercise.


```
[student@workstation ~]$ lab start cli-interfaces
```

Instructions

1. Log in to the OpenShift web console as the developer user. Locate the installation file for the `oc` OpenShift command-line interface (CLI).

Open a web browser and go to <https://console-openshift-console.apps.ocp4.example.com>.

Click **Red Hat Identity Management** and log in as the developer user with the developer password.



Locate the installation file for the `oc` CLI. From the OpenShift web console, select **Help** → **Command line tools**. The **Help** menu is represented by a `?` icon.



Command Line Tools

[Copy login command](#)

oc - OpenShift Command Line Interface (CLI)

With the OpenShift command line interface, you can create applications and manage OpenShift projects from a terminal.

The `oc` binary offers the same capabilities as the `kubectl` binary, but it is further extended to natively support OpenShift Container Platform features.

- [Download oc for Linux for x86_64](#)
- [Download oc for Mac for x86_64](#)
- [Download oc for Windows for x86_64](#)
- [Download oc for Linux for ARM 64](#)
- [Download oc for Mac for ARM 64](#)
- [Download oc for Linux for IBM Power, little endian](#)
- [Download oc for Linux for IBM Z](#)
- [LICENSE](#)

The `oc` binary is available for multiple operating systems and architectures. For each operating system and architecture, the `oc` binary also includes the `kubectl` binary.

NOTE

You do not need to download or install the `oc` and `kubectl` binaries, which are already installed on the workstation machine.

2. Download an authorization token from the web console. Then, use the token and the `oc` command to log in to the OpenShift cluster.

From the **Command Line Tools** page, click the **Copy login command** link.

The link opens a login page. Click **Red Hat Identity Management** and log in as the `developer` user with the `developer` password.

A web page is displayed. Click the **Display token** link to show your API token and the login command.

Your API token is

sha256~nJg06D38lkgTfN9K2Ib7cTvBs3dvVKQfnrXrm5oBiU4

Log in with this token

```
oc login --token=sha256~nJg06D38lkgTfN9K2Ib7cTvBs3dvVKQfnrXrm5oBiU4
--server=https://api.ocp4.example.com:6443
```

Use this token directly against the API

```
curl -H "Authorization: Bearer sha256~nJg06D38lkgTfN9K2Ib7cTvBs3dvVKQfnrXrm5oBiU4"
"https://api.ocp4.example.com:6443/apis/user.openshift.io/v1/users/~"
```

[Request another token](#)

Copy the `oc login` command to your clipboard. Open a terminal window and then use the copied command to log in to the cluster with your token.

```
[student@workstation ~]$ oc login --token=sha256-fypX...Ot6A \
--server=https://api.ocp4.example.com:6443
Logged into "https://api.ocp4.example.com:6443" as "developer" using the token provided.
...output omitted...
```

3. Compare the available commands for the `kubectl` and `oc` commands.

Use the `help` command to list and review the available commands for the `kubectl` command.

```
[student@workstation ~]$ kubectl help
kubectl controls the Kubernetes cluster manager.

Find more information at: https://kubernetes.io/docs/reference/kubectl/

Basic Commands (Beginner):
  create      Create a resource from a file or from stdin
  expose      Take a replication controller, service, deployment or pod and expose it as a new Kubernetes service
  run         Run a particular image on the cluster
  set         Set specific features on objects

Basic Commands (Intermediate):
  explain     Get documentation for a resource
  get         Display one or many resources
  edit        Edit a resource on the server
  delete      Delete resources by file names, stdin, resources and names, or by resources and label selector
...output omitted...
```

Notice that the `kubectl` command does not provide a login command.

Examine the available subcommands and options for the `kubectl create` command by using the `--help` option.

```
[student@workstation ~]$ kubectl create --help
Create a resource from a file or from stdin.

JSON and YAML formats are accepted.

Examples:
# Create a pod using the data in pod.json
kubectl create -f ./pod.json
...output omitted...
Available Commands:
clusterrole          Create a cluster role
clusterrolebinding   Create a cluster role binding for a particular cluster role
configmap            Create a config map from a local file, directory or literal value
cronjob              Create a cron job with the specified name
deployment            Create a deployment with the specified name
...output omitted...
Options:
--allow-missing-template-keys=true:
    If true, ignore any errors in templates when a field or map key is missing in the template. Only applies to
    golang and jsonpath output formats.

--dry-run='none':
    Must be "none", "server", or "client". If client strategy, only print the object that would be sent, without
    sending it. If server strategy, submit server-side request without persisting the resource.
...output omitted...
Usage:
  kubectl create -f FILENAME [options]

Use "kubectl create <command> --help" for more information about a given command.
Use "kubectl options" for a list of global command-line options (applies to all commands).
```

You can use the `--help` option with any `kubectl` command. The `--help` option provides information about a command, including the available subcommands and options, and the command syntax.

List and review the available commands for the `oc` binary by using the `help` command.

```
[student@workstation ~]$ oc help
OpenShift Client

This client helps you develop, build, deploy, and run your applications on any
OpenShift or Kubernetes cluster. It also includes the administrative
commands for managing a cluster under the 'adm' subcommand.

Basic Commands:
login          Log in to a server
new-project    Request a new project
new-app        Create a new application
status         Show an overview of the current project
project        Switch to another project
projects       Display existing projects
explain        Get documentation for a resource
...output omitted...
```

The `oc` command supports the same capabilities as the `kubectl` command. The `oc` command provides additional commands to natively support an OpenShift cluster. For example, the `new-project` command creates a project, which is a Kubernetes namespace, in the OpenShift cluster. The `new-app` command is unique to the `oc` command. It creates applications by using existing source code or prebuilt images.

Use the `--help` option with the `oc create` command to view the available subcommands and options.

```
[student@workstation ~]$ oc create --help
Create a resource from a file or from stdin.

JSON and YAML formats are accepted.

Examples:
# Create a pod using the data in pod.json
oc create -f ./pod.json
...output omitted...

Available Commands:
build                Create a new build
clusterresourcequota Create a cluster resource quota
clusterrole          Create a cluster role
clusterrolebinding   Create a cluster role binding for a particular cluster role
configmap            Create a config map from a local file, directory or literal value
cronjob              Create a cron job with the specified name
deployment           Create a deployment with the specified name
...output omitted...

Options:
--allow-missing-template-keys=true:
    If true, ignore any errors in templates when a field or map key is missing in the template. Only applies to
    golang and jsonpath output formats.

--dry-run='none':
    Must be "none", "server", or "client". If client strategy, only print the object that would be sent, without
    sending it. If server strategy, submit server-side request without persisting the resource.
...output omitted...

Usage:
  oc create -f FILENAME [options]
...output omitted...
```

The `oc create` command includes the same subcommands and options as the `kubectl create` command, and provides additional subcommands for OpenShift resources. For example, you can use the `oc create` command to create OpenShift resources such as a deployment, a route, and an image stream.

4. Use the `oc login` command with the `--web` option to log in as the admin user with `redhatocp` as the password. Identify the components and Kubernetes resources of an OpenShift cluster by using the terminal. Regular cluster users, such as the developer user, cannot list resources at a cluster scope. Unless otherwise noted, all commands are available for the `oc` and `kubectl` commands.

In a terminal, use the `oc login --web` command.

```
[student@workstation ~]$ oc login --web
```

In the browser tab that opens, click **Red Hat Identity Management** and log in as the admin user with `redhatocp` as the password. You get the access token received successfully; please return to your terminal message. Close the browser tab.

Return to the terminal window. Identify the cluster version with the `version` command.

```
[student@workstation ~]$ oc version
Client Version: 4.18.6
Kustomize Version: v5.4.2
Server Version: 4.18.6
Kubernetes Version: v1.31.6
```

Use the `cluster-info` command to identify the URL for the Kubernetes control plane.

```
[student@workstation ~]$ oc cluster-info
Kubernetes control plane is running at https://api.ocp4.example.com:6443

To further debug and diagnose cluster problems, use 'kubectl cluster-info dump'.
```

Identify the supported API versions by using the `api-versions` command.

```
[student@workstation ~]$ oc api-versions
admissionregistration.k8s.io/v1
admissionregistration.k8s.io/v1beta1
apiextensions.k8s.io/v1
apiregistration.k8s.io/v1
apiserver.openshift.io/v1
apps.openshift.io/v1
apps/v1
...output omitted...
```

List cluster operators with the `get clusteroperator` command.

```
[student@workstation ~]$ oc get clusteroperator
NAME                VERSION  AVAILABLE  PROGRESSING  DEGRADED  SINCE ...
authentication      4.18.6   True       False        False     5d5h
baremetal           4.18.6   True       False        False     41d
cloud-controller-manager 4.18.6   True       False        False     41d
cloud-credential     4.18.6   True       False        False     41d
cluster-autoscaler   4.18.6   True       False        False     41d
config-operator      4.18.6   True       False        False     41d
console             4.18.6   True       False        False     29d
control-plane-machine-set 4.18.6   True       False        False     41d
csi-snapshot-controller 4.18.6   True       False        False     41d
dns                 4.18.6   True       False        False     32m
etcd                4.18.6   True       False        False     41d
image-registry       4.18.6   True       False        False     41d
ingress             4.18.6   True       False        False     41d
...output omitted...
```

Use the `get` command to list pods in the `openshift-api` project. Specify the project with the `-n` option.

```
[student@workstation ~]$ oc get pods -n openshift-apiserver
NAME                                READY  STATUS   RESTARTS  AGE
apiserver-68c9485699-ndqlc        2/2    Running  6          18d
```

Use the `oc status` command to retrieve the status of resources in the `openshift-authentication` project.

```
[student@workstation ~]$ oc status -n openshift-authentication
Warning: apps.openshift.io/v1 DeploymentConfig is deprecated in v4.14+, unavailable in v4.10000+
In project openshift-authentication on server https://api.ocp4.example.com:6443

https://oauth-openshift.apps.ocp4.example.com (passthrough) to pod port 6443 (svc/oauth-openshift)
deployment/oauth-openshift deploys quay.io/openshift-release-dev/ocp-v4.0-art-dev@sha256:64e6...de42
deployment #7 running for 2 weeks - 1 pod
deployment #6 deployed 2 weeks ago
deployment #4 deployed 2 weeks ago
deployment #5 deployed 2 weeks ago
deployment #3 deployed 2 weeks ago
deployment #2 deployed 2 weeks ago
deployment #1 deployed 2 weeks ago
...output omitted...
```

Use the `explain` command to list the description and available fields for services resources.

```
[student@workstation ~]$ oc explain services
KIND:      Service
VERSION:   v1

DESCRIPTION:
  Service is a named abstraction of software service (for example, mysql)
  consisting of local port (for example 3306) that the proxy listens on, and
  the selector that determines which pods will answer requests sent through
  the proxy.

FIELDS:
  apiVersion    <string>
    APIVersion defines the versioned schema of this representation of an
    object. Servers should convert recognized schemas to the latest internal
    value, and may reject unrecognized values.
  ...output omitted...
```

Use the `get` command to list cluster nodes.

```
[student@workstation ~]$ oc get nodes
```

NAME	STATUS	ROLES	AGE	VERSION
master01	Ready	control-plane,master,worker	18d	v1.31.6

A single node exists in the cluster.

Finish

On the workstation machine, use the `lab` command to complete this exercise. This step is important to ensure that resources from previous exercises do not impact upcoming exercises.

```
[student@workstation ~]$ lab finish cli-interfaces
```