

26

EXPLORER

OPEN EDITORS

DEMO-APPLICATION-UNI

app

assets

channels

controllers

concerns

application\_controller.rb

users\_controller.rb

frontend

channels

consumer.js

index.js

js

packs

helpers

jobs

mailers

models

services

sample\_api\_client.rb

views

layouts

users

\_form.html.erb

\_user.json.jbuilder

edit.html.erb

index.html.erb

index.json.jbuilder

new.html.erb

sample\_api.html.erb

OUTLINE

TIMELINE

sample\_api.html.erb U

users\_controller.rb M X

app > controllers > users\_controller.rb

48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82

```
format.html { render :edit, status: :unprocessable_entity }  
format.json { render json: @user.errors, status: :unprocessable_entity }  
end  
end  
end  
  
# DELETE /users/1 or /users/1.json  
def destroy  
  @user.destroy  
  
  respond_to do |format|  
    format.html { redirect_to users_url, notice: "User was successfully destroyed." }  
    format.json { head :no_content }  
  end  
end  
  
def sample_api # api method  
  @data = SampleApiClient.new.get_user  
end  
  
private  
  # Use callbacks to share common setup or constraints between actions.  
  def set_user  
    @user = User.find(params[:id])  
  end  
  
  # Only allow a list of trusted parameters through.  
  def user_params  
    params.require(:user).permit(:name, :phone_number)  
  end  
end  
  
# Rahil Dutta  
# Created 16th November 2023  
# Matriculation Number : 1360929
```

Ln 80, Col 13


Spaces: 2


UTF-8


LF

Ruby










# Users

Name	Phone Number			
asdsa	asds	Show	Edit	Destroy

New User

[Sample Api Call](#)



# Data from API

User ID: 1

Username: Bret