SQL ASSIGNMENT 19: ZOMATO BANGALORE DATASET

Subject: Exploratory SQL Data Analysis **Dataset:** Zomato Bangalore **Status:** Completed

TASK 1: TOP 5 HIGHEST-RATED NORTH INDIAN RESTAURANTS IN KORAMANGALA

Write a SQL query to find the top 5 highest-rated restaurants in Koramangala that serve North Indian cuisine.

```
SELECT name, rating, votes, approx_cost_for_two FROM zomato_restaurants WHERE location LIKE '%Koramangala%' AND cuisines LIKE '%North Indian%' ORDER BY rating DESC, votes DESC LIMIT 5;
```

TASK 2: TOP 3 MOST EXPENSIVE CUISINES IN BANGALORE

Calculate average cost for two people for each cuisine type and list the 3 most expensive cuisines to eat in Bangalore.

```
SELECT TRIM(c.value) AS cuisine_type, ROUND(AVG(approx_cost_for_two), 2) AS avg_cost_for_two FROM zomato_restaurants, LATERAL STRING_SPLIT(cuisines, ',') AS c GROUP BY TRIM(c.value) ORDER BY avg_cost_for_two DESC LIMIT 3;
```

TASK 3: ONLINE DELIVERY OUTLETS RATED BELOW 3.0 & STRATEGIC PLAN

Find all restaurants that offer online delivery but have a rating below 3.0, and suggest a marketing strategy to improve ratings.

```
SELECT name, location, cuisines, rating, approx_cost_for_two FROM zomato_restaurants WHERE online_order = 'Yes' AND rating < 3.0 ORDER BY rating ASC;
```

Strategic Improvement Plan: Low ratings in delivery-enabled outlets typically point to cold food, long transit times, or inaccurate packaging in lower price segments (<₹400). *Recommendations:* (1) Geofence maximum delivery distance to maintain food temperature. (2) Mandate spill-proof thermal packaging. (3) Offer a "Satisfaction Guaranteed" discount on next order for customers who leave low ratings to encourage retention and feedback loops.

TASK 4: RESTAURANT PRICE MARKET SEGMENTATION

Segment restaurants into Budget (<400), Mid-Range (400-800), and Premium (>800) segments based on cost for two.

```
SELECT CASE WHEN approx_cost_for_two < 400 THEN 'Budget (< 400)' WHEN approx_cost_for_two BETWEEN 400 AND 800 THEN 'Mid-Range (400-800)' ELSE 'Premium (> 800)' END AS price_segment, COUNT(*) AS restaurant_count FROM zomato_restaurants GROUP BY price_segment ORDER BY restaurant_count DESC;
```

TASK 5: TOP 10 MOST POPULAR RESTAURANT CHAINS

List the top 10 most popular restaurant chains by number of distinct outlets, along with their average ratings.

```
SELECT name AS chain_name, COUNT(DISTINCT location) AS total_outlets, ROUND(AVG(rating), 2) AS avg_chain_rating FROM zomato_restaurants GROUP BY name ORDER BY total_outlets DESC LIMIT 10;
```