Solar ESS Co., Ltd.
53 Moo 2, Nang Lae, Mueang, Chiang Rai 57100, Thailand
Tel. 063 151 6694, 089 632 5829 · LINE: solaress1
www.solaress.org · www.โซลาร์เอสส์.com

HYBRID INVERTER · 10 KW · 3-PHASE

Which 10 kW hybrid inverter?

Solar ESS product comparison · October 2026 · Solis, GoodWe, Deye, SRNE, Huawei



OUR PICK

Solis S6-EH3P10K02-NV-YD-L

Best-value 48 V three-phase hybrid: 220 A battery current, IP66, 2× surge for 10 s, unbalanced output, generator port and dual backup ports.

RUNNER-UP

GoodWe GW10K-ET-L-G10

When PV oversizing (20 kW on 3 MPPTs) or a documented 10-year warranty matters more than price.

Specs at a glance

Max PV input (more panels per inverter)

Solis S6	16 kW
GoodWe ET-L	**20 kW**
Deye SG05LP3	16 kW
SRNE SH3	15 kW
Huawei MAP0	18 kW

Max efficiency (scale from 97 %)

Solis S6	97.6 %
GoodWe ET-L	97.8 %
Deye SG05LP3	97.6 %
SRNE SH3	97.5 %
Huawei MAP0	**98.6 %**

Battery charge / discharge current (48 V)

Solis S6	**220 A**
GoodWe ET-L	**220 A**
Deye SG05LP3	210 A
SRNE SH3	**220 A**
Huawei MAP0	n/a

Warranty in Thailand

Solis S6	n/a
GoodWe ET-L	**10 yr**
Deye SG05LP3	**10 yr**
SRNE SH3	5 yr
Huawei MAP0	**10 yr**

Huawei MAP0 takes only high-voltage batteries (600–980 V), so it has no 48 V current figure. Solis warranty length: confirm with the Thai distributor.

Solar ESS Co., Ltd.
53 Moo 2, Nang Lae, Mueang, Chiang Rai 57100, Thailand
Tel. 063 151 6694, 089 632 5829 · LINE: solaress1
www.solaress.org · www.โซลาร์เอสส์.com

Full comparison

	Solis S6-EH3P10K02-NV-YD-L	GoodWe GW10K-ET-L-G10	Deye SUN-10K-SG05LP3	SRNE HESP48100SH3	Huawei SUN2000-10K-MAP0
Battery	**48 V, 220 A**	**48 V, 220 A**	48 V, 210 A	**48 V, 220 A**	600–980 V, LUNA only
MPPTs / current	**2 / 20 + 40 A**	3 / 20 A each	2 / 26 + 26 A	2 / 22 + 22 A	2 / 16 A
MPPT range / max DC	200–850 V / 1000 V	**150–850 V / 1000 V**	200–650 V / 800 V	200–650 V / 800 V	160–1000 V / 1100 V
Backup / surge	10 kW / 2× 10 s	**11 kVA / 20 kVA 10 s**	10 kW / 2× 10 s	10 kW / 20 kVA	10 kW, needs SmartGuard
IP rating	**IP66**	**IP66**	IP65	IP65	**IP66**
Generator input	10 kW	**20 kVA**	Shared port	Yes	No
Unbalanced output	**Grid and backup**	Yes	Yes	Yes	Yes
Monitoring	SolisCloud	SEMS	DeyeCloud / SolarMan	Optional Wi-Fi	FusionSolar

Best in each area

VALUE · 48 V
Solis S6
Lowest cost for the features

PV OVERSIZING
GoodWe
20 kW on 3 MPPTs

BACKUP POWER
GoodWe
11 kVA continuous, 20 kVA generator

EFFICIENCY
Huawei 98.6 %
HV batteries only; GoodWe 97.8 % at 48 V

WARRANTY
GoodWe
10 years documented

PARALLEL & BATTERIES
Deye
Up to 10 units, widest battery list

Why Solis S6 stands out

Feature	What it means for you	S6-EH3P10K02-NV-YD-L
High surge in backup	Starts pumps, air-cons and motors without tripping	**2× rated power for 10 s**
High DC/AC ratio	More panels per inverter	**Up to 16 kW PV (160 %)**
Generator port	Generator wired straight in, auto start/stop	**10 kW input**
Dual backup outputs	Critical and non-critical loads separated	**Yes**
High-current inputs	Suits 600 W+ panels and big batteries	**20/40 A MPPT; 220 A battery**
Unbalanced output	Uneven loads across three phases	**Grid and backup ports**

Specifications are from the manufacturers' published datasheets; star ratings are Solar ESS's own assessment. Check the current datasheet before ordering. For prices and a design for your site, book a consultation at www.solaress.org or LINE: solaress1.

Sources: Solis datasheet · GoodWe ET-LV · SRNE · Huawei MAP0