Solar ESS Co., Ltd.
53 Moo 2, Nang Lae, Mueang, Chiang Rai 57100, Thailand
Tel. 063 151 6694, 089 632 5829 · LINE: solaress1
www.solaress.org · www.โซลาร์เอสส์.com

SOLAR PANELS · 650 W · BACK-CONTACT

LONGi or AIKO?

Solar ESS product comparison · October 2026 · LONGi Hi-MO X10 and AIKO ABC



OUR PICK

LONGi Hi-MO X10 Guardian Anti-Glare (LR7-72HVHF)

The only panel here with measured anti-glare data, the same efficiency class as AIKO, and the better value in Thailand.

ALSO EXCELLENT

AIKO Comet 2U

Highest efficiency at 650 W and a product warranty extendable to 25 years.

Specs at a glance

Module efficiency at 650 W (scale from 23.5 %)

LONGi Guardian SG	24.1 %
LONGi Guardian DG	24.06 %
LONGi Scientist	24.1 %
AIKO Comet 2U	**24.4 %**
AIKO Stellar 1N+	24.1 %

Glass reflectivity (lower = less glare)

LONGi anti-glare	**0.9 %**
Standard glass	2.9 %

Weight (lower is easier on the roof)

LONGi Guardian SG	28.5 kg
LONGi Guardian DG	32.5 kg
LONGi Scientist	28.5 kg
AIKO Comet 2U	**28.1 kg**
AIKO Stellar 1N+	32.3 kg

Max series fuse

LONGi Guardian SG	25 A
LONGi Guardian DG	**30 A**
LONGi Scientist	25 A
AIKO Comet 2U	25 A
AIKO Stellar 1N+	**30 A**

Solar ESS Co., Ltd.
53 Moo 2, Nang Lae, Mueang, Chiang Rai 57100, Thailand
Tel. 063 151 6694, 089 632 5829 · LINE: solaress1
www.solaress.org · www.โซลาร์เอสส์.com

Full comparison

Model	Cell	Efficiency	Voc / Isc	Glass	Warranty
LONGi Guardian LR7-72HVHF	HPBC 2.0	24.1 %	53.90 V / 15.29 A	**Single, anti-glare**	15 yr
LONGi Guardian LR7-72HVD	HPBC 2.0	24.06 %	54.22 V / 15.14 A	**Dual, anti-glare, bifacial**	15 yr
LONGi Scientist LR7-72HVH	HPBC 2.0	24.1 %	53.90 V / 15.29 A	Single	15 yr
AIKO Comet 2U G-MCH72Mw	ABC	**24.4 %**	54.40 V / 15.12 A	Single	**15 yr, up to 25**
AIKO Stellar 1N+ G-MCH72Dw	ABC	24.1 %	54.00 V / 15.06 A	Dual, bifacial	Not stated

Best in each area

ANTI-GLARE
LONGi Guardian
0.9 % reflectivity, EN 17037 'AAA'

VALUE PER WATT
LONGi X10
Lower price in Thailand

EFFICIENCY
AIKO Comet 2U
24.4 % at 650 W; tie at 670 W

PRODUCT WARRANTY
AIKO Comet 2U
Extendable to 25 years

SHADING
LONGi
Publishes up to 70 % recovery

SAME ON BOTH
−0.26 %/°C
and 88.85 % output at year 30

Why back-contact? Both brands move all the cell contacts to the back, so the front has no busbars: more light reaches the cell, the panel looks uniform, and heat loss is among the lowest available (−0.26 % per °C), which matters on Thai rooftops.

Specifications are from the manufacturers' published datasheets; star ratings are Solar ESS's own assessment. Check the current datasheet before ordering. For prices and a design for your site, book a consultation at www.solaress.org or LINE: solaress1.

Sources: LONGi anti-glare · AIKO Comet 2U