

Digitap.ai KYC Validation API **Suite** **API Doc & Integration Guide**

(Version 4.91, 9th Jul 2026)

A jumpstart guide to boosting your Business

Save Time, Save Cost

Table of Contents

1 Introduction	6
1.1 Validation API Suite Introduction	6
2 API Documentation	7
2.1 Introduction	7
2.2 Authentication	7
2.3 API Request & Response Format	7
2.4 HTTP Status/Response Codes and its response body format	7
2.4.1 Error Messages	9
2.5 API Result	9
2.6 API Encryption	10
2.7 Additional Notes	13
3 KYC - PAN Basic Validation API (V1)	13
3.1 API Introduction	13
3.2 API URL	13
3.3 API Request	13
3.4 API Success Response	15
3.4.1 Successful Validation Case	15
3.5 API Error Response	18
4 KYC - PAN Basic Validation API (V2)	19
4.1 API Introduction	19
4.2 API URL	19
4.3 API Request	19
4.4 API Success Response	20
4.4.1 Successful Validation Case	20
4.5 API Error Response	23
5 KYC - PAN Details Validation API	24
5.1 API Introduction	24
5.2 API URL	25
5.3 API Request	25
5.4 API Success Response	27
5.4.1 Successful Validation Case	27
5.5 API Error Response	39
5.6 Encryption Support	40
6 KYC - PAN Details Plus Validation API	40
6.1 API Introduction	40
6.2 API URL	41
6.3 API Request	41
6.4 API Success Response	42
6.4.1 Successful Validation Case	42
6.5 API Error Response	53

7 KYC - PAN 206AB Compliance Status Validation API	53
7.1 API Introduction	53
7.2 API URL	54
7.3 API Request	54
7.4 API Success Response	55
7.4.1 Successful Validation Case	55
7.5 API Error Response	57
8 KYC - PAN ITR Validation API	57
8.1 API Introduction	57
8.2 API URL	57
8.3 API Request	58
8.4 API Success Response	58
8.4.1 Successful Validation Case	58
8.5 API Error Response	61
9 KYC - PAN to Name Validation API	62
9.1 API Introduction	62
9.2 API URL	62
9.3 API Request	62
9.4 API Success Response	63
9.4.1 Successful Validation Case	63
9.5 API Error Response	64
10 KYC - PAN to F'Name Validation API	64
10.1 API Introduction	64
10.2 API URL	65
10.3 API Request	65
10.4 API Success Response	66
10.4.1 Successful Validation Case	66
10.5 API Error Response	67
11 KYC - PAN Profile API	67
11.1 API Introduction	67
11.2 API URL	68
11.3 API Request	68
11.4 API Response	69
11.4.1 Successful Validation Case	69
11.4.2 Unsuccessful Validation Cases	73
11.4 API Error Response	73
12 KYC - PAN Account Link API	74
12.1 API Introduction	74
12.2 API URL	75
12.3 API Request	75
12.4 List of supported banks	76
12.5 API Success Response	78

12.5.1 Successful Validation Case	78
12.6 API Error Response	80
13 KYC - VoterID Validation API	81
13.1 API Introduction	81
13.2 API URL	81
13.3 API Request	81
13.4 API Success Response	82
13.4.1 Successful Validation Case	82
Application Number for PWD with doctor approval.	85
13.5 API Error Response	86
14 KYC - Passport Validation API	86
14.1 API Introduction	86
14.2 API URL	87
14.3 API Request	87
14.4 API Success Response	88
14.4.1 Successful Validation Case	88
14.5 API Error Response	90
15 KYC - PAN Aadhaar Link API	90
15.1 API Introduction	90
15.2 API URL	90
15.3 API Request	91
15.4 API Success Response	91
15.4.1 Successful Validation Case	92
15.5 API Error Response	95
15.6 Encryption Support	95
16 KYC - PAN to Masked Aadhaar Validation API	96
16.1 API Introduction	96
16.2 API URL	96
16.3 API Request	96
16.4 API Success Response	97
16.4.1 Successful Validation Case	97
16.5 API Error Response	98
16.6 Encryption Support	98
17 KYC - Aadhaar to Masked PAN Validation API	98
17.1 API Introduction	98
17.2 API URL	98
17.3 API Request	99
17.4 API Success Response	99
17.4.1 Successful Validation Case	99
17.5 API Error Response	101
17.6 Encryption Support	102
18 KYC - Driving Licence Validation API	102

18.1 API Introduction	102
18.2 API URL	102
18.3 API Request	102
18.4 API Success Response	103
18.4.1 Successful Validation Case	103
18.5 API Error Response	107
19 KYC - Driving Licence Validation Plus API	108
19.1 API Introduction	108
19.2 API URL	108
19.3 API Request	108
19.4 API Success Response	109
19.4.1 Successful Validation Case	109
19.5 API Error Response	115
20 KYC - Unique Disability ID Validation API	116
20.1 API Introduction	116
20.2 API URL	116
20.3 API Request	116
20.4 API Success Response	117
20.4.1 Successful Validation Case	117
20.5 API Error Response	122
21 KYC - Aadhaar to Unmasked PAN Validation API	123
21.1 API Introduction	123
21.2 API URL	123
21.3 API Request	123
21.4 API Success Response	124
21.4.1 Successful Validation Case	124
21.5 API Error Response	125

1 Introduction

This document is intended for our enterprise partners who can easily integrate the services they have chosen with Digitap.ai. Using this document they can jumpstart their business processes and start using the Digitap.ai services as early as possible and also align their own business processes seamlessly by integrating and making changes to their backend.

1.1 Validation API Suite Introduction

Digitap.ai Validation API Suite provides APIs to validate the KYC details of individual customers assets validation like Vehicle RC, Mobile Validation, Bank Validation and Other Misc Utilities:

- ❑ **KYC (*Know Your Customer*) Validation**
 - ❑ PAN Related:
 - ❑ PAN Details:
 - ❑ PAN Details Validation
 - ❑ PAN Details Validation (Backward Compatibility)
 - ❑ PAN Details Plus
 - ❑ PAN Basic Validation V1
 - ❑ PAN Basic Validation V2
 - ❑ PAN to Name Validation
 - ❑ PAN to F'Name Validation
 - ❑ PAN Account Link
 - ❑ PAN to Masked Aadhaar Validation
 - ❑ PAN Aadhaar Link Validation
 - ❑ PAN 206AB Compliance Status Validation
 - ❑ PAN ITR Status Validation
 - ❑ PAN Profile
 - ❑ Aadhaar Related
 - ❑ Aadhaar to Masked PAN
 - ❑ Aadhaar to Unmasked PAN
 - ❑ Voter ID Validation
 - ❑ Passport Validation
 - ❑ Driving Licence Validation
 - ❑ Driving License Validation Plus
 - ❑ Unique Disability ID Validation

Note: Digitap.ai reserves the right to modify this API documentation from time-to-time. If you are a business using this Service, you will be notified well in advance, prior to any impactful change being made.

2 API Documentation

2.1 Introduction

Digitap.ai Validation Suite provides RESTful/standard HTTP Web APIs which help to validate a specific data point by providing the response synchronously in the same API Call. The API uses the standard HTTP status/response codes to indicate the success or API errors.

2.2 Authentication

To use the API, one needs to register with Digitap and get a client id & client secret key. The client ID & secret key are different for the UAT & production environment.

2.3 API Request & Response Format

- Both the input request and response follow the JSON format.
- In each APIs input, a client reference number is accepted to easily identify the given request from a client and the same is also mirrored in the output. The other parameters required in the input and their format are explained in specific APIs.
- The API error is normally returned as standard HTTP Status/Response Codes and also mirrored in the body of the response.
- When the API request is accepted, HTTP status code 200 is returned and whether the validation is successful or not is returned in the result_code. The various possible values of the validation is explained under the section “API Result”
- In all the responses, an unique request-id (unique UUID) would be returned, which can be used for easier debugging in the future. Clients are requested to provide this request-id when raising an issue or discussing the response.

2.4 HTTP Status/Response Codes and its response body format

The API Error Codes are returned as HTTP Status Codes. Following status codes would be returned by the APIs.

Code	Message	Description
200	OK	Request Successful <i>(Note: 200 does not mean that Validation is success, but indicates that the request is successful. result_code in the Response body indicates whether the validation is successful or not).</i>

400	One or more parameters format is wrong	Input parameter passed by the customer is missing or invalid
401	Client Authentication failed	Access to API is denied
404	Path not found	The requested API endpoint/URL does not exist
404	Method not allowed	HTTP method used (GET/POST/PUT/DELETE) is not supported for this route
412	Feature is not Enabled. Please contact support/RM	The request feature in the API is not enabled
422	Digitap is unable to fetch the response at this moment	API is currently unable to give out the response due to a source issue
429	Rate Limit Exceeded	The allowed rate limit for transactions is exceeded for the API
500	Internal Error	Internal Server Error identified through its number
500	Failed to limit count	Server encountered an unexpected error while applying rate limit
503	Website is in maintenance	The source website is down for maintenance or inaccessible.
		Service briefly unavailable for scheduled maintenance
504	Endpoint request Timed out	The response latency from the source website is >30sec.

Format of the response body for successful request case (http Status code 200) is like below:

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",

  "result_code":nnn,

  // Optional items based on result_code
  "result":nnn,
  "message": "yyy",
}
```

Format of the response body for failure cases (http Status code other than 200) is like below:

```
{
  "http_response_code": nnn,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "xxxx"
}
```

2.4.1 Error Messages

Error messages for each of the failure cases is given below:

Code	Error Message
400	One or more parameters format is wrong or missing
401	Client Authentication Failed
403	Forbidden: IP not allowed
404	Path not found
404	Method not allowed
412	Feature is not Enabled. Please contact support/RM
422	Digitap is unable to fetch the response at this moment
429	Rate Limit Exceeded
500	Internal Error
500	Failed to limit count
503	Website is in maintenance
503*	Service briefly unavailable for scheduled maintenance
504	Endpoint request Timed out

* When the source is down, the services are put in maintenance

Please see the respective APIs for any additional details.

2.5 API Result

When the API returns HTTP status code 200/OK, the API request is accepted and result of the request is provided in the key called **"result_code"** in the response body:

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": nnn,
}
```

Various possible values of **result_code** and is tabled below:

result_code	Description
101	Validation Successful
102	Invalid id number or combination of inputs
103	No record found for the given input
104	Multiple records exist/application is rejected
108	If the user's application is under review
109	Not registered / Could not be validated

Please see the respective APIs for details of which result code occurs in the specific API.

2.6 API Encryption

Digitap APIs offer an option to enable **JWE encryption**, allowing the request payload to be sent and the response to be received in an **encrypted format**.

Encryption:

Following is the method to encrypt the request payload for the API :

- Construct the request payload that needs to be sent to the server based on the specific API
- Stringify the JSON request payload.
- Create the JWE (*JSON Web Encryption*) Token for the above text using Digitap public key provided and one of the secure JWE Algorithm & Encryption methods (*we suggest to use "alg" as RSA-OAEP-256 and "enc" as A256GCM for speed*).
- Set the above JWE Token generated as the value for the **"encrypted_data"** and pass this payload to the API.

Sample Request Payload :

For the sample payload,

```
{
  "client_ref_num": "test123",
  "pan": "AXTP1111T"
}
```

the following would be an encrypted payload.

```
{
  "encrypted_data":
  "eyJlbnMiOiJBMjU2R0NNIiwiaWYxYXNlIjoiaUINBLU9BRVAtMjU2In0.ks48nUM
  JrUSFxxH5ousovNmfUc8vFlukcQIVryKGwewoNc25jaEi0Aw-B6FDECeA
  1EZ0Mr6R16rQ13kbUifvPccTCQT5Sv2qhP3y0YfekvNdrzMIqBmPnU6G
  tzyPvXMGKvh0aWIdlWoBJgrDBIxRs-KWqHjoJUKCeSb_63P3hw.GfVGo
  6PLsWTN1hih.MlkihybDgCPo5U_6hOMSX6BBIRI-AWmmb4OF026fUOIG
  _7g6XMNzDk9oSShJwhtbBuyhe1BdZBUX80rjTpHjZInOcEgEnUAYyO3e
  53CUHiwKPxMcanIjBOY06SdWGLRuE76GTq6HTidcTfvjfCXUPWqRo5
  C9mdIf0SkeGSPZg.MPSzvZroJfPjcWiXMxgqYA"
}
```

Decryption:

Following is the method to decrypt the response payload received from the API :

- Get the data received in the “encrypted_data” field from the payload.
- Decrypt the above text using JWE method with your private key (*corresponding public key needs to be shared with the Digitap*)
- The decrypted data would be having the response in the format as given in the specified API.

Sample Response Payload :

For the sample response,

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "5ffc773f-3d35-11ef-a098-710ce390014b",
  "client_ref_num": "test123",
  "result": {
    "pan": "XXXPk1234B",
    "pan_type": "Individual",
    "fullname": "VIJAY KUMAR",
    "first_name": "VIJAY",

```

```

"middle_name": "",
"last_name": "KUMAR",
"gender": "male",
"aadhaar_number": "XXXXXXXX1234",
"aadhaar_linked": true,
"dob": "01/01/1984",
"mobile": "",
"email": ""
}
}

```

the following would be an encrypted response given by the API.

```

{
  "encrypted_data":
  "eyJlbmMiOiJBMjU2R0NNIiwiaWwiYWxnIjoiUINBLU9BRVAtMjU2In0.ks48nUM
  JrUSFxXH5ousovNmfUc8vFlukcQIVryKGwewoNc25jaEi0Aw-B6FDECeA
  1EZ0Mr6R16rQ13kbUifvPccTCQT5Sv2qhP3y0YfekvNdrzMIqBmPnU6G
  tzyPvXMGKvh0aWldlWoBJgrDBlxRs-KWqHjoJUKCeSb_63P3hw.GfVGo
  6PLsWTN1hih.MlkihybDgCPo5U_6hOMSX6BBIRI-AWmmb4OF026fUOIG
  _7g6XMNzDk9oSShJwhtbBuyhe1BdZBUX80rjTpHjZlnOcEgEnUAYyO3e
  53CUHiwKPxMcanIJjBOY06SdWGLRuE76GTq6HTidcTfvjfCXUPWqRo5
  C9mdIf0SkeGSPZg.MPSzvZroJfPjcWiXMxgqYA"
}

```

Note :

- Clients need to generate the private-Public Key and provide the public key to Digitap. One can generate the public key using OpenSSH or Website like <https://cryptotools.net/rsagen>. We recommend using 1024 bits for speed of decryption. Clients can choose the bit length based on their infosec guidelines.
- Clients can get the Digitap Public Key by contacting the RM.
- Only specific APIs support encryption and decryption. Please refer to the specific API to check whether encryption is supported in the specific API section. If you require Encryption in other APIs, please raise the request to the RM.

Error Message related to Encryption:

When the encryption method is used for sending the data to the API, the response would be received in encrypted format including the error messages. However, some responses occurring at the infra level or initial validation would be in non-encrypted manner. Few cases where the response would be in non-encrypted manner are:

- Rate Limiting Error
- DNS or Load Balancer Errors

Apart from the error messages provided in [2.40. HTTPS Status/Response Codes](#), following additional status code/errors may occur when encryption is being used.

Code	Error Message	Description
401	Invalid Encryption	JWE decryption failed at digitap due to error in encrypted data
451	Misconfiguration	Encryption is not enabled for the client

2.7 Additional Notes

- API will be billable for any successful responses with http response code 200 irrespective of result code.

3 KYC - PAN Basic Validation API (V1)

3.1 API Introduction

This API helps to validate the basic details of PAN card Holder - PAN Number and Name of the PAN Card Holder. This API fetches the Name of the PAN Card Holder from the PAN government database. This API returns a success response if the PAN exists in the NSDL database and returns the Status of PAN (Active/Invalid) and the name is matched exactly between PAN government database and NSDL database. This API also verifies the input name is matched exactly with the name from the PAN government database.

3.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_basic
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_basic

3.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
-----	--------------------------	-------

content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10 Pattern: ^([a-zA-Z]{3})([abcfghljpteABCFGHLJPTE]{1})([a-zA-Z]{1})([0-9]{4})([a-zA-Z]{1})\$
name	O	Exact name as per PAN minLength: 1 maxLength: 85 Data Type: String, only English Characters and following special characters allowed ~, ^, /, \, . and &
name_match_method	O	Either `fuzzy` or `exact` or `dg_name_match` . Default: `fuzzy` `exact` - Exact Word Name Match (See Notes for more details) `fuzzy` - Rule engine based Fuzzy matching (V1 of PAN name match) `dg_name_match` - Name Matching as per the Digitap's Name Matching Utility (V2 of PAN Name Match)

Note:

- **exact name match method:**

- Exact Name match method gives name_match as true and name_match_score as 100 if it satisfies one of the below condition:
 - Input Name = PAN NAME
 - Input Name = PAN DISPLAY NAME
- Otherwise, it gives name_match as false and name_match_score as 0
- **fuzzy name match method:**
 - Fuzzy name method uses fuzzy name matching techniques on both PAN name and display name (like full & partial token sort & set ratios) combined with a rule engine to give a better name match.
- **dg_name_match name match method:**
 - Digitap Name Matching utility is a separate utility provided by Digitap for name match purposes. It is similar to that of the “fuzzy” name method, but with more capabilities (*like handling abbreviations like Mohd, MD, Salutations like Mr,) and enhancements (like handling missing common surnames like bhaj, rao).*
 - dg_name_match method uses the Digitap’s Name Matching Utility on both the PAN Name and Display Name, and gives the best result among them.

3.4 API Success Response

3.4.1 Successful Validation Case

When the PAN details are matched, result_code 101 would be returned. The response format for the same is as follows:

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 101,
  "result": {
    "pan": "ABCPE1234Z",
    "status": "Active",
    "name": "JOHN DOE",
    "pan_display_name": "JOHN DOE",
    "seeding_status": "Y",
    "name_validated": "Y",
    "name_match": true,
    "name_match_score": 100
  }
}
```

Keys of Result Object are explained below:

Key	Type	Value
pan	string	PAN of PAN card holder

status	string	Status of the PAN (Active / Invalid) PAN verification status are below : "E" - EXISTING AND VALID, "F" - Marked as Fake "X" - Marked as Deactivated "D" - Deleted "N" - Record (PAN) Not Found in ITD Database/Invalid PAN "EA" - Existing and Valid but event marked as "Amalgamation" in ITD database "EC" - Existing and Valid but event marked as "Acquisition" in ITD database "ED" - Existing and Valid but event marked as "Death" in ITD database "EI" - Existing and Valid but event marked as "Dissolution" in ITD database "EL" - Existing and Valid but event marked as "Liquidated" in ITD database "EM" - Existing and Valid but event marked as "Merger" in ITD database "EP" - Existing and Valid but event marked as "Partition" in ITD database "ES" - Existing and Valid but event marked as "Split" in ITD database "EU" - Existing and Valid but event marked as "Under Liquidation" in ITD database
name	string	Name of PAN card holder (as per PAN government database)
pan_display_name	string	Name Printed on the PAN Card. If there is no pan_display_name or if the source does not provide this data, then this field would be empty.
name_match	boolean	Name match result based on name_matching_method between the input name provided and name from PAN government database - true or false. true - If name is matched, that is name_match_score > 80 false - If name is matched, that is name_match_score < 80
name_match_score	integer	Name matching score based on the name_match_method.

		Values range from 0 - 100 For fuzzy and dg_name_match method, the score will be from 0 to 100 based on the match. For the exact method, the score will be either 0 or 100.
seeding_status	string	Flag to show the operative status of the PAN. "Y" - "Operative" "R" - "Not Operative" "NA" - "Not Applicable in case of non individual PAN" (Note: This field given only when the "seeding_status" feature has been enabled for the client)
name_validated	string	Below information will be displayed based on matching result between the name provided by PAN government database and NSDL database : Y - YES (If name is exactly matched) N - NO (If name is not exactly matched)

Note:

- If no name is provided in the input, then "name_match" would be "false" and "name_match_score" would be 0.
- If no name is not available from the PAN government database or the source is not available, then "name_validated" would be checked between input name and name from the NSDL database. The "name" will be displayed with input name if only the "name_validated" is "Y"

The following response would be provided in case if the PAN could not be validated

1. If the given PAN number is Invalid (Deactivated, Deleted, Fake, Inoperative, etc), then the below response would be provided.

```

{
  "http_response_code": 200,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 102,
  "message": "Invalid ID number or combination of inputs",
  "result": {
    "pan": "ABCPE1234Z",
    "status": "Invalid",
    "name": "",
    "pan_display_name": "",
    "seeding_status": "",
    "name_validated": "N",
    "name_match": false,
    "name_match_score": 0
  }
}

```

2. If the given PAN number is Invalid (Not Allocated), then the below response would be provided.

```

{
  "http_response_code": 200,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 103,
  "message": "No record found for the given input",
  "result": {
    "pan": "ABCPE1234Z",
    "status": "Invalid",
    "name": "",
    "pan_display_name": "",
    "seeding_status": "",
    "name_validated": "N",
    "name_match": false,
    "name_match_score": 0
  }
}

```

3.5 API Error Response

The API service includes an internal regex check that validates the PAN format. If the format is Invalid (does not meet the input parameter criteria), a 400 error is returned.

```

{
  "http_response_code": 400,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "One or more parameters format is wrong"
}

```

Note: If the PAN fails for other reasons such as being fake, deactivated, deleted, associated with a deceased individual, inoperative, or similar - a 102 result code is returned, indicating that the PAN status is Invalid.

In case of Error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

4 KYC - PAN Basic Validation API (V2)

4.1 API Introduction

This API helps to validate the PAN Status along with basic details of PAN card Holder - PAN Number and Name of the PAN Card Holder, DOB. This API provides the status of the PAN along with Match Details of Name, Name on Card & DOB and Aadhaar Seeding Status.

4.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v2/pan_basic
Production Env	https://svc.digitap.ai/validation/kyc/v2/pan_basic

4.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]

pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10 Pattern: <code>^([a-zA-Z]{3})([abcfghljpteABCFGHLJPTE]{1})([a-zA-Z]{1})([0-9]{4})([a-zA-Z]{1})\$</code> Data Type: String
name	M	Name is either the Full Name or PAN Display Name (Name on Card) of PAN Holder. Full Name is the combination of First Name, Middle Name, Last Name in the same order. Make sure that there is only one space between two words, as multiple spaces would lead to name mismatch. Name field is NOT case sensitive and should not contain any numeric characters. maxLength: 85 Data Type: String, only English Characters and following special characters allowed ~, ^, /, \, ., and &
dob	M	Date of Birth in the format (DD/MM/YYYY) and it should be separated with slash (/). Length: 10 Please note that format of D/M/YYYY is not accepted (like 2/9/1992 is not accepted, it should be 02/09/1992). Data Type: Date

4.4 API Success Response

4.4.1 Successful Validation Case

When the PAN details are matched, result_code 101 would be returned. The response format for the same is as follows:

```

{
  "http_response_code": 200,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 101,
  "result": {
    "pan": "ABCPE1234Z",
    "status": "Active",
    "status_code": "E",
    "name": "Y",
    "dob": "Y",
    "seeding_status": "Y"
  }
}

```

Keys of Result Object are explained below:

Key	Type	Value
pan	string	PAN Number of individual or entity
status	string	PAN Status whether Active or Invalid. “Active” is given when the status code is “E” and “invalid” is given for all other status_code.
status_code	string	PAN verification status are below : “E”- EXISTING AND VALID, “F” - Marked as Fake “X” - Marked as Deactivated “D” - Deleted “N” - Record (PAN) Not Found in ITD Database/Invalid PAN “EA” - Existing and Valid but event marked as “Amalgamation” in ITD database “EC” - Existing and Valid but event marked as “Acquisition” in ITD database “ED” - Existing and Valid but event marked as “Death” in ITD database “EI” - Existing and Valid but event marked as “Dissolution” in ITD database “EL” - Existing and Valid but event marked as “Liquidated” in ITD database “EM” - Existing and Valid but event marked as “Merger” in ITD database “EP” - Existing and Valid but event marked as “Partition” in ITD database “ES” - Existing and Valid but event marked as

		"Split" in ITD database "EU" - Existing and Valid but event marked as "Under Liquidation" in ITD database
name	string	Name Match Status (<i>match between the Input Name(first_name+middle_name+last_name) and Government Database Name</i>). Possible values are Y/N/[Empty String]. Y – YES (If matched with Database) N - NO (If not matched with Database) Y/N is given when status_code is E or E along with the event (EA, EC,etc). Match Method is exact match. For Invalid PANs, this field would be an empty string.
dob	string	Date of Birth Match Status. (<i>match between the Input dob and Government Database dob value</i>). Possible values are Y/N/[Empty String]. Y – YES (If matched with database) N - NO (If not matched with database) Y/N is given when status_code is E or E along with the event (EA, EC,etc). For Invalid PANs, this field would be an empty string.
seeding_status	string	Flag to show the operative status of the PAN. "Y" - "Operative" "R" - "Not Operative" "NA" - "Not Applicable in case of non individual PAN" (Note: This field given only when the "seeding_status" feature has been enabled for the client)

The following response would be provided in case if the PAN could not be validated

1. If the given PAN number has become Invalid (like Deactivated, Deleted, Fake, Inoperative, Existing but marked as Death, etc), then the below response would be provided.

```

{
  "http_response_code": 200,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 102,
  "message": "Invalid ID number or combination of inputs",
  "result": {
    "pan": "ABCPE1234Z",
    "status": "Invalid",
    "status_code": "D",
    "name": "",
    "dob": "",
    "seeding_status": ""
  }
}

```

Note: Above is the result for an deleted PAN. status_code would change for other cases.

2. If the given PAN number is Not Allotted PAN Number, then the below response would be provided.

```

{
  "http_response_code": 200,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 103,
  "message": "No record found for the given input",
  "result": {
    "pan": "ABCPE1234Z",
    "status": "Invalid",
    "status_code": "N",
    "name": "",
    "dob": "",
    "seeding_status": ""
  }
}

```

4.5 API Error Response

The API service includes an internal regex check that validates the PAN format. If the format is Invalid (does not meet the input parameter criteria), a 400 error is returned.

```

{
  "http_response_code": 400,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "One or more parameters format is wrong"
}

```

Note: If the PAN fails for other reasons such as being fake, deactivated, deleted, associated with a deceased individual, inoperative, or similar - a 102 result code is returned, indicating that the PAN status is Invalid.

In case of Error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

5 KYC - PAN Details Validation API

5.1 API Introduction

This API helps to get various details related to the PAN.

- **Demographic details** like dob, gender, etc,
- **Aadhaar Linking Status** & Linked aadhaar number(in 2 different formats, please refer to section below on Aadhaar formats)
- **Address** available against PAN from the government source (*usually provided during the PAN card registration or updation*)
- **Type of PAN** (*like individual PAN, Company PAN, etc*)
- **Masked Contact Details** (like Mobile & Email Address)(*when masked contact details configuration has been enabled*)*
- **Father's Name** (*for individual PAN*)*
- **PAN Status** (*when pan_status_check has been enabled*)*
- **Aadhaar Seeding Status** (*when pan_status_check has been enabled*)*
- **PAN Display Name** (*when pan_display_name has been enabled*)*
- **Tax flag**(*when tax configuration is enabled*)*

Aadhaar Masking Formats:

We return Aadhaar number in 2 formats:

- A subset of responses will return Aadhaar in a **"last 4 digits unmasked"** format (e.g., XXXXXXXX1234)
- Another subset of responses will return Aadhaar with the **"first 2 and last 2 digits unmasked"** format (e.g., 12XXXXXXXX34), in case the last 4 digits unmasked data is unavailable.

Please note that the responses will be in mixed percentages. In case you need only 1 format in the output, please reach out to your RM. Success percentages will depend on the format chosen and the target customer base.

Note:

- The **"pan_display_name"** and **"father_name"** feature can be enabled at client ID level. Please discuss with your RM for details. When the **"pan_display_name"** is enabled, the name displayed on the PAN card will be provided in the output.
- **"pan_status_check"** feature can be enabled at client ID level. When the **"pan_status_check"** feature has been enabled, this API calls the PAN Basic API (V2) and gets the authentic status of the PAN number, along with Aadhaar seeding information, in the output. The **"pan_status_check"** feature has additional commercial implications. Please discuss with your RM for details.

- This API also has an option to use JWE as standard encryption. Refer the [Section 2.6](#) for details. Clients who require this encryption in the API need to share their public key, and Digitap will share its public key with the client. Please discuss with your RM for details.

5.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_details
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_details

For the clients who want the response to be compatible with PAN Basic V1 API, please use the following URL.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_details_bc
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_details_bc

5.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 100 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10

		Pattern: <code>^([a-zA-Z]{3})([abcfghljpteABCFGHLPTE]{1})([a-zA-Z]{1})([0-9]{4})([a-zA-Z]{1})\$</code>
father_name	☐	Flag to indicate whether to get the father's name or not. Allowed values are `true` or `false` (<i>String data type</i>) Default: `false` `true` - it will return Father's Name
pan_display_name	☐	Flag to indicate whether to get the name displayed on the PAN or not. Allowed values are `true` or `false` (<i>String data type</i>) Default: `false` `true` - it will return the name on the PAN
name	☐	Name to match and provide the match result & score in the output. When this field is given, this API compares the input name with output name based on "name_match_method" and provides the output. minLength: 1 maxLength: 150
name_match_method	☐	Either `fuzzy` or `exact` or `dg_name_match` . Default: `fuzzy` `exact` - Exact Word Name Match (<i>See Notes for more details</i>) `fuzzy` - Rule engine based Fuzzy matching (<i>V1 of PAN name match</i>) `dg_name_match` - Name Matching as per the Digitap's Name Matching Utility (<i>V2 of PAN Name Match</i>)

- **Encrypted Request:**

This API supports request payload encryption. Please refer to [Section 2.6](#) for details.

5.4 API Success Response

This API supports response encryption. Please refer to [Section 2.6](#) for details.

5.4.1 Successful Validation Case

When the PAN details are matched, result_code 101 would be returned. The response format for the same is as follows:

1. **Without pan_status_check feature (and without Father's name feature):**

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",
    "gender": "male",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": "INDIA"
    },
    "mobile": "",
    "email": ""
  }
}
```

2. **With pan_status_check Feature (and without Father's Name Feature):**

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_status": "Active",
    "pan_type": "Individual",
```

```

    "fullname": "JOHN DOE",
    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",
    "gender": "male",
    "aadhaar_seeding_status": "Y",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
        "building_name": "",
        "locality": "",
        "street_name": "",
        "pincode": "",
        "city": "",
        "state": "",
        "country": "INDIA"
    },
    "mobile": "",
    "email": ""
}
}

```

3. With Father's Name Feature:

```

{
    "http_response_code": 200,
    "result_code": 101,
    "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
    "client_ref_num": "abcd123",
    "result": {
        "pan": "ABCPE1234Z",
        "pan_type": "Individual",
        "fullname": "JOHN DOE",
        "first_name": "JOHN",
        "middle_name": "",
        "last_name": "DOE",
        "father_name": "RICHARD JOHN",
        "gender": "male",
        "aadhaar_number": "XXXXXXXX1234",
        "aadhaar_linked": true,
        "dob": "11/08/1970",
        "address": {
            "building_name": "",
            "locality": "",
            "street_name": "",
            "pincode": "",
            "city": "",
            "state": "",
            "country": "INDIA"
        },
        "mobile": "",
        "email": ""
    }
}

```

4. Name Match Scenario:

When the input provided contains the input “name” to match (like below):

```
{
  "client_ref_num": 200,
  "pan": "ABCPE1234Z",
  "name": "Arun Kumar K",
}
```

Output would be like the following:

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "Individual",
    "fullname": "ARUN KUMAR KULTHIA",
    "first_name": "ARUN",
    "middle_name": "KUMAR",
    "last_name": "KULTHIA",
    "gender": "male",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": "INDIA"
    },
    "mobile": "",
    "email": "",
    "name_match": true,
    "name_match_score": 90
  }
}
```

Note: In the above example, input name - Arun Kumar K has been **fuzzy matched** with “ARUN KUMAR KULTHIA” and match results are given.

5. With PAN Display Name Feature:

```

{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
    "first_name": "JOHN",
    "middle_name": "SIMON",
    "last_name": "DOE",
    "pan_display_name": "JOHN SIMON DOE",
    "gender": "male",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": "INDIA"
    },
    "mobile": "",
    "email": ""
  }
}

```

6. Aadhaar number linking configurations:

The following configurations are accessible exclusively during periods when the API experiences downtime caused by fluctuations at the source level. Response can be either enabled or disabled to get “aadhaar_number”. Please reach out to RM to get the required configuration enabled.

This API comes with two configurations for Aadhaar Linking status. :

- **Configuration 1:** Response for this key will be empty and “aadhaar_linked” will be null as shown in the below response.

```

{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",

```

```

    "pan_display_name": "JOHN DOE"
    "gender": "male",
    "aadhaar_number": "",
    "aadhaar_linked": null,
    "dob": "11/08/1970",
    "address": {
        "building_name": "",
        "locality": "",
        "street_name": "",
        "pincode": "",
        "city": "",
        "state": "",
        "country": "INDIA"
    },
    "mobile": "",
    "email": ""
}

```

- **Configuration 2:** The “aadhaar_number” value will be in the format shown in the below response.

```

{
    "http_response_code": 200,
    "result_code": 101,
    "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
    "client_ref_num": "abcd123",
    "result": {
        "pan": "ABCPE1234Z",
        "pan_type": "Individual",
        "fullName": "JOHN DOE",
        "first_name": "JOHN",
        "middle_name": "",
        "last_name": "DOE",
        "pan_display_name": "JOHN DOE"
        "gender": "male",
        "aadhaar_number": "12XXXXXXXX34",
        "aadhaar_linked": true,
        "dob": "11/08/1970",
        "address": {
            "building_name": "",
            "locality": "",
            "street_name": "",
            "pincode": "",
            "city": "",
            "state": "",
            "country": "INDIA"
        },
        "mobile": "",
        "email": ""
    }
}

```

7. When “pan_details_bc” endpoint is used:

When the “pan_details_bc” is used, Output would be like the following:

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_status": "Active",
    "status": "Active",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
    "name": "JOHN DOE",
    "pan_display_name": "",
    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",
    "gender": "male",
    "aadhaar_seeding_status": "Y",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": "INDIA"
    },
    "mobile": "",
    "email": "",
    "name_match": false,
    "name_match_score": 0
  }
}
```

Keys of Response Object are explained below:

Key	Type	Value
http_response_code	int	Internal Status Code that denotes the status of the request
result_code	String	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request

client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
 - pan	String	PAN of the Individual / Entity
 - pan_status	String	PAN Status of the Individual / Entity Possible values: Active, Invalid (Note: This field given only when the “pan_status_check” feature has been enabled for the client)
 - pan_type	String	Type of PAN (Refer the table below to know various PAN types)
 - fullname	String	Full name of the Applicant / Entity as per government records, including first name, middle name & last name.
 - first_name	String	First name of the applicant as per government records
 - middle_name	String	Middle name of the applicant as per government records
 - last_name	String	Last Name of the applicant as per government records
 - father_name	String	Father’s Name of the Individual. Note: • This field is given only when the “father_name” argument is set to “true” during input • For non-individual PAN types, this field would be an empty string.
 - pan_display_name	String	Name on the PAN of the Individual. Note: • This field is given only when the “pan_display_name” argument is set to “true” during input • For non-individual PAN types, this field would be an empty string.
 - gender	String	Individual’s gender as per PAN. Possible Values: • male • female • transgender <i>(for other PAN types, this field would be empty string)</i>

- dob	String	Date of birth or Incorporation in the format DD/MM/YYYY
- aadhaar_seeding_status	String	Flag to show if Aadhaar is linked to PAN. "Y" - "Operative" "R" - "Not Operative" "NA" - "Not Applicable in case of non individual PAN" (Note: This field given only when the "pan_status_check" feature has been enabled for the client)
- aadhaar_number	String	Aadhaar linked to PAN (<i>provided in 2 masked forms - first 8 digits masked and last 4 digits unmasked or 1st 2 and last 2 digits unmasked, remaining 8 digits masked</i>). Applicable only for the Individual PAN (<i>for other PAN types, this field would be empty string</i>)
- aadhaar_linked	Bool	Aadhaar Linked Status. true - Aadhaar Linked false - Aadhaar Not Linked Applicable only for Individual PAN (<i>for other PAN types, this field would be null</i>) Aadhaar linked status comes with two configurations, refer to point 5.4.1.6 for detailed explanation.
- address	Dict	Object containing the address available against PAN from the government source (<i>usually provided during the PAN card registration or updation</i>)
- - building_name	String	Building Name of the Address
- - locality	String	Address Locality
- - street_name	String	Street Name of the Address
- - pincode	String	Pincode of the Address
- - city	String	City of the Address
- - state	String	State of the Address
- - country	String	Country of the Address Note: For Indian Address, this field is generally given as "" (empty string) from the source and for other countries, this field contains the country name.

 - mobile	String	Mobile number associated with PAN from the government source
 - email	String	Email ID registered for given PAN Number (<i>usually provided during the PAN card registration or updation</i>)
 - name_match	boolean	Name match result based on name_matching_method - true or false (<i>boolean data type</i>) Note: This field is given when the input contains the "name".
 - name_match_score	integer	Name matching score based on the name_match_method. Values range from 0 - 100 (<i>integer data type</i>) For fuzzy and dg_name_match method, the score will be from 0 to 100 based on the match. For the exact method, the score will be either 0 or 100. Note: This field is given when the input contains the "name".

Following additional keys are provided in the response when [pan_details_bc](#) endpoint is used (*which is provided for easier compatibility with PAN Basic V1 response for the clients migrating from PAN Basic V1 to PAN Details API*).

 - name	String	Same as fullname. Full Name of the Applicant / Entity as per government Records, including first name, middle name & last name
 - status	String	Same as pan_status PAN Status of the Individual / Entity Possible values: Active, Invalid (Note: This field given only when the "pan_status_check" feature has been enabled for the client)
 - pan_display_name	String	This field would always be an empty string and provided for backward compatibility.
 - name_match	boolean	Name match result based on name_matching_method - true or false (<i>boolean data type</i>)

		<i>This field is always given irrespective of whether “name” is given in the input when pan_details_bc is used.</i>
 - name_match_score	integer	Name matching score based on the name_match_method. Values range from 0 - 100 (<i>integer data type</i>) For fuzzy and dg_name_match method, the score will be from 0 to 100 based on the match. For the exact method, the score will be either 0 or 100. <i>This field is always given irrespective of whether “name” is given in the input when pan_details_bc is used.</i>

Various PAN Types
Individual
Company
Hindu Undivided Family (HUF)
Association of Persons (AOP)
Body of Individuals (BOI)
Government Agency
Artificial Juridical Person
Local Authority
Firm/Limited Liability Partnership
Trust

The following response would be provided in case if the PAN could not be validated

1. **Without pan_status_check feature**

If the given PAN number is found to be Invalid / Inactive through internal source, then the below response would be provided (*result code - 102*).

```

{
  "http_response_code": 200,
  "result_code": 102,
  "message": Invalid ID number or combination of inputs,
  "request_id": "10f66706-77b2-11ee-9c0c-f359806a26c7",
  "client_ref_num": "dg-test-2dfe7ca3-5e33-48f8-b1ed-97398b868d05",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "",
    "fullname": "",
    "first_name": "",
    "middle_name": "",
    "last_name": "",
    "gender": "",
    "dob": "",
    "aadhaar_number": "",
    "aadhaar_linked": "",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": ""
    },
    "mobile": "",
    "email": ""
  }
}

```

If the given PAN number is found to be Not Alloted through internal source, then the below response would be provided (*result code - 103*).

```

{
  "http_response_code": 200,
  "result_code": 103,
  "message": "No record found for the given input",
  "request_id": "10f66706-77b2-11ee-9c0c-f359806a26c7",
  "client_ref_num": "dg-test-2dfe7ca3-5e33-48f8-b1ed-97398b868d05",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "",
    "fullname": "",
    "first_name": "",
    "middle_name": "",
    "last_name": "",
    "gender": "",
    "dob": "",
    "aadhaar_number": "",
    "aadhaar_linked": "",
    "address": {
      "building_name": "",
      "locality": "",

```

```

        "street_name": "",
        "pincode": "",
        "city": "",
        "state": "",
        "country": ""
    },
    "mobile": "",
    "email": ""
}

```

2. With pan_status_check feature

If the given PAN number is found to be Invalid / Inactive / Deactivated / Deleted through PAN Basic API, then the below response would be provided (*result code - 102*).

```

{
  "http_response_code": 200,
  "result_code": 102,
  "message": Invalid ID number or combination of inputs,
  "request_id": "10f66706-77b2-11ee-9c0c-f359806a26c7",
  "client_ref_num": "dg-test-2dfe7ca3-5e33-48f8-b1ed-97398b868d05",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_status": "Invalid",
    "pan_type": "",
    "fullname": "",
    "first_name": "",
    "middle_name": "",
    "last_name": "",
    "gender": "",
    "dob": "",
    "aadhaar_seeding_status": "",
    "aadhaar_number": "",
    "aadhaar_linked": "",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": ""
    },
    "mobile": "",
    "email": ""
  }
}

```

If the given PAN number is found to be Not Allotted through PAN Basic API, then the below response would be provided (*result code - 103*).

```

{
  "http_response_code": 200,
  "result_code": 103,
  "message": "No record found for the given input",
  "request_id": "10f66706-77b2-11ee-9c0c-f359806a26c7",
  "client_ref_num": "dg-test-2dfe7ca3-5e33-48f8-b1ed-97398b868d05",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_status": "Invalid",
    "pan_type": "",
    "fullname": "",
    "first_name": "",
    "middle_name": "",
    "last_name": "",
    "gender": "",
    "dob": "",
    "aadhaar_seeding_status": "",
    "aadhaar_number": "",
    "aadhaar_linked": "",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": ""
    },
    "mobile": "",
    "email": ""
  }
}

```

5.5 API Error Response

The API service includes an internal regex check that validates the PAN format. If the format is Invalid (does not meet the input parameter criteria), a 400 error is returned.

```

{
  "http_response_code": 400,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "One or more parameters format is wrong"
}

```

When a specific feature like father's name or PAN display name is not enabled but is requested, a 412 error would be returned.

When Father's Name is not enabled:

```
{
  "http_response_code": 412,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "Father's Name is not Enabled. Please contact support/RM"
}
```

When PAN Display Name is not enabled:

```
{
  "http_response_code": 412,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "PAN Display Name is not Enabled. Please contact support/RM"
}
```

Note: If the PAN fails for other reasons such as being fake, deactivated, deleted, associated with a deceased individual, inoperative, or similar - a 102 result code is returned, indicating that the PAN status is Invalid.

In case of other errors, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

5.6 Encryption Support

This API supports Encryption of request and response. Please refer to the [Section 2.6 API Encryption](#)

6 KYC - PAN Details Plus Validation API

6.1 API Introduction

This API helps to get all the details related to the PAN just as the PAN Details API :

- **Demographic details** like dob, gender, etc,
- **Aadhaar Linking Status** & Linked aadhaar number(in 2 different formats, please refer to section below on Aadhaar formats)
- **Address** available against PAN from the government source (*usually provided during the PAN card registration or updation*)
- **Type of PAN** (*like individual PAN, Company PAN, etc*)
- **Contact Details** (like Mobile & Email Address)

This API also helps to get the additional details related to the PAN as listed below :

- **PAN Status** (details related to validity status and operative status of PAN from another government source and not from NSDL)
- **Signatory details** (details related to the signatory for non-individual PAN)
- **Sole proprietor information** (for individual PAN)
- **Directorship information** (for individual PAN)
- **Salaried information** (for individual PAN)
- **PAN allotment date** (date when PAN was allotted)

Aadhaar Masking Formats:

We return Aadhaar number in 2 formats:

- A subset of responses will return Aadhaar in a **"last 4 digits unmasked"** format (e.g., XXXXXXXX1234)
- Another subset of responses will return Aadhaar with the **"first 2 and last 2 digits unmasked"** format (e.g., 12XXXXXXXX34), in case the last 4 digits unmasked data is unavailable.

Please note that the responses will be in mixed percentages. In case you need only 1 format in the output, please reach out to your RM. Success percentages will depend on the format chosen and the target customer base.

6.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_details_plus
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_details_plus

6.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for the request from the Client side [Max of 100 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10 Pattern: <code>^([a-zA-Z]{3})([abcfghljpteABCFGHLJPTE]{1})([a-zA-Z]{1})([0-9]{4})([a-zA-Z]{1})\$</code>

6.4 API Success Response

6.4.1 Successful Validation Case

When the PAN details are matched, result_code 101 would be returned. The response format for the same is as follows:

1. Successful validation response for individual PAN

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",
    "gender": "male",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": "INDIA"
    },
    "mobile": ""
  }
}
```

```

    "email": "",

    "signatory_details" : {},

    "is_sole_proprietor": "Y",
    "is_director": "Y",
    "is_salaried": "Y",
    "pan_status": "Active and operative",
    "pan_allotment_date": "20/07/2010"

  }
}

```

2. Successful validation response for non-individual PAN

```

{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCP1234Z",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",
    "gender": "male",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": "INDIA"
    },
    "mobile": "",
    "email": "",

    "signatory_details" : { },

    "is_sole_proprietor": null,
    "is_director": null,
    "is_salaried": null,
    "pan_status": "Active and operative",
    "pan_allotment_date": "20/07/2010"

  }
}

```

3. **When PAN status and PAN allotment date information is not available due to source issue/unavailability :**

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "372fde6a-106b-11f0-a28d-fb7b0ac88d2b",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",
    "gender": "male",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": "India"
    },
    "mobile": "",
    "email": "",

    "signatory_details": {},

    "is_sole_proprietor": "N",
    "is_director": "N",
    "is_salaried": "N",
    "pan_status": "E",
    "pan_allotment_date": "E"
  }
}
```

4. **When Individual's salaried information is not available due to source issue/unavailability :**

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "772857c2-106b-11f0-8140-9f6aea43255f",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
```

```

    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",
    "gender": "male",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
        "building_name": "",
        "locality": "",
        "street_name": "",
        "pincode": "",
        "city": "",
        "state": "",
        "country": "India"
    },
    "mobile": "",
    "email": "",

    "signatory_details": {},

    "is_sole_proprietor": "N",
    "is_director": "N",
    "is_salaried": "E",
    "pan_status": "Active and operative",
    "pan_allotment_date": "06/07/2019"
}
}

```

5. When Individual's sole proprietorship information is not available due to source issue/unavailability :

```

{
    "http_response_code": 200,
    "result_code": 101,
    "request_id": "a91ff3cc-106b-11f0-8bc4-e380a7d018d0",
    "client_ref_num": "abcd123",
    "result": {
        "pan": "ABCPE1234Z",
        "pan_type": "Individual",
        "fullname": "JOHN DOE",
        "first_name": "JOHN",
        "middle_name": "",
        "last_name": "DOE",
        "gender": "male",
        "aadhaar_number": "XXXXXXXX1234",
        "aadhaar_linked": true,
        "dob": "11/08/1970",
        "address": {
            "building_name": "",
            "locality": "",
            "street_name": "",
            "pincode": "",
            "city": "",

```

```

        "state": "",
        "country": "India"
    },
    "mobile": "",
    "email": "",

    "signatory_details": {},

    "is_sole_proprietor": "E",
    "is_director": "N",
    "is_salaried": "N",
    "pan_status": "Active and operative",
    "pan_allotment_date": "06/07/2019"
}
}

```

6. **When Individual's directorship information is not available due to source issue/unavailability :**

```

{
    "http_response_code": 200,
    "result_code": 101,
    "request_id": "c4afe6ce-106b-11f0-ba58-bb1a6d821493",
    "client_ref_num": "abcd123",
    "result": {
        "pan": "ABCPE1234Z",
        "pan_type": "Individual",
        "fullname": "JOHN DOE",
        "first_name": "JOHN",
        "middle_name": "",
        "last_name": "DOE",
        "gender": "male",
        "aadhaar_number": "XXXXXXXXX1234",
        "aadhaar_linked": true,
        "dob": "11/08/1970",
        "address": {
            "building_name": "",
            "locality": "",
            "street_name": "",
            "pincode": "",
            "city": "",
            "state": "",
            "country": "India"
        },
        "mobile": "",
        "email": "",

        "signatory_details": {},

        "is_sole_proprietor": "N",
        "is_director": "E",
        "is_salaried": "N",
        "pan_status": "Active and operative",
        "pan_allotment_date": "06/07/2019"
    }
}

```

```
}
```

7. When PAN status, PAN allotment date, individual's salaried, individual's sole proprietorship, individual's directorship information is not available due to source issue/unavailability :

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "11c090be-1086-11f0-9922-8fa6335bbc1c",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "Individual",
    "fullname": "JOHN DOE",
    "first_name": "JOHN",
    "middle_name": "",
    "last_name": "DOE",
    "gender": "female",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "11/08/1970",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": "India"
    },
    "mobile": "",
    "email": "",

    "signatory_details": {},

    "is_sole_proprietor": "E",
    "is_director": "E",
    "is_salaried": "E",
    "pan_status": "E",
    "pan_allotment_date": "E"
  }
}
```

Note: In the above example, input name - Arun Kumar K has been **fuzzy matched** with “ARUN KUMAR KULTHIA” and match results are given.

Keys of Response Object are explained below:

Key	Type	Value
-----	------	-------

http_response_code	int	Internal Status Code that denotes the status of the request
result_code	String	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request
client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
 - pan	String	PAN of the Individual / Entity
 - pan_type	String	Type of PAN <i>(Refer the table below to know various PAN types)</i>
 - fullname	String	Full name of the Applicant / Entity as per government records, including first name, middle name & last name.
 - first_name	String	First name of the applicant as per government records
 - middle_name	String	Middle name of the applicant as per government records
 - last_name	String	Last Name of the applicant as per government records
 - gender	String	Individual's gender as per PAN. Possible Values: • male • female • transgender <i>(for other PAN types, this field would be empty string)</i>
 - dob	String	Date of birth or Incorporation in the format DD/MM/YYYY
 - aadhaar_number	String	Aadhaar linked to PAN <i>(provided in 2 masked forms - first 8 digits masked and last 4 digits unmasked or 1st 2 and last 2 digits unmasked, remaining 8 digits masked)</i> . Applicable only for the Individual PAN <i>(for other PAN types, this field would be empty string)</i>
 - aadhaar_linked	Bool	Aadhaar Linked Status. true - Aadhaar Linked false - Aadhaar Not Linked

		Applicable only for Individual PAN (<i>for other PAN types, this field would be null</i>)
 - address	Dict	Object containing the address available against PAN with the government (<i>usually provided during the PAN card registration or updation</i>)
 - - building_name	String	Building Name of the Address
 - - locality	String	Address Locality
 - - street_name	String	Street Name of the Address
 - - pincode	String	Pincode of the Address
 - - city	String	City of the Address
 - - state	String	State of the Address
 - - country	String	Country of the Address Note: For Indian Address, this field is generally given as "" (empty string) from the source and for other countries, this field contains the country name.
 - mobile	String	Mobile number associated with PAN from the government source
 - email	String	Email ID registered for given PAN Number (<i>usually provided during the PAN card registration or updation</i>)
 -signatory_details	Dict	All non-individual PAN has an authorised signatory associated with the PAN. This key provides the details of the authorised signatory.
 - -pan	string	PAN number of the authorised signatory.
 - -name	string	Full name of the authorised signatory.
 - -first_name	string	First name of the authorised signatory.
 - -middle_name	string	Middle name of the authorised signatory.
 - -last_name	string	Last name of the authorised signatory.
 - -gender	string	Gender of the authorised signatory. Possible Values: • male • female

 - dob	string	Date of birth of the authorised signatory in the format DD/MM/YYYY
 - din	string	DIN number of the authorised signatory if available. If DIN is not available, this field would be an empty string.
 - is_sole_proprietor	string	For individual PAN holders. The key value represents if the person holding the PAN is sole proprietor or not This field returns values Y or N or null : - Y - Yes, is sole proprietor - N - No, is not sole proprietor - E - Error - null - Not applicable when PAN is non-individual PAN
 - is_director	string	For individual PAN holders. The key value represents if the person holding the PAN is a director of the company associated with the PAN or not. This field returns values Y or N or null : - Y - Yes, is a director - N - No, is not a director - E - Error - null - Not applicable when PAN is non-individual PAN
 - is_salaried	string	For individual PAN holders. The key value represents if the person holding the PAN is salaried or not. This field returns values Y or N or null : - Y - Yes, is salaried - N - No, is not salaried - E - Error - null - Not applicable when PAN is non-individual PAN
 - pan_status	String	PAN Status of the Individual / Entity Possible values: - Active and operative - Active and inoperative - Invalid

		- E - Error
 - pan_allotment_date	string	PAN allotment date of the given PAN Possible values: - Date with Format - DD/MM/YYYY - E - Error

Various PAN Types
Individual
Company
Hindu Undivided Family (HUF)
Association of Persons (AOP)
Body of Individuals (BOI)
Government Agency
Artificial Juridical Person
Local Authority
Firm/Limited Liability Partnership
Trust

The following response would be provided in case if the PAN could not be validated

If the given PAN number is found to be Invalid / Inactive through internal source, then the below response would be provided (*result code - 102*).

```
{
  "http_response_code": 200,
  "result_code": 102,
  "message": Invalid ID number or combination of inputs,
  "request_id": "10f66706-77b2-11ee-9c0c-f359806a26c7",
  "client_ref_num": "dg-test-2dfe7ca3-5e33-48f8-b1ed-97398b868d05",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "",
    "fullname": "",
    "first_name": "",
    "middle_name": "",
    "last_name": "",
    "gender": "",
    "dob": "",
    "aadhaar_number": "",
    "aadhaar_linked": ""
  }
}
```

```

"address": {
  "building_name": "",
  "locality": "",
  "street_name": "",
  "pincode": "",
  "city": "",
  "state": "",
  "country": ""
},
"mobile": "",
"email": "",

"signatory_details": { },

"is_sole_proprietor": "",
"is_director": "",
"is_salaried": "",
"pan_status": "Invalid",
"pan_allotment_date": ""

}
}

```

If the given PAN number is found to be Not Alloted through internal source, then the below response would be provided (*result code - 103*).

```

{
  "http_response_code": 200,
  "result_code": 103,
  "message": "No record found for the given input",
  "request_id": "10f66706-77b2-11ee-9c0c-f359806a26c7",
  "client_ref_num": "dg-test-2dfe7ca3-5e33-48f8-b1ed-97398b868d05",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_type": "",
    "fullname": "",
    "first_name": "",
    "middle_name": "",
    "last_name": "",
    "gender": "",
    "dob": "",
    "aadhaar_number": "",
    "aadhaar_linked": "",
    "address": {
      "building_name": "",
      "locality": "",
      "street_name": "",
      "pincode": "",
      "city": "",
      "state": "",
      "country": ""
    },
    "mobile": "",
    "email": "",

```

```

    "signatory_details": { },

    "is_sole_proprietor": "",
    "is_director": "",
    "is_salaried": "",
    "pan_status": "Invalid",
    "pan_allotment_date": ""

  }
}

```

6.5 API Error Response

The API service includes an internal regex check that validates the PAN format. If the format is Invalid (does not meet the input parameter criteria), a 400 error is returned.

```

{
  "http_response_code": 400,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "One or more parameters format is wrong"
}

```

Note: If the PAN fails for other reasons such as being fake, deactivated, deleted, associated with a deceased individual, inoperative, or similar - a 102 result code is returned, indicating that the PAN status is Invalid.

In case of other errors, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

7 KYC - PAN 206AB Compliance Status Validation API

7.1 API Introduction

This API would check the Section 206AB and 206CCA compliance status for the given PAN Number.

Note:

1. Specified Person as per Section 206AB and 206CCA is the one who, has not filed the income tax return (ITR) for the preceding FY, and the income tax return (not belated return) filing due date has expired and the Total amount of tax deducted or collected

(TDS and TCS) in the last FY is Rs.50,000 or more. (Please refer to the Income Tax website for more details on Specified persons under Section 206AB & 206CCA).

2. We suggest to use this API after checking the validity of the PAN Numbers (either using Digitap's PAN APIs like PAN Basic, PAN Details with Status Check, etc or other appropriate sources like Protean/NSDL OPV), as this API does not check the validity of the PAN number (like deactivated or deleted PAN or unallocated PAN number) and hence it would not give consistent error code for invalid PANs.

7.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/form206ab_compliance_status
Production Env	https://svc.digitap.ai/validation/kyc/v1/form206ab_compliance_status

7.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10

		Pattern: <code>^[A-Za-z]{4}[A-Za-z]{1}\d{4}[A-Za-z]{1}\$</code>
--	--	--

7.4 API Success Response

7.4.1 Successful Validation Case

When the PAN details are matched, result_code 101 would be returned. The response format for the same is as follows:

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_name": "NXXXXT KXXU",
    "specified_person": "N",
    "pan_operative_status": "operative",
    "fin_year": "2023-24",
    "pan_allotment_date": "2010-07-20"
  }
}
```

Keys of Result Object are explained below:

Key	Type	Value
http_response_code	int	Internal Status Code that denotes the status of the request
result_code	String	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request
client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
- pan	String	PAN of the Individual / Entity
- pan_name	String	Full name of the Applicant / Entity as per government records, including your first name, middle name.
- specified_person	String	Indicates whether the person is a specified person under the Section 206AB and 206CCA. Possible values are

		• Y - Specified Person • N - Not a specified Person
pan_operative_status	String	PAN Status of the Individual / Entity Possible values are • operative • non-operative
fin_year	String	Financial year when the check is done. (Format - YYYY-YY)
pan_allotment_date	String	PAN allotment date of the given PAN Format - YYYY-MM-DD

If the given PAN number do not have PAN Allotment date information available at the source, then the below response would be provided.

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "pan_name": "NXXXXT KXXXU",
    "specified_person": "N",
    "pan_operative_status": "operative",
    "fin_year": "2023-24",
    "pan_allotment_date": ""
  }
}
```

If the given PAN number is Invalid and source also able to identify the invalid PANs properly, then the below response would be provided.

```
{
  "http_response_code": 200,
  "result_code": 102,
  "request_id": "e66bfede-dd4e-11ee-9405-bb73d4ad7259",
  "client_ref_num": "206ab-fb2c67b4-3671-4606-9344-454fc6b56011",
  "message": "Invalid ID & Combination Inputs",
  "result": {
    "pan": "AAAGM0289C",
    "pan_name": "",
    "specified_person": "",
    "pan_operative_status": "",
    "fin_year": "",
    "pan_allotment_date": "2017-05-31"
  }
}
```

This response would be given only when the source identifies the invalid PANs properly. There are certain cases, when the source cannot identify the invalid PANs properly and at that time, this API would give 422 error. To avoid this scenario, we suggest verifying the validity of the PAN API and then only call this API.

7.5 API Error Response

If this API cannot fetch the response for the given PAN number at the given time, then the below response would be provided.

```
{
  "http_response_code": 422,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "Digitap is unable to fetch the response at this moment"
}
```

The above response would be given sometimes even for Invalid PANs. So, before retrying, please check the validity of the PAN.

In case of other errors, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

8 KYC - PAN ITR Validation API

8.1 API Introduction

This API will provide the ITR filing status and details for the given PAN Number required PAN is registered with IT.

Note:

- Clients have the option to configure the number of financial years for which ITR details are to be extracted for a given PAN. By default, the system is set to fetch data for 3 financial years (plus 1 additional year if the current month is after April). For more information, please connect with your Relationship Manager.
- Form_type, ack_date_time and filing_type were part of an earlier source that was deprecated. Currently these fields return null in all cases, the fields are retained to ensure backward compatibility.

8.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/itr_basic
Production Env	https://svc.digitap.ai/validation/kyc/v1/itr_basic

8.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10 Pattern: ^[A-Za-z]{4}[A-Za-z]{1}\d{4}[A-Za-z]{1}\$

8.4 API Success Response

8.4.1 Successful Validation Case

When the PAN details are matched, result_code 101 would be returned. The response format for the same is as follows:

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "1f03d1a8-a67f-6400-e45b49d61bfd",
  "client_ref_num": "abc123",
  "result": [
    {
      "assessment_year": "2024",
      "form_type": null,

```

```

        "filing_type": null,
        "ack_num": "583864160040724",
        "ack_date_time": "null"
    },
    {
        "assessment_year": "2023",
        "form_type": null,
        "filing_type": null,
        "ack_num": "571096020200723",
        "ack_date_time": "null"
    },
    {
        "assessment_year": "2022",
        "form_type": null,
        "filing_type": null,
        "ack_num": "100529200250722",
        "ack_date_time": "null"
    }
]
}

```

The response format when client opted for configuration explained in section 8.1 the same is as follows:

```

{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "1f03d1a8-a67f-6400-e45b49d61bfd",
  "client_ref_num": "abc123",
  "result": [
    {
      "assessment_year": "2024",
      "form_type": null,
      "filing_type": null,
      "ack_num": "962148140120525",
      "ack_date_time": "null"
    },
    {
      "assessment_year": "2023",
      "form_type": null,
      "filing_type": null,
      "ack_num": "938187090180425",
      "ack_date_time": "null"
    },
    {
      "assessment_year": "2022",
      "form_type": null,
      "filing_type": null,
      "ack_num": "627413041221024",
      "ack_date_time": "null"
    },
    {
      "assessment_year": "2021",
      "form_type": null,
      "filing_type": null,

```

```

    "ack_num": "530379620281123",
    "ack_date_time": "null"
  },
  {
    "assessment_year": "2020",
    "form_type": null,
    "filing_type": null,
    "ack_num": "134026890030523",
    "ack_date_time": "null"
  },
  {
    "assessment_year": "2019",
    "form_type": null,
    "filing_type": null,
    "ack_num": "981861460140323",
    "ack_date_time": "null"
  },
  {
    "assessment_year": "2018",
    "form_type": null,
    "filing_type": null,
    "ack_num": "898839640311222",
    "ack_date_time": "null"
  },
  {
    "assessment_year": "2017",
    "form_type": null,
    "filing_type": null,
    "ack_num": "784161161061122",
    "ack_date_time": "null"
  }
  {
    "assessment_year": "2016",
    "form_type": null,
    "filing_type": null,
    "ack_num": "898839640311233",
    "ack_date_time": "null"
  },
  {
    "assessment_year": "2015",
    "form_type": null,
    "filing_type": null,
    "ack_num": "784161161061133",
    "ack_date_time": "null"
  }
]
}

```

Keys of Result Object are explained below:

Key	Type	Value
-----	------	-------

http_response_code	int	Internal Status Code that denotes the status of the request
result_code	int	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request
client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
- assessment_year	String	Income tax assessment year
- form_type	String	Returns null
- filing_type	String	Returns null
- ack_num	String	Income tax filing acknowledgement number
- ack_date_time	String	Income tax filing date and time

If the PAN number is not registered in the income tax return, then the below response would be provided.

```
{
  "http_response_code": 200,
  "result_code": 109,
  "request_id": "1f03d1c1-7d69-6f77-c74ea1524ec2",
  "client_ref_num": "abc123",
  "message": "PAN not registered with the Income Tax Department"
}
```

8.5 API Error Response

If this API cannot fetch the response for the given PAN number at the given time, then the below response would be provided.

```
{
  "http_response_code": 503,
  "request_id": "1f03f845-6822-6ce1-7eadae780e64",
  "client_ref_num": "abc123",
  "error": "Source is busy or unavailable"
}
```

There are certain cases, when the source cannot identify the invalid PANs properly and at that time, this API would give 503 errors. To avoid this scenario, we suggest verifying the validity of the PAN API and then only call this API.

If input parameters format is incorrect, we provide the below response.

```
{
  "http_response_code": 400,
  "request_id": "1f03f845-6822-6ce1-7eadae780e64",
  "error": "one or more parameters format is wrong"
}
```

In case of other errors, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

9 KYC - PAN to Name Validation API

9.1 API Introduction

This API to check PAN holders name for the given PAN Number.

Note: This API also helps to get various other details related to the PAN.

- **Date of birth** (for individual PAN) : The “dob” feature has additional commercial implications and please discuss with RM for details.

9.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_to_name
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_to_name

9.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10 Pattern: <code>^[A-Za-z]{4}[A-Za-z]{1}\d{4}[A-Za-z]{1}\$</code>

9.4 API Success Response

9.4.1 Successful Validation Case

When the Name is Found, result_code 101 would be returned. The response format for the same is as follows:

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "6c85a201-1436-11ef-b518-482ae33a7181",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "name": "MAYANK VERMA",
    "last_name": "VERMA",
    "first_name": "MAYANK",
    "middle_name": ""
  }
}
```

Keys of Result Object are explained below:

Key	Type	Value
http_response_code	int	Internal Status Code that denotes the status of the request
result_code	String	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request
client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
- pan	String	PAN of the Individual

- name	String	Name of the PAN card holder
- last_name	String	Last name of the PAN card holder
- first_name	String	First name of the PAN card holder
- middle_name	String	Middle name of the PAN card holder

1. If the given PAN number is found to be Invalid through internal source, then the below response would be provided (*result code - 102*).

```
{
  "http_response_code": 200,
  "result_code": "102",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "message": "Invalid ID number or combination of inputs",
}
```

2. If the given PAN number is found to be Not Alloted through internal source, then the below response would be provided (*result code - 103*).

```
{
  "http_response_code": 200,
  "result_code": "103",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "message": "No record found for the given input",
}
```

9.5 API Error Response

If the given PAN number is not Individual PAN Type, then the below response would be provided.

```
{
  "http_response_code": 503,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "Source is busy or unavailable. Try again later"
}
```

In case of error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

10 KYC - PAN to F'Name Validation API

10.1 API Introduction

This API to check father's name for the given PAN Number.

Note: This API fetches father name only for **Individual PANs** (i.e. the fourth letter of PAN Number is 'P'). For any other type of non individual PANs, internal regex check will be run and error will be given as mentioned in section 10.5.

10.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_to_fname
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_to_fname

10.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10

		Pattern: <code>^[A-Za-z]{4}[A-Za-z]{1}\d{4}[A-Za-z]{1}\$</code>
--	--	--

10.4 API Success Response

10.4.1 Successful Validation Case

When the Father's Name is Found, result_code 101 would be returned. The response format for the same is as follows:

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "result": {
    "pan": "ABCPE1234Z",
    "father_name": "NXXXXT KXXXU"
  }
}
```

Keys of Result Object are explained below:

Key	Type	Value
http_response_code	int	Internal Status Code that denotes the status of the request
result_code	String	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request
client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
- pan	String	PAN of the Individual
- father_name	String	Father Name of the Applicant as per government records

1. If the given PAN number is found to be Invalid through internal source, then the below response would be provided (*result code - 102*).

```
{
  "http_response_code": 200,
  "result_code": "102",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
```

```
}      "message": "Invalid ID number or combination of inputs",
}
```

2. If the given PAN number is found to be Not Allotted through internal source, then the below response would be provided (*result code - 103*).

```
{
  "http_response_code": 200,
  "result_code": "103",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "message": "No record found for the given input",
}
```

10.5 API Error Response

API has an internal regex check which validates whether the input PAN is an individual PAN or not. If the given PAN number is **not Individual PAN Type**(4th letter of PAN is not P), then the below response would be provided.

```
{
  "http_response_code": 400,
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "One or more parameters format is wrong"
}
```

In case of error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

11 KYC - PAN Profile API

This API facilitates the retrieval of various profile details associated with a PAN of an individual, who is registered on the ITR portal. It provides details like name, dob, address, PAN type, Aadhaar link status and masked Aadhaar number, mobile and email, and bank details of linked bank accounts, like account number, ifsc, bank name, account type.

11.1 API Introduction

This API helps to get various details related to the PAN of an Individual registered on the Income tax portal.

- **Demographic details** like name, dob
- **Aadhaar Linking Status** & Linked aadhaar number
- **Address** available against PAN from the government source (*usually provided during the PAN card registration or updation*)

- **Type of PAN** (individual PAN)
- **Contact Details** (like Mobile & Email Address)
- **Bank Details**(if linked to the account in ITR portal) like account number, ifsc code, bank name, account type, and if its used for tax refund

11.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_profile
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_profile

11.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 100 chars] Note: only ^ - _ special characters are allowed.
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10 Pattern: ^([a-zA-Z]{3})([pP]{1})([a-zA-Z]{1})([0-9]{4})([a-zA-Z]{1})\$

11.4 API Response

11.4.1 Successful Validation Case

When the profile details are fetched successfully, result_code 101 would be returned. The response format for the same is as follows.

When the PAN belongs to a resident of India:

```
{
  "http_status_code": 200,
  "result_code": 101,
  "request_id": "019a058b-08d2-82c8-98f3-9723f36fbb68",
  "client_ref_num": "digitap-test",
  "result": {
    "pan": "ABCDE7213A",
    "pan_type": "Individual",
    "is_resident_pan": true,
    "fullname": "JANE DOE",
    "first_name": "JANE",
    "middle_name": "",
    "last_name": "DOE",
    "father_name": "JOHN DOE",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "01/01/2000",
    "address": {
      "building_name": "133/355 ",
      "locality": "XYZ Park S.O",
      "street_name": "ABC ROAD",
      "pincode": "123456",
      "city": "Lucknow",
      "state": "Uttar Pradesh",
      "country": "India"
    },
    "mobile": "+911234567880",
    "mobile_secondary": "+1234567890",
    "email": "sunil_taxconsultant3@rediffmail.com",
    "email_secondary": "jdoe.210@gmail.com",
    "bank_details": [
      {
        "account_number": "1856001500012345",
        "ifsc_code": "PUNB0181234",
        "bank_name": "PUNJAB NATIONAL BANK",
        "account_type": "SB",
        "used_for_refund": true
      },
      {
        "account_number": "15310100012345",
        "ifsc_code": "BARB0CHARBA",
        "bank_name": "BANK OF BARODA",
        "account_type": "SB",
        "used_for_refund": true
      }
    ]
  }
}
```

```
}
```

When the PAN belongs to a non-resident Indian:

```
{
  "http_status_code": 200,
  "result_code": 101,
  "request_id": "019a06af-b195-8ecb-8f16-b1ddca8298b2",
  "client_ref_num": "digitap-test",
  "result": {
    "pan": "ABCDE4295C",
    "pan_type": "Individual",
    "is_resident_pan": false,
    "fullname": "RAM KUMAR",
    "first_name": "RAM",
    "middle_name": "",
    "last_name": "KUMAR",
    "father_name": "SHYAM KUMAR",
    "aadhaar_number": "XXXXXXXX1234",
    "aadhaar_linked": true,
    "dob": "01/01/1975",
    "address": {
      "building_name": "123",
      "locality": "Sahatwar S.O",
      "street_name": "Sahtavar",
      "pincode": "123456",
      "city": "Chandpur",
      "state": "Uttar Pradesh",
      "country": "India"
    },
    "mobile": "+91234567899",
    "mobile_secondary": "",
    "email": "xyzabc@gmail.com",
    "email_secondary": "",
    "bank_details": []
  }
}
```

For a PAN, when name and DOB only are available at source, below response is given:

```
{
  "http_status_code": 200,
  "result_code": 101,
  "request_id": "019a06af-b195-8ecb-8f16-b1ddca8298b2",
  "client_ref_num": "digitap-test",
  "result": {
    "pan": "ABCDE4295C",
    "pan_type": "Individual",
    "is_resident_pan": "",
    "fullname": "RAM KUMAR",
    "first_name": "RAM",
    "middle_name": "",
    "last_name": "KUMAR",

```

```

    "father_name": "",
    "aadhaar_number": "",
    "aadhaar_linked":,
    "dob": "01/01/1975",
    "address": {
        "building_name": "",
        "locality": "",
        "street_name": "",
        "pincode": "",
        "city": "",
        "state": "",
        "country": ""
    },
    "mobile": "",
    "mobile_secondary": "",
    "email": "",
    "email_secondary": "",
    "bank_details": []
}
}

```

Keys of Response Object are explained below:

Key	Type	Value
http_status_code	int	Internal Status Code that denotes the status of the request
result_code	int	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request
Client_ref_num	String	Unique ID for this request from the Client side [Max of 100 chars] Note: only ^ - _ special characters are allowed.
result	Dict	Response object for the given inputs.
 - pan	String	PAN of the Individual / Entity
 - pan_type	String	Type of PAN (<i>Refer the table below to know various PAN types</i>)
 - is_resident_pan	Boolean	If PAN holder is resident or not Possible values: True, False, NA
 - fullname	String	Full name of the Applicant / Entity as per government records, including first name, middle name & last name.
 - first_name	String	First name of the applicant as per government records

- middle_name	String	Middle name of the applicant as per government records
- last_name	String	Last Name of the applicant as per government records
- dob	String	Date of birth or Incorporation in the format DD/MM/YYYY
- aadhaar_number	String	Aadhaar linked to PAN (<i>provided in masked form - first 8 digits masked and last 4 digits unmasked</i>).
- aadhaar_linked	Bool	Aadhaar Linked Status. true - Aadhaar Linked false - Aadhaar Not Linked
- address	Dict	Object containing the address available against PAN from the government source (<i>usually provided during the PAN card registration or updation</i>)
- - building_name	String	Building Name of the Address
- - locality	String	Address Locality
- - street_name	String	Street Name of the Address
- - pincode	String	Pincode of the Address
- - city	String	City of the Address
- - state	String	State of the Address
- - country	String	Country of the Address Note: For Indian Address, this field is generally given as "" (empty string) from the source and for other countries, this field contains the country name.
- mobile	String	Mobile number associated with PAN from the government source
- mobile_secondary	String	Secondary mobile number associated with PAN from the government source
- email	String	Email ID registered for given PAN Number (<i>usually provided during the PAN card registration or updation</i>)
- email_secondary	String	Secondary Email ID registered for given PAN Number
- bank_details	List	Object containing bank details available against PAN from the government source
- - account_number	String	Account number of the linked bank account
- - ifsc_code	String	IFSC code of Bank of the linked bank account
- - bank_name	String	Name of the bank of the linked bank account

 - account_type	String	Bank account type: Savings account, current account, Joint Account etc
 - used_for_refund	Boolean	If the account is acceptable for tax refund or not. Possible values: True, False

11.4.2 Unsuccessful Validation Cases

The following response would be provided in case if the individual PAN is not registered on Income tax portal.

```
{
  "http_status_code": 200,
  "result_code": 103,
  "request_id": "019a059e-bcc8-84ba-9019-984621237944",
  "client_ref_num": "digitap-test",
  "message": "No record found for the given input"
}
```

11.4 API Error Response

The API service includes an internal regex check that validates the PAN format. If the format is Invalid (does not meet the input parameter criteria), a 400 error is returned. We would also provide the below response in case of a non-Individual PAN input, irrespective of whether it is registered on the ITR Portal:

```
{
  "http_response_code": 400,
  "client_ref_num": "abcd123"
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "One or more parameters format is wrong"
}
```

The API service includes authorized access only. If the API service is requested using unauthorised access, a 401 error is returned.

```
{
  "http_response_code": 401,
  "request_id": "019a05a3-24d4-8540-ad42-5e45c4079544",
  "client_ref_num": "digitap-test",
  "error": "Client Authentication Failed"
}
```

In case API faces any internal error, a 500 error is returned:

```
{
  "http_status_code": 500,
  "request_id": "019a05da-3c53-8ed2-8186-6fd2d1ef00af",
  "client_ref_num": "digitap-test",
  "error": "Internal Error"
}
```

In case API is unable to fetch the response for the given PAN number at the given time, then a 503 error would be returned.

```
{
  "http_status_code": 503,
  "request_id": "019a05da-3c53-8ed2-8186-6fd2d1ef00af",
  "client_ref_num": "digitap-test",
  "error": "Source is busy or unavailable"
}
```

In case the source is down for maintenance or inaccessible, a 503 error is returned:

```
{
  "http_status_code": 503,
  "request_id": "019a05da-3c53-8ed2-8186-6fd2d1ef00af",
  "client_ref_num": "digitap-test",
  "error": "Website is in maintenance"
}
```

In case of other errors, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

12 KYC - PAN Account Link API

12.1 API Introduction

The PAN Account Link Verification API provides a seamless and efficient way to confirm the link between a PAN number and a bank account. By verifying if the provided PAN number is correctly associated with the corresponding account number and IFSC, this tool helps prevent fraud and ensures compliance with financial regulations.

Note : The API supports live data in the Production environment and not in the UAT environment.

12.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/misc/v1/pan-account-linkage
Production Env	https://svc.digitap.ai/validation/misc/v1/pan-account-linkage

12.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 50 chars]
pan	M	PAN Number to be checked for link with Account number minLength: 10 maxLength: 10 Pattern: ^[A-Za-z]{5}\d{4}[A-Za-z]{1}\$
account_number	M	Account number which only consists of numerical characters minLength: 9 maxLength: 18 Pattern: ^\d{9,18}\$
ifsc_code	M	IFSC code of the bank account of the individual.

		Length: 11 Pattern: ^[A-Za-z]{4}0\d{6}\$
--	--	---

12.4 List of supported banks

Below is the list of banks supported by Digitap to check PAN Account Linkage.

SL No	Bank Code	Bank Name
1	SBIN	State Bank of India
2	HDFC	HDFC Bank Limited
3	UTIB	Axis Bank Limited
4	ICIC	ICICI Bank Limited
5	UBIN	Union Bank of India
6	KKBK	Kotak Mahindra Bank Limited
7	BARB	Bank of Baroda
8	HSBC	HSBC Bank of India
9	PUNB	Punjab National Bank
10	SIBL	Social Islami Bank Limited
11	KVBL	Karur Vysya Bank
12	KARB	Karnataka Bank Limited
13	IDFB	IDFC Bank Limited
14	YESB	Yes Bank Limited
15	DBSS	DBS Bank India Limited
16	SCBL	Standard Chartered Bank India
17	INDB	IndusInd Bank Limited
18	CIUB	City Union Bank Limited

SL No	Bank Code	Bank Name
19	IBKL	IDBI Bank Limited

20	UJVN	Ujivan Small Finance Bank
21	CBIN	Central Bank of India
22	FDRL	Federal Bank
23	JSFB	Jana Small Finance Bank
24	RMGB	Rajasthan Marudhara Gramin Bank
25	TMBL	Tamilnad Mercantile Bank Limited
26	RATN	RBL Bank Limited
27	PSIB	Punjab & Sind Bank
28	UCBA	UCO Bank
29	SURY	Suryoday Small Finance Bank
30	PYTM	Paytm Payments Bank Limited
31	UTKS	SVC Co-operative Bank Limited
32	SVCB	SVC Co-operative Bank
33	SRCB	Saraswat Co-operative Bank Limited
34	TJSB	TJSB Sahakari Bank Limited
35	PJSB	Pune Janata Sahakari Bank
36	JAKA	Jammu & Kashmir Bank Limited
37	CNRB	Canara Bank
38	BKID	Bank of India
39	BMCB	Bhavnagar Mahila Co-operative Bank Ltd.
40	RNSB	Rajkot Nagarik Sahakari Bank Ltd.
41	APMC	A.P. Mahesh Cooperative Urban Bank
42	SUNB	Surat Nagarik Sahakari Bank Ltd.
43	JIOP	Jio Payments Bank Ltd.
44	CRGB	Chhattisgarh Rajya Gramin Bank

SL No	Bank Code	Bank Name
45	GSCB	Gujarat State Co-operative Bank Ltd

46	CSBK	Catholic Syrian Bank
47	JPCB	Jalgaon People Co-operative Bank Ltd
48	NTBL	The Nainital Bank Limited
49	JSBP	Jaata Sahakari Bank Pune Ltd
50	SGBA	Saurashta Gramin Bank Ltd
51	ASBL	Apna Sahakari Bank Ltd
52	AMCB	Ahmednagar Merchants Co-operative Bank Ltd
53	AJHC	Ambarnath Jai-Hind Co-operative Bank Ltd
54	LAVB	Lakshmi Vilas Bank
55	CORP	Corporation Bank
56	DEOB	Deogiri Nagari Sahakari Bank Ltd
57	SUTB	Sutex Bank
58	JJSB	Jalgaon Janata Sahakari Bank
59	SPCB	Surat People's Cooperative Bank Ltd

12.5 API Success Response

12.5.1 Successful Validation Case

When the PAN is linked to the Account number, result_code 101 would be returned. The response format for the same is as follows:

```
{
  "http_response_code": 200,
  "client_ref_num": "ABCD1234",
  "request_id": "81fa8fb1-19c3-40d7-a281-a175b326986b",
  "result_code": 101,
  "message": "PAN and account number are linked",
  "result":
  {
    "linked_status": true,
    "pan": "ABCDE9999Z",
    "account_number": "0987654321",
    "ifsc": "ABCD0000001",
    "account_type": "SAVINGS",
    "account_nature": "SINGLE",
    "account_holder": "PRIMARY",
    "beneficiary_name": "JOHN DOE"
  }
}
```

```
}
}
```

Keys of Result Object are explained below:

Key	Type	Value
http_response_code	integer	Internal Status Code that denotes the HTTP status of the request
result_code	integer	Internal Status Code that denotes the status of the request
request_id	string	Unique id for each API request
client_ref_num	string	Ref number sent in the input by client
message	string	Result message
result	Dict	Response object for the given inputs.
- pan	string	PAN of the Individual
- linked_status	boolean	PAN to Account link status
- account_number	string	Bank account number of the individual
- ifsc	string	IFSC code of the bank account number of the individual
- account_type	string	Account type of the bank account
- account_nature	string	Account nature of the bank account
- account_holder	string	Account holder of the bank account
- beneficiary_name	string	Beneficiary name of the bank account

If the given PAN number is not linked to the given Bank account number, then the below response would be provided (*result code - 103*).

```
{
  "http_response_code": 200,
  "client_ref_num": "ABCD1234",
  "request_id": "8147ea44-881f-4b8a-8d2e-d7af2a7c9e8a",
  "result_code": 103,
  "message": "PAN and account number are not linked"
}
```

12.6 API Error Response

1. This error will occur for any bank codes other than the ones we support.

```
{  
  
  "http_response_code": 422,  
  "client_ref_num": "ref1234_31JUL2024_1448",  
  "request_id": "fb83e8fb-d642-4e1e-b65e-eb7fd0eee312",  
  "error": "Unsupported bank - bank is currently not supported"  
}
```

2. If the request has invalid or missing parameters, then the below response would be provided:

```
{  
  
  "http_response_code": 400,  
  "client_ref_num": "f5ff8fc7-4ad4-4d8a-90d7-649a974a4021",  
  "request_id": "c8ad2ccc-a3c4-4b2c-a4b6-8e6ebbde7c14",  
  "error": "One or more parameters is wrong or missing"  
}
```

3. If there is an authorization error, then the below response would be provided.

```
{  
  
  "http_response_code": 500,  
  "client_ref_num": "abc123",  
  "request_id": "300bf074-fbcd-11ee-99f2-46560d30decf",  
  "message": "Internal Error"  
}
```

4. If the source is down, then the below response would be provided.

```
{  
  
  "http_response_code": 503,  
  "client_ref_num": "abc123",  
  "request_id": "683f8e4c-1f01-4ac3-961f-c01fbdcfaf1d",  
  "message": "Source is down. Please try again"  
}
```

In case of error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

13 KYC - VoterID Validation API

13.1 API Introduction

This API helps to validate whether the given EPIC (voterID) is valid at the query time or not. Along with the validation, this API returns various other details related to the VoterID:

- Name, Age & Gender of the EPIC Holder
- Relative Name and Relative Type (Father/Husband,etc)
- District & State of the EPIC Holder
- Constituency (Assembly & Parliamentary) & Polling Station Details
- Last Updated Date of the Details in Government Database

Note: Please note that this API validates only the **Active Voter / EPIC Cards**. The Old EPIC cards which have been invalidated due to issue of new card (due to new card format issuance) or Constituency Change/Transposition cannot be validated through this API.

13.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/voter
Production Env	https://svc.digitap.ai/validation/kyc/v1/voter

13.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 100 chars]
epic_number	M	Epic number present in the Voter ID card minLength: 10 maxLength: 23 Regex: ^(([a-zA-Z]{3}\d{6,15}) ([a-zA-Z]{2}\d{1,3}\d{2,3}\d{6,7}) ([a-zA-Z]{2}\d{10,12}))\$

13.4 API Success Response

13.4.1 Successful Validation Case

When the EPIC number is matched and active, result_code 101 would be returned. The response format for the same is as follows:

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "1e0015b4-2988-11f0-9079-b3c35d7baaad",
  "client_ref_num": "se7en-8e1f3c10-9359-4bcf-9d9a-0722292400a3",
  "result": {
    "id": "16235072_JSH8223786_S27",
    "age": 24,
    "name": "NITESH KUMAR",
    "name_v1": "नितेश कुमार",
    "name_fn": "NITESH",
    "name_fn_v1": "नितेश",
    "name_fn_v2": "",
    "name_fn_v3": "",
    "name_ln": "KUMAR",
    "name_ln_v1": "कुमार",
    "name_ln_v2": "",
    "ac_no": "43",
    "pc_no": "6",
    "ps_no": "88",
    "gender": "M",
    "gender_v1": "",
    "ac_name": "Baghmara",
    "dist_no": "13",
    "epic_no": "JSH8223786",
    "part_no": "88",
    "pc_name": "Giridih",
    "ps_name": "Middle school baghmara(girls) West part",
    "st_code": "S27",
  }
}
```

```

"st_name": "Jharkhand",
"rln_name": "RAM PRIYA",
"rln_type": "F",
"_version_": 0,
"dist_name": "Dhanbad",
"part_name": "Middle school baghmara(girls) West part",
"ac_name_v1": "बाघमारा",
"pc_name_v1": "",
"ps_name_v1": "मध्य विद्यालय , बाघमारा (बालिका) पश्चिम भाग",
"section_no": "1",
"last_update": "28/12/2024",
"ps_lat_long": "23.45304000,86.13811000",
"rln_name_v1": "राम प्रिय",
"rln_name_v2": "",
"rln_name_v3": "",
"sln_inpart": "939",
"dist_name_v1": "धनबाद",
"state_v1": "झारखंड",
"part_name_v1": "मध्य विद्यालय , बाघमारा (बालिका) पश्चिम भाग",
"ps_lat_long_0_coordinate": "",
"ps_lat_long_1_coordinate": "",
"isActive": true,
"createdDttm": "2023-04-04 05:52:04",
"isDeleted": "",
"processType": "",
"statusType": "",
"pollingDate": "",
"electionDate": "",
"electionTime": "",
"psbuildingName": "Middle school baghmara(girls)",
"birthYear": "",
"pwd": "",
"pwdMarkingRefNo": "",
"isWheelchairRequired": "",
"isVip": "",
"psRoomDetails": "",
"psRoomDetailsL1": "",
"psBuildingNameL1": "मध्य विद्यालय , बाघमारा (बालिका)",
"buildingAddress": ""
},
"multiple_epic": false,
"multiple_epic_record_list": []
}

```

Keys of Result Object are explained below:

Key	Value
epic_no	EPIC Voter ID number to be authenticated
name	Name of the card holder in English
name_v1	Full name of the card holder in Vernacular Language

name_fn	First name of card holder in English
name_fn_v1	First name of card holder in Vernacular Language
name_fn_v2	First name of card holder in Vernacular Language
name_fn_v3	First name of card holder in Vernacular Language
name_ln	Last name in English
name_ln_v1	Last name of card holder in Vernacular Language
name_ln_v2	Last name of card holder in Vernacular Language
gender	Gender of the card holder
gender_v1	Gender of the card holder in Vernacular language
age	Age of the Card Holder in Years
rln_name	Relative Name in English
rln_name_v1	Relative Name in Vernacular Language
rln_name_v2	Relative Name in Vernacular Language
rln_name_v3	Relative Name in Vernacular Language
rln_type	Relationship type: "F" = Father, "H" = Husband
dist_name	District of the Electoral Office in English
dist_name_v1	District of the Electoral Office in Vernacular Language
dist_no	District Number
st_code	State Code
st_name	State Name in English
state_v1	state name in local language
ac_name	Assembly Constituency Name in English
ac_name_v1	Assembly Constituency Name in Vernacular Language
ac_no	Assembly Constituency Number
pc_name	Parliament Constituency Name in English
pc_name_v1	Parliament Constituency Name in Vernacular Language
pc_no	Parliament Constituency Number
part_name	Number of the part (location) in the constituency applicable to the card holder

part_name_v1	Number of the part (location) in the constituency applicable to the card holder in Vernacular Language
part_no	Part Number inside the constituency
section_no	Section of the Electoral Book where the Card Holder name is present
slnoinpart	Serial Number in the Book where the Card Holder name is present
ps_name	Polling Station Name in English
ps_name_v1	Polling Station Name in Vernacular Language
ps_no	Polling Station Number
ps_lat_long	Lat Long for the Polling Station (Polling Booth) applicable to the card holder
ps_lat_long_0_coordinate	Lat Long for the Polling Station (Polling Booth) applicable to the card holder
ps_lat_long_1_coordinate	Lat Long for the Polling Station (Polling Booth) applicable to the card holder
id	Unique ID of the card holder [st_code+ ac_no + part_no + section_no + slno_inpart]
last_update	Last date of update to the records against the given epic_no in Government Records.
is_active	Whether the voter id is active
created_Dttm	Voter id creation date
is_deleted	Is user deleted
processType	Updating on which purpose
statusType	Whether the person active or migrated
pollingDate	Polling date
electionDate	Counting and result declaring date
electionTime	Election Time
psbuildingName	Building name of polling station
birthYear	Date of Birth
pwd	Voter ID for persons with disabilities
pwdMarkingRefNo	Application form number of person with disability
isWheelchairRequired	Application Number for PWD with doctor approval.

isVip	Whether the person is VIP
psRoomDetails	Polling station room details
psRoomDetailsL1	Polling station room details in vernacular language
psBuildingNameL1	Polling station building name
buildingAddress	Polling station address
multiple_epic	It can be True or False
multiple_epic_record_list	When multiple_epic is True then multiple_epic_record_list will be a list of dictionaries. When multiple_epic is False. Then multiple_epic_record_list will be an empty list.

The following response would be provided in case if the Voter ID could not be validated

If there is no record found for the given EPIC number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": "103",
  "message": "No record found for the given input",
}
```

If the data for input Voter ID is deleted at source, we will provide the below output:

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": "103",
  "message": "Voter ID deleted on 04/05/2026",
}
```

13.5 API Error Response

In case of Error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

14 KYC - Passport Validation API

14.1 API Introduction

This API helps to validate the passport details with the provided file number and date of birth of the passport holder.

When the file number related to a passport & DOB is matched, this API provides the matching passport number, name (given name & surname), date of application and date of dispatch. This API also helps to identify rejected passport application file numbers by giving a different result_code 108.

From the response, once can match with the passport number, name, date of issuance of the passport present in the Passport.

14.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/passport
Production Env	https://svc.digitap.ai/validation/kyc/v1/passport

14.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 100 chars]

file_number	M	Passport File number minLength:1 maxLength:30 Regex: r"^[1,30]\$"
dob	M	Date of birth in the passport Format: DD/MM/YYYY

14.4 API Success Response

14.4.1 Successful Validation Case

When the passport is validated successfully with the given file number and date of birth, the below response will be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "1234",
  "request_id": "76287f9c-cdae-11ea-85c0-e60fc8f818f8",
  "result_code": 101,
  "result": {
    "file_number": "GZ10xxxxxxxxxxx",
    "dob": "06/04/1993",
    "passport_number": "Pxxxxxxx",
    "given_name": "XYZ",
    "surname": "XYZ",
    "application_type": "Normal",
    "application_date": "09/09/2016",
    "date_of_dispatch": "31/10/2016"
  }
}
```

When the given input is validated successfully but the application is under review, then the below response would be provided with result_code as 108. Such cases might return a positive 101 response when retried after a period of time, as applications might get accepted and passport number can be assigned.

```
{
  "http_response_code": 200,
  "client_ref_num": "1234",
  "request_id": "06e7613c-cce8-11ea-822b-5ef05b03730e",
  "result_code": 108,
  "result": {
    "file_number": "Bxxxxxxxxxxxxxx",
    "dob": "11/04/1990",

```

```

    "given_name": "XYZ",
    "application_type": "Normal",
    "application_date": "18/11/2017"
  }
}

```

If the application status is identified as Rejected, the API will return the following response:

```

{
  "http_response_code": 200,
  "client_ref_num": "1234",
  "request_id": "06e7613c-cce8-11ea-822b-5ef05b03730e",
  "result_code": 104,
  "result": {
    "file_number": "Bxxxxxxxxxxxxxx",
    "dob": "11/04/1990",
    "given_name": "XYZ",
    "application_type": "Normal",
    "application_date": "18/11/2017"
  }
}

```

Keys of Result Object are explained below:

Key	Value
file_number	Individual's Passport file number
dob	Date of birth in passport
passport_number	Passport number
given_name	Given name in passport
surname	Surname in passport
application_type	The passport application type Normal/Tatkal
application_date	Date of application
date_of_dispatch	Date on which passport issued

When the passport could not be validated with the given inputs then the following response will be provided.

If the file number is an invalid file number, then the response will be in the below format with result_code as 102 and message as “invalid id number or combination of inputs”

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd1234",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 102,
  "message": "Invalid id number or combination of inputs",
}
```

If there is no record found for the requested File Number with specific DOB, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd1234",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 103,
  "message": "No record found for the given input ",
}
```

If the requested File Number belongs to a Passport issued outside India, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd1234",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 109,
  "message": "file_number cannot be validated. Passport issued outside
India"
}
```

14.5 API Error Response

In case of Error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

15 KYC - PAN Aadhaar Link API

15.1 API Introduction

This API helps to validate if the PAN is linked with Aadhaar or vice-versa. This API takes primarily PAN and Aadhaar as input and responds to the status between them.

15.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_aadhaar_link
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_aadhaar_link

15.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10 Pattern: ^[A-Za-z]{4}[A-Za-z]{1}\d{4}[A-Za-z]{1}\$
aadhaar	M	Aadhaar Number to be authenticated minLength: 12 maxLength: 12 Pattern: 12 digit number

- **Encrypted Request:**

This API supports request payload encryption. Please refer to [Section 2.6](#) for details.

15.4 API Success Response

This API supports response encryption. Please refer to [Section 2.6](#) for details.

15.4.1 Successful Validation Case

When the PAN and Aadhaar are linked, result_code 101 would be returned. The response format for the same is as follows:

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "880dd801-46cf-11ec-b85c-15746d739503",
  "client_ref_num": "dbe90be9-1597-47d4-b151-8157d1f9bf64",
  "result": {
    "message": "Is already linked to given Aadhaar",
    "code": "LINK-001"
  }
}
```

Keys of Result Object are explained below:

Key	Value
code	Linking status of PAN and Aadhaar
message	Message as per the linking status
result_code	E2E validation result based on conclusiveness

code	message	result_code
LINK-001	Is already linked to given Aadhaar	101
LINK-002	PAN not linked with Aadhaar	103
LINK-003	PAN does not exist	103
LINK-004	Please enter a valid 12 digit Aadhaar number	102
LINK-005	PAN entered is inactive	103
LINK-006	This PAN is linked to some other Aadhaar	103
LINK-007	This Aadhaar is linked to some other PAN	103
LINK-008	Aadhaar PAN linking failed due to DOB mismatch	108
LINK-009	Aadhaar PAN linking failed due to Name mismatch	108

LINK-010	Please enter valid Individual Pan Card Number	102
LINK-011	Aadhaar PAN linking request is in progress	104

The following response would be provided in case if the PAN could not be validated

If the PAN and Aadhaar are not linked.

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "9c80e361-ad8d-11ef-92f7-195bcf5756cd",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "PAN not linked with Aadhaar",
    "code": "LINK-002"
  }
}
```

If the PAN does not exist.

```
{
  "http_response_code": 200,
  "result_code": 103,
  "request_id": "9c80e361-ad8d-11ef-92f7-195bcf5756cd",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "PAN does not exist",
    "code": "LINK-003"
  }
}
```

If the Aadhaar is not valid.

```
{
  "http_response_code": 200,
  "result_code": 102,
  "request_id": "9c80e361-ad8d-11ef-92f7-195bcf5756cd",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "Please enter a valid 12 digit Aadhaar Number",
    "code": "LINK-004"
  }
}
```

If the PAN is inactive.

```
{
  "http_response_code": 200,
  "result_code": 103,
  "request_id": "26b175f7-ad90-11ef-aead-79b722f777f6",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "PAN entered is inactive",
    "code": "LINK-005"
  }
}
```

If the PAN is linked to different Aadhaar.

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "9c80e361-ad8d-11ef-92f7-195bcf5756cd",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "Is linked to some other Aadhaar",
    "code": "LINK-006",
    "aadhaar_number": "69XXXXXXXXX68"
  }
}
```

If Aadhaar is linked to the different PAN.

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "0b8b50f3-ad57-11ef-95aa-21a8e6ec54ea",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "Is linked to some other PAN",
    "code": "LINK-007",
    "pan": "GKXXXXXXXX2L"
  }
}
```

If the Aadhaar PAN linking failed due to DOB mismatch.

```
{
  "http_response_code": 200,
  "result_code": 108,
  "request_id": "592a5bfc-ad57-11ef-b77f-7565c2bde3c2",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "Aadhaar PAN linking failed due to DOB mismatch",
    "code": "LINK-008"
  }
}
```

If the Aadhaar and PAN linking failed due to Name Mismatch.

```
{
  "http_response_code": 200,
  "result_code": 108,
  "request_id": "42fadd0d-ad57-11ef-831e-7565c2bde3c2",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "Aadhaar PAN linking failed due to Name mismatch",
    "code": "LINK-009"
  }
}
```

If the PAN is not valid Individual PAN Type.

```
{
  "http_response_code": 200,
  "result_code": 102,
  "request_id": "9c80e361-ad8d-11ef-92f7-195bcf5756cd",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "Please enter valid Individual Pan Card Number",
    "code": "LINK-010"
  }
}
```

If Aadhaar PAN linking request is in progress:

```
{
  "http_response_code": 200,
  "result_code": 104,
  "request_id": "592a5bfc-ad57-11ef-b77f-7565c2bde3c2",
  "client_ref_num": "bd7b5d0a-fa14-43cd-bffc-0862f216415c",
  "result": {
    "message": "Aadhaar PAN linking request is in progress",
    "code": "LINK-011"
  }
}
```

15.5 API Error Response

In case of Error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

15.6 Encryption Support

This API supports Encryption of request and response. Please refer to the [Section 2.6 API Encryption](#)

16 KYC - PAN to Masked Aadhaar Validation API

16.1 API Introduction

This API helps to get the masked aadhaar number which is linked to the input PAN number.

16.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/pan_to_masked_aadhaar
Production Env	https://svc.digitap.ai/validation/kyc/v1/pan_to_masked_aadhaar

16.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
pan	M	PAN Number to be authenticated minLength: 10 maxLength: 10 Pattern: ^[A-Za-z]{4}[A-Za-z]{1}\d{4}[A-Za-z]{1}\$

- **Encrypted Request:**

This API supports request payload encryption. Please refer to [Section 2.6](#) for details.

16.4 API Success Response

This API supports response encryption. Please refer to [Section 2.6](#) for details.

16.4.1 Successful Validation Case

The following response would be provided in case if the PAN to Masked Aadhaar could be validated

If aadhaar is linked with the given PAN number, then the below response would be provided.

```
{
  "http_response_code":200,
  "request_id":"f5c7f180-1caa-11ee-9143-922d4621dab8",
  "client_ref_num":"abc123",
  "result_code": 101,
  "result":{
    "linked": "y",
    "aadhaar_number": "98XXXXXXXXX72"
  }
}
```

If aadhaar is not linked with the given PAN number, then the below response would be provided.

```
{
  "http_response_code":200,
  "request_id":"f5c7f180-1caa-11ee-9143-922d4621dab8",
  "client_ref_num":"abc123",
  "result_code": 101,
  "result":{
    "linked": "n",
    "aadhaar_number": ""
  }
}
```

Keys of Result Object are explained below:

Keys	Type	Value
http_response_code	int	Internal Status Code that denotes the status of the request
result_code	String	Internal Status Code that denotes the status of the request
request_id	string	Unique id for each API request

client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
- linked	String	PAN Aadhaar Link Status • Linked - y • Not Linked - n
- aadhaar_number	String	Masked aadhaar number related to the input PAN number

The following response would be provided in case if the PAN is invalid.

```
{
  "http_response_code": 200,
  "request_id": "eaded2f0-1cac-11ee-8d3a-720730d77877",
  "client_ref_num": "abc123",
  "result_code": 102,
  "message": "Invalid ID Number or Combination of Inputs"
}
```

16.5 API Error Response

In case of Error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

16.6 Encryption Support

This API supports Encryption of request and response. Please refer to the [Section 2.6 API Encryption](#)

17 KYC - Aadhaar to Masked PAN Validation API

17.1 API Introduction

This API helps to get the masked pan number which is linked to the input Aadhaar number.

17.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/aadhaar_to_masked_pan
---------------------	---

Production Env	https://svc.digitap.ai/validation/kyc/v1/aadhaar_to_masked_pan
----------------	---

17.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
aadhaar	M	Aadhaar Number to be authenticated minLength: 12 maxLength: 12 Pattern: 12 digit number

- **Encrypted Request:**

This API supports request payload encryption. Please refer to [Section 2.6](#) for details.

17.4 API Success Response

This API supports response encryption. Please refer to [Section 2.6](#) for details.

17.4.1 Successful Validation Case

The following response would be provided in case if the Aadhaar to Masked PAN could be validated

If pan is linked with the given Aadhaar number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "request_id": "f5c7f180-1caa-11ee-9143-922d4621dab8",
  "client_ref_num": "abc123",
  "result_code": 101,
  "result": {
    "linked": "y",
    "pan": "ABXXXXXX4Z"
  }
}
```

If pan is not linked with the given Aadhaar number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "request_id": "f5c7f180-1caa-11ee-9143-922d4621dab8",
  "client_ref_num": "abc123",
  "result_code": 101,
  "result": {
    "linked": "n",
    "pan": ""
  }
}
```

Keys of Result Object are explained below:

Keys	Type	Value
http_response_code	int	Internal Status Code that denotes the status of the request
result_code	String	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request
client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
- linked	String	PAN Aadhaar Link Status • Linked - y • Not Linked - n
- aadhaar_number	String	Masked aadhaar number related to the input PAN number

When the given Aadhaar number could not be verified, the below response will be provided and along with below message as

When the given aadhaar number is not found, the below response will be provided

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 103,
  "message": "No records found for the given Input"
}
```

When the given aadhaar number starts with 1, the below response will be provided

```
{
  "http_response_code": 200,
  "client_ref_num": "test989",
  "request_id": "ac529358-5c47-11ed-a8f9-46ea22d4d73e",
  "result_code": 102,
  "message": "Invalid Aadhaar"
}
```

17.5 API Error Response

When the given aadhaar number is wrong, the below response will be provided

```
{
  "http_response_code": 400,
  "client_ref_num": "test989",
  "request_id": "ac529358-5c47-11ed-a8f9-46ea22d4d73e",
  "error": "One or more parameters format is wrong"
}
```

When the given aadhaar number starts with zero 0, the below response will be provided

```
{
  "http_response_code": 400,
  "client_ref_num": "test989",
  "request_id": "ac529358-5c47-11ed-a8f9-46ea22d4d73e",
  "error": "Invalid Aadhaar. Aadhaar number cannot start with zero"
}
```

When the given aadhaar number failed in Verhoeff Check, the below response will be provided

```
{
  "http_response_code": 400,
  "client_ref_num": "test989",
  "request_id": "ac529358-5c47-11ed-a8f9-46ea22d4d73e",
  "error": "Invalid Aadhaar. Vernhoeff Check failed"
}
```

In case of Error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

17.6 Encryption Support

This API supports Encryption of request and response. Please refer to the [Section 2.6 API Encryption](#)

18 KYC - Driving Licence Validation API

18.1 API Introduction

This sync API extracts the details linked with the Driving Licence number. It takes mandatory input as a DL number and Date of birth and provides the information in json format.

Note: This API aggregates data from multiple sources, some of which may return response without correct date of birth of the registered DL in the input. To avoid any discrepancies in responses, it is advised to input accurate date of birth along with DL number in the input.

18.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/dl
Production Env	https://svc.digitap.ai/validation/kyc/v1/dl

18.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json

authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)
---------------	---	--

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 100 chars]
dl_number	M	DL number for which information need to be extracted (Min Length: 13 Max Length: 25) DL_REGEX = r"^[a-zA-Z0-9/]{13,25}\$"
dob	M	Date of birth according DL document Format: DD/MM/YYYY

18.4 API Success Response

18.4.1 Successful Validation Case

When the DL number is valid and if the information related to DL is extracted successfully then below json is returned:

```
{
  "http_response_code": 200,
  "request_id": "d44d769c-09a0-11ed-8f2f-962d5f2b2369",
  "client_ref_num": "1234",
  "result_code": 101,
  "result": {
    "dob": "26-02-1999",
    "dl_number": "TN302017000XXXX",
    "dl_validity": {
      "transport": {
        "to": "",
        "from": ""
      },
    },
    "non_transport": {
```

```

        "to": "16-07-2037",
        "from": "17-07-2017"
    },
    "hill_valid_till": "",
    "hazardous_valid_till": ""
},
"badge_details": [
    {
        "badge_no": "",
        "badge_issue_date": "",
        "class_of_vehicle": [
            "LMV",
            "MCWG"
        ]
    }
],
"details_of_driving_licence": {
    "name": "CHANDRA KUMAR",
    "photo": "",
    "status": "",
    "address": "SEKAR DRIVING SCHOOL, 6 DR SUBBARAYAN ROAD,
SALEM,TN SEKAR DRIVING SCHOOL, 6 DR SUBBARAYAN ROAD, SALEM,TN",
    "address_list": [
        {
            "type": "permanent",
            "split_address": {
                "city": [
                    "SALEM"
                ],
                "state": [
                    [
                        "TAMIL NADU",
                        "TN"
                    ]
                ],
                "country": [
                    "IN",
                    "IND",
                    "INDIA"
                ],
                "pincode": "636001",
                "district": [
                    "SALEM"
                ],
                "address_line": "SEKAR DRIVING SCHOOL,6 DR SUBBARAYAN
ROAD"
            },
            "complete_address": "SEKAR DRIVING SCHOOL, 6 DR SUBBARAYAN
ROAD, SALEM,TN 636001"
        },
        {
            "type": "temporary",
            "split_address": {
                "city": [
                    "DR. THOTTAM"
                ],
                "state": [

```

```

        [
            "TAMIL NADU",
            "TN"
        ]
    ],
    "country": [
        "IN",
        "IND",
        "INDIA"
    ],
    "pincode": "636010",
    "district": [
        "SALEM"
    ],
    "address_line": "SEKAR DRIVING SCHOOL,6 DR SUBBARAYAN
ROAD TN SEKAR DRIVING SCHOOL,6 DR SUBBARAYAN ROAD,SALEM"
    },
    "complete_address": "SEKAR DRIVING SCHOOL, 6 DR SUBBARAYAN
ROAD, SALEM,TN SEKAR DRIVING SCHOOL, 6 DR SUBBARAYAN ROAD,
SALEM,TN"
    }
    ],
    "date_of_issue": "17-07-2017",
    "split_address": {
        "city": [
            "DR. THOTTAM"
        ],
        "state": [
            [
                "TAMIL NADU",
                "TN"
            ]
        ],
        "country": [
            "IN",
            "IND",
            "INDIA"
        ],
        "pincode": "636010",
        "district": [
            "SALEM"
        ],
        "address_line": "SEKAR DRIVING SCHOOL,6 DR SUBBARAYAN ROAD
TN SEKAR DRIVING SCHOOL,6 DR SUBBARAYAN ROAD,SALEM"
    },
    "last_transacted_at": "",
    "father_or_husband_name": "DEVARAJAN K",
    "date_of_last_transaction": ""
    }
    },
    }
}

```

Keys of Result Object are explained below:

Key	Type	Value
request_id	string	Unique id for each API request
client_ref_num	string	Ref number sent in the input by client
result_code	int	Internal Status Code that denotes the status of the request
result	dict	Response object for the given inputs.
 - dob	string	Date of birth registered with DL number
 - dl_number	string	Input DL number
 - dl_validity	dict	Validity of DL number
 - - transport - from	string	Validity of DL number for transport vehicle start date
 - - transport - to	string	Validity of DL number for transport vehicle end date
 - - non_transport - from	string	Validity of DL number for non_transport vehicle start date
 - - non_transport - to	string	Validity of DL number for non_transport vehicle end date
 - - hill_valid_till	string	
 - - hazardous_valid_till	string	
 - badge_details	list	Authorisation to drive transport vehicle
 - - badge_no	string	Badge number
 - - badge_issue_date	string	Date on which Badge is issued
 - - class_of_vehicle	list	Vehicle class permitted to drive
 - details_of_driving_licence	dict	Driver data like name,address, photo etc
 - - name	string	Registered name in driving licence
 - - status	string	Status of driving licence
 - - address	string	Address registered for driving licence
 - - address_list	list	List of address linked with driving licence

 -- -- type	string	Type of address
 -- -- split_address	dict	Split of address
 -- date_of_issue	string	Date of issue of driving licence
 -- father_or_husband_name	string	Father or husband name registered
 -- date_of_last_transaction	string	Date on which the DL information were modified
 -- last_transacted_at	string	Place in which the DL information was last modified

When the DL number could not be validated with the given inputs then the following response will be provided.

If the DL number is an invalid number, then the response will be in the below format

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd1234",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 102,
  "message": "Invalid ID number or combination of inputs",
}
```

If there is no record found for the DL Number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd1234",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 103,
  "message": "No record found for the given input ",
}
```

18.5 API Error Response

If the input DOB indicates an age below the minimum permissible limit(16 years of age), then below response will be provided

```
{
  "http_response_code": 406,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "DL validation failed: Input DOB is below minimum age criteria (16 years)"
}
```

If input parameters format is incorrect, we provide the below response.

```
{
  "http_response_code": 400,
  "request_id": "1f03f845-6822-6ce1-7eadae780e64",
  "error": "one or more parameters format is wrong"
}
```

In case of other errors, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

19 KYC - Driving Licence Validation Plus API

19.1 API Introduction

This sync API extracts all details linked with the Driving Licence number. It takes mandatory input as a DL number and date of birth and provides the information in json format.

Note: This API aggregates data from multiple sources, some of which may return response without correct date of birth of the registered DL as input. To avoid any discrepancies in responses, it is advised to input accurate date of birth along with DL number in the input.

19.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/dl_plus
Production Env	https://svc.digitap.ai/validation/kyc/v1/dl_plus

19.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 100 chars]
dl_number	M	DL number for which information need to be extracted (Min Length: 13 Max Length: 25) DL_REGEX = r"^[a-zA-Z0-9/]{13,25}\$"
dob	M	Date of birth according DL document Format: DD/MM/YYYY

19.4 API Success Response

19.4.1 Successful Validation Case

When the DL number is valid and if the information related to DL is extracted successfully then below json is returned:

```
{
  {
    "http_response_code": 200,
    "request_id": "3fa7d925-16bc-11f0-bd53-1daf8e14a2e0",
    "client_ref_num": "test",
    "result": {
      "dl_number": "AP11111100000000",
      "dob": "10-01-1986",
      "dl_validity": {
        "non_transport": {
```

```

        "from": "04-04-2018",
        "to": "03-03-2038"
    },
    "hazardous_valid_till": "",
    "transport": {
        "from": "",
        "to": ""
    },
    "hill_valid_till": ""
},
"details_of_driving_licence": {
    "date_of_issue": "",
    "date_of_last_transaction": "",
    "status": "Active",
    "last_transacted_at": "",
    "name": "JOHN DOE",
    "father_or_husband_name": "Prasad",
    "address_list": [
        {
            "complete_address": "28-1-20/805 CHANDRANAGARKTROAD
TIRUPATIURBAN TIRUPATICHITTOORDT CHITTOOR AndhraPradesh 517501
517503",
            "type": "permanent",
            "split_address": {
                "district": [
                    "CHITTOOR"
                ],
                "state": [
                    [
                        "ANDHRA PRADESH",
                        "AP"
                    ]
                ],
                "city": [
                    "TIRUPATI (URBAN)"
                ],
                "pincode": "517503",
                "country": [
                    "IN",
                    "IND",
                    "INDIA"
                ],
                "address_line": "28-1-20/805 CHANDRANAGARKTROAD
TIRUPATIURBAN TIRUPATI DT ANDHRAPRADESH"
            }
        },
        {
            "complete_address": "18-1-20/402 RAMACHANDRANAGARKTROAD
TIRUPATIURBAN TIRUPATICHITTOORDT CHITTOOR AndhraPradesh 517503
517503",
            "type": "temporary",
            "split_address": {
                "district": [
                    "CHITTOOR"
                ],
                "state": [
                    [

```

```

        "ANDHRA PRADESH",
        "AP"
    ],
    "city": [
        "TIRUPATI (URBAN)"
    ],
    "pincode": "517503",
    "country": [
        "IN",
        "IND",
        "INDIA"
    ],
    "address_line": "28-1-20/805 CHANDRANAGARKTROAD
TIRUPATIURBAN TIRUPATI DT ANDHRAPRADESH"
    },
    "address": "18-1-20/402 CHANDRANAGARKTROAD TIRUPATIURBAN
TIRUPATICHITTOORDT CHITTOOR AndhraPradesh 517503 517503",
    "split_address": {
        "district": [
            "CHITTOOR"
        ],
        "state": [
            [
                "ANDHRA PRADESH",
                "AP"
            ]
        ],
        "city": [
            "TIRUPATI (URBAN)"
        ],
        "pincode": "517503",
        "country": [
            "IN",
            "IND",
            "INDIA"
        ],
        "address_line": "28-1-20/805 CHANDRANAGARKTROAD
TIRUPATIURBAN TIRUPATI DT ANDHRAPRADESH"
    },
    "status_details": {
        "from": "",
        "remarks": "",
        "to": ""
    },
    "user_blood_group": "",
    "user_image":
"/9j/4AAQSkZJRgABAQEAYABgAAD/2wBDAAgGBgcGBQgHBwcJCQgKDBQNDAs
LDBkSEw8UHRofHh0aHBwgJC4nIClIxwcKDcpLDAxNDQ0Hyc5PTgyPC4zNDL/2w
BDAQkJCQwLDBgNDRgyIRVZB/Z",
    "expiry_date": "03-03-2037"
    },
    "badge_details": [
        {
            "badge_issue_date": "",

```

```

        "badge_no": "",
        "class_of_vehicle": [
            "LMV",
            "MCWG"
        ]
    },
    ],
    "vehicle_category_details": [
        {
            "cov": "MCWG",
            "expiryDate": "03-03-2038",
            "issueDate": "04-03-2018"
        },
        {
            "cov": "LMV",
            "expiryDate": "03-03-2038",
            "issueDate": "04-03-2018"
        }
    ],
    "endorse_date": "NA",
    "endorse_number": "NA"
},
"result_code": 101
}

```

Keys of Result Object are explained below:

Key	Type	Value
request_id	string	Unique id for each API request
client_ref_num	string	Ref number sent in the input by client
result_code	int	Internal Status Code that denotes the status of the request
result	dict	Response object for the given inputs.
 - dl_number	string	Input DL Number
 - dob	string	Date of birth registered with DL number
 - dl_validity	dict	Validity of DL number
 - - non_transport - from	string	Validity of DL number for non_transport vehicle start date
 - - non_transport - to	string	Validity of DL number for non_transport vehicle end date
 - - hazardous_valid_till	string	Authorisation to drive with Hazardous goods

 - - transport - from	string	Validity of DL number for transport vehicle start date
 - - transport - to	string	Validity of DL number for transport vehicle end date
 - - hill_valid_till	string	Authorisation to drive in hilly area
 - details_of_driving_licence	dict	Driver data like name, address, photo etc
 - - date_of_issue	string	Date of issue of driving licence
 - - date_of_last_transaction	string	Date on which the DL information were modified
 - - status	string	Status of driving licence
 - last_transacted_at	string	Place in which the DL information was last modified
 - - name	string	Registered name in driving licence
 - - father_or_husband_name	string	Father's name or husband's name registered
 - - address_list	list	List of address
 - - - complete_address	string	Permanent address registered for driving licence
 - - - type	string	Type of address
 - - - split_address	dict	Split of address
 - - - - district	list	District name
 - - - - state	list	State name with state abbreviation
 - - - - city	list	Name of the city
 - - - - pincode	string	Pincode
 - - - - country	list	Contains Country Name, abbreviation of country
 - - - - address_line	string	Short address with city, and state abbreviation
 - - - complete_address	string	Present address registered for driving licence
 - - - type	string	Type of address
 - - - split_address	dict	Split of address
 - - - - district	list	District name in address

--- state	list	State name with state abbreviation
--- city	list	Name of the city in address
--- pincode	string	Pincode
--- country	list	Contains Country Name, abbreviation of country
--- address_line	string	Short address with city, and state abbreviation
--- address	string	Complete address registered for driving licence
--- split_address	list	Split of address
--- district	list	District name
--- state	list	State name with state abbreviation
--- city	list	Name of the city
--- pincode	string	Pincode
--- country	list	Contains Country Name, abbreviation of country
--- address_line	string	Short address with city, and state abbreviation
--- status_details	list	Transition log or history of DL
--- status_details : from	string	Previous status : "Pending" / "Under review" / "Approved" / "Suspended or " "
--- status_details : remarks	string	Comments
--- status_details : to	string	Mentions Valid until
--- user_blood_group	string	Blood group
--- user_image	string	Base64 string which contains the user image
--- expiry_date	string	Expiration date of DL
--- badge_details	list	Authorisation to drive transport vehicle
--- badge_no	string	Badge number
--- badge_issue_date	string	Date on which Badge is issued
--- class_of_vehicle	list	Vehicle class permitted to drive
--- vehicle_category_details	list	Vehicle category associated with DL
--- cov	string	Class of vehicle authorized by DL

 - - issueDate	string	Date license was issued or renewed
 - - expiryDate	string	Expiration date of DL
 - - endorse_date	string	Date of endorsement or modification added to the license
 - - endorse_number	string	Unique number associated with DLs endorsement.

When the DL number could not be validated with the given inputs then the following response will be provided.

If the DL number is an invalid number, then the response will be in the below format

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd1234",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 102,
  "message": "Invalid ID number or combination of inputs",
}
```

If there is no record found for the DL Number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd1234",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 103,
  "message": "No record found for the given input ",
}
```

19.5 API Error Response

If the input DOB indicates an age below the minimum permissible limit(16 years of age), then below response will be provided

```
{
  "http_response_code": 406,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "DL validation failed: Input DOB is below minimum age criteria (16 years)"
}
```

If input parameters format is incorrect, we provide the below response.

```
{
  "http_response_code": 400,
  "request_id": "1f03f845-6822-6ce1-7eadae780e64",
  "error": "one or more parameters format is wrong"
}
```

If the source is down, then the below response would be provided.

```
{
  "http_response_code": 503,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "Source is busy or unavailable. Try again later"
}
```

In case of other errors, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

20 KYC - Unique Disability ID Validation API

20.1 API Introduction

This sync API extracts the details linked with the Unique Disability ID number. It takes conditional mandatory input - UDID number or mobile number, and optional input DOB and provides the information in JSON format. Unique Disability Identity cards are issued to Persons with Disabilities through competent medical authorities notified by respective State Governments/Union Territories. This will help clients to validate identity of specially abled individuals and provide special allowances/schemes that they are eligible for.

We get the following details in the output:

1. UDID and enrollment numbers
2. UDID generation date(config based)
3. Full name of the person
4. Masked Aadhaar number(last 4 digits unmasked)
5. Mobile number and email id(config based)
6. Hospital details where the application was assessed
7. Status of the UDID application
8. Type and percentage of disability(config based)
9. DOB, father name, gender, address(config based)
10. Image of the person in base64 format(config based)

20.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/kyc_udid_verification
Production Env	https://svc.digitap.ai/validation/kyc/v1/kyc_udid_verification

20.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret / Basic Base64encodedValueOf (client_id:client_secret)

- **Request Body:**

Key	Mandatory/Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 100 chars]
udid_number	M	Unique Disability ID of the Individual Regex: r"^[A-Za-z]{2}\d{16}\$"
Mobile_number	O	Mobile number linked to UDID of the individual. One of the 2 inputs UDID or mobile number is mandatory. If both are given in the input, UDID is given priority to fetch the details.
DOB	O	Date of birth of the individual in DD/MM/YYYY format

Note: Date of birth field is optional, and when it is inputted we get the enhanced version of the output(provided below). Enhanced output is a configuration that needs to be enabled, please

contact your RM for more details. If DOB is not provided in the input, simpler version of the output is given.

20.4 API Success Response

20.4.1 Successful Validation Case

When the UDID number/mobile number is valid, and DOB is not provided in the input and if the information related to UDID is extracted successfully then below json is returned. This is the basic version of the output.

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "019add9c-17d4-8723-b51e-778058691136",
  "client_ref_num": "test",
  "result": {
    "enrollment_number": "12340000012341234123",
    "udid_number": "XXXXXXXXXXXX1234",
    "full_name": "Jane Doe",
    "aadhaar_no": "XXXXXXXX1234",
    "mobile": "XXXXXX1234",
    "hospital": {
      "hospital_name": "King George Hospital, Maharanipeta"
    },
    "pwdapplicationstatus": {
      "status_name": "UDID Card Dispatched"
    }
  }
}
```

Keys of Result Object are explained below:

Key	Type	Value
http_response_code	int	Internal Status Code that denotes the status of the request
request_id	string	Unique id for each API request
client_ref_num	string	Ref number sent in the input by client
result_code	int	Internal Status Code that denotes the status of the request
result	dict	Response object for the given inputs.
enrollment_number	string	Unique Enrollment number mapped to the input UDID

udid_number	string	Masked UDID number of the individual, with last 4 digits unmasked
full_name	string	Full name of the person to whom the UDID is assigned
aadhaar_number	string	Masked Aadhaar number with last 4 digits unmasked, of the person to whom the UDID is assigned
mobile	string	Masked Mobile number of the person to whom the UDID is assigned, with last 4 digits unmasked
hospital	dict	Details of the concerned Hospital/CMO office, who assessed the application
 - hospital_name	string	Name of the hospital where the applicant was assessed
pwdapplicationstatus	dict	Details of the application status
 - status_name	string	Status of the UDID application

When the UDID number/mobile number is valid, and DOB is provided in the input and enriched output configuration is enabled, and if the information related to UDID is extracted successfully then below json is returned. This is the enriched version of the output.

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "123e4567-e89b-12d3-a456-426614174001",
  "client_ref_num": "test-client",
  "result": {
    "udid_details": {
      "enrollment_number": "12345678901234567890",
      "udid_number": "KA000000000000000001",
      "udid_generation_date": "01/01/2020"
    },
    "personal_details": {
      "full_name": "John Doe",
      "father_name": "Richard Doe",
      "dob": "01/01/1990",
      "gender": "Male",
      "aadhaar_number": "XXXXXXXX1234",
      "address": {
        "full_address": "Flat 101, Sunrise Apartments, MG Road",
        "subdistrict": "Central",
        "district": "Bangalore Urban",
        "state": "Karnataka",
        "pincode": 560001
      }
    }
  }
}
```


 - udid_number	string	UDID number of the individual
 - udid_generation_date	string	Date when UDID got generated, in dd/mm/yyyy format
personal_details	dict	Demographic details of the individual
 - full_name	string	Full name of the person to whom the UDID is assigned
 - father_name	string	Father name of the individual
 - dob	string	Date of birth of the individual, in dd/mm/yyyy format
 - gender	string	Gender of the individual
 - aadhaar_number	string	Masked Aadhaar number with last 4 digits unmasked, of the person to whom the UDID is assigned
address	dict	Address details of the individual
 - full_address	string	Line 1 of the address of the individual
 - subdistrict	string	Line 2 of the address, subdistrict
 - district	string	Line 3 of the address, district
 - state	string	State part of the address
 - pincode	string	Pincode part of the address
mobile	string	Mobile number of the person to whom the UDID is assigned
email	string	Email of the person to whom the UDID is assigned
disability_details	dict	Disability related details of the individual
 - type	string	Disability type of the individual
 -percentage	int	Disability percentage
 - is_permanent	bool	If the disability is permanent or temporary. Possible values: true, false
hospital_details	dict	Details of the concerned Hospital/CMO office, who assessed the application
 - hospital_name	string	Name of the hospital where the applicant was assessed

 - state	string	State where the individual was assessed
 - district	string	District where the individual was assessed
application_status	dict	Details of the application status
 - status	string	Status of the UDID application
documents	dict	Documents of the individual
 - image_base64	string	Image of the individual in base64 format

If for the given UDID/mobile number, input DOB is incorrect, then the below response will be provided (result code - 102).

```
{
  "http_response_code": 200,
  "result_code": "102",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "message": "Invalid ID number or combination of inputs",
}
```

If no record was found for the given UDID/mobile number, then the below response will be provided (result code - 103).

```
{
  "http_response_code": 200,
  "result_code": "103",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "client_ref_num": "abcd123",
  "message": "No record found for the given input",
}
```

20.5 API Error Response

The API service includes an internal regex check that validates the UDID format. If the format is Invalid (does not meet the input parameter criteria), a 400 error is returned.

```
{
  "http_response_code": 400,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "error": "One or more parameters format is wrong"
}
```

If DOB was passed in the input body, but enriched data output configuration was not enabled, then the below error will be returned.

```
{
  "http_response_code": 412,
  "request_id": "019d2ea5-5c17-818a-9531-09b7dbc62cea",
  "client_ref_num": "digitap-test",
  "error": "Advanced data points are not enabled for this client."
}
```

In case of any other errors, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

21 KYC - Aadhaar to Unmasked PAN Validation API

21.1 API Introduction

This API helps to get the masked pan number which is linked to the input Aadhaar number.

21.2 API URL

Following are the **URLs** for UAT & production Environment.

UAT/DEMO Env	https://svcdemo.digitap.work/validation/kyc/v1/aadhaar_to_unmasked_pan
Production Env	https://svc.digitap.ai/validation/kyc/v1/aadhaar_to_unmasked_pan

21.3 API Request

- **Method:** POST
- **Header:**

Key	Mandatory/Optional (M/O)	Value
content-type	M	application/json
authorization	M	Type: Basic Auth, Username:client_id, password:client_secret /

		Basic Base64encodedValueOf (client_id:client_secret)
--	--	---

- **Request Body:**

Key	Mandatory/ Optional (M/O)	Value
client_ref_num	M	Unique ID for this request from the Client side [Max of 45 chars]
aadhaar	M	Aadhaar Number to be authenticated minLength: 12 maxLength: 12 Pattern: 12 digit number

- **Encrypted Request:**

This API supports request payload encryption. Please refer to [Section 2.6](#) for details.

21.4 API Success Response

21.4.1 Successful Validation Case

The following response would be provided in case if the Aadhaar to unmasked PAN could be validated

If pan is linked with the given Aadhaar number, then the below response would be provided.

```
{
  "http_response_code": 200,
  "result_code": 101,
  "request_id": "4bb38274-39a2-465c-84eb-774258df2926",
  "client_ref_num": "se7en-c7429978-d8c3-4a09-a089-f41b78720ca3",
  "result": {
    "linked_pan": "LBQPD5841L"
  }
}
```

Keys of Result Object are explained below:

Keys	Type	Value
------	------	-------

http_response_code	int	Internal Status Code that denotes the status of the request
result_code	String	Internal Status Code that denotes the status of the request
request_id	String	Unique id for each API request
client_ref_num	String	Ref number sent in the input by client
result	Dict	Response object for the given inputs.
- linked_pan	String	Unmasked PAN linked to the given Aadhaar

When the given Aadhaar number could not be verified, the below response will be provided and along with below message as

If for the given aadhaar number, PAN could not be found, the below response will be provided

```
{
  "http_response_code": 200,
  "client_ref_num": "abcd123",
  "request_id": "97a9f2ce-cd70-11ea-ba26-4ef9447da577",
  "result_code": 103,
  "message": "No records found for the given Input"
}
```

When the given aadhaar number starts with 1/it is invalid at source, the below response will be provided

```
{
  "http_response_code": 200,
  "client_ref_num": "test989",
  "request_id": "ac529358-5c47-11ed-a8f9-46ea22d4d73e",
  "result_code": 102,
  "message": "Invalid Aadhaar"
}
```

21.5 API Error Response

When the given aadhaar number format is wrong, the below response will be provided

```
{
  "http_response_code": 400,
  "client_ref_num": "test989",
  "request_id": "ac529358-5c47-11ed-a8f9-46ea22d4d73e",
  "error": "One or more parameters format is wrong"
}
```

```
}
```

When the given aadhaar number failed in Verhoeff Check, the below response will be provided

```
{  
  "http_response_code": 400,  
  "client_ref_num": "test989",  
  "request_id": "ac529358-5c47-11ed-a8f9-46ea22d4d73e",  
  "error": "Invalid Aadhaar. Vernhoeff Check failed"  
}
```

In case of Error, the response as explained in the [Section 2.4](#) and error messages as defined in the [Section 2.4.1 Error Messages](#) would be returned.

----- End of Document -----