

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

Problem Statement: Comprehensive exploratory data analysis, profitability evaluation, discount impact modeling, and time-series forecasting on retail store transaction data using Python.

Objective: Identify key drivers of sales, identify unprofitability root causes, evaluate discounting impact, and deliver actionable data-driven business recommendations.

Dataset Name: Sample - Superstore.csv (9,994 transaction records x 21 features)

Academic Submission Details	
Student Name:	Krishna
Enrollment / Roll No.:	SF-DA-2026-T2
Domain:	Data Analytics & Data Science
Submission Date:	September 15, 2026
Environment:	Antigravity AI Agentic IDE / Python 3.11

SECTION 2 — PROBLEM STATEMENT

In modern retail management, businesses often experience high overall sales volume but struggle to maintain healthy profit margins. Without granular data analysis, retail managers may mistakenly assume that top-selling products or high-volume sales transactions translate into high profitability. In reality, aggressive discounting, unmonitored operational overhead, and unprofitable product lines can quietly erode corporate net margins.

The problem addressed in this project is to perform a rigorous end-to-end data analysis of the Superstore retail dataset using Python. The analysis must dissect transaction-level data to uncover underlying profitability drivers, evaluate the precise impact of discount rates on bottom-line returns, examine regional and customer segment variations, and identify specific products that generate top-line revenue at the expense of net bottom-line profit.

SECTION 3 — OBJECTIVES & IMPORTANCE

- 1. Importance of Sales Analysis:** Sales analysis provides fundamental visibility into top-line revenue patterns, transaction volume growth, customer purchasing behavior, and market demand across product categories and regions.
- 2. Importance of Profit Analysis:** Profitability analysis ensures long-term business viability. It reveals true net margin efficiency, highlighting products that actively generate value versus loss-leaders that drain company capital.
- 3. Strategic Customer, Product & Regional Evaluation:** Categorical and geographic segmentation allows management to optimize resource allocation, tailor marketing campaigns to high-value customer segments, and address regional underperformance.
- 4. Role of Python in Large-Scale Analytics:** Python provides scalable, reproducible, and automated data processing tools (Pandas, NumPy, Matplotlib) capable of efficiently handling thousands of raw records, cleansing dirty data, computing complex metrics, and rendering professional data visualizations.
- 5. Data-Driven Decision Making:** Transitioning from intuitive gut-feel decision-making to empirical data insights empowers retail executives to optimize discount policies, restructure pricing models, and improve operational profitability.

SECTION 4 — DATASET OVERVIEW

The dataset analyzed in this project is Sample - Superstore.csv. It represents retail transaction records spanning four calendar years (2014–2017) across the United States. Below is the technical structural breakdown of the dataset:

Dataset Attribute	Value / Details
File Name	Sample - Superstore.csv
Total Row Count	9,994 transaction records
Total Column Count	21 feature columns
File Encoding	ISO-8859-1 (Latin-1)
Missing Values	0 missing values (Complete dataset)
Duplicate Rows	0 duplicate records

Detailed Column Descriptions:

Column Name	Data Type	Description & Business Purpose
Row ID	int64	Unique numerical identifier for each dataset row.
Order ID	object	Unique transaction order code assigned to customer purchases.
Order Date	datetime64	Date when the customer placed the transaction order.
Ship Date	datetime64	Date when the ordered item was dispatched to the customer.
Ship Mode	object	Shipping class (Standard Class, Second Class, First Class, Same Day).
Customer ID	object	Unique identifier assigned to each customer account.
Customer Name	object	Full name of the purchasing customer.
Segment	object	Target market segment (Consumer, Corporate, Home Office).
Country / City / State	object	Geographic location details of the order delivery.
Region	object	Geographic territory (West, East, Central, South).
Product ID / Name	object	Unique SKU code and full descriptive product title.
Category / Sub-Category	object	Product classification hierarchy (e.g. Technology -> Copiers).
Sales	float64	Monetary transaction revenue generated (\$).
Quantity	int64	Number of product units purchased in the order line.
Discount	float64	Promotional discount rate applied (range: 0.0 to 0.80).
Profit	float64	Net profit or loss generated by the order transaction (\$).

SECTION 5 — TECHNOLOGIES USED

Technology / Library	Version / Role	Primary Application in Project
Python	v3.11+	Core programming language powering the analysis script execution.
Pandas	v2.2+	DataFrame manipulation, data cleansing, aggregations, and grouping.
NumPy	v1.26+	Vectorized numerical calculations, statistical functions, matrix ops.
Matplotlib	v3.8+	Rendering bar charts, pie charts, line graphs, scatter plots.
ReportLab	v5.0+	Programmatic PDF document generation, layout styling, table rendering.
Antigravity IDE	v1.0	Google DeepMind agentic environment for execution, testing, and report build.

SECTION 6 — COMPLETE FINAL PYTHON CODE

Below is the complete, final executable Python script `store_sales_profit_analysis.py` created and tested for this project:

```
"""
Store Sales and Profit Analysis
=====
This script performs a comprehensive analysis of the Superstore retail sales dataset.
It covers data inspection, cleaning, analysis, visualization, and business recommendations.
"""

# =====
# 1. IMPORT LIBRARIES
# =====
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from datetime import datetime
import warnings
warnings.filterwarnings('ignore')

# =====
# 2. LOAD DATASET
# =====
print("=" * 80)
print("STEP 2: LOAD DATASET")
print("=" * 80)

csv_path = 'Sample - Superstore.csv'
# Use ISO-8859-1 encoding to handle special characters in product names
df = pd.read_csv(csv_path, encoding='ISO-8859-1')

print(f"Dataset loaded successfully: {csv_path}")
print(f"Shape: {df.shape[0]:,} rows x {df.shape[1]} columns")

# =====
# 3. DATASET OVERVIEW
# =====
print("\n" + "=" * 80)
print("STEP 3: DATASET OVERVIEW")
print("=" * 80)

print(f"\nColumn Names ({len(df.columns)} columns):")
for col in df.columns:
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
print(f" - {col}")

print(f"\nFirst 5 rows:")
print(df.head())

print(f"\nLast 5 rows:")
print(df.tail())

# =====
# 4. DATA INSPECTION
# =====

print("\n" + "=" * 80)
print("STEP 4: DATA INSPECTION")
print("=" * 80)

print("\nData Types:")
print(df.dtypes)

print("\nSample values for key columns:")
print(f"Order Date sample: {df['Order Date'].iloc[0]}")
print(f"Segment values: {df['Segment'].unique()}")
print(f"Category values: {df['Category'].unique()}")
print(f"Sub-Category values: {df['Sub-Category'].unique()}")
print(f"Region values: {df['Region'].unique()}")

# =====
# 5. DATA CLEANING
# =====

print("\n" + "=" * 80)
print("STEP 5: DATA CLEANING")
print("=" * 80)

# Store original row count
original_rows = len(df)
print(f"Original dataset: {original_rows:,} rows")

# 5.1 Check for duplicates
duplicates = df.duplicated().sum()
print(f"\nDuplicate rows found: {duplicates}")
if duplicates > 0:
    print("Action: Removing duplicate rows")
    df = df.drop_duplicates()
else:
    print("Action: No duplicates found - no action needed")

# 5.2 Check for missing values
print("\nMissing values per column:")
missing = df.isna().sum()
total_missing = missing.sum()
print(f"Total missing values: {total_missing}")
if total_missing > 0:
    print("Details:")
    for col, count in missing[missing > 0].items():
        print(f" - {col}: {count} missing ({count/len(df)*100:.2f}%)")
else:
    print("Action: No missing values found - no action needed")

# 5.3 Check for empty strings in string columns
print("\nEmpty string check:")
string_cols = ['Order ID', 'Customer ID', 'Customer Name', 'City', 'State', 'Product ID', 'Product Name']

for col in string_cols:
    empty_count = (df[col] == '').sum() + (df[col] == ' ').sum()
    if empty_count > 0:
        print(f" - {col}: {empty_count} empty/blank values")
    else:
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
print(f" - {col}: No empty values")

# 5.4 Convert date columns to datetime
print("\nDate conversion:")
df['Order Date'] = pd.to_datetime(df['Order Date'], format='%m/%d/%Y')
df['Ship Date'] = pd.to_datetime(df['Ship Date'], format='%m/%d/%Y')
print(" - Converted 'Order Date' to datetime")
print(" - Converted 'Ship Date' to datetime")

# 5.5 Check for invalid numerical values
print("\nNumerical validation:")
print(f" - Sales: Min={df['Sales'].min():.2f}, Max={df['Sales'].max():.2f}")
print(f" - Profit: Min={df['Profit'].min():.2f}, Max={df['Profit'].max():.2f}")
print(f" - Quantity: Min={df['Quantity'].min()}, Max={df['Quantity'].max()}")
print(f" - Discount: Min={df['Discount'].min()}, Max={df['Discount'].max()}")

# Check for negative sales (potential issues)
negative_sales = (df['Sales'] < 0).sum()
if negative_sales > 0:
    print(f" WARNING: {negative_sales} negative sales values found")

# Check for impossible discount values (> 1)
invalid_discount = (df['Discount'] > 1).sum()
if invalid_discount > 0:
    print(f" WARNING: {invalid_discount} discount values > 1.0 found")
else:
    print(" - All discount values are valid (0-1 range)")

# Final row count
final_rows = len(df)
print(f"\nFinal dataset: {final_rows:,} rows")
if original_rows != final_rows:
    print(f"Rows removed: {original_rows - final_rows}")

# =====
# 6. MISSING VALUE & OUTLIER ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 6: MISSING VALUE & OUTLIER ANALYSIS")
print("=" * 80)
print(f"Total missing values in dataset: {df.isna().sum().sum()}")
print("Dataset is complete - no missing values to handle")

# IQR Outlier Detection for Sales and Profit
def detect_iqr_outliers(series):

    q1 = series.quantile(0.25)
    q3 = series.quantile(0.75)
    iqr = q3 - q1
    lower_bound = q1 - 1.5 * iqr
    upper_bound = q3 + 1.5 * iqr
    return (series < lower_bound) | (series > upper_bound), lower_bound, upper_bound

sales_outliers, s_low, s_high = detect_iqr_outliers(df['Sales'])
profit_outliers, p_low, p_high = detect_iqr_outliers(df['Profit'])

print(f"\n--- Outlier Detection (IQR Method) ---")
print(f"Sales Outliers (Bounds: [{s_low:.2f}, {s_high:.2f}]): {sales_outliers.sum():,} rows ({sales_outliers.mean()*100:.1f}%)"
print(f"Profit Outliers (Bounds: [{p_low:.2f}, {p_high:.2f}]): {profit_outliers.sum():,} rows ({profit_outliers.mean()*100:.1f}%)"
print("Note: Outliers represent high-value enterprise sales and extreme discount losses; retained for full analysis."
)

# =====
# 7. DUPLICATE ANALYSIS & EFFICIENCY RATIOS
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
# =====
print("\n" + "=" * 80)
print("STEP 7: DUPLICATE ANALYSIS & EFFICIENCY METRICS")
print("=" * 80)
print(f"Duplicate rows in dataset: {df.duplicated().sum()}")
print("Dataset is clean - no duplicate rows")

# Add Sales-to-Profit Ratio column
df['Sales_to_Profit_Ratio'] = np.where(df['Profit'] != 0, df['Sales'] / df['Profit'], np.nan)
df['Profit_Margin_%'] = (df['Profit'] / df['Sales']) * 100

# =====
# 8. DESCRIPTIVE STATISTICS
# =====
print("\n" + "=" * 80)
print("STEP 8: DESCRIPTIVE STATISTICS")
print("=" * 80)

print("\nNumerical columns descriptive statistics:")
print(df[['Sales', 'Quantity', 'Discount', 'Profit']].describe())

print("\nProfit by Category:")
profit_by_cat = df.groupby('Category')['Profit'].agg(['sum', 'mean', 'count'])
profit_by_cat.columns = ['Total Profit', 'Avg Profit', 'Num Orders']
print(profit_by_cat)

print("\nSales by Region:")
sales_by_region = df.groupby('Region')['Sales'].agg(['sum', 'mean'])
sales_by_region.columns = ['Total Sales', 'Avg Sales']
print(sales_by_region)

# =====
# 9. SALES ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 4: SALES ANALYSIS")
print("=" * 80)

# 9.1 Basic Sales Metrics
total_sales = df['Sales'].sum()
avg_sales = df['Sales'].mean()
min_sales = df['Sales'].min()
max_sales = df['Sales'].max()
median_sales = df['Sales'].median()
std_sales = df['Sales'].std()

print(f"\n--- Basic Sales Metrics ---")
print(f"Total Sales: ${total_sales:,.2f}")
print(f"Average Sales: ${avg_sales:,.2f}")
print(f"Median Sales: ${median_sales:,.2f}")
print(f"Min Sales: ${min_sales:,.2f}")
print(f"Max Sales: ${max_sales:,.2f}")
print(f"Std Dev: ${std_sales:,.2f}")

# 9.2 Number of Transactions
num_transactions = len(df)
num_orders = df['Order ID'].nunique()
print(f"\nNumber of Order Lines: {num_transactions:,}")
print(f"Number of Unique Orders: {num_orders:,}")

# 9.3 Sales by Category
print(f"\n--- Sales by Category ---")
sales_by_category = df.groupby('Category')['Sales'].sum().sort_values(ascending=False)
for cat, sales in sales_by_category.items():
    pct = sales / total_sales * 100
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
print(f" {cat}: ${sales:,.2f} ({pct:.1f}%)")

# Identify best and worst categories
best_category = sales_by_category.idxmax()
worst_category = sales_by_category.idxmin()
best_cat_sales = sales_by_category.max()
worst_cat_sales = sales_by_category.min()

print(f"\nHighest-selling category: {best_category} (${best_cat_sales:,.2f}")
print(f"Lowest-selling category: {worst_category} (${best_cat_sales:,.2f}")

# 9.4 Sales by Sub-Category
print(f"\n--- Sales by Sub-Category ---")
sales_by_subcat = df.groupby('Sub-Category')['Sales'].sum().sort_values(ascending=False)
for sc, sales in sales_by_subcat.items():
    pct = sales / total_sales * 100
    print(f" {sc}: ${sales:,.2f} ({pct:.1f}%)")

# Top 5 and Bottom 5 products by sales
print(f"\n--- Top 5 Products by Sales ---")
top_products = df.groupby(['Category', 'Sub-Category'])['Sales'].sum().sort_values(ascending=False).head(5)
for idx, sales in top_products.items():
    print(f" {idx[0]} - {idx[1]}: ${sales:,.2f}")

print(f"\n--- Bottom 5 Products by Sales ---")
bottom_products = df.groupby(['Category', 'Sub-Category'])['Sales'].sum().sort_values(ascending=True).head(5)
for idx, sales in bottom_products.items():
    print(f" {idx[0]} - {idx[1]}: ${sales:,.2f}")

# 9.5 Sales by Region
print(f"\n--- Sales by Region ---")
sales_by_region = df.groupby('Region')['Sales'].sum().sort_values(ascending=False)
for region, sales in sales_by_region.items():
    pct = sales / total_sales * 100
    print(f" {region}: ${sales:,.2f} ({pct:.1f}%)")

best_region = sales_by_region.idxmax()
worst_region = sales_by_region.idxmin()
print(f"\nBest-performing region: {best_region} (${sales_by_region[best_region]:,.2f}")
print(f"Weak-performing region: {worst_region} (${sales_by_region[worst_region]:,.2f}")

# 9.6 Sales by Customer Segment
print(f"\n--- Sales by Customer Segment ---")
sales_by_segment = df.groupby('Segment')['Sales'].sum().sort_values(ascending=False)
for seg, sales in sales_by_segment.items():
    pct = sales / total_sales * 100
    print(f" {seg}: ${sales:,.2f} ({pct:.1f}%)")

# 9.7 Sales Over Time
print(f"\n--- Sales Over Time ---")
# Convert Order Date to year-month for monthly analysis
df['Order_Month'] = df['Order Date'].dt.to_period('M')
sales_by_month = df.groupby('Order_Month')['Sales'].sum()
print("First 6 months of sales data:")
for month, sales in sales_by_month.head(6).items():
    print(f" {month}: ${sales:,.2f}")

# Find highest and lowest sales months
best_month = sales_by_month.idxmax()
worst_month = sales_by_month.idxmin()
print(f"\nPeak sales month: {best_month} (${sales_by_month[best_month]:,.2f}")
print(f"Lowest sales month: {worst_month} (${sales_by_month[worst_month]:,.2f}")

# =====
# 10. PROFIT ANALYSIS
# =====
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
print("\n" + "=" * 80)
print("STEP 10: PROFIT ANALYSIS")

print("=" * 80)

# 10.1 Basic Profit Metrics
total_profit = df['Profit'].sum()
avg_profit = df['Profit'].mean()
min_profit = df['Profit'].min()
max_profit = df['Profit'].max()
median_profit = df['Profit'].median()

print(f"\n--- Basic Profit Metrics ---")
print(f"Total Profit: ${total_profit:,.2f}")
print(f"Average Profit: ${avg_profit:,.2f}")
print(f"Median Profit: ${median_profit:,.2f}")
print(f"Min Profit: ${min_profit:,.2f} (loss)")
print(f"Max Profit: ${max_profit:,.2f}")

# Profit Margin
profit_margin = (total_profit / total_sales) * 100
print(f"\nOverall Profit Margin: {profit_margin:.2f}%")

# 10.2 Profit by Category
print(f"\n--- Profit by Category ---")
profit_by_category = df.groupby('Category')['Profit'].agg(['sum', 'mean', 'count']).sort_values('sum', ascending=False)
for cat, row in profit_by_category.iterrows():
    margin = row['sum'] / df[df['Category'] == cat]['Sales'].sum() * 100
    print(f" {cat}: ${row['sum']:,.2f} total, ${row['mean']:,.2f} avg, Margin: {margin:.1f}% ({row['count']:,.0f} orders)")

# 10.3 Profit by Sub-Category
print(f"\n--- Profit by Sub-Category ---")
profit_by_subcat = df.groupby('Sub-Category')['Profit'].sum().sort_values(ascending=False)
for sc, profit in profit_by_subcat.items():
    sales = df[df['Sub-Category'] == sc]['Sales'].sum()
    margin = profit / sales * 100 if sales > 0 else 0
    print(f" {sc}: ${profit:,.2f} (Margin: {margin:.1f}%)")

# Identify most profitable and least profitable
most_profitable = profit_by_subcat.idxmax()
least_profitable = profit_by_subcat.idxmin()
print(f"\nMost profitable sub-category: {most_profitable} (${profit_by_subcat[most_profitable]:,.2f})")
print(f"Least profitable sub-category: {least_profitable} (${profit_by_subcat[least_profitable]:,.2f})")

# 10.4 Profit by Region
print(f"\n--- Profit by Region ---")
profit_by_region = df.groupby('Region')['Profit'].sum().sort_values(ascending=False)
for region, profit in profit_by_region.items():
    sales = df[df['Region'] == region]['Sales'].sum()
    margin = profit / sales * 100 if sales > 0 else 0
    print(f" {region}: ${profit:,.2f} (Margin: {margin:.1f}%)")

# 10.5 Profit by Segment
print(f"\n--- Profit by Customer Segment ---")
profit_by_segment = df.groupby('Segment')['Profit'].sum().sort_values(ascending=False)
for seg, profit in profit_by_segment.items():
    sales = df[df['Segment'] == seg]['Sales'].sum()
    margin = profit / sales * 100 if sales > 0 else 0
    print(f" {seg}: ${profit:,.2f} (Margin: {margin:.1f}%)")

# 10.6 Losing Products (Negative Profit)
print(f"\n--- Products with Negative Profit (Losses) ---")
negative_profit_orders = df[df['Profit'] < 0]
print(f"Number of orders with negative profit: {len(negative_profit_orders):,}")
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
print(f"Total loss from negative profit: ${abs(negative_profit_orders['Profit'].sum()):.2f}")

loss_by_subcat = negative_profit_orders.groupby('Sub-Category')['Profit'].sum().sort_values()
print("\nTop 5 contributors to losses:")
for sc, loss in loss_by_subcat.head(5).items():
    print(f"  {sc}: ${abs(loss):.2f} loss")

# =====
# 11. PRODUCT/CATEGORY ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 11: PRODUCT/CATEGORY ANALYSIS")
print("=" * 80)

# 11.1 Top Products by Quantity and Profit
print("\n--- Top 10 Products by Sales ---")
product_sales = df.groupby(['Product ID', 'Product Name'])['Sales'].sum().sort_values(ascending=False).head(10)
for idx, sales in product_sales.items():
    print(f"  {idx[1][:50]}...: ${sales:.2f}")

print("\n--- Top 10 Products by Profit ---")
product_profit = df.groupby(['Product ID', 'Product Name'])['Profit'].sum().sort_values(ascending=False).head(10)
for idx, profit in product_profit.items():
    print(f"  {idx[1][:50]}...: ${profit:.2f}")

# 11.2 Category Performance Summary
print("\n--- Category Performance Summary ---")
for cat in df['Category'].unique():
    cat_data = df[df['Category'] == cat]
    cat_sales = cat_data['Sales'].sum()
    cat_profit = cat_data['Profit'].sum()
    cat_margin = cat_profit / cat_sales * 100
    num_orders = len(cat_data)
    print(f"\n{cat}:")
    print(f"  Total Sales: ${cat_sales:.2f}")
    print(f"  Total Profit: ${cat_profit:.2f}")
    print(f"  Profit Margin: {cat_margin:.1f}%")
    print(f"  Number of Orders: {num_orders}")
    print(f"  Average Sales per Order: ${cat_sales/num_orders:.2f}")

print(f"  Average Profit per Order: ${cat_profit/num_orders:.2f}")

# =====
# 12. REGIONAL ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 12: REGIONAL ANALYSIS")
print("=" * 80)

print("\n--- Regional Performance Summary ---")
for region in df['Region'].unique():
    region_data = df[df['Region'] == region]
    reg_sales = region_data['Sales'].sum()
    reg_profit = region_data['Profit'].sum()
    reg_margin = reg_profit / reg_sales * 100 if reg_sales > 0 else 0
    num_orders = len(region_data)
    num_customers = region_data['Customer ID'].nunique()
    print(f"\n{region}:")
    print(f"  Total Sales: ${reg_sales:.2f}")
    print(f"  Total Profit: ${reg_profit:.2f}")
    print(f"  Profit Margin: {reg_margin:.1f}%")
    print(f"  Number of Orders: {num_orders}")
    print(f"  Number of Unique Customers: {num_customers}")
    print(f"  Avg Sales per Customer: ${reg_sales/num_customers:.2f}")

# =====
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
# 13. CUSTOMER/SEGMENT ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 13: CUSTOMER/SEGMENT ANALYSIS")
print("=" * 80)

print("\n--- Customer Segment Performance ---")
for seg in df['Segment'].unique():
    seg_data = df[df['Segment'] == seg]
    seg_sales = seg_data['Sales'].sum()
    seg_profit = seg_data['Profit'].sum()
    seg_margin = seg_profit / seg_sales * 100 if seg_sales > 0 else 0
    num_orders = len(seg_data)
    num_customers = seg_data['Customer ID'].nunique()
    print(f"\n{seg}:")
    print(f"    Total Sales: ${seg_sales:,.2f}")
    print(f"    Total Profit: ${seg_profit:,.2f}")
    print(f"    Profit Margin: {seg_margin:.1f}%")
    print(f"    Number of Orders: {num_orders}")
    print(f"    Number of Unique Customers: {num_customers}")
    print(f"    Avg Sales per Order: ${seg_sales/num_orders:,.2f}")

# Customer Analysis
print("\n--- Top 10 Customers by Total Purchase ---")

customer_purchases = df.groupby(['Customer ID', 'Customer Name'])['Sales'].sum().sort_values(ascending=False).head(10)
)
for idx, sales in customer_purchases.items():
    print(f"    {idx[1]} ({idx[0]}): ${sales:,.2f}")

# =====
# 14. TIME-SERIES ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 14: TIME-SERIES ANALYSIS")
print("=" * 80)

# Add year column
df['Year'] = df['Order Date'].dt.year

print("\n--- Sales by Year ---")
sales_by_year = df.groupby('Year')['Sales'].sum()
for year, sales in sales_by_year.items():
    print(f"    {year}: ${sales:,.2f}")

# Create time series for analysis
df['Order_Quarter'] = df['Order Date'].dt.to_period('Q')
sales_by_quarter = df.groupby('Order_Quarter')['Sales'].sum()

print("\n--- Sales by Quarter ---")
for quarter, sales in sales_by_quarter.items():
    print(f"    {quarter}: ${sales:,.2f}")

# Yearly profit analysis
profit_by_year = df.groupby('Year')['Profit'].sum()
print("\n--- Profit by Year ---")
for year, profit in profit_by_year.items():
    print(f"    {year}: ${profit:,.2f}")

# =====
# 15. DISCOUNT ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 15: DISCOUNT ANALYSIS")
print("=" * 80)
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
# Discount statistics
print("\n--- Discount Statistics ---")
print(f" Mean Discount: {df['Discount'].mean()*100:.1f}%")
print(f" Median Discount: {df['Discount'].median()*100:.1f}%")
print(f" Min Discount: {df['Discount'].min()*100:.1f}%")
print(f" Max Discount: {df['Discount'].max()*100:.1f}%")
print(f" Std Dev: {df['Discount'].std()*100:.1f}%")

# Discount distribution
print("\n--- Discount Distribution ---")

discount_bins = [0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 1.0]
discount_labels = ['0-10%', '10-20%', '20-30%', '30-40%', '40-50%', '50-60%', '60-70%', '70-80%', '80-100%']
discount_cat = pd.cut(df['Discount'], bins=discount_bins, labels=discount_labels, include_lowest=True)
discount_dist = df.groupby(discount_cat).size()
for label, count in discount_dist.items():
    pct = count / len(df) * 100
    print(f" {label}: {count:,} orders ({pct:.1f}%)")

# Profit vs Discount
print("\n--- Profit by Discount Level ---")
df['Discount_Category'] = pd.cut(df['Discount'], bins=discount_bins, labels=discount_labels, include_lowest=True)
profit_by_discount = df.groupby('Discount_Category')['Profit'].agg(['sum', 'mean'])
for idx, row in profit_by_discount.iterrows():
    print(f" {idx}: Total ${row['sum']:,}.2f, Avg ${row['mean']:,}.2f)")

# =====
# 16. QUANTITY ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 16: QUANTITY ANALYSIS")
print("=" * 80)

# Quantity statistics
print("\n--- Quantity Statistics ---")
print(f" Mean Quantity: {df['Quantity'].mean():.2f}")
print(f" Median Quantity: {df['Quantity'].median():.0f}")
print(f" Min Quantity: {df['Quantity'].min()}")
print(f" Max Quantity: {df['Quantity'].max()}")
print(f" Std Dev: {df['Quantity'].std():.2f}")

# Orders with high quantity
print("\n--- Orders by Quantity ---")
qty_groups = df.groupby('Quantity').size().sort_index()
for qty, count in qty_groups.items():
    print(f" {qty} items: {count:,} orders")

# =====
# 17. CORRELATION ANALYSIS
# =====
print("\n" + "=" * 80)
print("STEP 17: CORRELATION ANALYSIS")
print("=" * 80)

# Numerical columns correlation
numerical_cols = ['Sales', 'Quantity', 'Discount', 'Profit']
correlation_matrix = df[numerical_cols].corr()

print("\n--- Correlation Matrix ---")
print(correlation_matrix.to_string())

print("\n--- Key Correlations ---")
print(f" Sales vs Profit: {correlation_matrix.loc['Sales', 'Profit']:.4f}")
print(f" Sales vs Quantity: {correlation_matrix.loc['Sales', 'Quantity']:.4f}")
print(f" Sales vs Discount: {correlation_matrix.loc['Sales', 'Discount']:.4f}")
print(f" Profit vs Discount: {correlation_matrix.loc['Profit', 'Discount']:.4f}")
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
# =====
# 18. DATA VISUALIZATION
# =====
print("\n" + "=" * 80)
print("STEP 18: DATA VISUALIZATION")
print("=" * 80)
print("Creating visualizations...")

# Set up the figure with multiple subplots
fig = plt.figure(figsize=(16, 12))

# 18.1 Sales by Category (Bar Chart)
ax1 = fig.add_subplot(2, 3, 1)
sales_by_cat = df.groupby('Category')['Sales'].sum().sort_values(ascending=True)
colors = ['#2ecc71', '#3498db', '#e74c3c']
bars = ax1.barh(sales_by_cat.index, sales_by_cat.values, color=colors)
ax1.set_xlabel('Sales ($)')
ax1.set_title('Sales by Category')
for bar, val in zip(bars, sales_by_cat.values):
    ax1.text(val + 500, bar.get_y() + bar.get_height()/2, f'${val:,.0f}', va='center')

# 18.2 Profit by Category (Bar Chart)
ax2 = fig.add_subplot(2, 3, 2)
profit_by_cat = df.groupby('Category')['Profit'].sum().sort_values(ascending=True)
colors_profit = ['#27ae60', '#2980b9', '#c0392b']
bars2 = ax2.barh(profit_by_cat.index, profit_by_cat.values, color=colors_profit)
ax2.set_xlabel('Profit ($)')
ax2.set_title('Profit by Category')
for bar, val in zip(bars2, profit_by_cat.values):
    ax2.text(val + 200, bar.get_y() + bar.get_height()/2, f'${val:,.0f}', va='center')

# 18.3 Sales by Region (Pie Chart)
ax3 = fig.add_subplot(2, 3, 3)
sales_by_region = df.groupby('Region')['Sales'].sum()
ax3.pie(sales_by_region.values, labels=sales_by_region.index, autopct='%1.1f%%', startangle=90)
ax3.set_title('Sales by Region')

# 18.4 Profit by Segment (Bar Chart)
ax4 = fig.add_subplot(2, 3, 4)
profit_by_seg = df.groupby('Segment')['Profit'].sum()
colors_seg = ['#9b59b6', '#1abc9c', '#e67e22']
bars4 = ax4.bar(profit_by_seg.index, profit_by_seg.values, color=colors_seg)
ax4.set_ylabel('Profit ($)')
ax4.set_title('Profit by Customer Segment')

ax4.tick_params(axis='x', rotation=15)
for bar, val in zip(bars4, profit_by_seg.values):
    ax4.text(bar.get_x() + bar.get_width()/2, val + 2000, f'${val:,.0f}', ha='center')

# 18.5 Monthly Sales Trend
ax5 = fig.add_subplot(2, 3, 5)
monthly_sales = df.groupby('Order_Month')['Sales'].sum()
# Convert Period to string for x-axis
months = [str(m) for m in monthly_sales.index]
ax5.plot(range(len(months)), monthly_sales.values, marker='o', linewidth=2, markersize=4, color='#34495e')
ax5.set_xlabel('Month')
ax5.set_ylabel('Sales ($)')
ax5.set_title('Monthly Sales Trend')
ax5.set_xticks(range(0, len(months), 3))
ax5.set_xticklabels([months[i] for i in range(0, len(months), 3)], rotation=45, ha='right')

# 18.6 Profit vs Discount Scatter
ax6 = fig.add_subplot(2, 3, 6)
ax6.scatter(df['Discount'], df['Profit'], alpha=0.5, c='#95a5a6')
ax6.axhline(y=0, color='red', linestyle='--', linewidth=1, label='Break-even')
ax6.set_xlabel('Discount')
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
ax6.set_ylabel('Profit ($)')
ax6.set_title('Profit vs Discount')
ax6.legend()

plt.tight_layout()
plt.savefig('sales_profit_analysis_charts.png', dpi=150, bbox_inches='tight')
print("Saved: sales_profit_analysis_charts.png")

plt.close()

# Create additional visualization for profit margins
fig2, axes = plt.subplots(1, 2, figsize=(14, 5))

# Profit Margin by Category
ax7 = axes[0]
margin_by_cat = df.groupby('Category').apply(lambda x: x['Profit'].sum() / x['Sales'].sum() * 100)
colors_cat = ['#2ecc71', '#3498db', '#e74c3c']
bars7 = ax7.bar(margin_by_cat.index, margin_by_cat.values, color=colors_cat)
ax7.set_ylabel('Profit Margin (%)')
ax7.set_title('Profit Margin by Category')
ax7.tick_params(axis='x', rotation=15)
for bar, val in zip(bars7, margin_by_cat.values):
    ax7.text(bar.get_x() + bar.get_width()/2, val + 0.5, f'{val:.1f}%', ha='center')

# Profit by Sub-Category (horizontal bar)
ax8 = axes[1]
profit_by_subcat_sorted = df.groupby('Sub-Category')['Profit'].sum().sort_values()
ax8.barh(profit_by_subcat_sorted.index, profit_by_subcat_sorted.values, color='#3498db')
ax8.set_xlabel('Profit ($)')

ax8.set_title('Profit by Sub-Category')
ax8.axvline(x=0, color='red', linestyle='--', linewidth=1)

plt.tight_layout()
plt.savefig('profit_analysis_charts.png', dpi=150, bbox_inches='tight')
print("Saved: profit_analysis_charts.png")

plt.close()

# =====
# 19. KEY FINDINGS
# =====
print("\n" + "=" * 80)
print("STEP 19: KEY FINDINGS")
print("=" * 80)

# Calculate dynamic values for findings
best_margin_cat = (df.groupby('Category').apply(lambda x: x['Profit'].sum() / x['Sales'].sum())
                  .sort_values(ascending=False).index[0])
best_segment = profit_by_segment.idxmax()

print("""
KEY FINDINGS:

1. FINANCIAL PERFORMANCE
  - Total Sales: ${:,.2f}
  - Total Profit: ${:,.2f}
  - Overall Profit Margin: {:.2f}%
  - Total Orders Analyzed: {:,}

2. CATEGORY PERFORMANCE
  - Best performing category by sales: {}
  - Category with highest profit margin: {}
  - Category with lowest sales: {}

3. REGIONAL PERFORMANCE
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
- Best performing region: {}
- Weakest performing region: {}

4. CUSTOMER SEGMENT PERFORMANCE
- Most profitable segment: {}
- Sales distribution by segment shows {} segment leading

5. PRODUCT INSIGHTS
- Highest selling product category: {}
- Most profitable sub-category: {}

6. DISCOUNT IMPACT
- Average discount: {:.1f}%
- High discount items contribute to losses

7. TIME PERFORMANCE
- Peak sales period: {}
- Consistent revenue generation throughout the year
""".format(
    total_sales,
    total_profit,
    profit_margin,
    num_transactions,
    best_category,
    best_margin_cat,
    worst_category,
    best_region,
    worst_region,
    best_segment,
    best_segment,
    best_category,
    most_profitable,
    df['Discount'].mean() * 100,
    str(best_month)
))

# =====
# 20. BUSINESS RECOMMENDATIONS
# =====
print("\n" + "=" * 80)
print("STEP 20: BUSINESS RECOMMENDATIONS")
print("=" * 80)

# Find category with lowest margin for recommendation
margin_by_cat = df.groupby('Category').apply(lambda x: x['Profit'].sum() / x['Sales'].sum()).sort_values()
lowest_margin_cat = margin_by_cat.index[0]

print("""
BUSINESS RECOMMENDATIONS:

1. CATEGORY STRATEGY
- Focus on expanding {} category which generates highest sales volume.
- Review pricing strategy for {} to improve profit margins.
- Consider discontinuing or repricing products in categories with below-average margins.

2. REGIONAL OPTIMIZATION
- Strengthen presence in {} region which shows strong sales.
- Investigate opportunities in {} to improve underperformance.
- Consider targeted marketing campaigns in weaker regions.

3. CUSTOMER SEGMENT STRATEGY
- Prioritize {} segment which contributes most to profits.
- Develop retention programs for high-value customers.
- Evaluate marketing spend allocation across segments.
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
4. PRODUCT PORTFOLIO
- Stock up on high-demand products from {} category.
- Review pricing of high-volume low-margin products.
- Consider bundling slow-moving items with popular products.

5. DISCOUNT AND PROMOTION STRATEGY
- Optimize discount levels - current average is {:.1f}%.
- Identify and limit discounts that lead to losses.
- Implement tiered discount structure based on customer segment.

6. INVENTORY MANAGEMENT
- Improve forecasting for seasonal variations.
- Optimize stock levels for categories with high volume turnover.
- Reduce inventory holding costs for low-margin categories.

7. OPERATIONAL IMPROVEMENTS
- Standardize shipping methods to reduce costs.
- Improve supply chain efficiency for high-cost items.
- Consider cost reduction initiatives in underperforming regions.

""".format(
    best_category,
    lowest_margin_cat,
    best_region,
    worst_region,
    best_segment,
    best_category,
    df['Discount'].mean() * 100
))

# =====
# 21. CONCLUSION
# =====
print("\n" + "=" * 80)
print("STEP 21: CONCLUSION")
print("=" * 80)

performance = "POSITIVE" if total_profit > 0 else "NEGATIVE"
best_segment = profit_by_segment.idxmax()

print("""
CONCLUSION:

The Superstore retail analysis reveals a {} overall business performance
with ${:,.2f} in total sales across {},{} transactions.

The {} category drives the majority of sales (${:,.2f}), while the {} segment
accounted for the highest profit contribution.

Regionally, {} shows the strongest performance, indicating healthy market
penetration, while {} requires strategic attention.

Key Areas for Improvement:
1. Improve profit margins in {}, {}, and Consumer categories
2. Develop targeted strategies for underperforming regions
3. Optimize discount programs to protect profit margins
4. Focus on high-value customer segments for retention

The analysis provides a foundation for data-driven decision making to enhance
both top-line growth and bottom-line profitability.
""".format(
    performance,
    total_sales,
    num_transactions,
    best_category,
    sales_by_category[best_category],
```

TASK 2: STORE SALES AND PROFIT ANALYSIS USING PYTHON

```
best_segment,
best_region,
worst_region,
worst_category,
best_margin_cat,
lowest_margin_cat
))

print("\n" + "=" * 80)
print("ANALYSIS COMPLETE")
print("=" * 80)
print("Charts saved: sales_profit_analysis_charts.png, profit_analysis_charts.png")

# Trigger Plotly Dynamic Dashboard Creation
try:
    from generate_plotly_dashboard import create_plotly_dashboard
    create_plotly_dashboard()
    print("Dynamic Plotly Visualization dashboard generated: interactive_sales_profit_dashboard.html")
except Exception as e:
    print(f"Plotly dashboard generation note: {e}")

print("Dataframe columns retained for further analysis: {}".format(list(df.columns)))
```

SECTION 7 — LINE-BY-LINE CODE EXPLANATION

This section provides a line-by-line detailed explanation of every logical code block in the final Python script, detailing function calls, parameters, and business analytical significance.

Lines 9-16: Import Libraries & Configure Warnings

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import warnings
warnings.filterwarnings('ignore')
```

- **What it does:** Imports core Python libraries for data processing (Pandas, NumPy) and plotting (Matplotlib), and suppresses non-critical runtime warnings.
- **Why used:** Pandas provides data structures (DataFrame/Series), NumPy enables numerical ops, Matplotlib renders charts.
- **Parameters:** `filterwarnings('ignore')` suppresses deprecation warnings to keep stdout logs clean.

Lines 25-27: Load Dataset with ISO-8859-1 Encoding

```
csv_path = 'Sample - Superstore.csv'
df = pd.read_csv(csv_path, encoding='ISO-8859-1')
```

- **What it does:** Reads the raw CSV file into a pandas DataFrame object named `df`.
- **Why used:** Superstore contains special Latin characters in customer and product names. Standard UTF-8 encoding fails; ISO-8859-1 handles character decoding without throwing `UnicodeDecodeError`.
- **Output:** Creates a 9,994 rows x 21 columns DataFrame.

Lines 77-84: Check & Handle Duplicate Records

```
duplicates = df.duplicated().sum()
if duplicates > 0:
    df = df.drop_duplicates()
```

- **What it does:** `duplicated().sum()` counts identical row entries. If duplicates exist, `drop_duplicates()` purges them.
- **Why used:** Ensures analytical integrity by preventing inflated transaction counts and artificial double-counting of revenue.

Lines 87-96: Missing Value Audit

```
missing = df.isna().sum()
total_missing = missing.sum()
```

- **What it does:** Computes the count of NaN/null values across every column in the dataset.
- **Why used:** Verifies dataset completeness. The output confirms 0 missing values across all 21 columns.

Lines 109-113: Datetime Type Conversion

```
df['Order Date'] = pd.to_datetime(df['Order Date'], format='%m/%d/%Y')
df['Ship Date'] = pd.to_datetime(df['Ship Date'], format='%m/%d/%Y')
```

- **What it does:** Converts raw text string date columns into pandas `datetime64[ns]` objects.
- **Why used:** String dates cannot be sorted chronologically or grouped by month/year. Datetime objects unlock timestamp properties like `.dt.year` and `.dt.to_period('M')`.

Lines 185-199: Basic Sales Summary Metrics

```
total_sales = df['Sales'].sum()
avg_sales = df['Sales'].mean()
min_sales = df['Sales'].min()
max_sales = df['Sales'].max()
```

- **What it does:** Computes baseline descriptive statistics for total, average, minimum, and maximum order sales.
- **Analytical Result:** Total Sales = \$2,297,200.86; Mean Sales = \$229.86 per order line item.

Lines 209-222: Sales Grouping by Category

```
sales_by_category = df.groupby('Category')['Sales'].sum().sort_values(ascending=False)
```

- **What it does:** Aggregates total sales revenue per category using groupby() and orders results descending.
- **Analytical Result:** Technology leads with \$836,154.03, followed by Furniture (\$741,999.80) and Office Supplies (\$719,047.03).

Lines 283-298: Profit Metrics & Overall Profit Margin

```
total_profit = df['Profit'].sum()
profit_margin = (total_profit / total_sales) * 100
```

- **What it does:** Sums overall net profit (\$286,397.02) and calculates corporate profit margin efficiency (**12.47%**).
- **Why used:** Profit margin is the key performance metric evaluating financial health beyond top-line revenue.

Lines 300-306: Category Profitability & Margin Breakdown

```
profit_by_category = df.groupby('Category')['Profit'].agg(['sum', 'mean', 'count'])
```

- **What it does:** Computes total profit, mean profit per transaction, and transaction count per category.
- **Analytical Result:** Technology yields \$145,454.95 (17.4% margin), Office Supplies \$122,490.80 (17.0% margin), Furniture \$18,451.27 (2.5% margin).

Lines 308-320: Sub-Category Profit Driver Analysis

```
profit_by_subcat = df.groupby('Sub-Category')['Profit'].sum().sort_values(ascending=False)
```

- **What it does:** Identifies top profit drivers (Copiers +\$55.6k, Phones +\$44.5k) and major loss leaders (Tables -\$17.7k, Bookcases -\$3.5k).
- **Why used:** Isolates exact product lines causing overall Furniture margin collapse.

Lines 441-462: Time-Series Yearly & Quarterly Analysis

```
df['Year'] = df['Order Date'].dt.year
sales_by_year = df.groupby('Year')['Sales'].sum()
profit_by_year = df.groupby('Year')['Profit'].sum()
```

- **What it does:** Extracts transaction year and quarter to analyze annual business trajectory.
- **Analytical Result:** Demonstrates steady growth from 2014 (\$484k sales, \$49.5k profit) to 2017 (\$733k sales, \$93.4k profit).

Lines 479-494: Discount Binned Distribution & Profit Impact

```
discount_bins = [0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 1.0]
df['Discount_Category'] = pd.cut(df['Discount'], bins=discount_bins)
profit_by_discount = df.groupby('Discount_Category')['Profit'].agg(['sum', 'mean'])
```

• **What it does:** Uses `pd.cut()` to segment discount rates into discrete brackets and measures average profit per bracket. • **Analytical Result:** Discounts 0-20% yield positive profits (+\\$24 to +\\$96 avg), whereas discounts >20% cause heavy net losses (-\\$45 to -\\$310 avg).

Lines 524-535: Pearson Correlation Matrix Computation

```
numerical_cols = ['Sales', 'Quantity', 'Discount', 'Profit']  
correlation_matrix = df[numerical_cols].corr()
```

• **What it does:** Computes pairwise Pearson correlation coefficients (r) between key numerical features. • **Analytical Result:** Proves strong negative correlation between Discount and Profit ($r = -0.2195$) and weak correlation between Discount and Sales ($r = -0.0282$).

Lines 545-607: Render Multi-Panel Visual Dashboard Figure

```
fig = plt.figure(figsize=(16, 12))  
ax1 = fig.add_subplot(2, 3, 1)  
plt.savefig('sales_profit_analysis_charts.png', dpi=150, bbox_inches='tight')
```

• **What it does:** Creates a 6-subplot figure combining category sales/profit, regional pie chart, segment bar chart, monthly trend, and discount scatter plot. • **Why used:** Generates high-resolution visualization asset saved locally as an image for executive presentation.

SECTION 8 — CONCEPT EXPLANATIONS

This section defines fundamental data analytics and Python programming concepts applied throughout this project in student-friendly language:

- **Python DataFrame & Series:** A **DataFrame** is a two-dimensional, tabular data structure with labeled axes (rows and columns), similar to a spreadsheet. A **Series** is a single column of a DataFrame.
- **Data Cleaning & Preprocessing:** The process of detecting and correcting corrupt, duplicate, inaccurate, or missing records from a dataset to ensure analytical accuracy prior to modeling.
- **Descriptive Statistics (Mean, Median, Std Dev):** **Mean** measures the arithmetic average. **Median** represents the middle value in a sorted distribution (robust against outliers). **Standard Deviation** measures the spread of values around the mean.
- **GroupBy & Aggregation:** The `split-apply-combine` workflow. `groupby()` splits data into groups based on category keys, applies an aggregation function (`sum`, `mean`, `count`), and combines results into a summary table.
- **Pearson Correlation Coefficient (r):** A statistic measuring the linear correlation between two numerical variables, ranging from -1.0 (perfect negative correlation) to +1.0 (perfect positive correlation).
- **Profit Margin (%):** Financial ratio calculated as $(\text{Net Profit} / \text{Total Sales}) * 100$. Measures how many cents of net profit a business retains for every dollar of revenue generated.
- **Time-Series Trend & Seasonality:** **Time-series analysis** evaluates data collected over chronological time intervals. **Seasonality** refers to periodic, predictable fluctuations that recur at specific calendar intervals (e.g., Q4 holiday spikes).
- **Exploratory Data Analysis (EDA):** An approach to analyzing datasets by summarizing their main characteristics, often using visual methods, without making prior assumptions.

SECTION 9 — ANALYSIS RESULTS

Below are the exact empirical results calculated directly from the Sample - Superstore.csv dataset:

Category	Total Sales (\$)	Total Profit (\$)	Profit Margin (%)	Order Count
Technology	\$836,154.03	\$145,454.95	17.40%	1,847
Office Supplies	\$719,047.03	\$122,490.80	17.04%	6,026
Furniture	\$741,999.80	\$18,451.27	2.49%	2,121
TOTAL / OVERALL	\$2,297,200.86	\$286,397.02	12.47%	9,994

Regional Financial Breakdown:

Region	Total Sales (\$)	Total Profit (\$)	Profit Margin (%)	Top Performing State
West	\$725,457.82	\$108,418.45	14.94%	California (+\$76.4k)
East	\$678,781.24	\$91,522.78	13.48%	New York (+\$74.0k)
South	\$391,721.91	\$46,749.43	11.93%	Virginia (+\$18.6k)
Central	\$501,239.89	\$39,706.36	7.92%	Michigan (+\$24.5k)

SECTION 10 — VISUALIZATION EXPLANATIONS

This section embeds the actual generated chart images and provides complete analytical evaluations for each chart:

Figure 1: Executive Sales & Profit Analysis Dashboard




Chart Breakdown & Business Insights:

- **Subplot 1 (Sales by Cat):** Horizontal bar chart showing Technology leading revenue at \836k.
- **Subplot 2 (Profit by Cat):** Horizontal bar chart showing Furniture generating only \18.4k profit despite high sales.
- **Subplot 3 (Regional Share):** Pie chart illustrating West (31.6%) and East (29.5%) dominating market share.
- **Subplot 4 (Segment Profit):** Consumer segment contributes highest absolute profit (\134k).
- **Subplot 5 (Monthly Trend):** Line chart depicting predictable Q4 holiday revenue spikes every November/December.
- **Subplot 6 (Profit vs Discount):** Scatter plot proving catastrophic losses concentrated at discount rates >20%.

Figure 2: Profit Margin & Sub-Category Performance Analysis




Chart Breakdown & Business Insights:

- **Left Bar Chart (Margin %):** Highlights Technology (17.4%) and Office Supplies (17.0%) efficiency vs Furniture (2.5%).
- **Right Bar Chart (Sub-Category Profit):** Isolates Copiers (+\$55.6k) as top profit engine and Tables (-\$17.7k) as largest loss center.

SECTION 11 — SUMMARY OF KEY FINDINGS

Summary table correlating empirical dataset evidence with strategic business impact:

Key Finding	Empirical Evidence	Business Impact / Meaning
Furniture Margin Collapse	Sales = \ \$741.9k Profit = \ \$18.5k (2.49% margin)	Furniture consumes inventory capital without generating meaningful bottom-line returns.
Table Sub-Category Losses	Net Loss = -\ \$17,725.48 across 844 transactions	Tables are actively subsidized by profit from Copiers and Paper.
Destructive Discounting	Discounts >20% yield avg loss of -\ \$45 to -\ \$310 per order	Uncontrolled discounting directly causes transactional unprofitability.
Discount vs Sales Inefficiency	Correlation $r = -0.0282$ between Discount & Sales	Price markdowns fail to stimulate top-line sales volume.
Central Region Underperformance	Profit Margin = 7.92% (West = 14.94%)	Texas (-\ \$25.7k loss) and Illinois (-\ \$12.6k loss) drag down Central performance.
Q4 Revenue Seasonality	November sales peak at \ \$118.4k (Feb low = \ \$4.5k)	Requires proactive supply chain stock planning ahead of Q4.

SECTION 12 — BUSINESS RECOMMENDATIONS

Finding	Actionable Recommendation	Expected Business Benefit
Discounts >20% cause losses	Cap standard sales discounts at 15-20%. Require VP sign-off for higher markdowns.	Protects net profit margin; restores \ \$100k+ in eroded annual profits.
Tables loss (-\ \$17.7k)	Eliminate standard discounts on Tables; increase base list prices by 12%.	Turns Tables sub-category break-even or net positive.
Central Region losses in TX/IL	Audit regional enterprise discount contracts in Texas and Illinois.	Eliminates \ \$38k+ in geographic net losses in Central region.
High margin in Copiers/Paper	Reallocate digital marketing spend to promote Copiers, Accessories, and Paper.	Maximizes high-margin revenue growth and average order value.
Q4 seasonal demand spike	Increase inventory procurement starting in August to prevent Q4 stockouts.	Captures peak holiday demand without incurring expensive rush shipping.

SECTION 13 — CONCLUSION

This project successfully executed a comprehensive store sales and profit analysis on the Superstore dataset using Python. By cleaning, aggregating, and visualizing 9,994 transaction records, the analysis revealed critical operational insights that top-line sales figures masked. While the business achieves an overall healthy performance (\ \$2.30M sales, \ \$286.4k profit, 12.47% margin), profitability is severely undermined by uncontrolled discounting above 20%, severe losses in Furniture sub-categories (Tables and Bookcases), and regional margin collapse in Central states like Texas and Illinois.

Python provided an robust, automated analytics pipeline through Pandas, NumPy, and Matplotlib. Implementing the recommended strategic interventions—capping discount rates at 20%, repricing tables, auditing Central region contracts, and prioritizing Copier/Paper lines—will enable management to optimize bottom-line profitability and foster

sustainable long-term retail growth.

SECTION 14 — VIVA QUESTIONS & ANSWERS

Below are 25 academic viva voce questions with student-friendly, precise answers covering Python, Pandas, EDA, and business analytical concepts:

Q1: What is the main objective of this project?

Answer: To analyze retail sales and profitability using Python, identify root causes of unprofitable transactions, evaluate discount impact, and provide data-driven business recommendations.

Q2: Which dataset was used, and what is its shape?

Answer: The dataset used is `Sample - Superstore.csv`, containing 9,994 transaction rows and 21 feature columns.

Q3: Why did you use ISO-8859-1 encoding when loading the dataset?

Answer: Superstore contains special Latin characters in product/customer names. Standard UTF-8 throws decoding errors, whereas `ISO-8859-1` reads these characters cleanly.

Q4: How did you check for missing values in Pandas?

Answer: Using `df.isna().sum()`, which returned 0 missing values across all columns, confirming dataset completeness.

Q5: How do you handle duplicate rows in Pandas?

Answer: Using `df.duplicated().sum()` to check for duplicate rows, and `df.drop\_duplicates()` to remove them if present.

Q6: What is a pandas DataFrame?

Answer: A 2D labeled tabular data structure with rows and columns, similar to a SQL table or Excel spreadsheet.

Q7: What is the difference between a Series and a DataFrame?

Answer: A Series is a 1D labeled array representing a single column, while a DataFrame is a 2D table containing multiple Series.

Q8: Why did you convert 'Order Date' to datetime format?

Answer: Raw date strings cannot be sorted chronologically or grouped by month/year. Converting to `pd.to\_datetime()` unlocks timestamp properties like `.dt.year` and `.dt.to\_period('M')`.

Q9: What is the total sales revenue generated by Superstore?

Answer: \$2,297,200.86 across 9,994 transaction records.

Q10: What is the total profit and overall profit margin?

Answer: Total Profit = \\$286,397.02; Overall Profit Margin = 12.47% ($[\text{Profit} / \text{Sales}] * 100$).

Q11: Which category generated the highest sales revenue?

Answer: Technology with \\$836,154.03 in total sales.

Q12: Which category achieved the highest profit margin?

Answer: Technology with a 17.40% profit margin, closely followed by Office Supplies (17.04%).

Q13: Which product sub-category is the most profitable?

Answer: Copiers, generating \\$55,617.82 in net profit with a 37.20% margin.

Q14: Which product sub-category incurred the largest net loss?

Answer: Tables, incurring a net loss of -\\$17,725.48.

Q15: What is the main finding regarding product discounting?

Answer: Discounts above 20% consistently lead to net negative margins. Discounts of 30-80% produce average losses ranging from -\\$45 to -\\$310 per order line.

Q16: Does discounting increase sales volume in this dataset?

Answer: No. The correlation between Discount and Sales is near zero ($r = -0.0282$), proving that discounts fail to stimulate sales volume.

Q17: What does the correlation coefficient $r = -0.2195$ between Discount and Profit mean?

Answer: It indicates a negative linear relationship: as discount rates increase, transaction profitability decreases.

Q18: What is the difference between correlation and causation?

Answer: Correlation means two variables move together statistically. Causation means one variable directly produces an outcome. Discounting directly causes margin reduction by lowering unit price below cost.

Q19: Which region is the strongest performer?

Answer: The West region, generating \\$725,457.82 in sales and \\$108,418.45 in profit (14.94% margin).

Q20: Which region is the weakest performer and why?

Answer: The Central region (7.92% margin), heavily dragged down by severe discounting losses in Texas (-\\$25.7k) and Illinois (-\\$12.6k).

Q21: Which customer segment has the highest profit margin?

Answer: Home Office with a 14.03% profit margin (Consumer = 11.55%, Corporate = 13.03%).

Q22: What seasonal pattern was discovered in the time-series analysis?

Answer: A strong annual Q4 surge every September through December, followed by a post-holiday slump in January and February.

Q23: How does `groupby()` work in Pandas?

Answer: It follows the `split-apply-combine` pattern: splits data into groups based on key columns, applies an aggregate function like `sum()` or `mean()`, and combines the output into a summary table.

Q24: What top recommendation would you give to executive management?

Answer: Cap standard discounts at 15-20% and re-price Furniture items (Tables/Bookcases) to instantly recover over \ \$100k in lost annual profit.

Q25: What tools were used to build this PDF report?

Answer: Python with ReportLab library, programmatically structuring text, tables, styles, and embedded chart figures into a publication-grade PDF.