

■ React Hooks — Quick Classroom Guide

useState + useEffect + Popular Hooks • Short, colourful & easy to explain

■ 1. useState — Remember a Value

useState stores data that can change inside a React component.

```
const [count, setCount] = useState(0);
```

Part	Simple meaning
count	Current value ■
setCount	Function to change the value ■
0	Default / starting value ■■

Example: **setCount(count + 1)** → count changes → React renders again.

■ 2. useEffect — Run Code After Render

useEffect is used to run some code **after the component renders**.

Examples: API call, console.log, timer, document title, etc.

■ Only remember these 3 ways:

Code	When?	TRICK
<code>useEffect(() => { ... });</code>	Every render	■ No [] → EVERY TIME
<code>useEffect(() => { ... }, []);</code>	First render only	■ [] → ONCE
<code>useEffect(() => { ... }, [count]);</code>	When count changes	■ [count] → WATCH count

Super trick: NO [] = Every time | [] = Once | [count] = When count changes

■ 3. Popular React Hooks — Very Short Intro

Hook	Use it for	Easy meaning
useState	Store changing data	Remember a value ■
useEffect	Run code after render	Do something after render ■
useContext	Share data	Share data without passing props ■
useRef	Keep a value / access DOM	Remember without re-render ■
useMemo	Optimize calculations	Remember a calculated result ■
useCallback	Optimize functions	Remember a function ■

■ Easy Hook Memory

- **useState** → Store value
- **useEffect** → Run code after render
- **useContext** → Share data
- **useRef** → Remember/access DOM
- **useMemo** → Remember calculation
- **useCallback** → Remember function

■ Classroom One-Liner

Hook = a special React function that gives a component extra abilities.

For beginners, first learn **useState** and **useEffect**. Then move to the other hooks.