

```
let arr = [10, 20, 30, 40, 50];
```

Method	Function (Purpose)	Syntax	No. of Arguments	Argument Data Type	Example	Result
push()	Adds element(s) at the end of the array	array.push(item1, item2...)	1 or more	Any	arr.push(60)	[10,20,30,40, 50,60]
pop()	Removes the last element	array.pop()	0	None	arr.pop()	Returns 50, array becomes [10,20,30,40]
shift()	Removes the first element	array.shift()	0	None	arr.shift()	Returns 10, array becomes [20,30,40,50]
unshift()	Adds element(s) at the beginning	array.unshift(item1, item2...)	1 or more	Any	arr.unshift(5)	[5,10,20,30,4 0,50]
splice()	Adds, removes, or replaces elements	array.splice(start, deleteCount, items...)	2 or more	Number, Number, Any	arr.splice(2,1,25)	[10,20,25,40, 50]
slice()	Extracts a portion of an array	array.slice(start,end)	1 or 2	Number	arr.slice(1,4)	Returns [20,30,40]
sort()	Sorts array elements	array.sort(compareFn)	0 or 1	Function	[40,10,50,20].sort((a,b)=>a-b)	[10,20,40,50]
reverse()	Reverses the array order	array.reverse()	0	None	arr.reverse()	[50,40,30,20, 10]
concat()	Combines arrays	array.concat(array2)	1 or more	Array/Any	arr.concat([60,70])	[10,20,30,40, 50,60,70]
indexOf()	Finds first index of an element	array.indexOf(value)	1 or 2	Any	arr.indexOf(30)	2
lastIndexOf()	Finds last index of an element	array.lastIndexOf(value)	1 or 2	Any	[10,20,30,20].lastIndexOf(20)	3
includes()	Checks whether an element exists	array.includes(value)	1 or 2	Any	arr.includes(40)	true

join()	Converts array into a string	array.join(separator)	0 or 1	String	arr.join("-")	"10-20-30-40-50"
toString()	Converts array to comma-separated string	array.toString()	0	None	arr.toString()	"10,20,30,40,50"
find()	Returns first element matching condition	array.find(callback)	1	Function	arr.find(x=>x>25)	30
findIndex()	Returns index of first matching element	array.findIndex(callback)	1	Function	arr.findIndex(x=>x>25)	2
filter()	Returns elements matching condition	array.filter(callback)	1	Function	arr.filter(x=>x>25)	[30,40,50]
map()	Creates new array after transformation	array.map(callback)	1	Function	arr.map(x=>x*2)	[20,40,60,80,100]
forEach()	Executes a function for each element	array.forEach(callback)	1	Function	arr.forEach(x=>console.log(x))	Prints all elements
reduce()	Reduces array to a single value	array.reduce(callback, initialValue)	1 or 2	Function, Any	arr.reduce((a,b)=>a+b,0)	150
some()	Checks if at least one element satisfies condition	array.some(callback)	1	Function	arr.some(x=>x>45)	true
every()	Checks if all elements satisfy condition	array.every(callback)	1	Function	arr.every(x=>x>5)	true
fill()	Fills array with a	array.fill(value,start, end)	1 to 3	Any, Number	arr.fill(0,1,3)	[10,0,0,40,50]

	specified value					
copyWithin()	Copies part of array to another position	array.copyWithin(target,start,end)	2 or 3	Number	[10,20,30,40,50].copyWithin(0,3)	[40,50,30,40,50]