Advanced Programming Practice · 21CSC203P

Unit 5 · Session 10 · SLO 2 — Solved Worksheet

Name: R L KRISHE YADAV R L KRISHE YADAV | **Reg. No:** RA2511030010473

Unit â€“ 5 : Session â€“ 10 : SLO â€“ 2 | Integrating Backend Logic with Event Responses

I. Questions & Answers

1. Example of backend logic â€” a function that computes a result without touching the GUI, e.g. def add(a, b): return a + b, or a database query / file-processing routine.

2. Showing results on a label â€” the event handler calls the backend function and updates the widget: result_label.config(text=str(add(2, 3))) â€” the label refreshes immediately on screen.

3. Why integrate logic with events â€ so user actions drive real computation: the interface stays responsive and each interaction (click, input) produces meaningful output, separating presentation (GUI) from computation (backend) for cleaner, testable code.

II. Mini Example

- import tkinter as tk
- def compute():
- lbl.config(text=f"Sum = {int(e1.get()) + int(e2.get())}")
- root = tk.Tk()
- e1, e2 = tk.Entry(root), tk.Entry(root)
- e1.pack(); e2.pack()
- tk.Button(root, text="Add", command=compute).pack()
- lbl = tk.Label(root, text="Sum = ?"); lbl.pack()
- root.mainloop()