JIRA STORY / AUTHENTICATION

Test Plan: KAN-4

Add Passkey and SSO Login Options to VWO Login Page

DRAFT - PENDING HUMAN REVIEW

ISSUE	TYPE / PRIORITY	VERSION / PREPARED	COMPONENTS
KAN-4	Story / High	2.0 / 2026-10-30	Not provided

Ticket metadata: Labels, fix versions, linked issues, and attachments were not returned for this Jira issue. Company details beyond the Nagarro logo were not available in the provided company-details file.

Version 2 update: Incorporates author feedback. Best-practice criteria below are proposals for review, not confirmed product requirements.

1. Scope & Objectives

Purpose: Assess the change that adds SSO and passkey sign-in choices to the existing VWO login page.

Objective: Verify placement and behavior of both options, successful and unsuccessful authentication, passkey availability and device support, safe handling of authentication data, and regressions to existing login options.

Scope of testing: The login-page options and authentication journeys described in KAN-4, including UI visibility, SSO, passkey, error handling, compatibility, security, and the ticket's stated staging Definition of Done.

In scope:

- Both new buttons appear below "Sign in with Google".
- Successful and failed SSO authentication, including configured identity providers.
- Successful passkey authentication, no registered passkey, verification failure, and unsupported browser/device behavior.
- Responsive presentation, accessibility checks, security protocol use, and exposure of sensitive data in UI or network logs.
- Regression smoke checks for existing login methods on the same page.

Out of scope: Passkey registration and SSO provider configuration, both explicitly excluded by the story.

Deliverables: This draft test plan and, after review, execution evidence and defect records linked to KAN-4.

2. Gaps & Questions for the Author

Checklist status reflects the ticket as fetched and author feedback. Items the author marked "Ignore" are omitted from follow-up. Best-practice proposals remain subject to author confirmation.

Checklist area	Status	Finding / question for author
Clear user story / goal	**PRESENT**	Story states the user goal: secure, convenient sign-in using SSO or passkey.
Testable acceptance criteria	**PARTIAL**	**Proposed oracle:** each login option is visible in the specified position; successful authentication establishes a valid session and reaches the dashboard; rejected or incomplete authentication creates no session; redirect targets are restricted to the dashboard or an approved internal return URL. Exercise every configured SSO provider and every platform in the approved support matrix. Confirm the redirect rule and the provider/platform matrix before sign-off.
Happy path	**PRESENT**	Successful SSO and verified registered-passkey login should reach the dashboard.
State transitions	**PARTIAL**	**Proposed oracle:** cancellation, timeout, or interrupted authentication returns to a safe login state without creating a session; retry starts a fresh authentication transaction; browser Back or a repeated callback cannot reuse a stale transaction or expose authenticated content. Confirm the intended user-visible result for each transition.
Preconditions / setup	**PARTIAL**	Staging accounts and authentication fixtures are required. How will account states, SSO provider state, and registered/no-passkey fixtures be provisioned, reset, and owned?
Performance / load	**MISSING**	**Proposed oracle:** set numeric latency and load targets before sign-off; measure application-side initiation/verification separately from external identity-provider time, report p50/p95/p99 and error rate, and exercise an agreed normal/peak concurrency profile. Confirm thresholds, measurement boundaries, and load profile; no numbers were supplied.
Audit / logging	**PARTIAL**	**Proposed minimum:** record timestamped, correlation-ID-linked authentication start/completion/failure, method/provider, outcome, and normalized failure category in access-controlled audit logs. Exclude credentials, tokens, authorization codes, passkey challenges/responses, session identifiers, and unnecessary personal data. Confirm log destination, fields, access, and retention.
Backward compatibility / migration	**PARTIAL**	**Proposed oracle:** existing accounts remain correctly associated and can use existing supported sign-in paths after rollout; no unintended account duplication, lockout, or forced passkey re-registration occurs. Confirm any account migration, enrollment, and session-impact behavior.
Browser / device matrix	**PARTIAL**	**Proposed coverage:** use the product-supported browser/OS matrix; include the latest stable and previous major version of each supported browser, supported desktop/mobile operating systems, and platform authenticators. Include roaming security keys only if supported. Confirm the exact matrix and supported authenticator types.

3. Test Scenarios

Priorities are proposed risk-based priorities, not values assigned by the ticket. Scenario IDs below map directly to the ticket criteria or explicitly identified gaps.

ID	Priority	Type	Scenario	Maps to
TS-01	P1	Positive / UI	Open the login page and verify both new buttons are visible, correctly labeled, and positioned below "Sign in with Google".	AC: UI Visibility
TS-02	P0	Positive / E2E	For each configured SSO provider, sign in with valid test credentials; verify successful authentication and arrival at the dashboard.	AC: SSO Login Flow; Compatibility
TS-03	P1	Negative	Attempt authentication with rejected credentials or a failed verification; verify no session is created and feedback does not reveal whether an account exists or expose authentication data.	AC: SSO / Passkey Login Flow; security best practice

ID	Priority	Type	Scenario	Maps to
TS-04	P0	Positive / E2E	On each platform in the confirmed support matrix, sign in with a registered and successfully verified passkey; verify a valid session is established and the user reaches the dashboard.	AC: Passkey Login Flow; proposed compatibility matrix
TS-05	P1	Boundary / Empty	Attempt passkey sign-in for an account with no registered passkey; verify the specified fallback or guidance appears and no session is created.	AC: Passkey Login Flow
TS-06	P1	Negative / State transition	Cancel or time out an authentication attempt, retry, use browser Back, and replay an interrupted callback; verify safe return to login, a fresh transaction on retry, no stale callback acceptance, and no authenticated session before success.	AC: State transitions; proposed best-practice oracle
TS-07	P1	Negative / Compatibility	Test each confirmed browser/OS/authenticator combination, plus one unsupported combination; verify supported combinations complete passkey login and unsupported ones fail safely without trapping the user.	AC: Compatibility; proposed browser/device matrix
TS-08	P0	Security / Audit	Verify success and failure events are correlated and contain only approved fields in the designated audit logs; confirm credentials, tokens, codes, passkey challenge/response data, session identifiers, and unnecessary personal data are absent from logs, UI, and URLs.	AC: Security; proposed audit/logging policy
TS-09	P1	Regression	Verify existing Google and email/password sign-in remain available and their successful and failed flows are not regressed by the new options.	Ticket: options added alongside existing methods; Gap: regression scope
TS-10	P1	Positive / UI	Check layout at viewport sizes in the confirmed device matrix; verify both options remain readable and operable without obscuring existing controls.	Ticket test scenario: responsiveness; proposed device matrix
TS-11	P1	Accessibility	Keyboard-navigate to and activate both buttons; verify accessible names, focus visibility, and screen-reader announcements against the agreed accessibility target.	Ticket test scenario: accessibility; Gap: conformance target
TS-12	P1	Performance	Measure login-page initiation and application-side authentication processing separately from identity-provider response time; report p50/p95/p99 latency and error rate under the agreed normal and peak load profile.	Gap: performance/load; proposed measurement approach
TS-13	P1	Compatibility / Migration	Using existing accounts created before rollout, verify identity association and existing login paths remain intact; check for unintended duplication, lockout, or forced passkey re-registration.	Gap: backward compatibility/migration; proposed oracle

4. Test Data & Environment

- **Environment:** Staging is specified by the Definition of Done; URL, build, and feature-flag state must be supplied by the team.
- **Data:** Dedicated SSO identities for each configured provider; a valid account with a registered passkey; an account without a registered passkey; invalid-credential and failed-verification conditions.
- **Platforms:** Product-approved browser/device matrix, including relevant operating systems and supported platform or roaming authenticators.
- **Roles / permissions:** KAN-4 does not define roles or permission differences. Author confirmation is required before role-specific coverage is added.

- **Handling:** Use non-production accounts and synthetic test identities. Never place secrets or real user credentials in screenshots, logs, or defect reports.

5. Risks & Assumptions

Assumptions made: The dashboard is the expected destination for successful sign-in; staging is the execution environment because it is named in DoD; existing Google and email/password methods remain in scope for regression; the proposed redirect, state-transition, logging, performance, migration, and compatibility oracles are recommendations pending author confirmation.

Risks: Until the proposed browser/device matrix, performance thresholds, audit policy, account migration behavior, and fixture setup are confirmed, execution may not cover all release risks. Authentication defects can create account-access or sensitive-data exposure risks.

6. Entry / Exit Criteria

Entry: KAN-4 implementation is deployed to the agreed staging build; fixtures are provisioned; the provider/browser matrix and proposed authentication oracles are confirmed; performance targets and audit-log access are agreed.

Exit: All agreed scenarios have recorded results; ticket acceptance criteria pass or have linked defects; agreed performance targets and audit checks are reported; no open critical/high defects remain per DoD; deviations and blocked tests are documented; QA owner completes sign-off.

7. Test Strategy

- **Testing levels:** UI verification, authentication integration checks, end-to-end system acceptance, browser/device compatibility, accessibility, and focused security validation.
- **System acceptance:** Both options are presented in the required order; successful supported flows establish a valid session and reach the dashboard; failed or interrupted flows do not establish a session; redirect destinations follow the approved policy.
- **Team composition:** QA owner, login/authentication implementation owner, and SSO/identity-provider contact for configuration and test-account support.

8. Test Approach

- **Test design:** Requirement-based scenarios mapped to the ticket's UI, SSO, passkey, state-transition, compatibility, and security criteria; apply proposed performance, audit, and migration oracles after author confirmation.
- **Test data strategy:** Isolated staging identities and controlled account states; use provider-approved test credentials and registered test authenticators only.
- **Test data management:** Keep credentials in approved secret storage; reset or clean up test sessions after execution; redact tokens and personal data from evidence.

9. Bug Tracking Process

- **Tool:** Jira, with defects linked to KAN-4 (confirm project workflow and issue type).
- **Priority / severity:** Assign using the team's Jira definitions. Treat inability to authenticate or a security exposure as release-blocking candidates pending triage; do not infer the team's exact scale.

- **Reporting:** Include build, environment, browser/device, test identity state, steps, expected vs. actual result, and sanitized evidence. Never attach credentials, tokens, or unredacted sensitive logs.

10. Assumptions and Dependencies

- **Assumptions:** Successful authentication ends at the dashboard; KAN-4 does not include passkey registration or SSO provider setup; the supplied ticket description and acceptance criteria are the source of truth.
- **Dependencies:** Staging deployment; configured SSO providers; identity-provider test accounts; passkey-capable devices and authenticators; agreed browser/device support list; approved security and accessibility criteria.

Human Review Gate

I assumed: The staging environment is the target, successful login redirects to the dashboard, and existing login methods should continue to work. All best-practice criteria are proposals, not ticket-approved requirements.

I could not confirm: Redirect allowlist policy; exact state-transition outcomes; staging fixture provisioning; performance thresholds and load profile; audit-log destination, access, and retention; account migration behavior; and the supported browser/OS/authenticator matrix. Components, labels, fix versions, links, and attachments were not returned in the Jira response. Questions marked "Ignore" by the author were removed from this draft's follow-up list.

Open questions blocking sign-off: Confirm the proposed acceptance oracles and redirect policy; state-transition behavior; staging fixture provisioning; performance targets/load profile; audit event fields and retention/access policy; existing-account migration expectations; and the supported browser/device/authenticator matrix.

Approve or edit this draft before proceeding. No test cases or automation are included or authorized by this draft.