nagarro

Quality Engineering
Test Planning

JIRA STORY / AUTHENTICATION

Test Plan: KAN-4

Add Passkey and SSO Login Options to VWO Login Page

DRAFT - PENDING HUMAN REVIEW

ISSUE	TYPE / PRIORITY	PREPARED	COMPONENTS
KAN-4	Story / High	2026-10-28	Not provided

Ticket metadata: Labels, fix versions, linked issues, and attachments were not returned for this Jira issue. Company details beyond the Nagarro logo were not available in the provided company-details file.

1. Scope & Objectives

Purpose: Assess the change that adds SSO and passkey sign-in choices to the existing VWO login page.

Objective: Verify placement and behavior of both options, successful and unsuccessful authentication, passkey availability and device support, safe handling of authentication data, and regressions to existing login options.

Scope of testing: The login-page options and authentication journeys described in KAN-4, including UI visibility, SSO, passkey, error handling, compatibility, security, and the ticket's stated staging Definition of Done.

In scope:

- Both new buttons appear below "Sign in with Google".
- Successful and failed SSO authentication, including configured identity providers.
- Successful passkey authentication, no registered passkey, verification failure, and unsupported browser/device behavior.
- Responsive presentation, accessibility checks, security protocol use, and exposure of sensitive data in UI or network logs.
- Regression smoke checks for existing login methods on the same page.

Out of scope: Passkey registration and SSO provider configuration, both explicitly excluded by the story.

Deliverables: This draft test plan and, after review, execution evidence and defect records linked to KAN-4.

2. Gaps & Questions for the Author

Checklist status reflects the ticket as fetched. Every partial or missing item below needs clarification or an agreed test oracle before sign-off.

Checklist area	Status	Finding / question for author
Clear user story / goal	**PRESENT**	Story states the user goal: secure, convenient sign-in using SSO or passkey.

Checklist area	Status	Finding / question for author
Testable acceptance criteria	**PARTIAL**	Core outcomes are observable, but exact error text, redirect destination behavior, and supported-provider/browser sets are unspecified. What are the pass/fail oracles?
Happy path	**PRESENT**	Successful SSO and verified registered-passkey login should reach the dashboard.
Negative / error paths	**PARTIAL**	Failure types are named, but expected messages, retry behavior, and recovery paths are not. What should the user see and be able to do after each failure?
Boundary & empty states	**PARTIAL**	No-passkey is covered; empty/expired SSO state, cancellation, timeout, repeated attempts, and rate-limit behavior are not specified. Which are in scope?
State transitions	**PARTIAL**	Click, authentication, and dashboard outcomes are stated. Expected behavior for cancel, retry, back navigation, and interrupted redirects is unclear.
Test data	**MISSING**	Provide staging accounts, SSO test identities for each configured provider, and passkey-registered / no-passkey accounts.
Environment / flags	**PARTIAL**	Staging is named in DoD, but the environment URL, feature flags, and configuration are not. Which build and flags should QA use?
External dependencies	**PARTIAL**	SSO providers and passkey-capable platform support are dependencies, but providers and service owners are not identified. Which IdPs are configured?
Preconditions / setup	**PARTIAL**	Valid SSO credentials and an available registered passkey are referenced. How are accounts, provider state, and passkey fixtures provisioned in staging?
Performance / load	**MISSING**	No authentication latency or load expectation is specified. Are response-time or concurrency targets required?
Security / authorization	**PARTIAL**	Secure protocols and no sensitive-data exposure are required. Which OAuth/SAML/WebAuthn flows, session controls, and user/role permissions must be verified?
Accessibility	**PARTIAL**	Accessibility is named in the test-scenario list, but no standard or acceptance criteria are given. Which conformance target applies?
Internationalization	**MISSING**	No supported locales, translations, or text-expansion requirements are stated. Is localization in scope?
Audit / logging	**PARTIAL**	Secrets must not appear in UI or network logs, but audit events and safe diagnostic logging are not defined. What should be logged, and where?
Existing-feature impact	**PARTIAL**	New methods are added alongside existing methods, but regression coverage is not explicit. Confirm Google and email/password login remain unchanged.
Backward compatibility / migration	**PARTIAL**	No migration is described. Confirm whether older supported browsers or existing accounts need compatibility coverage.
Browser / device matrix	**PARTIAL**	"Supported browsers/devices" is not enumerated. Provide the required browser, OS, and authenticator matrix.
Rollback / feature flag	**MISSING**	No disable/rollback behavior is described. Is a feature flag used, and what should users see when it is off?
Unambiguous wording	**PARTIAL**	"Appropriate error messages", "smooth", "supported", and "all configured" need defined expected behavior and lists.
Defined terminology	**PARTIAL**	SSO, provider, passkey availability, and verification are used without provider or protocol-specific details. Confirm intended flows.
Design / mockup	**MISSING**	No design attachment was returned. Provide the approved login-page design or confirm the current page is the source of truth.

3. Test Scenarios

Nagarro | KAN-4 | Draft for human review | Prepared 2026-10-28

Priorities are proposed risk-based priorities, not values assigned by the ticket. Scenario IDs below map directly to the ticket criteria or explicitly identified gaps.

ID	Priority	Type	Scenario	Maps to
TS-01	P1	Positive / UI	Open the login page and verify both new buttons are visible, correctly labeled, and positioned below "Sign in with Google".	AC: UI Visibility
TS-02	P0	Positive / E2E	For each configured SSO provider, sign in with valid test credentials; verify successful authentication and arrival at the dashboard.	AC: SSO Login Flow; Compatibility
TS-03	P1	Negative	Attempt SSO with invalid credentials; verify authentication is rejected, the agreed error is displayed, and no authenticated session is created.	AC: SSO Login Flow; Error Handling; Gap: error oracle
TS-04	P0	Positive / E2E	On each agreed supported browser/device, sign in with a registered and successfully verified passkey; verify the user reaches the dashboard.	AC: Passkey Login Flow; Compatibility
TS-05	P1	Boundary / Empty	Attempt passkey sign-in for an account with no registered passkey; verify the specified fallback or guidance appears and no session is created.	AC: Passkey Login Flow
TS-06	P1	Negative	Make passkey verification fail or cancel it; verify the agreed failure message and recovery behavior, without falsely authenticating the user.	AC: Error Handling; Gap: cancellation/retry behavior
TS-07	P1	Negative / Compatibility	Use a browser/device outside the confirmed passkey support matrix; verify a clear unsupported-platform message and usable alternative login methods.	AC: Error Handling; Compatibility; Gap: support matrix
TS-08	P0	Security	Inspect SSO and passkey exchanges to confirm the approved OAuth/SAML/WebAuthn protocols are used and authentication material is not exposed in UI, URLs, or network logs.	AC: Security; Gap: exact protocol and logging oracle
TS-09	P1	Regression	Verify existing Google and email/password sign-in remain available and their successful and failed flows are not regressed by the new options.	Ticket: options added alongside existing methods; Gap: regression scope
TS-10	P1	Positive / UI	Check layout at agreed viewport sizes and supported devices; verify both options remain readable and operable without obscuring existing controls.	Ticket test scenario: responsiveness; Gap: viewport matrix
TS-11	P1	Accessibility	Keyboard-navigate to and activate both buttons; verify accessible names, focus visibility, and screen-reader announcements against the agreed accessibility target.	Ticket test scenario: accessibility; Gap: conformance target
TS-12	P1	Security / Boundary	Exercise agreed interruption and retry cases (cancel, timeout, back navigation); verify no partial or stale authenticated session remains.	AC: Security; Gap: state transitions and recovery

4. Test Data & Environment

- **Environment:** Staging is specified by the Definition of Done; URL, build, and feature-flag state must be supplied by the team.
- **Data:** Dedicated SSO identities for each configured provider; a valid account with a registered passkey; an account without a registered passkey; invalid-credential and failed-verification conditions.

- **Platforms:** Product-approved supported and unsupported browser/device combinations, including relevant operating systems and authenticators.

Nagarro | KAN-4 | Draft for human review | Prepared 2026-10-28

- **Roles / permissions:** KAN-4 does not define roles or permission differences. Author confirmation is required before role-specific coverage is added.
- **Handling:** Use non-production accounts and synthetic test identities. Never place secrets or real user credentials in screenshots, logs, or defect reports.

5. Risks & Assumptions

Assumptions made: The dashboard is the expected destination for both successful sign-in flows; staging is the execution environment because it is named in DoD; existing Google and email/password methods remain in scope for regression because the new choices are described as additions.

Risks: An undefined support matrix can leave browser/device gaps; unspecified SSO providers limit integration coverage; vague error expectations can produce inconsistent acceptance decisions; authentication defects can create account-access or sensitive-data exposure risks.

6. Entry / Exit Criteria

Entry: KAN-4 implementation is deployed to the agreed staging build; required providers and flags are configured; QA test identities and passkey fixtures are ready; supported platform matrix and error expectations are agreed; test accounts are accessible.

Exit: All agreed scenarios have recorded results; ticket acceptance criteria pass or have linked defects; no open critical/high defects remain per DoD; security checks confirm no sensitive data exposure; deviations and blocked tests are documented; QA owner completes sign-off.

7. Test Strategy

- **Testing levels:** UI verification, authentication integration checks, end-to-end system acceptance, browser/device compatibility, accessibility, and focused security validation.
- **System acceptance:** Both options are presented in the required order; successful supported flows reach the dashboard; failure and unsupported states provide agreed guidance; security requirements are met.
- **Team composition:** QA owner, login/authentication implementation owner, and SSO/identity-provider contact for configuration and test-account support.

8. Test Approach

- **Test design:** Requirement-based scenarios mapped to the ticket's UI, SSO, passkey, error, compatibility, and security criteria; supplement with gap-driven exploratory checks after author decisions.
- **Test data strategy:** Isolated staging identities and controlled account states; use provider-approved test credentials and registered test authenticators only.
- **Test data management:** Keep credentials in approved secret storage; reset or clean up test sessions after execution; redact tokens and personal data from evidence.

9. Bug Tracking Process

- **Tool:** Jira, with defects linked to KAN-4 (confirm project workflow and issue type).

- **Priority / severity:** Assign using the team's Jira definitions. Treat inability to authenticate or a security exposure as release-blocking candidates pending triage; do not infer the team's exact scale.
- **Reporting:** Include build, environment, browser/device, test identity state, steps, expected vs. actual result, and sanitized evidence. Never attach credentials, tokens, or unredacted sensitive logs.

Nagarro | KAN-4 | Draft for human review | Prepared 2026-10-28

10. Assumptions and Dependencies

- **Assumptions:** Successful authentication ends at the dashboard; KAN-4 does not include passkey registration or SSO provider setup; the supplied ticket description and acceptance criteria are the source of truth.
- **Dependencies:** Staging deployment; configured SSO providers; identity-provider test accounts; passkey-capable devices and authenticators; agreed browser/device support list; approved security and accessibility criteria.

Human Review Gate

I assumed: The staging environment is the target, successful login redirects to the dashboard, and existing login methods should continue to work.

I could not confirm: Provider list, platform matrix, exact error messages, identity/role rules, performance and localization expectations, accessibility target, rollback behavior, or test-account setup. Components, labels, fix versions, links, and attachments were not provided in the Jira response.

Open questions blocking sign-off: Confirm the gaps in Section 2, especially supported IdPs/platforms, test identities, failure/recovery behavior, security protocol expectations, and acceptance oracles.

Approve or edit this draft before proceeding. No test cases or automation are included or authorized by this draft.