

Aim: Program to implement k-NN classification using any standard dataset available in the public domain and find the accuracy of the algorithm

Algorithm:

The class of an unknown instance is computed using the following steps:

1. The distance between the unknown instance and all other training instances is computed.
2. The k nearest neighbors are identified.
3. The class labels of the k nearest neighbors are used to determine the class label of the unknown instance by using techniques like majority voting.

```
1 from sklearn import neighbors, datasets, preprocessing
2 from sklearn.model_selection import train_test_split
3 from sklearn.metrics import accuracy_score
4 from sklearn.metrics import confusion_matrix
5 from sklearn.metrics import classification_report
6 iris=datasets.load_iris()
7 x=iris.data[:,:]
8 y=iris.target
9 x_train,x_test,y_train,y_test=train_test_split(x,y,stratify=y,random_state=42)
10 scalar=preprocessing.StandardScaler().fit(x_train)
11 x_train=scalar.transform(x_train)
12 x_test=scalar.transform(x_test)
13 x_train
14
15
16
```

```
↳ array([[ 1.79213839, -0.60238047,  1.31532306,  0.92095427],
        [ 2.14531053, -0.60238047,  1.65320421,  1.05135487],
        [-0.4446185 , -1.50797259, -0.03620155, -0.25265117],
        [ 0.26172578, -0.60238047,  0.13273902,  0.13855064],
        [-0.4446185 , -1.28157456,  0.13273902,  0.13855064],
        [ 0.49717388,  0.52960968,  1.25900953,  1.70335789],
        [-1.50413492,  0.75600771, -1.33141264, -1.1654554 ],
        [ 0.49717388, -0.8287785 ,  0.63956075,  0.79055366],
        [-1.26868682,  0.07681362, -1.21878559, -1.295856  ],
        [ 0.37944983, -0.60238047,  0.58324723,  0.79055366],
        [-0.91551468,  1.66159983, -1.04984501, -1.03505479],
        [ 0.61489792, -0.8287785 ,  0.86481486,  0.92095427],
        [-1.03323873, -2.41356471, -0.1488286 , -0.25265117],
        [-0.4446185 ,  2.56719194, -1.33141264, -1.295856  ],
        [-0.79779064,  2.34079391, -1.27509911, -1.42625661],
        [-0.09144636, -0.8287785 ,  0.0764255 ,  0.00815004],
        [ 1.55669029, -0.14958441,  1.14638248,  0.52975245],
        [-0.91551468,  0.98240574, -1.33141264, -1.1654554 ],
        [-0.2091704 ,  3.019988 , -1.27509911, -1.03505479],
        [-0.79779064, -0.8287785 ,  0.0764255 ,  0.26895125],
        [ 1.3212422 ,  0.30321165,  0.5269337 ,  0.26895125],
        [ 1.20351815,  0.07681362,  0.63956075,  0.39935185],
        [-0.68006659,  1.4352018 , -1.27509911, -1.295856  ]],
```

```
[ -0.32689445, -0.37598244, -0.09251508, 0.13855064 ],
[ 0.96807006, -0.14958441, 0.80850133, 1.44255668 ],
[ -1.15096278, -0.14958441, -1.33141264, -1.295856 ],
[ 1.08579411, 0.30321165, 1.20269601, 1.44255668 ],
[ 0.49717388, -1.73437062, 0.35799313, 0.13855064 ],
[ 1.20351815, 0.30321165, 1.09006896, 1.44255668 ],
[ -1.03323873, 1.20880377, -1.33141264, -1.295856 ],
[ -1.15096278, 0.07681362, -1.27509911, -1.295856 ],
[ 0.96807006, 0.07681362, 0.5269337, 0.39935185 ],
[ -1.15096278, 0.07681362, -1.27509911, -1.42625661 ],
[ 0.49717388, -0.60238047, 0.7521878, 0.39935185 ],
[ -1.15096278, 1.20880377, -1.33141264, -1.42625661 ],
[ -1.26868682, 0.75600771, -1.04984501, -1.295856 ],
[ -0.32689445, -0.14958441, 0.18905255, 0.13855064 ],
[ -0.91551468, 0.75600771, -1.27509911, -1.295856 ],
[ 0.14400174, -0.37598244, 0.41430665, 0.39935185 ],
[ -1.85730706, -0.14958441, -1.50035321, -1.42625661 ],
[ -1.26868682, -0.14958441, -1.33141264, -1.42625661 ],
[ -0.2091704, -0.14958441, 0.24536608, 0.00815004 ],
[ -0.09144636, -0.60238047, 0.7521878, 1.57295728 ],
[ -0.09144636, -0.8287785, 0.7521878, 0.92095427 ],
[ -1.03323873, -0.14958441, -1.21878559, -1.295856 ],
[ 0.73262197, 0.30321165, 0.7521878, 1.05135487 ],
[ 0.61489792, -0.37598244, 0.3016796, 0.13855064 ],
[ -0.91551468, 1.66159983, -1.27509911, -1.1654554 ],
[ 1.08579411, -0.14958441, 0.97744191, 1.18175547 ],
[ -1.38641087, 0.30321165, -1.21878559, -1.295856 ],
[ 0.61489792, -0.60238047, 1.03375543, 1.18175547 ],
[ 2.14531053, 1.66159983, 1.65320421, 1.31215608 ],
[ -0.56234254, 1.88799786, -1.38772616, -1.03505479 ],
[ 0.73262197, -0.60238047, 0.47062018, 0.39935185 ],
[ 0.49717388, -1.28157456, 0.69587428, 0.92095427 ],
[ 2.38075862, 1.66159983, 1.48426364, 1.05135487 ],
[ 0.96807006, 0.07681362, 0.35799313, 0.26895125 ],
[ 0.49717388, -1.28157456, 0.63956075, 0.39935185 ],
```

```
1 # Identify the ideal value for k
2 scores=[]
3 for k in range(1,15):
4     knn=neighbors.KNeighborsClassifier(n_neighbors=k)
5     knn.fit(x_train,y_train)
6     y_pred=knn.predict(x_test)
7     scores.append(accuracy_score(y_test,y_pred))
8     print('when k=%s,accuracy is %s'%(k,accuracy_score(y_test,y_pred)))
9
10
11
```

```
when k=1,accuracy is 0.9473684210526315
when k=2,accuracy is 0.9210526315789473
when k=3,accuracy is 0.9210526315789473
when k=4,accuracy is 0.9210526315789473
when k=5,accuracy is 0.9210526315789473
when k=6,accuracy is 0.9210526315789473
when k=7,accuracy is 0.9473684210526315
when k=8,accuracy is 0.9210526315789473
when k=9,accuracy is 0.9736842105263158
when k=10,accuracy is 0.9736842105263158
when k=11,accuracy is 0.9736842105263158
```

when k=12,accuracy is 0.9736842105263158  
 when k=13,accuracy is 0.9736842105263158  
 when k=14,accuracy is 0.9473684210526315

```

1 # S4.2: Train kNN regressor model for 'k = 6'.
2
3 knn6=neighbors.KNeighborsClassifier(n_neighbors=6)
4 knn6.fit(x_train,y_train)
5
6
7 # Perform prediction using 'predict()' function.
8 y_pred=knn6.predict(x_test)
9
10
11 # Call the 'score()' function to check the accuracy score of the train set and test set
12
13 print("Test set accuracy:",knn6.score(x_test,y_test))
14 print("confusion matrix")
15 print(confusion_matrix(y_test,y_pred))
16 print(classification_report(y_test,y_pred))
17

```

Test set accuracy: 0.9210526315789473

confusion matrix

```

[[12  0  0]
 [ 0 13  0]
 [ 0  3 10]]

```

	precision	recall	f1-score	support
0	1.00	1.00	1.00	12
1	0.81	1.00	0.90	13
2	1.00	0.77	0.87	13
accuracy			0.92	38
macro avg	0.94	0.92	0.92	38
weighted avg	0.94	0.92	0.92	38

