

How to Handle Multiple Windows or Pages in Playwright

Introduction

To handle multiple windows in Playwright, we can use **browser context**.

A **browser context** is created using a browser instance and inside the browser context, we can create **multiple pages**.

Using Page Fixture

When we write a new test in Playwright, we usually pass the page fixture.

This page fixture is already provided by Playwright and represents a browser with a page.

- This default page fixture helps in writing simple test cases.
 - However, if we want to handle **multiple browsers, multiple windows** or **multiple pages**, we need to **create our own page** using **browser context**.
-

How to Create Our Own Page Using Browser Context

Step-by-Step:

1. **Import chromium** from @playwright/test instead of importing page, because we are going to create our own page using chromium.
2. **Launch the browser** using chromium:

```
const browser = await chromium.launch();
```
3. **Create a new context** from the browser:

```
const context = await browser.newContext();
```
4. **Create a page** inside the context:

```
const page = await context.newPage();
```

So here:

- **Browser** contains the **context**
 - **Context** contains **multiple pages**
-

Note

If you want to use the existing page, you can simply use the page fixture in your test and write your code with it.

Example Code with Page Fixture

```
import { page, test, expect } from "@playwright/test";

test("Page with existing page fixture", async ({ page }) => {

  await page.goto("https://...");

});
```

Example Code Without Page Fixture (Creating Our Own Page)

```
import { chromium, test, expect } from "@playwright/test";

test("Creating our own page", async () => {

  const browser = await chromium.launch();

  const context = await browser.newContext();

  const page = await context.newPage();

  await page.goto("https://...");

});
```

Creating Multiple Pages in Same Context

```
import { chromium, test, expect } from "@playwright/test";

test("Creating multiple pages", async () => {

  const browser = await chromium.launch();

  const context = await browser.newContext();

  const pageOne = await context.newPage();

  const pageTwo = await context.newPage();

});
```

Check How Many Pages Are Created

You can use the `pages()` function to get the list of all created pages:

```
const allPages = context.pages();  
console.log("No of pages created:", allPages.length);
```

Note

Even though both pages are created under the same context, they are **independent**.

You can open **two different applications** on each page:

```
await pageOne.goto("https://instagram.com");  
expect(pageOne).toHaveTitle("Instagram");  
await pageTwo.goto("https://whatsapp.com");  
expect(pageTwo).toHaveTitle("Windows");
```

- These are two **independent pages**.
 - We are **not navigating** from one page to another.
-

How to Navigate from One Page to Another Page in Playwright

Understanding the Difference

There's a difference between:

- **Opening multiple independent pages**, and
- **Navigating from one page to another** because of a user action (like clicking a link or button).

Opening Multiple Pages

- In the previous example, we saw how to create multiple pages using `browserContext`.
- Each page was created manually and works **independently**.
- We can perform different actions on each of them.

Navigating to Another Page

- Sometimes, an **action on one page (like a click)** will **open another page**.
- In this case, there's a **link or relation** between the first and the second page.
- This is considered **navigating** from one page to another.

Handling Linked Pages (Triggering a New Page)

When we click a button or link that opens a new page, it **triggers an event**.

To handle this scenario in Playwright:

Step-by-Step:

1. Use the `waitForEvent` function from the **context** to wait for the new page event.

```
const pagePromise = context.waitForEvent('page');
```

This creates an empty page and waits for the 'page' event to be triggered.

2. Then, perform the action that **triggers the new page**, like clicking a link:

```
await page.locator("//a[@id='newPageWillOpen']").click();
```

3. After the click, the new page will be captured in `pagePromise`. So, **assign it to a new variable**:

```
const newPage = await pagePromise;
```

4. You can now perform actions on `newPage`, such as verifying the title:

```
await expect(newPage).toHaveTitle("New page title");
```

Full Example

```
import { chromium, test, expect } from '@playwright/test';

test("Handling multiple pages", async () => {
  const browser = await chromium.launch();
  const context = await browser.newContext();
  const page = await context.newPage();
  await page.goto("https://LukesCafeMainMenuPage");
  await expect(page).toHaveTitle("Luke's Cafe Main Menu Page");
});
```

```
// Before clicking the link, wait for the new page event
const pagePromise = context.waitForEvent('page');

// Click the link that opens the coffee list page
await page.locator("//a[@id='newPageCoffeeListed']").click();

// pagePromise now holds the new page
const newPage = await pagePromise;

// Validate the title of the new page
await expect(newPage).toHaveTitle("Coffee list in Luke's cafe");

// Close the new page only (not the main menu page)
await newPage.close();

});
```

Important Note

Unlike Selenium, where we manually **switch to a new window or tab**, in Playwright:

- We **create multiple pages using context**.
 - We use `waitForEvent('page')` to **wait for the new page** to be created after a triggering action.
 - This gives us control to decide **which page to use or close**, without needing to switch back and forth.
-

Summary

- Use `browser.newContext()` and `context.newPage()` to create **multiple independent pages**.
- Use `context.waitForEvent('page')` to handle **new pages opened by user actions** like clicking a link.
- **Independent pages** work separately.
- **Triggered pages** are connected to the main page and require event handling.