

Content Projection in Angular

The Hidden Power of `<ng-content>`



Sreeram Saikumar

Angular Developer

 /sreeramsaikumar

What is Content Projection?

- It allows parent components to pass custom HTML into child components.
- Achieved using the tag `<ng-content>`.
- Makes your components flexible, clean, and reusable.

Think of it as a portal that shows whatever content the parent sends!

 /sreeramsaikumar

Basic Example

```
<!-- parent.component.html -->  
<app-card>  
  <p>This is projected content!</p>  
</app-card>
```

```
<!-- card.component.html -->  
<div class="card">  
  <ng-content></ng-content>  
</div>
```

The `<p>` tag is projected inside the card component.

That's **basic content projection**.

 /sreeramsaikumar

Multiple Slots

```
<!-- parent.component.html -->
<app-dialog>
  <h2 header>Warning!</h2>
  <p body>Are you sure you want to delete?</p>
</app-dialog>
```

```
<!-- dialog.component.html -->
<div class="dialog">
  <header>
    <ng-content select="[header]"></ng-content>
  </header>
  <section>
    <ng-content select="[body]"></ng-content>
  </section>
</div>
```

Each `<ng-content>` gets specific content using `select`.

This is called **multi-slot content projection**.

 /sreeramsaikumar

Fallback & Default Slots

```
<div class="card">  
  <ng-content>Select something!</ng-content>  
</div>
```

If no content is projected, this default text appears!

- You can also use one plain `<ng-content>` (without `select`) to catch unmatched content from other slots.

 /sreeramsaikumar

Advanced — ngProjectAs

Sometimes, you want an element to be treated as if it had a different selector when projecting content.

```
<!-- parent.component.html -->
<app-dialog>
|   <div ngProjectAs="[header]">Alert!</div>
</app-dialog>
```

```
<!-- dialog.component.html -->
<ng-content select="[header]"></ng-content>
```

- Even though the `<div>` doesn't have a header attribute, `ngProjectAs="[header]"` **makes Angular treat it like it does.**

 /sreeramsaikumar

ngProjectAs – Useful when

- You can't modify the original element's attributes
- You want to reuse content projection slots flexibly

 /sreeramsaikumar

When & Why to Use It

- Build reusable layouts (cards, modals, tabs, lists)
- Avoid hardcoding inner HTML
- Improve flexibility and separation of concerns

Pro tip: Combine it with `@ContentChild` / `@ContentChildren` for more control.

 /sreeramsaikumar

Have you used Content Projection before

— or just learned it now?

Comment “**Yes**” or “**Now I will!**” and
follow for more smart Angular bites

 /sreeramsaikumar

 /sreeramsaikumar

+ Follow

 /sreeramsaikumar