



Save it



Like it



Angular Series

HostListener & HostBinding



Hostlistener

In javascript to add events on an element we use **addEventListener**

```
// Get the button element
const myButton = document.getElementById('myButton');

// Add a click event listener
myButton.addEventListener('click', function() {
  console.log('Button clicked!');
});
```



- In Angular, this can also be done using **Hostlistener** to listen for events on the host element (any element like button, window, textbox, etc)



Host Listener

Handles events like click, mouseover, keydown, etc.

Host Element



@coder_aishya



Usecases of HostListener

On Window Scroll , show go to Top button



```
import { HostListener } from '@angular/core';

export Class AppComponent{
  @HostListener('window:scroll')
  onWindowScroll() {
    const number = this.document.body.scrollTop;
    if (number > 150) {
      this.isScrolled = true;
    } else if (this.isScrolled && number < 10) {
      this.isScrolled = false;
    }
  }
}
```

Disable RightClick for any web application

```
import { HostListener } from '@angular/core';

export Class AppComponent{
  @HostListener('contextMenu')
  onRightClick(event:any) {
    event.preventDefault();
  }
}
```



@coder_aishya



Disable Copy for your application using Directive

● ● ● [disablecopy.directive.ts](#)

```
import { Directive, HostListener } from '@angular/core';
```

```
@Directive({  
  selector: '[appNoCopyPaste]',  
  standalone: true // Add this if using Angular 14+  
})
```

```
export class NoCopyPasteDirective {
```

```
  @HostListener('copy', ['$event'])
```

```
  @HostListener('cut', ['$event'])
```

```
  @HostListener('paste', ['$event'])
```

```
  onEvent(event: ClipboardEvent): void {
```

```
    event.preventDefault();
```

```
    // Optional: Log a message or display a tooltip
```

```
    console.log('Copy/Cut/Paste action blocked!');
```

```
  }
```

```
}
```

attach events using
HostListener



```
<div appNoCopyPaste>
```

```
  <!-- All content within this div cannot be copied/pasted -->
```

```
  <router-outlet></router-outlet>
```

```
</div>
```

Attach DisableCopy directive
to component



@coder_aishya



@HostBinding

- Host Binding binds a Host element property to a variable in the directive or component
- **This allows for dynamically modifying the host element's properties (like class, style, or attr attributes) from within the component or directive logic**

Classes → @HostBinding('class.className')

Styles → @HostBinding('style.propertyName')

Attributes → @HostBinding('attr.attributeName')

DOM Properties → @HostBinding('propertyName')



Disable form after submitting using hostbinding

```
import { Component } from '@angular/core';
import { CommonModule } from '@angular/common';
import { FormsModule } from '@angular/forms';

@Component({
  selector: 'app-login-form',
  standalone: true,
  imports: [CommonModule, FormsModule],
  templateUrl: './login.component.html',
  styleUrls: ['./login.component.css'],
  host: {
    // Bind 'pointer-events' style to 'none' when the form is
    // submitting
    '[style.pointer-events]': 'isSubmitting ? "none" : "auto"',

    // Bind the 'class.form-submitting' class for visual styling
    '[class.form-submitting]': 'isSubmitting'
  }
})
export class LoginFormComponent {
  email = '';
  password = '';
  isSubmitting = false;

  onSubmit() {
    this.isSubmitting = true; // Set this flag to true on submit

    console.log('Form submitted. API call started...');

    // Simulate an asynchronous API call that takes 2 seconds
    setTimeout(() => {
      console.log('API call finished.');
      this.isSubmitting = false; // Reset the flag when complete
      // Handle navigation or success message here
    }, 2000);
  }
}
```



**Follow me for me frontend
related Content**



coder_aishya



aishwarya-dhuri

