



COMPONENT COMMUNICATION (Parent to Child)



codewithrutu_09

✓ Why Component Communication

📌 In real-world Angular apps, components must share data to function cohesively.

🧠 Common use cases:

1. Passing user info to a profile component
2. Sending list items to a child card
3. Reusing components with different inputs

👉 @Input() helps pass data from parent to child

✓ Introducing @Input() Decorator

```
app.component.ts  
  
@Input() productName: string;
```

Declare the property in the child component using the @Input() decorator.

This allows the parent to bind a value to this property.

✓ Parent → Child Binding Syntax

In parent component HTML:

```
app.component.html  
  
<app-product [productName]="selectedProduct"></app-product>
```

🔗 [productName] is the binding

📦 selectedProduct is a variable in the parent class

📌 Data flows one-way → from parent to child

✓ Full Example

Parent Component TS:

```
app.component.ts  
  
selectedProduct = 'Laptop';
```

Child Component TS:

```
app.component.ts  
  
@Input() productName: string;
```

Parent Template:



app.component.html

```
<app-product [productName]="selectedProduct"></app-product>
```

Child Template:



app.component.html

```
<p>Selected Product: {{ productName }}</p>
```

✓ Using Aliases for Inputs

You can alias input names to avoid naming conflicts:

```
app.component.ts  
  
@Input( 'name' ) productName: string;
```

In parent template:

```
app.component.html  
  
<app-product [name]="selectedProduct"></app-product>
```


✓ Input Property Best Practices

🧠 Best Practices:

- Keep input types specific (string, number, etc.)
- Use @Input() for configuration and display data only
- Avoid modifying @Input() values in the child
- Use OnChanges for reacting to input updates



app.component.ts

```
ngOnChanges(changes: SimpleChanges) {  
  console.log('Input changed:', changes);  
}
```


Input Property Best Practices

- Use `@Input()` in the child to receive data
- Bind from parent using square brackets `[]`
- Input binding is one-way only
- Alias inputs if needed
- React to changes using `ngOnChanges`



codewithrutu_09



Like this post!



Share with your friends



Save it for later



**Tell us what you think in
comment**



codewithrutu_09



Rutuja Shinde