



INTERPOLATION IN ANGULAR



codewithrutu_09

What is Interpolation?

Interpolation allows us to include expressions as part of any string literal, which we use in our HTML. Angular interpolation is also known by the name **string interpolation**.

Interpolation Syntax

The Angular uses the `{{ }}` (double curly braces) in the template to denote the interpolation.



```
{{ templateExpression }}
```

Interpolation is one way binding

Interpolation is one way as values go from the component to the template. When the component values change, the Angular updates the view. But if the values change in the view components are not updated.

Works only on Properties & not attributes

Interpolation and property binding can set only properties, not attributes. For Attributes use attribute binding.

Interpolation Examples

app.component.ts



```
import { Component } from '@angular/core';

@Component({
  selector : 'app-root',
  templateUrl : './app.component.html',
  styleUrls: ['./app.component.css']
})

export class AppComponent{
  fullname = 'Rutuja Shinde';
}
```

app.component.html



```
<p>Welcome {{fullname}}</p>
```

Output: Welcome Rutuja Shinde

Invoke a method in the component

app.component.ts



```
export class AppComponent{  
  title = 'Angular interpolation Example';  
  getTitle() : string {  
    return this.title;  
  }  
}
```

app.component.html



```
{{getTitle()}}
```

Concatenate two strings

app.component.html



```
<p>Welcome to {{title}}</p>
<p>{{'Hello & Welcome to '+' Angular Interpolation'}}</p>
<p>Welcome to {{firtsName}},{{lastName}}</p>
<p>Welcome to {{getFirstNme( )}},{{getLastName( )}}</p>
```

Bind to an image source

app.component.html



```
<div></div>
```

Use Pipes

You can make use of Angular Pipes to transform the expression result. Like converting to an uppercase, date formats, adding currency symbols, etc.

app.component.html



```
<p>uppercase pipe: {{title | uppercase}}</p>
<p>pipe chain: {{title | uppercase | lowercase}}</p>
<p>json pipe: {{items | json}}</p>
```

The safe navigation operator (?)

You can make use of a safe navigation operator (?) to guards against null and undefined values.

app.component.html



```
<p>The null item name is {{nullitem?.itemName}}</p>
```




codewithrutu_09



Like this post!



Share with your friends



Save it for later



**Tell us what you think in
comment**



codewithrutu_09



Rutuja Shinde