



PIPES IN ANGULAR



codewithrutu_09

✓ What Are Pipes?

📌 Pipes are simple functions that transform data before display.

You use them in templates like this:



```
{{ user.name | uppercase }}
```

Pipes are pure, lightweight, and declarative — perfect for formatting content directly in your HTML.

✓ Built-in Pipes in Angular

Here are some commonly used pipes:

1.  uppercase / lowercase
2.  currency
3.  date
4.  number
5.  percent
6.  slice
7.  json
8.  decimal



```
{{ price | currency:'USD':'symbol' }}  
{{ today | date:'MMM d, y' }}
```

✓ Chaining Multiple Pipes

You can combine pipes:

```
[[ name | lowercase | slice:0:5 ]]
```

This example will lowercase the name and extract the first 5 letters.

📌 Pipes are evaluated left to right.

✓ Creating a Custom Pipe

You can build your own pipe for custom logic.



```
ng generate pipe truncate
```



```
@Pipe({ name: 'truncate' })
export class TruncatePipe implements PipeTransform {
  transform(value: string, limit: number): string {
    return value.length > limit ? value.slice(0, limit) + '...' : value;
  }
}
```



```
{{ description | truncate:50 }}
```

✓ Pure vs Impure Pipes

Called only when input changes.

Impure pipes run on every change detection cycle, which may impact performance.

Set impure pipe:



```
@Pipe({ name: 'custom', pure: false })
```

Use impure pipes cautiously.

✓ Pipes vs Functions in Templates

✗ Avoid using complex functions in templates:



```
<!-- NOT RECOMMENDED -->
{{ getFormattedName(user) }}
```

Prefer Pipes:



```
{{ user.name | customFormat }}
```

Pipes are **optimized**, more **readable**, and don't trigger extra change detection.

Key Takeaways

- **Use built-in pipes for fast formatting**
- **Build custom pipes for reusable logic**
- **Chain and parameterize them for power**
- **Prefer pipes over functions in templates**
- **Use impure pipes sparingly**



codewithrutu_09



Like this post!



Share with your friends



Save it for later



**Tell us what you think in
comment**



codewithrutu_09



Rutuja Shinde