



PROPERTY BINDING IN ANGULAR



codewithrutu_09

✓ What is Property Binding?

Property Binding allows you to bind DOM element properties to component class properties.

Instead of hardcoding values:

```
app.component.html  
  

```

We bind dynamically:

```
app.component.html  
  
<img [src]="imageUrl" />
```

✓ Property Binding Syntax



app.component.html

```
<tagName [propertyName]="componentProperty" />
```

✓ Examples:



app.component.html

```
<input [value]="username" />  
<button [disabled]="isDisabled">Submit</button>  
<div [hidden]="!isVisible">Hello</div>
```

📌 The value inside [] is an expression evaluated in the component context.



codewithrutu_09



Rutuja Shinde

✓ Use Cases in Real Projects

1. Dynamically disabling/enabling buttons
2. Displaying user profile images
3. Toggling visibility of components
4. Changing classes or styles conditionally

Example :



app.component.html

```
<button [class.active]="isActive">Click</button>
```

✓ Example with Component Logic

Component :

```
app.component.ts

export class ProductComponent {
  product = {
    name: 'Laptop',
    inStock: true,
    image: 'laptop.jpg'
  };
}
```

Template :

```
app.component.html

<img [src]="product.image" />
<h3>{{ product.name }}</h3>
<button [disabled]="!product.inStock">Buy Now</button>
```



codewithrutu_09



Like this post!



Share with your friends



Save it for later



**Tell us what you think in
comment**