



ROUTING IN ANGULAR



codewithrutu_09

✓ **What Is Angular Routing?**

🔄 **Angular Routing enables Single Page Application (SPA) behavior.**

- **Routes map URLs to components**
- **No full-page reloads**
- **Efficient navigation without latency**
- **Works using the Angular Router module**

📌 **Routing is defined in a dedicated routing module (commonly app-routing.module.ts)**

✓ Configuring Routes

Define routes using Routes array:

```
app.component.ts

const routes: Routes = [
  { path: 'home', component: HomeComponent },
  { path: 'products', component: ProductListComponent },
  { path: '', redirectTo: '/home', pathMatch: 'full' },
]
```

- Use **RouterModule.forRoot(routes)** in **AppModule**
- Route paths are matched from top to bottom

📌 **redirectTo** is useful for default or fallback paths

✓ router-outlet – Dynamic View Placeholder



```
<!-- app.component.html -->  
<nav>  
  <a routerLink="/home">Home</a>  
  <a routerLink="/products">Products</a>  
</nav>  
  
<router-outlet></router-outlet>
```

- Acts as a viewport where routed components render
- Each time the route changes, Angular injects the new component here

✓ Configuring Routes

Template-driven navigation



```
<a routerLink="/about">About</a>
```

Programmatic navigation



```
this.router.navigate([' /about']);
```



```
<a routerLink="/about" routerLinkActive="active-link">About</a>
```



✓ Route Parameters & Dynamic URLs

Define dynamic route:

```
app.component.ts  
  
{ path: 'user/:id', component: UserProfileComponent }
```

Get parameter in component:

```
app.component.ts  
  
this.route.snapshot.paramMap.get('id');
```

```
app.component.ts  
  
this.route.paramMap.subscribe(params => {  
  const id = params.get('id');  
});
```

✓ Lazy Loading – Optimize Your App

Break your app into modules and load them only when needed:

```
app.component.ts

{
  path: 'admin',
  loadChildren: () => import('./admin/admin.module').then(m => m.AdminModule)
}
```

- ◆ Great for performance
- ◆ Reduces initial bundle size
- ◆ Each module can have its own routing

✓ Route Guards – Control Access

Use canActivate to protect routes:

```
app.component.ts  
  
{ path: 'dashboard', component: DashboardComponent, canActivate: [AuthGuard]
```

Auth Guard Example:

```
app.component.ts  
  
canActivate(): boolean {  
    return this.authService.isLoggedIn();  
}
```

- canActivate
- canDeactivate
- canLoad
- resolve
- canActivateChild



codewithrutu_09



Like this post!



Share with your friends



Save it for later



**Tell us what you think in
comment**



codewithrutu_09



Rutuja Shinde