



@CODE.CLASH

Fetch API In JavaScript



NEXT →

1

@CODE.CLASH

Hey Everyone 🖐️

Javascript is everywhere. Millions of webpages are built on JS.

in this Post, **you'll learn** about the **JavaScript Fetch API** and how to use it to make **asynchronous HTTP requests**.

Do **Like, save and Share** This Post If You Found This Helpful.

NEXT ➡️

Fetch API

The **Fetch API** is a modern interface that allows you to make **HTTP requests to servers** from web browsers.

- If you have worked with **XMLHttpRequest (XHR)** object.
- Fetch API can perform **all the tasks** as the XHR object does.
- Fetch API is much **simpler** and **cleaner**.
- It uses the **Promise** to deliver more **flexible features** to make requests to servers from the web browsers.

Sending a Request

The `fetch()` method is available in the **global scope** that instructs the web browsers to send a **request to a URL**.

- The `fetch()` requires only **one parameter** which is the **URL** of the resource that you want to fetch.
- When the **request completes**, the **promise** will resolve into a **Response** object.

```
let response = fetch(url);
```


The `text()` method returns a Promise that resolves with the complete contents of the fetched resource.

```
fetch('/readme.txt')  
  .then(response => response.text())  
  .then(data => console.log(data));
```

- Besides the `text()` method, the Response object has other methods such as `json()`, `blob()`, `formData()` and `arrayBuffer()` to handle the respective type of data.

Reading the Response

The `fetch()` method returns a `Promise` so you can use the `then()` and `catch()` methods to handle it.

```
fetch(url)
  .then((response) => {
    // handle the response
  })
  .catch((error) => {
    // handle the error
  });
```

- If the contents of the `response` are in the `raw text format`, you can use the `text()` method.

In practice, you often use the `async/await` with the `fetch()` method like this:

```
async function fetchText() {  
  let response = await fetch('/readme.txt');  
  let data = await response.text();  
  console.log(data);  
}
```


Handling the status codes

The `Response` object provides the `status` `code` and `status text` via the `status` and `statusText` properties.

```
async function fetchText() {  
  let response = await fetch('/readme.txt');  
  
  console.log(response.status); // 200  
  console.log(response.statusText); // OK  
  
  if (response.status === 200) {  
    let data = await response.text();  
    // handle data  
  }  
}  
  
fetchText();
```


Did you find it **Useful?**

Leave a **comment!**



Alamin CodePapa

@CodePapa360

FOLLOW FOR MORE

Like



Comment



Repost

