

JavaScript Web APIs

A QUICK REFERENCE

The Most Complete Full Stack
Developer Roadmap

www.thedevspace.io

DOM API

Inspect and manipulate the document structure, attributes, events, and layout using JavaScript.

Querying



```
1 document.querySelector(".btn"); // Returns the first match
2 document.querySelectorAll(".item"); // Returns a static NodeList of matches
3 document.getElementById("main");
4 document.getElementsByClassName("card");
```

Create / Insert / Remove



```
1 document.createElement("div");
2 parent.appendChild(node);
3 parent.insertBefore(node, refNode);
4 node.remove();
```

DOM API

Attributes & Classes



```
1 el.getAttribute("data-id");
2 el.setAttribute("role", "button");
3 el.removeAttribute("title");
4 el.classList.add("is-active");
```

Content



```
1 el.textContent = "plain text";
2 el.innerHTML = "<strong>html</strong>"; // sanitize untrusted HTML
```

Content



```
1 el.addEventListener("click", handler);
2 el.removeEventListener("click", handler);
3 el.dispatchEvent(new Event("custom"));
```

FETCH API

Send network requests.



```
1 fetch("http://www.example.com/api/data")
2   .then((response) => response.json())
3   .then((data) => console.log(data))
4   .catch((error) => console.error(error));
```

STORAGE API

Simple in-browser key-value storage.

localStorage: persists until cleared



```
1 localStorage.setItem("theme", "dark");  
2 const theme = localStorage.getItem("theme");  
3 localStorage.removeItem("theme");
```

sessionStorage: persists only for the current tab



```
1 sessionStorage.setItem("temp", "value");  
2 const temp = sessionStorage.getItem("temp");  
3 sessionStorage.clear();
```

CLIPBOARD API

Write/read text from clipboard.



```
1 await navigator.clipboard.writeText("copy me");  
2 const text = await navigator.clipboard.readText();
```

GEOLOCATION API



```
1 navigator.geolocation.getCurrentPosition((pos) => {  
2     console.log("Latitude:", pos.coords.latitude);  
3     console.log("Longitude:", pos.coords.longitude);  
4 });
```

DEVICE ORIENTATION API

Listen for device orientation.

```
1 window.addEventListener("deviceorientation", (e) => {  
2   console.log("alpha", e.alpha, "beta", e.beta, "gamma", e.gamma);  
3 });
```

DEVICE MOTION API



```
1 window.addEventListener("devicemotion", (e) => {  
2   console.log("acceleration", e.acceleration);  
3   console.log("rotationRate", e.rotationRate);  
4 });
```

NOTIFICATIONS API



```
1 const p = await Notification.requestPermission();  
2 if (p === "granted") new Notification("Hello from the site");
```

CANVAS API

Drawing on your webpage.



```
1  const c = document.createElement("canvas");
2  const ctx = c.getContext("2d");
3
4  ctx.fillStyle = "#1a73e8";
5  ctx.fillRect(10, 10, 120, 60); // draw a rectangle
```

BATTERY API

Check battery status.



```
1 if (navigator.getBattery) {  
2   const battery = await navigator.getBattery();  
3   console.log("level", battery.level, "charging", battery.charging);  
4 }
```

This is not available in all browsers.

POINTER EVENTS



```
1 el.addEventListener("pointerdown", (e) => {  
2   console.log("pointer id", e.pointerId, "type", e.pointerType);  
3 });
```

SCREEN WAKE LOCK API

Prevent screen sleep while a task is running.



```
1 if ("wakeLock" in navigator) {  
2   const lock = await navigator.wakeLock.request("screen");  
3   // Call lock.release() when done  
4 }
```