

JavaScript DOM Manipulation

A QUICK REFERENCE

The Most Complete Full Stack
Developer Roadmap

www.thedevspace.io

SELECT AN ELEMENT

Select a single element using modern selectors.



```
1 const el = document.querySelector(".btn"); // first match
2 const root = document.getElementById("root");
```

SELECT MULTIPLE ELEMENTS

Select multiple elements and return a live **HTMLCollection** or a static **NodeList** of matches.



```
1 document.querySelectorAll(".list > li"); // NodeList (static)
2 document.getElementsByClassName("col"); // HTMLCollection (live)
3 document.getElementsByTagName("div"); // HTMLCollection (live)
4 document.getElementsByName("username"); // NodeList (static)
```

CREATE ELEMENTS

Create elements and set properties before inserting.



```
1  const div = document.createElement("div");  
2  div.className = "card";  
3  div.textContent = "Hello";
```

INSERT ELEMENTS

Use **append()/prepend()/insertBefore()** to insert elements.



```
1 container.append(div); // end
2 container.prepend(div); // start
3 reference.before(div);
```

Use the modern **insertAdjacent*()** for fine control.



```
1 reference.insertAdjacentHTML("afterend", "<span>hi</span>");
```

REMOVE ELEMENTS

Remove nodes with **remove()** or swap with **replaceWith()**.



```
1 el.remove();  
2 old.replaceWith(newNode);
```

SET ATTRIBUTES

Use **setAttribute()/getAttribute()** for arbitrary attributes.



```
1 el.setAttribute("role", "button");  
2 const role = el.getAttribute("role");
```

Use **dataset** for **data-*** attributes.



```
1 el.dataset.id = "42"; // data-id
```

EVENT HANDLERS

Attach handlers with **addEventListener()**.



```
1 el.addEventListener("click", (e) => {  
2   // handle click  
3 });
```