

# DEEP LEARNING FOR COMPUTER VISION

Summer Seminar UPC TelecomBCN, 4 - 8 July 2016



## Instructors



Xavier  
Giró-i-Nieto

Elisa  
Sayrol

Amaia  
Salvador

Jordi  
Torres

Eva  
Moledano

Kevin  
McGuinness

## Organizers



UNIVERSITAT POLITÈCNICA  
DE CATALUNYA  
BARCELONATECH



Barcelona  
Supercomputing  
Center  
Centro Nacional de Supercomputación



Dublin City University  
Olióll Chathair Bhaile Átha Cliath



Insight  
Centre for Data Analytics



GPU  
CENTER OF  
EXCELLENCE

Co-funded by the  
Erasmus+ Programme  
of the European Union



Elisa Sayrol



UNIVERSITAT POLITÈCNICA DE CATALUNYA  
BARCELONATECH

Department of Signal Theory  
and Communications

*Image Processing Group*

+ info: [TelecomBCN.DeepLearning.Barcelona](http://TelecomBCN.DeepLearning.Barcelona)


# Overview

Restrictive Boltzmann Machine (RBM)

Training. Contrastive Divergence (CD)

Deep Belief Networks (DBN)

# Restricted Boltzmann Machine (RBM)



- Shallow two-layer net.
- Restricted=No two nodes in a layer share a connection
- Bipartite graph.
- Bidirectional graph
  - Shared weights.
  - Different biases.

Figure: Geoffrey Hinton (2013)

# Restricted Boltzmann Machine (RBM)






Figure: Geoffrey Hinton (2013)

Salakhutdinov, Ruslan, Andriy Mnih, and Geoffrey Hinton. ["Restricted Boltzmann machines for collaborative filtering."](#) Proceedings of the 24th international conference on Machine learning. ACM, 2007. 4

# Restricted Boltzmann Machine (RBM)




# Restricted Boltzmann Machine (RBM)



# Restricted Boltzmann Machine (RBM)

The reconstructed values at the visible layer are compared with the actual ones with the [KL Divergence](#).



# What are the Maths behind RBMs?

(Estimation of the parameters)



Geoffrey Hinton, ["Introduction to Deep Learning & Deep Belief Nets"](#) (2012)

Geoffrey Hinton, ["Tutorial on Deep Belief Networks"](#). NIPS 2007.



# What are the Maths behind RBMs?

Other references:


Deeplearning.net: [Restricted Boltzmann Machines](#) (with Theano functions and concepts)

Hugo Larochelle: [Course on NN](#)

Let's take a look at some of his slides on RBM....

# RESTRICTED BOLTZMANN MACHINE

**Topics:** RBM, visible layer, hidden layer, energy function



Energy function: 
$$E(\mathbf{x}, \mathbf{h}) = -\mathbf{h}^\top \mathbf{W} \mathbf{x} - \mathbf{c}^\top \mathbf{x} - \mathbf{b}^\top \mathbf{h}$$

$$= -\sum_j \sum_k W_{j,k} h_j x_k - \sum_k c_k x_k - \sum_j b_j h_j$$

Distribution:  $p(\mathbf{x}, \mathbf{h}) = \exp(-E(\mathbf{x}, \mathbf{h})) / Z$

← partition function (intractable)

# TRAINING

## Topics: training objective

- To train an RBM, we'd like to minimize the average negative log-likelihood (NLL)

$$\frac{1}{T} \sum_t l(f(\mathbf{x}^{(t)})) = \frac{1}{T} \sum_t -\log p(\mathbf{x}^{(t)})$$

- We'd like to proceed by stochastic gradient descent

$$\frac{\partial -\log p(\mathbf{x}^{(t)})}{\partial \theta} = \underbrace{\mathbf{E}_{\mathbf{h}} \left[ \frac{\partial E(\mathbf{x}^{(t)}, \mathbf{h})}{\partial \theta} \middle| \mathbf{x}^{(t)} \right]}_{\text{positive phase}} - \underbrace{\mathbf{E}_{\mathbf{x}, \mathbf{h}} \left[ \frac{\partial E(\mathbf{x}, \mathbf{h})}{\partial \theta} \right]}_{\text{negative phase}}$$

hard to compute  
↙


# CONTRASTIVE DIVERGENCE (CD)

(HINTON, NEURAL COMPUTATION, 2002)

**Topics:** contrastive divergence, negative sample

• Idea:

1. replace the expectation by a point estimate at  $\tilde{\mathbf{x}}$
2. obtain the point  $\tilde{\mathbf{x}}$  by Gibbs sampling
3. start sampling chain at  $\mathbf{x}^{(t)}$




# CONTRASTIVE DIVERGENCE (CD)

(HINTON, NEURAL COMPUTATION, 2002)

**Topics:** contrastive divergence, negative sample

$$E_{\mathbf{h}} \left[ \frac{\partial E(\mathbf{x}^{(t)}, \mathbf{h})}{\partial \theta} \middle| \mathbf{x}^{(t)} \right] \approx \frac{\partial E(\mathbf{x}^{(t)}, \tilde{\mathbf{h}}^{(t)})}{\partial \theta} \quad E_{\mathbf{x}, \mathbf{h}} \left[ \frac{\partial E(\mathbf{x}, \mathbf{h})}{\partial \theta} \right] \approx \frac{\partial E(\tilde{\mathbf{x}}, \tilde{\mathbf{h}})}{\partial \theta}$$



# DERIVATION OF THE LEARNING RULE

**Topics:** contrastive divergence

- Derivation of  $\frac{\partial E(\mathbf{x}, \mathbf{h})}{\partial \theta}$  for  $\theta = W_{jk}$

$$\frac{\partial E(\mathbf{x}, \mathbf{h})}{\partial W_{jk}} = \frac{\partial}{\partial W_{jk}} \left( - \sum_{jk} W_{jk} h_j x_k - \sum_k c_k x_k - \sum_j b_j h_j \right)$$

$$= - \frac{\partial}{\partial W_{jk}} \sum_{jk} W_{jk} h_j x_k$$

$$= -h_j x_k$$

$$\nabla_{\mathbf{W}} E(\mathbf{x}, \mathbf{h}) = -\mathbf{h} \mathbf{x}^\top$$



# DERIVATION OF THE LEARNING RULE

**Topics:** contrastive divergence

- Derivation of  $E_h \left[ \frac{\partial E(x, h)}{\partial \theta} \right]_x$  for  $\theta = W_{jk}$

$$\begin{aligned}
 E_h \left[ \frac{\partial E(x, h)}{\partial W_{jk}} \right]_x &= E_h \left[ -h_j x_k \right]_x = \sum_{h_j \in \{0,1\}} -h_j x_k p(h_j | x) \\
 &= -x_k p(h_j = 1 | x)
 \end{aligned}$$

$$E_h [r_w E(x, h) | x] = -h(x) x^T$$

$$\begin{aligned}
 h(x) &\stackrel{\text{def}}{=} \begin{pmatrix} p(h_1 = 1 | x) \\ \vdots \\ p(h_H = 1 | x) \end{pmatrix} \\
 &= \text{sigm}(b + W x)
 \end{aligned}$$

# DERIVATION OF THE LEARNING RULE

**Topics:** contrastive divergence

- Given  $\mathbf{x}^{(t)}$  and  $\tilde{\mathbf{x}}$  the learning rule for  $\theta = \mathbf{W}$  becomes

$$\begin{aligned}
 \mathbf{W} &\Leftarrow \mathbf{W} - \alpha \left( \nabla_{\mathbf{W}} - \log p(\mathbf{x}^{(t)}) \right) \\
 &\Leftarrow \mathbf{W} - \alpha \left( \mathbb{E}_{\mathbf{h}} \left[ \nabla_{\mathbf{W}} E(\mathbf{x}^{(t)}, \mathbf{h}) \mid \mathbf{x}^{(t)} \right] - \mathbb{E}_{\mathbf{x}, \mathbf{h}} [\nabla_{\mathbf{W}} E(\mathbf{x}, \mathbf{h})] \right) \\
 &\Leftarrow \mathbf{W} - \alpha \left( \mathbb{E}_{\mathbf{h}} \left[ \nabla_{\mathbf{W}} E(\mathbf{x}^{(t)}, \mathbf{h}) \mid \mathbf{x}^{(t)} \right] - \mathbb{E}_{\mathbf{h}} [\nabla_{\mathbf{W}} E(\tilde{\mathbf{x}}, \mathbf{h}) \mid \tilde{\mathbf{x}}] \right) \\
 &\Leftarrow \mathbf{W} + \alpha \left( \mathbf{h}(\mathbf{x}^{(t)}) \mathbf{x}^{(t)\top} - \mathbf{h}(\tilde{\mathbf{x}}) \tilde{\mathbf{x}}^\top \right)
 \end{aligned}$$



# CD-K: PSEUDOCODE

**Topics:** contrastive divergence

- I. For each training example  $\mathbf{x}^{(t)}$ 
  - i. generate a negative sample  $\tilde{\mathbf{x}}$  using  
k steps of Gibbs sampling, starting at  $\mathbf{x}^{(t)}$
  - ii. update parameters

$$\mathbf{W} \Leftarrow \mathbf{W} + \alpha \left( \mathbf{h}(\mathbf{x}^{(t)}) \mathbf{x}^{(t)\top} - \mathbf{h}(\tilde{\mathbf{x}}) \tilde{\mathbf{x}}^\top \right)$$


$$\mathbf{b} \Leftarrow \mathbf{b} + \alpha \left( \mathbf{h}(\mathbf{x}^{(t)}) - \mathbf{h}(\tilde{\mathbf{x}}) \right)$$

$$\mathbf{c} \Leftarrow \mathbf{c} + \alpha \left( \mathbf{x}^{(t)} - \tilde{\mathbf{x}} \right)$$


2. Go back to I until stopping criteria

# FILTERS

(LAROCHELLE ET AL., JMLR2009)




# Deep Belief Networks (DBN)



- Architecture like an MLP.
- Training as a stack of RBMs.

Hinton, Geoffrey E., Simon Osindero, and Yee-Whye Teh. ["A fast learning algorithm for deep belief nets."](#) Neural computation 18, no. 7 (2006): 1527-1554.


# Deep Belief Networks (DBN)



- Architecture like an MLP.
- Training as a stack of RBMs.

Hinton, Geoffrey E., Simon Osindero, and Yee-Whye Teh. ["A fast learning algorithm for deep belief nets."](#) Neural computation 18, no. 7 (2006): 1527-1554.

# Deep Belief Networks (DBN)




- Architecture like an MLP.
- Training as a stack of RBMs.

Hinton, Geoffrey E., Simon Osindero, and Yee-Whye Teh. ["A fast learning algorithm for deep belief nets."](#) Neural computation 18, no. 7 (2006): 1527-1554.




# Deep Belief Networks (DBN)



- Architecture like an MLP.
- Training as a stack of RBMs.

Hinton, Geoffrey E., Simon Osindero, and Yee-Whye Teh. ["A fast learning algorithm for deep belief nets."](#) Neural computation 18, no. 7 (2006): 1527-1554.

# Deep Belief Networks (DBN)




- Architecture like an MLP.
- Training as a stack of RBMs...
- ...so they do not need labels:

Unsupervised  
learning

Hinton, Geoffrey E., Simon Osindero, and Yee-Whye Teh. ["A fast learning algorithm for deep belief nets."](#) Neural computation 18, no. 7 (2006): 1527-1554.

# Deep Belief Networks (DBN)



After the DBN is trained, it can be fine-tuned with a **reduced amount of labels** to solve a supervised task with superior performance.

Supervised  
learning

Hinton, Geoffrey E., Simon Osindero, and Yee-Whye Teh. ["A fast learning algorithm for deep belief nets."](#) Neural computation 18, no. 7 (2006): 1527-1554.



**Thank You!**