CS450 Computer Networks

The slides used in class are derived from the slides available on
our text book companion website:
http://wps.pearsoned.com/ecs_kurose_compnetw_6/

CS450 Computer Networks
Lesson 9
Transport Layer – Reliable Data Transfer

Purification Leads to Progress

Lesson 9: Transport Layer - Reliable Data Transfer

Our goal:

- understand principles behind reliable data transfer as a transport layer service

Principles of Reliable data transfer

- important in app., transport, link layers
- top-10 list of important networking topics!



(a) provided service

- characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Principles of Reliable data transfer

- important in app., transport, link layers
- top-10 list of important networking topics!



- characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Principles of Reliable data transfer

- important in app., transport, link layers
- top-10 list of important networking topics!



- characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Reliable data transfer: getting started

rdt_send(): called from above, (e.g., by app.). Passed data to deliver to receiver upper layer

deliver_data(): called by rdt to deliver data to upper



udt_send(): called by rdt, to transfer packet over unreliable channel to receiver

rdt_rcv(): called when packet arrives on rcv-side of channel

Reliable data transfer: getting started

We will:

- incrementally develop sender, receiver sides of reliable data transfer protocol (rdt)
- consider only unidirectional data transfer
  - but control info will flow on both directions!
- use finite state machines (FSM) to specify sender, receiver

state: when in this "state" next state uniquely determined by next event



Rdt1.0: reliable transfer over a reliable channel

- underlying channel perfectly reliable
  - no bit errors
  - no loss of packets
- separate FSMs for sender, receiver:
  - sender sends data into underlying channel
  - receiver read data from underlying channel



sender



receiver

Rdt2.0: channel with bit errors

- underlying channel may flip bits in packet
  - checksum to detect bit errors
- *the* question: how to recover from errors:

How do humans recover from "errors" during conversation?

List three ways we handle spoken communication in a noisy environment.

Rdt2.0: channel with bit errors

- underlying channel may flip bits in packet
  - checksum to detect bit errors
- *the* question: how to recover from errors:
  - *acknowledgements (ACKs):* receiver explicitly tells sender that pkt received OK
  - *negative acknowledgements (NAKs):* receiver explicitly tells sender that pkt had errors
  - sender retransmits pkt on receipt of NAK
- new mechanisms in **`rdt2.0`** (beyond **`rdt1.0`**):
  - error detection
  - receiver feedback: control msgs (ACK,NAK) rcvr->sender
  - retransmission

rdt2.0: FSM specification





rdt2.0: operation with no errors



rdt2.0: error scenario



rdt2.0 has a fatal flaw!

- Can you spot the problem?

rdt2.0 has a fatal flaw!

What happens if ACK/NAK corrupted?

- sender doesn't know what happened at receiver!
- can't just retransmit: possible duplicate

- How should we handle duplicates?

rdt2.0 has a fatal flaw!

Handling duplicates:

- sender retransmits current pkt if ACK/NAK garbled
- sender adds *sequence number* to each pkt
- receiver discards (doesn't deliver up) duplicate pkt

stop and wait

Sender sends one packet, then waits for receiver response

rdt2.1: sender, handles garbled ACK/NAKs



rdt2.1: receiver, handles garbled ACK/NAKs



rdt2.1: discussion

Sender:

- seq # added to pkt
- two seq. #'s (0,1) will suffice. Why?
- must check if received ACK/NAK corrupted
- twice as many states
  - state must "remember" whether "current" pkt has 0 or 1 seq. #

Receiver:

- must check if received packet is duplicate
  - state indicates whether 0 or 1 is expected pkt seq #
- note: receiver can *not* know if its last ACK/NAK received OK at sender

rdt2.2: a NAK-free protocol

- same functionality as rdt2.1, using ACKs only
- instead of NAK, receiver sends ACK for last pkt received OK
  - receiver must *explicitly* include seq # of pkt being ACKed
- duplicate ACK at sender results in same action as NAK: *retransmit current pkt*

rdt2.2: sender, receiver fragments



rdt3.0: channels with errors *and* loss

New assumption:

underlying channel can also lose packets (data or ACKs)

- checksum, seq. #, ACKs, retransmissions will be of help, but not enough

Approach: sender waits "reasonable" amount of time for ACK

- retransmits if no ACK received in this time
- if pkt (or ACK) just delayed (not lost):
  - retransmission will be duplicate, but use of seq. #'s already handles this
  - receiver must specify seq # of pkt being ACKed
- requires countdown timer

rdt3.0 sender



rdt3.0 in action



(a) operation with no loss



(b) lost packet

rdt3.0 in action



(c) lost ACK



(d) premature timeout

Performance of rdt3.0

- rdt3.0 works, but performance is very poor
- ex: 1 Gbps link, 15 ms prop. delay, 8000 bit packet:

$$d_{trans} = \frac{L}{R} = \frac{8000\text{bits}}{10^9\,\text{bps}} = 8\,\text{microseconds}$$

  - U_{sender}: utilization – fraction of time sender busy sending

$$U_{sender} = \frac{L / R}{RTT + L / R} = \frac{.008}{30.008} = 0.00027$$

  - if RTT=30 msec, 1KB pkt every 30 msec -> 33kB/sec thruput over 1 Gbps link
  - network protocol limits use of physical resources!

rdt3.0: stop-and-wait operation



$$U_{sender} = \frac{L / R}{RTT + L / R} = \frac{.008}{30.008} = 0.00027$$

rdt3.0: stop-and-wait operation



How do we solve the poor performance problem???

Pipelined protocols

pipelining: sender allows multiple, "in-flight", yet-to-be-acknowledged pkts

- range of sequence numbers must be increased
- buffering at sender and/or receiver



(a) a stop-and-wait protocol in operation

(b) a pipelined protocol in operation

- two generic forms of pipelined protocols: *go-Back-N, selective repeat*

Pipelining: increased utilization



Increase utilization by a factor of 3!

$$U_{sender} = \frac{3 * L / R}{RTT + L / R} = \frac{.024}{30.008} = 0.0008$$

Pipelined Protocols

Go-back-N: big picture:

- sender can have up to N unacked packets in pipeline
- rcvr only sends *cumulative* acks
  - doesn't ack packet if there's a gap
- sender has timer for oldest unacked packet
  - if timer expires, retransmit all unack'ed packets

Selective Repeat: big pic

- sender can have up to N unack'ed packets in pipeline
- rcvr sends *individual ack* for each packet
- sender maintains timer for each unacked packet
  - when timer expires, retransmit only unack'ed packet

Go-Back-N

Sender:

- k-bit seq # in pkt header
- "window" of up to N, consecutive unack'ed pkts allowed



- ACK(n): ACKs all pkts up to, including seq # n - "cumulative ACK"
  - may receive duplicate ACKs (see receiver)
- timer for each in-flight pkt
- *timeout(n):* retransmit pkt n and all higher seq # pkts in window

GBN: sender extended FSM



GBN: receiver extended FSM



ACK-only: always send ACK for correctly-received pkt with highest *in-order* seq #

- may generate duplicate ACKs
- need only remember **`expectedseqnum`**

- out-of-order pkt:
  - discard (don't buffer) -> no receiver buffering!
  - Re-ACK pkt with highest in-order seq #

GBN in action



GBN in action:

See animated applet at:

http://media.pearsoncmg.com/aw/aw_kurose_network_4/applets/go-back-n/index.html

Selective Repeat

- receiver *individually* acknowledges all correctly received pkts
  - buffers pkts, as needed, for eventual in-order delivery to upper layer
- sender only resends pkts for which ACK not received
  - sender timer for each unACKed pkt
- sender window
  - N consecutive seq #'s
  - again limits seq #s of sent, unACK'ed pkts

Selective repeat: sender, receiver windows



Selective repeat

sender

data from above :

- if next available seq # in window, send pkt

timeout(n):

- resend pkt n, restart timer

ACK(n) in [sendbase,sendbase+N]:

- mark pkt n as received
- if n smallest unACKed pkt, advance window base to next unACKed seq #

receiver

pkt n in [rcvbase, rcvbase+N-1]

- send ACK(n)
- out-of-order: buffer
- in-order: deliver (also deliver buffered, in-order pkts), advance window to next not-yet-received pkt

pkt n in [rcvbase-N,rcvbase-1]

- ACK(n)

otherwise:

- ignore

Selective repeat in action



Selective repeat: dilemma

Example:

- seq #'s: 0, 1, 2, 3
- window size=3

- receiver sees no difference in two scenarios!
- incorrectly passes duplicate data as new in (a)

Q: what relationship between seq # size and window size?



Selective repeat:

- See animated applet:

- http://media.pearsoncmg.com/aw/aw_kurose_network_4/applets/SR/index.html

Lesson 9: Summary

- Reliable data transfer is an optional transport layer service.
- Reliable data transfer using the stop-and-wait-for-ack approach has very poor performance.
- Pipelining addresses stop-and-wait performance issues. Two generic pipelining approaches:
  - Go-Back-N
  - Selective Repeat.
- We will see in the next lesson how TCP solves the RDT problem with a pipelined approach that is a combination of Go-Back-N and Selective Repeat.