

CS450 Computer Networks

The slides used in class are derived from the slides available on our text book companion website:

http://wps.pearsoned.com/ecs_kurose_compnetw_6/

copyright 1996-2012 J.F Kurose and K.W. Ross

© 2012 Maharishi University of Management

All additional course materials are copyright protected by international copyright laws and remain the property of the Maharishi University of Management. The materials are accessible only for the personal use of students enrolled in this course and only for the duration of the course. Any copying and distributing are not allowed and subject to legal action.

CS450 Computer Networks

Lesson 3

Application Layer – Socket Programming

Knowledge is for action, action is for
achievement, achievement is for
fulfillment

Lesson 3: Application layer – Socket Programming

Our Goal:

Learn how to build client/server applications that communicate using sockets

- ❖ Socket programming using TCP
- ❖ Socket programming using UDP

Socket programming

Socket API

- ❖ introduced in BSD4.1 UNIX, 1981
- ❖ explicitly created, used, released by apps
- ❖ client/server paradigm
- ❖ two types of transport service via socket API:
 - unreliable datagram
 - reliable, byte stream-oriented


socket

a *host-local*,
application-created,
OS-controlled interface (a
“door”) into which
application process can **both**
send and
receive messages to/from
another application process

Socket-programming using TCP

Socket: a door between application process and end-end-transport protocol (UCP or TCP)

TCP service: reliable transfer of *bytes* from one process to another



Socket programming *with TCP*

Client must contact server

- ❖ server process must first be running
- ❖ server must have created socket (door) that welcomes client's contact

Client contacts server by:

- ❖ creating client-local TCP socket
- ❖ specifying IP address, port number of server process
- ❖ when **client creates socket**: client TCP establishes connection to server TCP

- ❖ when contacted by client, **server TCP creates new socket** for server process to communicate with client
 - allows server to talk with multiple clients
 - source port numbers used to distinguish clients (more in Chap 3)


application viewpoint

TCP provides reliable, in-order transfer of bytes (“pipe”) between client and server

Client/server socket interaction: TCP


Server (running on `hostid`)

Client



Stream jargon

- ❖ **stream** is a sequence of characters that flow into or out of a process.
- ❖ **input stream** is attached to some input source for the process, e.g., keyboard or socket.
- ❖ **output stream** is attached to an output source, e.g., monitor or socket.



Socket programming with TCP

Example client-server app:

- 1) client reads line from standard input (**inFromUser** stream) , sends to server via socket (**outToServer** stream)
- 2) server reads line from socket
- 3) server converts line to uppercase, sends back to client
- 4) client reads, prints modified line from socket (**inFromServer** stream)

Example: Java client (TCP)

```
import java.io.*;
import java.net.*;
class TCPClient {
```

← This package defines Socket() and ServerSocket() classes

```
    public static void main(String argv[]) throws Exception
    {
```

```
        String sentence;
        String modifiedSentence;
```

create
input stream →

```
        BufferedReader inFromUser =
            new BufferedReader(new InputStreamReader(System.in));
```

create
clientSocket object
of type Socket,
connect to server →

```
        Socket clientSocket = new Socket("hostname", 6789);
```

server name,
e.g., www.umass.edu

server port #

create
output stream
attached to socket →

```
        DataOutputStream outToServer =
            new DataOutputStream(clientSocket.getOutputStream());
```

Example: Java client (TCP), cont.

create
input stream
attached to socket → `BufferedReader inFromServer =
new BufferedReader(new
InputStreamReader(clientSocket.getInputStream()));`

`sentence = inFromUser.readLine();`

send line
to server → `outToServer.writeBytes(sentence + '\n');`

read line
from server → `modifiedSentence = inFromServer.readLine();`

`System.out.println("FROM SERVER: " + modifiedSentence);`

close socket
(clean up behind yourself!) → `clientSocket.close();`

`}`
`}`

Example: Java server (TCP)

```
import java.io.*;  
import java.net.*;
```

```
class TCPServer {
```

```
    public static void main(String argv[]) throws Exception  
    {
```

```
        String clientSentence;  
        String capitalizedSentence;
```

create
welcoming socket
at port 6789

→ `ServerSocket welcomeSocket = new ServerSocket(6789);`

wait, on welcoming
socket accept() method
for client contact create,
new socket on return

```
        while(true) {
```

→ `Socket connectionSocket = welcomeSocket.accept();`

create input
stream, attached
to socket

```
            BufferedReader inFromClient =
```

→ `new BufferedReader(new
InputStreamReader(connectionSocket.getInputStream()));`

Example: Java server (TCP), cont

create output
stream, attached
to socket

→ `DataOutputStream outToClient =
new DataOutputStream(connectionSocket.getOutputStream());`

read in line
from socket

→ `clientSentence = inFromClient.readLine();`

`capitalizedSentence = clientSentence.toUpperCase() + '\n';`

write out line
to socket

→ `outToClient.writeBytes(capitalizedSentence);`

`}
}
}`

end of while loop,
loop back and wait for
another client connection

Socket programming *with UDP*

UDP: no “connection” between client and server

- ❖ no handshaking
- ❖ sender explicitly attaches IP address and port of destination to each packet
- ❖ server must extract IP address, port of sender from received packet

UDP: transmitted data may be received out of order, or lost

application viewpoint:

UDP provides unreliable transfer of groups of bytes (“datagrams”) between client and server

Client/server socket interaction: UDP

Server (running on `hostid`)

Client

create socket,
port= x.
`serverSocket =`
`DatagramSocket()`

read datagram from
`serverSocket`

write reply to
`serverSocket`
specifying
client address,
port number


create socket,
`clientSocket =`
`DatagramSocket()`

Create datagram with server IP and
port=x; send datagram via
`clientSocket`

read datagram from
`clientSocket`

close
`clientSocket`

Example: Java client (UDP)



Example: Java client (UDP)

```
import java.io.*;  
import java.net.*;
```

```
class UDPClient {  
    public static void main(String args[]) throws Exception  
    {
```

create
input stream

```
        BufferedReader inFromUser =  
            new BufferedReader(new InputStreamReader(System.in));
```

create
client socket

```
        DatagramSocket clientSocket = new DatagramSocket();
```

translate
hostname to IP
address using DNS

```
        InetAddress IPAddress = InetAddress.getByName("hostname");
```

```
        byte[] sendData = new byte[1024];  
        byte[] receiveData = new byte[1024];
```

```
        String sentence = inFromUser.readLine();  
        sendData = sentence.getBytes();
```

Example: Java client (UDP), cont.

```
create datagram with  
    data-to-send,  
length, IP addr, port → DatagramPacket sendPacket =  
                           new DatagramPacket(sendData, sendData.length, IPAddress, 9876);  
  
send datagram  
  to server → clientSocket.send(sendPacket);  
  
DatagramPacket receivePacket =  
    new DatagramPacket(receiveData, receiveData.length);  
  
read datagram  
  from server → clientSocket.receive(receivePacket);  
  
String modifiedSentence =  
    new String(receivePacket.getData());  
  
System.out.println("FROM SERVER:" + modifiedSentence);  
clientSocket.close();  
}  
}
```

Example: Java server (UDP)

```
import java.io.*;
import java.net.*;

class UDPServer {
    public static void main(String args[]) throws Exception
    {
        DatagramSocket serverSocket = new DatagramSocket(9876);

        byte[] receiveData = new byte[1024];
        byte[] sendData = new byte[1024];

        while(true)
        {
            DatagramPacket receivePacket =
                new DatagramPacket(receiveData, receiveData.length);

            serverSocket.receive(receivePacket);
```

create
datagram socket
at port 9876

create space for
received datagram

receive
datagram

Example: Java server (UDP), cont

```
String sentence = new String(receivePacket.getData());
```

get IP addr
port #, of
sender

```
→ InetAddress IPAddress = receivePacket.getAddress();  
→ int port = receivePacket.getPort();
```

```
String capitalizedSentence = sentence.toUpperCase();
```

```
sendData = capitalizedSentence.getBytes();
```

create datagram
to send to client

```
→ DatagramPacket sendPacket =  
    new DatagramPacket(sendData, sendData.length, IPAddress,  
                        port);
```

write out
datagram
to socket

```
→ serverSocket.send(sendPacket);  
    }  
  }  
}
```

end of while loop,
loop back and wait for
another datagram

Lesson 3: Summary

- ❖ *TCP provides reliable, in-order transfer of bytes (“pipe”) between client and server*
- ❖ *UDP provides unreliable transfer of groups of bytes (“datagrams”) between client and server*