

Aim:

Write a C program that uses functions to perform the following **operations on double linked list**

i) Creation ii) Insertion iii) Deletion iv) Traversal

Source Code:**AllOperationsDLL.c**

```
#include <stdio.h>
#include <stdlib.h>
#include <conio.h>

struct dnode
{
    struct dnode *prev;
    int data;
    struct dnode *next;
};

struct dnode *start = NULL;

void insert(int);
void remov(int);
void display();

int main()
{
    int n, ch;
    do
    {
        printf("Operations on doubly linked list");
        printf("\n1. Insert \n2.Remove\n3. Display\n0. Exit");
        printf("\nEnter Choice 0-4? : ");
        scanf("%d", &ch);
        switch (ch)
        {
            case 1:
                printf("Enter number: ");
                scanf("%d", &n);
                insert(n);
                break;
            case 2:
                printf("Enter number to delete: ");
                scanf("%d", &n);
                remov(n);
                break;
            case 3:
                display();
                break;
        }
    }while (ch != 0);
}
```

```
void insert(int num)
{
    struct dnode *nptr, *temp = start;

    nptr = malloc(sizeof(struct dnode));
    nptr->data = num;
    nptr->next = NULL;
    nptr->prev = NULL;

    if (start == NULL)
    {
        start = nptr;
    }
    else
    {
        while (temp->next != NULL)
            temp = temp->next;

        nptr->prev = temp;
        temp->next = nptr;
    }
}

void remov(int num)
{
    struct dnode *temp = start;

    while (temp != NULL)
    {
        if (temp->data == num)
        {
            if (temp == start)
            {
                start = start->next;
                start->prev = NULL;
            }
            else
            {
                if (temp->next == NULL)
                    temp->prev->next = NULL;
                else
                {
                    temp->prev->next = temp->next;
                    temp->next->prev = temp->prev;
                }
                free(temp);
            }
            return ;
        }
        temp = temp->next;
    }
}
```

```

    }
    printf("%d not found.\n", num);
}

void display()
{
    struct dnode *temp = start;
    while (temp != NULL)
    {
        printf("%d\t", temp->data);
        temp = temp->next;
    }
    printf("\n");
}

```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Operations on doubly linked list 1
1.Insert 1
2.Remove 1
3.Display 1
0.Exit 1
Enter Choice 0-4?: 1
Enter number: 15
Operations on doubly linked list 1
1.Insert 1
2.Remove 1
3.Display 1
0.Exit 1
Enter Choice 0-4?: 1
Enter number: 16
Operations on doubly linked list 1
1.Insert 1
2.Remove 1
3.Display 1
0.Exit 1
Enter Choice 0-4?: 1
Enter number: 17
Operations on doubly linked list 1
1.Insert 1
2.Remove 1
3.Display 1
0.Exit 1
Enter Choice 0-4?: 1
Enter number: 18
Operations on doubly linked list 3
1.Insert 3
2.Remove 3
3.Display 3
0.Exit 3

Enter Choice 0-4?: 3
15 16 17 18 2
Operations on doubly linked list 2
1.Insert 2
2.Remove 2
3.Display 2
0.Exit 2
Enter Choice 0-4?: 2
Enter number to delete: 19
19 not found 3
Operations on doubly linked list 3
1.Insert 3
2.Remove 3
3.Display 3
0.Exit 3
Enter Choice 0-4?: 3
15 16 17 18 2
Operations on doubly linked list 2
1.Insert 2
2.Remove 2
3.Display 2
0.Exit 2
Enter Choice 0-4?: 2
Enter number to delete: 16
Operations on doubly linked list 0
1.Insert 0
2.Remove 0
3.Display 0
0.Exit 0
Enter Choice 0-4?: 0