
## GE23131-Programming Using C-2024



Status	Finished	
Started	Started Monday, 13 January 2025, 8:45 AM	
Completed	Completed Monday, 13 January 2025, 9:14 AM	
Duration	28 mins 40 secs	

Question **1** 

Correct

Flag question

You are transporting some boxes through a tunnel, where each box is a parallelepiped, and is characterized by its length, width and height.

The height of the tunnel **41** feet and the width can be assumed to be infinite. A box can be carried through the tunnel only if its height is strictly less than the tunnel's height. Find the volume of each box that can be successfully transported to the other end of the tunnel. Note: Boxes cannot be rotated.

Input Format

The first line contains a single integer  $\mathbf{n}$ , denoting the number of boxes.

n lines follow with three integers on each separated by single spaces -  $length_i$ ,  $width_i$  and  $height_i$  which are length, width and height in feet of the i-th box.

Constraints

 $1 \le n \le 100$ 

Output Format
For every box from the input which has a height lesser than <b>41</b> feet, print its volume in a separate line.
Sample Input 0
4
5 5 5
1 2 40
10 5 41
7 2 42
Sample Output 0
125
80
Explanation 0
The first box is really low, only $\bf 5$ feet tall, so it can pass through the tunnel and its volume is $\bf 5 \times 5 \times 5 = 125$ .
The second box is sufficiently low, its volume is $1 \times 2 \times 4 = 80$ .

## **Answer:** (penalty regime: 0 %)

```
#include<stdio.h>
    int main()
 2
 3 ▼ {
        int n;
 4
        scanf("%d",&n);
 5
        for(int i=0;i<n;i++)</pre>
7 🔻
             int length, width, height;
 8
             scanf("%d %d %d",&length,&width,&height);
 9
             if(height<41)</pre>
10
11 🔻
12
                 int volume=length*width*height;
                 printf("%d\n",volume);
13
14
15
16
```

	Input	Expected	Got	
<b>/</b>	4	125	125	<b>~</b>
	5 5 5	80	80	
	1 2 40			
	10 5 41			
	7 2 42			

Passed all tests! <

Question 2

Correct

Flag question

You are given n triangles, specifically, their sides  $a_i$ ,  $b_i$  and  $c_i$ . Print them in the same style but sorted by their areas from the smallest one to the largest one. It is guaranteed that all the areas are different.

The best way to calculate a volume of the triangle with sides  $\boldsymbol{a}$ ,  $\boldsymbol{b}$  and  $\boldsymbol{c}$  is Heron's formula:

$$S = \ddot{O} p * (p - a) * (p - b) * (p - c)$$
 where  $p = (a + b + c) / 2$ .

**Input Format** 

First line of each test file contains a single integer n. n lines follow with  $a_i$ ,  $b_i$  and  $c_i$  on each separated by single spaces.

Constraints

$$1 \le n \le 100$$

$$1 \leq a_i, b_i, c_i \leq 70$$

$$a_i + b_i > c_i$$
,  $a_i + c_i > b_i$  and  $b_i + c_i > a_i$ 

**Output Format** 

Print exactly n lines. On each line print a integers separated by single spaces, which are  $a_i$ ,  $b_i$  and  $c_i$  of the corresponding triangle.

Sample Input 0

```
Sample Output 0
3 4 5
5 12 13
7 24 25
Explanation 0
The square of the first triangle is 84. The square of the second triangle is 30. The
square of the third triangle is 6. So the sorted order is the reverse one.
Answer: (penalty regime: 0 %)
   1 #include<stdio.h>
   2 #include<math.h>
      #include<stdlib.h>
    4 ▼ typedef struct{
           double area;
           int a,b,c;
      }Triangle;
       double calculate_area(int a,int b,int c){
           double p=(a+b+c)/2.0;
    9
           return sqrt(p*(p-a)*(p-b)*(p-c));
  10
   11
   12
  13 | int compare(const void*x,const void*y){
   14
           Triangle*t1=(Triangle*)x;
```

7 24 25

5 12 13

3 4 5

```
18
        return 0;
19
20 v int main(){
21
       int n;
22
       scanf("%d",&n);
       Triangle triangles[n];
23
       for(int i=0;i<n;i++){</pre>
24 ▼
           int a,b,c;
25
           scanf("%d %d %d",&a,&b,&c);
26
           triangles[i].a = a;
27
           triangles[i].b=b;
28
           triangles[i].c=c;
29
30
           triangles[i].area=calculate area(a,b,c);
31
32
33
       qsort(triangles,n,sizeof(Triangle),compare);
       for(int i=0;i<n;i++){</pre>
34 ▼
35
           printf("%d %d %d\n",triangles[i].a,triangles[i].b,triangles
36
37
```

	Input	Expected	Got	
~	7 24 25	3 4 5 5 12 13 7 24 25	3 4 5 5 12 13 7 24 25	<b>~</b>

Passed all tests! <

Finish review