
GE23131-Programming Using C-2024



Status	Status Finished	
Started	Monday, 23 December 2024, 5:33 PM	
Completed	saturday, 14 December 2024, 1:02 PM	
Duration	9 days 4 hours	

Question **1**

Correct

Marked out of 1.00

Flag question

Coders here is a simple task for you, you have given an array of size N and an integer M.

Your task is to calculate the *difference between maximum sum and minimum sum of N-M* elements of the given array.

Constraints:

Input:

First line contains an integer **T** denoting the number of testcases.

First line of every testcase contains two integer **N** and **M**.

Output: For every test case print your answer in new line SAMPLE INPUT 1 5 1 12345 SAMPLE OUTPUT 4 Explanation M is 1 and N is 5 so you have to calculate maximum and minimum sum using (5-1 =) 4 elements. Maximum sum using the 4 elements would be (2+3+4+5=)14. Minimum sum using the 4 elements would be (1+2+3+4=)10. Difference will be 14-10=4. **Answer:** (penalty regime: 0 %) 1 #include<stdio.h> int main()

```
while(t--)
 7 🔻
 8
 9
             int n,m,d,min,temp;
10
             scanf("%d %d",&n,&m);
11
12
             d=n-m;
13
             int arr[n];
             for(int i=0;i<n;i++)</pre>
14
15
             scanf("%d",&arr[i]);
             for(int j=0;j<n;j++)</pre>
16
17 🔻
18
                 min=j;
                 for(int k=j;k<n;k++)</pre>
19
20 1
21
                      if(arr[k]<arr[min])</pre>
22
                      min=k;
23
                      temp=arr[min];
24
25
                      arr[min]=arr[j];
26
                      arr[j]=temp;
27
28
             int maxsum=0,minsum=0;
             for(int a=0;a<d;a++)</pre>
29
30
             minsum+=arr[a];
             for(int b=n-1;b>m-1;b--)
31
             maxsum+=arr[b];
32
33
             printf("%d\n", maxsum-minsum);
34
35
36
         return 0;
37
```

	Input	Expected	Got	
	1	4	4	
	5 1			

Question **2**

Correct

Marked out of 1.00

Flag question

A new deadly virus has infected large population of a planet. A brilliant scientist has discovered a new strain of virus which can cure this disease. Vaccine produced from this virus has various strength depending on midichlorians count. A person is cured only if midichlorians count in vaccine batch is more than midichlorians count of person. A doctor receives a new set of report which contains midichlorians count of each infected patient, Practo stores all vaccine doctor has and their midichlorians count. You need to determine if doctor can save all patients with the vaccines he has. The number of vaccines and patients are equal.

Input Format

First line contains the number of vaccines - N. Second line contains N integers, which are strength of vaccines. Third line contains N integers, which are midichlorians count of patients.

Output Format

Print a single line containing 'Yes' or 'No'.

Input Constraint

1 < N < 10

Strength of vaccines and midichlorians count of patients fit in integer.

```
5
123 146 454 542 456
100 328 248 689 200
```

SAMPLE OUTPUT

No

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
    int main()
 2
 3 ▼
         int n,min1,min2,temp,flag=1;
         scanf("%d",&n);
         int vac[n],pat[n];
         for(int i=0;i<n;i++)</pre>
         scanf("%d",&vac[i]);
 8
         for(int i=0;i<n;i++)</pre>
 9
         scanf("%d",&pat[i]);
10
11
         for(int j=0;j<n-1;j++)</pre>
12 🔻
13
             min1=j,min2=j;
             for(int k=0;k<n;k++)</pre>
14
15 🔻
16
                  if(vac[k]<pat[min1])</pre>
                  min1=k;
17
                  if(pat[k]<pat[min2])</pre>
18
19
                  min2=k;
20
```

```
temp=pat[min2]=pat[j];
24
25
              pat[j]=temp;
26
         for(int i=0;i<n;i++)</pre>
27
28 •
29
              if(vac[i]<pat[i])</pre>
30 •
                  flag=<mark>0</mark>;
31
32
                   break;
33
34
         if(flag==1)
35
         printf("Yes");
36
         else
37
         printf("No");
38
39
40
```

	Input	Expected	Got	
	5	No	No	
	123 146 454 542 456			
	100 328 248 689 200			

Passed all tests!

You are given an array of n integer numbers a_1, a_2, \ldots, a_n . Calculate the number of pair of indices (i, j) such that $1 \le i < j \le n$ and a_i xor $a_j = 0$.

Marked out of 1.00

Flag question

- Second line: n space separated integers a_1, a_2, \ldots, a_n .

Output format

Output the required number of pairs.

Constraints

$$1 \le n \le 10^6$$

$$1 \leq a_i \leq 10^9$$

SAMPLE INPUT

5

13143

SAMPLE OUTPUT

2

Explanation

The 2 pair of indices are (1, 3) and (2,5).

```
Answer: (penalty regime: 0 %)
```

```
#include<stdio.h>
    int main()
 2
 3 ▼ {
         int n,count=0;
 4
         scanf("%d",&n);
 5
         int arr[n];
        for(int i=0;i<n;i++)</pre>
         scanf("%d",&arr[i]);
 8
         for(int i=0;i<n-1;i++)</pre>
 9
10 🔻
             for(int j=i+1;j<n;j++)</pre>
11
12 ▼
                 if((arr[i]^arr[j])==0)
13
14
                 count++;
15
16
17
         printf("%d",count);
18
```

Input	Expected	Got	
5 1 3 1 4 3	2	2	

Passed all tests!

Marked out of 1.00 Flag question

array.

Example:

$$A = \{4,5,3,7,1\}$$

After sorting the new array becomes $A = \{1,3,4,5,7\}$.

The required output should be "4 2 0 1 3"

INPUT:

The first line of input consists of the size of the array

The next line consists of the array of size m

OUTPUT:

Output consists of a single line of integers

CONSTRAINTS:

$$0 < =A[i] < =106$$

NOTE: The indexing of the array starts with 0.

5 45371

SAMPLE OUTPUT

42013

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
 2
    int main()
 3 ▼
         int n;
         scanf("%d",&n);
 5
         int arr[n];
         for(int i=0;i<n;i++)</pre>
         scanf("%d",&arr[i]);
 8
         int max=arr[0];
 9
         for(int i=1;i<n;i++)</pre>
10
11 🔻
12
             if(arr[i]>max)
13
             max=arr[i];
14
15
16
         max++;
         int min=0;
17
         for(int a=0;a<n;a++)</pre>
18
19 🔻
             for(int b=0;b<n;b++)</pre>
20
21 🔻
                  if(arr[b]<arr[min])</pre>
22
23
                  min=b;
24
25
             printf("%d ",min);
```

