

# Assignment\_2

Krishna Kumar Tavva - 811283461

2023-03-09

## install functions and call libraries needed

```
library(ISLR)
library(dplyr)
```

```
##
## Attaching package: 'dplyr'

## The following objects are masked from 'package:stats':
##
##   filter, lag

## The following objects are masked from 'package:base':
##
##   intersect, setdiff, setequal, union
```

## Load the Online Retail data into R

```
OR <- read.csv("E:/Business Analyst/Module 4/Online_Retail.csv")
summary(OR)
```

```
##   InvoiceNo      StockCode      Description      Quantity
## Length:541909 Length:541909 Length:541909 Min.   :-80995.00
## Class :character Class :character Class :character 1st Qu.:    1.00
## Mode  :character Mode  :character Mode  :character Median :    3.00
##                                     Mean  :    9.55
##                                     3rd Qu.:   10.00
##                                     Max.   : 80995.00
##
## InvoiceDate      UnitPrice      CustomerID      Country
## Length:541909 Min.   :-11062.06 Min.   :12346 Length:541909
## Class :character 1st Qu.:    1.25 1st Qu.:13953 Class :character
## Mode  :character Median :    2.08 Median :15152 Mode  :character
##                                     Mean  :    4.61 Mean  :15288
##                                     3rd Qu.:    4.13 3rd Qu.:16791
##                                     Max.   : 38970.00 Max.   :18287
##                                     NA's   :135080
```

1. Show the breakdown of the number of transactions by countries i.e., how many transactions are in the dataset for each country. Show this in total number and also in percentage. Show only countries accounting for more than 1% of the total transactions.

```
OR %>% group_by(Country) %>% summarise(Total_Trans=n(), Total_Perc = sum(n()/nrow(OR))*100) %>%
  filter(Total_Perc>1)
```

```
## # A tibble: 4 x 3
##   Country      Total_Trans Total_Perc
##   <chr>          <int>      <dbl>
## 1 EIRE             8196        1.51
## 2 France           8557        1.58
## 3 Germany          9495        1.75
## 4 United Kingdom  495478       91.4
```

2. Create a new variable 'TransactionValue' that is the product of the existing 'Quantity' and 'UnitPrice' variables. Add this variable to the dataframe

```
TransactionValue <- OR$Quantity*OR$UnitPrice
OR <- cbind(OR, TransactionValue)
colnames(OR)
```

```
## [1] "InvoiceNo"      "StockCode"      "Description"     "Quantity"
## [5] "InvoiceDate"    "UnitPrice"      "CustomerID"      "Country"
## [9] "TransactionValue"
```

3. Using the newly created variable, TransactionValue, show the breakdown of transaction values by countries i.e. how much money in total has been spent each country. Show this in total sum of transaction values. Show only countries with total transaction exceeding 130,000 British Pound.

```
OR %>% group_by(Country) %>% summarise(Total = sum(TransactionValue)) %>%
  filter(Total >= 130000) %>% arrange(desc(Total))
```

```
## # A tibble: 6 x 2
##   Country      Total
##   <chr>          <dbl>
## 1 United Kingdom 8187806.
```

```
## 2 Netherlands      284662.
## 3 EIRE              263277.
## 4 Germany           221698.
## 5 France            197404.
## 6 Australia         137077.
```

## 4. Converting Invoice Date into a POSIXlt object

```
Temp=strptime(OR$InvoiceDate,format='%m/%d/%Y %H:%M',tz='GMT')
head(Temp)
```

```
## [1] "2010-12-01 08:26:00 GMT" "2010-12-01 08:26:00 GMT"
## [3] "2010-12-01 08:26:00 GMT" "2010-12-01 08:26:00 GMT"
## [5] "2010-12-01 08:26:00 GMT" "2010-12-01 08:26:00 GMT"
```

```
#New_Invoice_Date
OR$New_Invoice_Date <- as.Date(Temp)

OR$New_Invoice_Date[20000]- OR$New_Invoice_Date[10]
```

```
## Time difference of 8 days
```

```
#Invoice_Day_Week
OR$Invoice_Day_Week= weekdays(OR$New_Invoice_Date)

#New_Invoice_Hour
OR$New_Invoice_Hour = as.numeric(format(Temp, "%H"))

#New_Invoice_Month
OR$New_Invoice_Month = as.numeric(format(Temp, "%m"))

#4(a).Percentage of transactions (by numbers) by days of the week

OR %>% group_by(Invoice_Day_Week) %>% summarise(count=n()) %>% mutate(Percentage=count/nrow(OR)*100)
```

```
## # A tibble: 6 x 3
##   Invoice_Day_Week count Percentage
##   <chr>          <int>      <dbl>
## 1 Friday         82193       15.2
## 2 Monday         95111       17.6
## 3 Sunday         64375       11.9
## 4 Thursday      103857       19.2
## 5 Tuesday       101808       18.8
## 6 Wednesday     94565       17.5
```

```
#4(b).Percentage of transactions (by transaction volume) by days of the week

OR %>% group_by(Invoice_Day_Week) %>% summarise(Total= sum(TransactionValue)) %>%
  mutate(Percentage = Total/sum(Total)*100)
```

```
## # A tibble: 6 x 3
##   Invoice_Day_Week    Total Percentage
##   <chr>             <dbl>     <dbl>
## 1 Friday            1540611.    15.8
## 2 Monday            1588609.    16.3
## 3 Sunday             805679.     8.27
## 4 Thursday          2112519    21.7
## 5 Tuesday           1966183.    20.2
## 6 Wednesday         1734147.    17.8
```

*#4(c).Percentage of transactions (by transaction volume) by month of the year*

```
OR %>% group_by(New_Invoice_Month) %>% summarise(Total = sum(TransactionValue))%>%
  mutate(Percentage = Total/sum(Total)*100)
```

```
## # A tibble: 12 x 3
##   New_Invoice_Month    Total Percentage
##   <dbl>             <dbl>     <dbl>
## 1                1 560000.     5.74
## 2                2 498063.     5.11
## 3                3 683267.     7.01
## 4                4 493207.     5.06
## 5                5 723334.     7.42
## 6                6 691123.     7.09
## 7                7 681300.     6.99
## 8                8 682681.     7.00
## 9                9 1019688.    10.5
## 10              10 1070705.    11.0
## 11              11 1461756.    15.0
## 12              12 1182625.    12.1
```

*#4(d).The date with the highest number of transactions from Australia*

```
OR %>% filter(Country == "Australia") %>% group_by(New_Invoice_Date) %>%
  summarise(Total_Count = n()) %>% arrange((desc(Total_Count)))
```

```
## # A tibble: 49 x 2
##   New_Invoice_Date Total_Count
##   <date>             <int>
## 1 2011-06-15          139
## 2 2011-07-19          137
## 3 2011-08-18           97
## 4 2011-03-03           84
## 5 2011-10-05           82
## 6 2011-05-17           73
## 7 2011-02-15           69
## 8 2011-01-06           48
## 9 2011-07-14           35
## 10 2011-09-16           34
## # ... with 39 more rows
```

#4(e). The company needs to shut down the website for two consecutive hours for maintenance. What would

```
transactVolumeByHour = OR %>%
  group_by(New_Invoice_Hour) %>% summarise(TransactionVolume =n())

transactVolumeByHour = transactVolumeByHour %>%
  arrange(New_Invoice_Hour) %>%
  mutate(TwoConsecutiveHourTraffic=TransactionVolume+lead(TransactionVolume),NextHour=lead(New_Invoice_Hour))
  filter(New_Invoice_Hour>=7,New_Invoice_Hour<19)


transactVolumeByHour %>%
  filter(TwoConsecutiveHourTraffic== min(transactVolumeByHour$TwoConsecutiveHourTraffic))
```

```
## # A tibble: 1 x 4
##   New_Invoice_Hour TransactionVolume TwoConsecutiveHourTraffic NextHour
##             <dbl>             <int>                <int>    <dbl>
## 1               7               383                9292      8
```

```
#transactVolumeByHour = OR %>% group_by(New_Invoice_Hour) %>% summarise(TransactionVolume =n()) %>% arrange(New_Invoice_Hour)
```

5. Plot the histogram of transaction values from Germany. Use the `hist()` function to plot.

```
Germany <- OR %>% filter(Country == "Germany") %>%
  group_by(New_Invoice_Date) %>%
  summarise(Total=sum(TransactionValue))
hist(Germany$Total, main = "Histogram of Germany's Transaction Values",
      xlab="Transactions", ylab="Frequency of Transactions")
```



**6. Which customer had the highest number of transactions? Which customer is most valuable (i.e. highest total sum of transactions)?**

```
OR %>% group_by(CustomerID) %>% summarise(Total_Transactions = n()) %>%
  arrange((desc(Total_Transactions))) %>% filter(!is.na(CustomerID))
```

```
## # A tibble: 4,372 x 2
##   CustomerID Total_Transactions
##   <int>         <int>
## 1    17841             7983
## 2    14911             5903
## 3    14096             5128
## 4    12748             4642
## 5    14606             2782
## 6    15311             2491
## 7    14646             2085
## 8    13089             1857
## 9    13263             1677
## 10   14298             1640
## # ... with 4,362 more rows
```

#Customer ID 17841 is having highest number of transactions (excluding NA)

```
OR %>% group_by(CustomerID) %>% summarise(Spending_max = sum(TransactionValue)) %>%
  arrange((desc(Spending_max))) %>% filter(!is.na(CustomerID))
```

```
## # A tibble: 4,372 x 2
##   CustomerID Spending_max
##       <int>       <dbl>
## 1      14646      279489.
## 2      18102      256438.
## 3      17450      187482.
## 4      14911      132573.
## 5      12415      123725.
## 6      14156      113384.
## 7      17511       88125.
## 8      16684       65892.
## 9      13694       62653.
## 10     15311       59419.
## # ... with 4,362 more rows
```

#Customer ID 14646 is having highest total sum of transactions (excluding NA)

## 7. Calculate the percentage of missing values for each variable in the dataset

```
colMeans(is.na(OR))
```

```
##      InvoiceNo      StockCode      Description      Quantity
##      0.0000000      0.0000000      0.0000000      0.0000000
##      InvoiceDate      UnitPrice      CustomerID      Country
##      0.0000000      0.0000000      0.2492669      0.0000000
## TransactionValue New_Invoice_Date Invoice_Day_Week New_Invoice_Hour
##      0.0000000      0.0000000      0.0000000      0.0000000
## New_Invoice_Month
##      0.0000000
```

#For the Customer ID, 24.92669% variables are missing.

## 8. What are the number of transactions with missing CustomerID records by countries

```
OR %>% filter(is.na(CustomerID)) %>% group_by(Country) %>% count()
```

```
## # A tibble: 9 x 2
## # Groups:   Country [9]
##   Country      n
##   <chr>    <int>
```

```
## 1 Bahrain          2
## 2 EIRE              711
## 3 France            66
## 4 Hong Kong        288
## 5 Israel            47
## 6 Portugal          39
## 7 Switzerland      125
## 8 United Kingdom 133600
## 9 Unspecified       202
```

9. On average, how often the costumers comeback to the website for their next shopping? (i.e. what is the average number of days between consecutive shopping)

```
Days_Gap <- OR %>% group_by(CustomerID) %>% distinct(New_Invoice_Date) %>%
  arrange(desc(CustomerID)) %>%
  mutate(Past_Date=lag(New_Invoice_Date), Days_Between = New_Invoice_Date-lag(New_Invoice_Date)) %>%
  filter(!is.na(Days_Between))
```

```
Days_Gap
```

```
## # A tibble: 15,200 x 4
## # Groups:   CustomerID [2,992]
##   CustomerID New_Invoice_Date Past_Date Days_Between
##   <int> <date> <date> <drtn>
## 1 18287 2011-10-12 2011-05-22 143 days
## 2 18287 2011-10-28 2011-10-12 16 days
## 3 18283 2011-01-23 2011-01-06 17 days
## 4 18283 2011-02-28 2011-01-23 36 days
## 5 18283 2011-04-21 2011-02-28 52 days
## 6 18283 2011-05-23 2011-04-21 32 days
## 7 18283 2011-06-14 2011-05-23 22 days
## 8 18283 2011-06-23 2011-06-14 9 days
## 9 18283 2011-07-14 2011-06-23 21 days
## 10 18283 2011-09-05 2011-07-14 53 days
## # ... with 15,190 more rows
```

```
mean(Days_Gap$Days_Between)
```

```
## Time difference of 38.4875 days
```



10. In the retail sector, it is very important to understand the return rate of the goods purchased by customers. In this example, we can define this quantity, simply, as the ratio of the number of transactions cancelled (regardless of the transaction value) over the total number of transactions. With this definition, what is the return rate for the French customers?

```
France_Cancel <- OR %>% filter(Country=="France",Quantity<0) %>% count()

France_Total <- OR %>% filter(Country=="France") %>% count()

Return_Rate_of_France <- France_Cancel/France_Total*100
Return_Rate_of_France
```

```
##           n
## 1 1.741264
```

#The return rate for the French customers is 1.741264%

11. What is the product that has generated the highest revenue for the retailer? (i.e. item with the highest total sum of 'Transaction-Value').

```
OR %>% group_by(Description) %>% summarise(Total=sum(TransactionValue)) %>%
  arrange(desc(Total))
```

```
## # A tibble: 4,224 x 2
##   Description                               Total
##   <chr>                                <dbl>
## 1 "DOTCOM POSTAGE"                      206245.
## 2 "REGENCY CAKESTAND 3 TIER"           164762.
## 3 "WHITE HANGING HEART T-LIGHT HOLDER" 99668.
## 4 "PARTY BUNTING"                     98303.
## 5 "JUMBO BAG RED RETROSPOT"            92356.
## 6 "RABBIT NIGHT LIGHT"                 66757.
## 7 "POSTAGE"                            66231.
## 8 "PAPER CHAIN KIT 50'S CHRISTMAS "    63792.
## 9 "ASSORTED COLOUR BIRD ORNAMENT"      58960.
## 10 "CHILLI LIGHTS"                     53768.
## # ... with 4,214 more rows
```

#DOTCOM POSTAGE is the highest revenue for the retailer

**12. How many unique customers are represented in the dataset?**  
You can use `unique()` and `length()` functions.

```
OR %>% select(CustomerID) %>% unique() %>% count()
```

```
##           n  
## 1  4373
```

```
#4373 unique customers are represented in the dataset
```