

Federated Learning with Partial Model Personalization

ICML 2022

**Krishna
Pillutla**



Kshitiz
Malik



Abdelrahman
Mohamed



Mike
Rabbat




Maziar
Sanjabi



Lin
Xiao



Personalized federated learning



Model on client $i = (\mathbf{u}, \mathbf{v}_i)$

Objective:
$$\min_{\mathbf{u}, \mathbf{v}_1, \dots, \mathbf{v}_n} \frac{1}{n} \sum_{i=1}^n F_i(\mathbf{u}, \mathbf{v}_i)$$

\mathbf{u} : shared parameters

\mathbf{v}_i : personal parameters

Our contributions

1. Theory: Analysis of 2 popular optimization algos

Objective:

$$\min_{u, v_1, \dots, v_n} \frac{1}{n} \sum_{i=1}^n F_i(u, v_i)$$

2. Extensive experiments: text, vision, and speech settings

u : shared parameters


v_i : personal parameters

Code:




Personalization architectures

Personalized output layer




Arivazhagan et al. (2019)
Collins et al. ICML (2021)

Personalized input layer



Liang et al. (2019)


Combined predictions



$$F_i(u, v_i) = \mathbb{E}_{(X,Y) \sim p_i} \left(\phi_g(X; u) + \phi_l(X; v_i) - Y \right)^2$$

Agarwal et al. (2020)


Personalized adapters



Multi-task learning: Caruana. Mach. Learn (1997), Baxter. JAIR (2000), Evgeniou & Pontil. KDD (2004), Collobert & Weston. ICML (2005), Argyriou et al. Mach. Learn (2008), ...


Personalization architectures

Personalized output layer




Arivazhagan et al. (2019)
Collins et al. ICML (2021)

Personalized input layer



Liang et al. (2019)


Combined predictions



$$F_i(u, v_i) = \mathbb{E}_{(X, Y) \sim p_i} \left(\phi_g(X; u) + \phi_l(X; v_i) - Y \right)^2$$

Agarwal et al. (2020)


Personalized adapters



Multi-task learning: Caruana. Mach. Learn (1997), Baxter. JAIR (2000),
Evgeniou & Pontil. KDD (2004), Collobert & Weston. ICML (2005),
Argyriou et al. Mach. Learn (2008), ...


Personalization architectures

Personalized output layer




Arivazhagan et al. (2019)
Collins et al. ICML (2021)

Personalized input layer



Liang et al. (2019)


Combined predictions



$$F_i(u, v_i) = \mathbb{E}_{(X, Y) \sim p_i} \left(\phi_g(X; u) + \phi_l(X; v_i) - Y \right)^2$$

Agarwal et al. (2020)


Personalized adapters



Multi-task learning: Caruana. Mach. Learn (1997), Baxter. JAIR (2000),
Evgeniou & Pontil. KDD (2004), Collobert & Weston. ICML (2005),
Argyriou et al. Mach. Learn (2008), ...


Personalization architectures

Personalized output layer




Arivazhagan et al. (2019)
Collins et al. ICML (2021)

Personalized input layer



Liang et al. (2019)


Combined predictions



$$F_i(u, v_i) = \mathbb{E}_{(X,Y) \sim p_i} \left(\phi_g(X; u) + \phi_l(X; v_i) - Y \right)^2$$

Agarwal et al. (2020)

Personalized adapters



Multi-task learning: Caruana. Mach. Learn (1997), Baxter. JAIR (2000),
Evgeniou & Pontil. KDD (2004), Collobert & Weston. ICML (2005),
Argyriou et al. Mach. Learn (2008), ...

Optimization

- Server samples m clients and broadcast global model u
- **Local updates** on client i :
 $(u_i^+, v_i^+) = \text{LocalUpdate}_i(u, v_i)$
- Aggregate updates to global part of the model:
$$u^+ = \frac{1}{m} \sum_i u_i^+$$

Alternating update

$$v_i^+ = v_i - \gamma \nabla_v F_i(u, v_i)$$

Collins et al. ICML (2021)
Singhal et al. NeurIPS (2021)

$$u_i^+ = u - \gamma \nabla_u F_i(u, v_i^+)$$

Simultaneous update

$$v_i^+ = v_i - \gamma \nabla_v F_i(u, v_i)$$

$$u_i^+ = u - \gamma \nabla_u F_i(u, v_i)$$

Liang et al. (2019)
Arivazhagan et al. (2019)

Optimization

- Server samples m clients and broadcast global model u

- **Local updates** on client i :
 $(u_i^+, v_i^+) = \text{LocalUpdate}_i(u, v_i)$

- Aggregate updates to global part of the model:

$$u^+ = \frac{1}{m} \sum_i u_i^+$$

Alternating update

$$v_i^+ = v_i - \gamma \nabla_v F_i(u, v_i)$$

$$u_i^+ = u - \gamma \nabla_u F_i(u, v_i^+)$$

Collins et al. ICML (2021)
Singhal et al. NeurIPS (2021)

Simultaneous update

$$v_i^+ = v_i - \gamma \nabla_v F_i(u, v_i)$$

$$u_i^+ = u - \gamma \nabla_u F_i(u, v_i)$$

Liang et al. (2019)
Arivazhagan et al. (2019)

Optimization

- Server samples m clients and broadcast global model u

- **Local updates** on client i :
 $(u_i^+, v_i^+) = \text{LocalUpdate}_i(u, v_i)$

- Aggregate updates to global part of the model:

$$u^+ = \frac{1}{m} \sum_i u_i^+$$

Alternating update

$$v_i^+ = v_i - \gamma \nabla_v F_i(u, v_i)$$

Collins et al. ICML (2021)
Singhal et al. NeurIPS (2021)

$$u_i^+ = u - \gamma \nabla_u F_i(u, v_i^+)$$

Simultaneous update

$$v_i^+ = v_i - \gamma \nabla_v F_i(u, v_i)$$

$$u_i^+ = u - \gamma \nabla_u F_i(u, v_i)$$

Liang et al. (2019)
Arivazhagan et al. (2019)

Contribution 1: Theory

Theorem [P., Malik, Mohamed, Rabbat, Sanjabi, Xiao]

For smooth, nonconvex functions and client sampling, we have the rates:

Alternating update: $\frac{\sigma_1^2}{\sqrt{t}}$

Simultaneous update: $\frac{\sigma_2^2}{\sqrt{t}}$

where $\sigma_1^2 < \sigma_2^2$ under typical scenarios

Alternating update

$$v_i^+ = v_i - \gamma \nabla_v F_i(u, v_i)$$

$$u_i^+ = u - \gamma \nabla_u F_i(u, v_i^+)$$

Simultaneous update

$$v_i^+ = v_i - \gamma \nabla_v F_i(u, v_i)$$

$$u_i^+ = u - \gamma \nabla_u F_i(u, v_i)$$


Experimentally, small but consistent trend of alternating \succ simultaneous

Contribution 1: Theory



Key technical challenge: Dependent random variables in alternating update algorithm due to random sampling of clients

Methodology: Developed technique of **virtual full participation**


Contribution 2: Experiments




Next word prediction



Speech recognition




Landmark detection




y-axis shows error: lower is better


Contribution 2: Experiments




Next word prediction



Speech recognition




Landmark detection




y-axis shows error: lower is better

Contribution 2: Experiments






Next word prediction



Speech recognition




Landmark detection



y-axis shows error: lower is better


Contribution 2: Experiments




Next word prediction



Speech recognition



Landmark detection



y-axis shows error: lower is better

Federated Learning with Partial Model Personalization



Paper: arXiv:2204.03809



Code: https://github.com/krishnap25/FL_partial_personalization